



U.S. Department of Energy Portsmouth Gaseous Diffusion Plant



At the X-611A prairie on the east side of PORTS, periodic burning supports the establishment of prairie grasses and flowers

Annual Site Environmental Report – 2015



March 2017

**U.S. Department of Energy
Portsmouth Gaseous Diffusion Plant
Annual Site Environmental Report – 2015
Piketon, Ohio**



**U.S. Department of Energy
DOE/PPPO/03-0765&D1**

March 2017

**By
Fluor-BWXT Portsmouth LLC, under Contract DE-AC30-10CC40017**

FBP-ER-RCRA-WD-RPT-0236, Revision 3

This document has been approved for public release:

Samuel Eldridge (signature on file)

3/3/2017

Classification Office

Date

This page intentionally left blank.

2.3.7	Executive Orders	2-12
2.3.7.1	Executive Order 11988, <i>Floodplain Management</i> , and Executive Order 11990, <i>Protection of Wetlands</i>	2-12
2.3.7.2	Executive Order 13693, <i>Planning for Federal Sustainability in the, Next Decade</i>	2-12
2.4	OTHER MAJOR ENVIRONMENTAL ISSUES AND ACTIONS	2-12
2.4.1	Environmental Program Inspections	2-13
2.4.2	Notices of Violation	2-13
2.5	UNPLANNED RELEASES	2-14
2.6	SUMMARY OF PERMITS	2-14
3.	ENVIRONMENTAL PROGRAM INFORMATION	3-1
3.1	SUMMARY	3-1
3.2	D&D PROGRAM	3-1
3.2.1	Process Buildings and Other Facilities	3-1
3.2.2	Site-wide Waste Disposition	3-2
3.3	ENVIRONMENTAL RESTORATION PROGRAM	3-2
3.3.1	Quadrant I	3-4
3.3.1.1	X-749/X-120 groundwater plume	3-4
3.3.1.2	PK Landfill	3-6
3.3.1.3	Quadrant I Groundwater Investigative (5-Unit) Area	3-7
3.3.2	Quadrant II	3-7
3.3.2.1	Quadrant II Groundwater Investigative (7-Unit) Area	3-7
3.3.2.2	X-701B Former Holding Pond	3-8
3.3.2.3	X-633 Former Recirculating Cooling Water Complex	3-8
3.3.3	Quadrant III	3-9
3.3.4	Quadrant IV	3-9
3.3.4.1	X-611A Former Lime Sludge Lagoons	3-9
3.3.4.2	X-734 Landfills	3-10
3.3.4.3	X-630 Former Recirculating Cooling Water Complex	3-10
3.4	WASTE MANAGEMENT PROGRAM	3-10
3.5	ENVIRONMENTAL SUSTAINABILITY PROGRAM	3-13
3.6	PUBLIC AWARENESS PROGRAM	3-14
4.	ENVIRONMENTAL RADIOLOGICAL PROGRAM INFORMATION	4-1
4.1	SUMMARY	4-1
4.2	ENVIRONMENTAL RADIOLOGICAL PROGRAM INTRODUCTION	4-2
4.3	RADIOLOGICAL EMISSIONS AND DOSES	4-3
4.3.1	Dose Terminology	4-3
4.3.2	Airborne Emissions	4-4
4.3.3	Dose Calculation Based on Airborne Emissions	4-5
4.3.4	Dose Calculation Based on Ambient Air Monitoring	4-6
4.3.5	Discharges of Radionuclides from NPDES Outfalls	4-6
4.3.5.1	FBP outfalls	4-6
4.3.5.2	Centrus outfalls	4-11
4.3.6	Dose Calculation for Releases to Surface Water	4-12
4.3.7	Radiological Dose Calculation for External Radiation	4-12
4.3.8	Radiological Dose Results for DOE Workers and Visitors	4-13
4.3.9	Radiological Dose Calculations for Off-site Environmental Monitoring Data	4-13
4.3.9.1	Dose calculation for sediment	4-15
4.3.9.2	Dose calculation for soil	4-15

4.3.9.3 Dose calculation for vegetation	4-15
4.4 PROTECTION OF BIOTA	4-16
4.4.1 Aquatic and Riparian Animals	4-16
4.4.2 Terrestrial Plants and Animals	4-16
4.5 UNPLANNED RADIOLOGICAL RELEASES	4-17
4.6 ENVIRONMENTAL RADIOLOGICAL MONITORING	4-17
4.6.1 Ambient Air Monitoring.....	4-17
4.6.2 External Radiation	4-18
4.6.3 Surface Water from Cylinder Storage Yards.....	4-20
4.6.3.1 FBP cylinder storage yards.....	4-20
4.6.3.2 BWCS cylinder storage yards	4-20
4.6.4 Local Surface Water	4-21
4.6.5 Sediment	4-21
4.6.6 Settleable Solids	4-23
4.6.7 Soil.....	4-23
4.6.8 Biological Monitoring	4-25
4.6.8.1 Vegetation	4-25
4.6.8.2 Deer	4-25
4.6.8.3 Fish	4-25
4.6.8.4 Crops	4-26
4.6.8.5 Milk and eggs	4-26
4.7 RELEASE OF PROPERTY CONTAINING RESIDUAL RADIOACTIVE MATERIAL	4-26
4.7.1 FBP Releases	4-26
4.7.2 BWCS Releases.....	4-26
5. ENVIRONMENTAL NON-RADIOLOGICAL PROGRAM INFORMATION.....	5-1
5.1 SUMMARY	5-1
5.2 ENVIRONMENTAL NON-RADIOLOGICAL PROGRAM INTRODUCTION	5-1
5.3 AIR.....	5-1
5.3.1 Airborne Discharges.....	5-1
5.3.2 Ambient Air Monitoring.....	5-2
5.4 WATER	5-2
5.4.1 Water Discharges (NPDES Outfalls)	5-2
5.4.1.1 FBP NPDES outfalls	5-3
5.4.1.2 BWCS NPDES outfalls	5-5
5.4.1.3 Centrus NPDES outfalls	5-5
5.4.2 Surface Water Monitoring Associated with BWCS Cylinder Storage Yards	5-5
5.5 SEDIMENT	5-5
5.5.1 Local Sediment Monitoring.....	5-5
5.5.2 Sediment Monitoring Associated with BWCS Cylinder Storage Yards	5-6
5.6 BIOLOGICAL MONITORING - FISH	5-6
6. GROUNDWATER PROGRAMS.....	6-1
6.1 SUMMARY	6-1
6.2 GROUNDWATER PROGRAMS INTRODUCTION	6-1
6.3 OVERVIEW OF GROUNDWATER MONITORING AT PORTS	6-1
6.3.1 Regulatory Programs	6-1
6.3.2 Groundwater Use and Geology	6-2
6.3.3 Monitoring Activities	6-2
6.4 GROUNDWATER MONITORING AREAS	6-2
6.4.1 X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility	6-4

6.4.1.1	X-749 Contaminated Materials Disposal Facility	6-7
6.4.1.2	X-120 Former Training Facility	6-7
6.4.1.3	Monitoring results for the X-749 Contaminated Materials Disposal Facility/ X-120 Former Training Facility in 2015	6-8
6.4.2	PK Landfill	6-10
6.4.2.1	Monitoring results for the PK Landfill in 2015	6-10
6.4.3	Quadrant I Groundwater Investigative (5-Unit) Area	6-10
6.4.3.1	Monitoring results for the Quadrant I Groundwater Investigative (5-Unit) Area in 2015	6-11
6.4.4	X-749A Classified Materials Disposal Facility	6-11
6.4.4.1	Monitoring results for the X-749A Classified Materials Disposal Facility in 2015	6-13
6.4.5	Quadrant II Groundwater Investigative (7-Unit) Area	6-13
6.4.5.1	Monitoring results for the Quadrant II Groundwater Investigative (7-Unit) Area in 2015	6-13
6.4.6	X-701B Former Holding Pond	6-15
6.4.6.1	Monitoring results for the X-701B Former Holding Pond in 2015	6-15
6.4.7	X-633 Former Recirculating Cooling Water Complex	6-17
6.4.7.1	Monitoring results for the X-633 Former Recirculating Cooling Water Complex in 2015	6-17
6.4.8	X-616 Former Chromium Sludge Surface Impoundments	6-19
6.4.8.1	Monitoring results for the X-616 Former Chromium Sludge Surface Impoundments in 2015	6-19
6.4.9	X-740 Former Waste Oil Handling Facility	6-19
6.4.9.1	Monitoring results for the X-740 Former Waste Oil Handling Facility in 2015	6-21
6.4.10	X-611A Former Lime Sludge Lagoons	6-21
6.4.10.1	Monitoring results for the X-611A Former Lime Sludge Lagoons in 2015	6-21
6.4.11	X-735 Landfills	6-21
6.4.11.1	Monitoring results for the X-735 Landfills in 2015	6-24
6.4.12	X-734 Landfills	6-24
6.4.12.1	Monitoring results for the X-734 Landfills in 2015	6-26
6.4.13	X-533 Former Switchyard Complex	6-26
6.4.13.1	Monitoring results for the X-533 Former Switchyard Complex in 2015	6-26
6.4.14	X-344C Former Hydrogen Fluoride Storage Building	6-26
6.4.14.1	Monitoring results for the X-344C Former Hydrogen Fluoride Storage Building in 2015	6-29
6.4.15	Surface Water Monitoring	6-29
6.4.15.1	Monitoring results for surface water in 2015	6-29
6.4.16	Water Supply Monitoring	6-31
6.5	DOE ORDER MONITORING PROGRAMS	6-33
6.5.1	Exit Pathway Monitoring	6-33
6.6	GROUNDWATER TREATMENT FACILITIES	6-35
6.6.1	X-622 Groundwater Treatment Facility	6-35
6.6.2	X-623 Groundwater Treatment Facility	6-36
6.6.3	X-624 Groundwater Treatment Facility	6-36
6.6.4	X-627 Groundwater Treatment Facility	6-36
7.	QUALITY ASSURANCE	7-1
7.1	SUMMARY	7-1
7.2	QUALITY ASSURANCE INTRODUCTION	7-1

7.3 FIELD SAMPLING AND MONITORING 7-2
7.4 ANALYTICAL QUALITY ASSURANCE 7-2

8. REFERENCES 8-1

APPENDIX A: RADIATION..... A-1
APPENDIX B: ENVIRONMENTAL PERMITS..... B-1
APPENDIX C: RADIONUCLIDE AND CHEMICAL NOMENCLATURE C-1

This page intentionally left blank.

FIGURES

1	Comparison of dose from various common radiation sources.....	ES-6
1.1	The Portsmouth Gaseous Diffusion Plant.....	1-1
1.2	Location of PORTS	1-3
3.1	Location of the OSWDF at PORTS.....	3-2
4.1	DOE ambient air and radiation monitoring locations	4-7
4.2	PORTS NPDES outfalls/monitoring points and cylinder storage yards sampling locations	4-8
4.3	On-site radiation and cylinder yard dose monitoring locations	4-19
4.4	Local surface water and sediment monitoring locations.....	4-22
4.5	DOE settleable solids monitoring locations.....	4-24
6.1	Groundwater monitoring areas at PORTS	6-3
6.2	TCE-contaminated Gallia groundwater plume at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015	6-9
6.3	TCE-contaminated Gallia groundwater plume at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015	6-12
6.4	TCE-contaminated Gallia groundwater plume at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015	6-14
6.5	TCE-contaminated Gallia groundwater plume at the X-701B Former Holding Pond – 2015....	6-16
6.6	Metal concentrations in groundwater at the X-633 Former Recirculating Cooling Water Complex and X-533 Former Switchyard Complex – 2015	6-18
6.7	TCE and metal concentrations in groundwater at the X-616 Former Chromium Sludge Surface Impoundments – 2015	6-20
6.8	TCE-contaminated Gallia groundwater plume near the X-740 Former Waste Oil Handling Facility – 2015	6-22
6.9	Metal concentrations in groundwater at the X-611A Former Lime Sludge Lagoons – 2015	6-23
6.10	Monitoring wells at the X-735 Landfills.....	6-25
6.11	Monitoring wells at the X-734 Landfills.....	6-27
6.12	Monitoring well at the X-344C Former Hydrogen Fluoride Storage Building.....	6-28
6.13	Surface water monitoring locations	6-30

6.14 Water supply monitoring locations 6-32

6.15 Exit pathway monitoring locations 6-34

TABLES

2.1	Chemicals reported in the Hazardous Chemical Inventory Report for 2015	2-4
2.2	Environmental inspections of DOE activities at PORTS for 2015	2-13
3.1	Remedial actions at PORTS in groundwater monitoring areas	3-5
3.2	Waste Management Program off-site treatment, disposal, and recycling accomplishments for 2015.....	3-12
4.1	Summary of potential doses to the public from PORTS in 2015.....	4-1
4.2	Summary of potential doses to the public from radionuclides detected by DOE environmental monitoring programs in 2015.....	4-14
4.3	Summary of FBP personal property releases in 2015.....	4-26
6.1	Analytical parameters for monitoring areas and programs at PORTS in 2015.....	6-5
6.2	Summary of TCE removed by PORTS groundwater treatment facilities in 2015.....	6-35

This page intentionally left blank.

ACRONYMS AND ABBREVIATIONS

ACP	American Centrifuge Plant
Bq	becquerel
BSFR	bulk survey for release
BWCS	BWXT Conversion Services, LLC
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CFR	<i>Code of Federal Regulations</i>
Ci	curie
CMS	corrective measures study
D&D	decontamination and decommissioning
DAS	Disposal Authorization Statement
DFF&O	<i>The April 13, 2010 Director's Final Findings and Orders for Removal Action and Remedial Investigation and Feasibility Study and Remedial Design and Remedial Action, including the July 16, 2012 Modification thereto</i> (Ohio EPA 2012)
DOE	U.S. Department of Energy
dps	disintegration per second
DUF ₆	depleted uranium hexafluoride
EMS	Environmental Management System
FBP	Fluor-BWXT Portsmouth LLC
Gy	gray
IRM	interim remedial measure
kg	kilogram
lbs	pounds
LFRG	Low-level Waste Disposal Facility Review Group
LLW	low-level radioactive waste
µg/g	microgram per gram (equivalent to part per million)
µg/kg	microgram per kilogram (equivalent to part per billion)
µg/L	microgram per liter (equivalent to part per billion)
µg/m ³	microgram per cubic meter
mg	milligram
mg/L	milligram per liter (equivalent to part per million)
mrem	millirem
mSv	millisievert
NCRP	National Council on Radiation Protection
NEPA	National Environmental Policy Act
NESHAP	National Emission Standards for Hazardous Air Pollutants
NPDES	National Pollutant Discharge Elimination System
Ohio EPA	Ohio Environmental Protection Agency
OSWDF	on-site waste disposal facility
OVEC	Ohio Valley Electric Corporation
PCB	polychlorinated biphenyl
pCi/g	picocurie per gram
pCi/L	picocurie per liter
pCi/mL	picocurie per milliliter
pCi/m ³	picocurie per cubic meter
PK	Peter Kiewit
PORTS	Portsmouth Gaseous Diffusion Plant
ppb	part per billion

ppm	part per million
rad	radiation absorbed dose
RCRA	Resource Conservation and Recovery Act
rem	roentgen equivalent man
RFI	RCRA facility investigation
SODI	Southern Ohio Diversification Initiative
Sv	sievert
TCE	trichloroethene
TLD	thermoluminescent dosimeter
TSCA	Toxic Substances Control Act
TUa	acute toxicity unit
USEC	United States Enrichment Corporation
U.S. EPA	U.S. Environmental Protection Agency
VOC	volatile organic compound
WEMS	Wastren-EnergX Mission Support, LLC

DEFINITIONS

absorption – In radiological terms, the taking up of energy from radiation by the medium or tissue through which the radiation is passing.

activity – See “radioactivity.”

air stripper – Equipment that bubbles air through water to remove volatile organic compounds from the water.

alpha activity – The rate of emission of alpha particles from a given material.

alpha particle – A positively charged particle consisting of two protons and two neutrons, identical with the nucleus of a helium atom; emitted by several radioactive substances.

ambient air – The atmosphere around people, plants, and structures. Ambient air usually means outdoor air (as opposed to indoor air).

analyte – The specific component that is being measured in a chemical analysis.

aquifer – A permeable layer of sand, gravel, and/or rock below the ground surface that is capable of yielding quantities of groundwater to wells and springs. A subsurface zone that yields economically important amounts of water to wells.

atom – Smallest unit of an element capable of entering into a chemical reaction.

background radiation – The radiation in humans’ natural environment, including cosmic rays and radiation from the naturally-occurring radioactive elements.

beta activity – The rate of emission of beta particles from a given material.

beta particle – A negatively charged particle emitted from the nucleus of an atom during radioactive decay. It has a mass and charge equal to those of an electron.

biota – Animal and plant life characterizing a given region.

categorical exclusion – A class of actions that either individually or cumulatively do not have a significant effect on the human environment and therefore do not require preparation of an environmental assessment or environmental impact statement under the National Environmental Policy Act.

chain-of-custody – A process that documents custody and control of a sample through sample collection, transportation and analysis.

closure – Formal shutdown of a hazardous waste management facility under the Resource Conservation and Recovery Act or Comprehensive Environmental Response, Compensation, and Liability Act.

compliance – Fulfillment of applicable regulations or requirements of a plan or schedule ordered or approved by a government authority.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) – An act to provide for liability, compensation, cleanup, and emergency response for hazardous substances released to the environment and the cleanup of inactive hazardous waste disposal sites.

concentration – The amount of a substance contained in a unit volume or mass of a sample.

contaminant – Any substance that enters a system (the environment, food, the human body, etc.) where it is not normally found. Contaminants include substances that spoil food, pollute the environment, or cause other adverse effects.

cosmic radiation – Ionizing radiation with very high energies that originates outside the earth's atmosphere. Cosmic radiation is one contributor to natural background radiation.

critical habitat – Specific geographic areas, whether occupied by a species listed under the Endangered Species Act or not, that are essential for conservation of the species and that have been formally designated by a rule published in the Federal Register.

curie (Ci) – A unit of radioactivity, defined as that quantity of any radioactive nuclide which has 3.7×10^{10} (37 billion) disintegrations per second. Several fractions of the curie are commonly used:

millicurie (mCi) – 10^{-3} Ci, one-thousandth of a curie; 3.7×10^7 disintegrations per second.

microcurie (μCi) – 10^{-6} Ci, one-millionth of a curie, 3.7×10^4 disintegrations per second.

picocurie (pCi) – 10^{-12} Ci, one-trillionth of a curie; 0.037 disintegration per second.

decontamination and decommissioning – Removing equipment, demolishing buildings, disposing of wastes, and investigating potential contamination in areas of PORTS that are no longer part of current operations.

deferred unit – An area at PORTS that was in or adjacent to the gaseous diffusion production and operational areas such that remedial activities would have interrupted operations, or an area that could have become recontaminated from ongoing operations.

derived concentration standard – The concentration of a radionuclide in air or water that under conditions of continuous exposure for one year by one exposure mode (i.e., ingestion of water, submersion in air, or inhalation) would result in either a dose of 0.1 rem (100 mrem) or a dose of 5 rem to any tissue, including skin and the lens of the eye. The DOE publication *Derived Concentration Technical Standard* (DOE 2011a) provides the derived concentration standards.

dose – In this document, “dose” is used exclusively to refer to a radiological dose; the energy imparted to matter by ionizing radiation.

- **absorbed dose** – The quantity of ionizing radiation energy absorbed by an organ divided by the organ's mass. The unit of absorbed dose is the rad, equal to 0.01 joule per kilogram in any medium. (1 rad = 0.01 gray).
- **dose** – The product of the absorbed dose (rad) in tissue and a quality factor. Dose is expressed in units of rem (or sievert) (1 rem = 0.01 sievert).
- **effective dose** – The sum of the doses received by all organs or tissues of the body after each one has been multiplied by the appropriate weighting factor. In this document, the term “effective dose” is often shortened to “dose.”

- **collective dose/collective effective dose** – The sums of the doses of all individuals in an exposed population expressed in units of person-rem (or person-sievert). The collective effective dose is also frequently called the “population dose.”

Note that “dose” can also be used to refer to a chemical dose; however, chemical doses are not discussed in this document.

downgradient – The direction that groundwater flows; similar to downstream for surface water.

downgradient well – A well installed downgradient of a site that may be capable of detecting migration of contaminants from a site.

duplicate sample – a sample collected from the same location at the same time and using the same sampling device (if possible) as the regular sample.

effluent – A liquid or gaseous discharge to the environment.

effluent monitoring – The collection and analysis of samples or measurement of liquid and gaseous effluents to characterize and quantify the release of contaminants, assess radiation exposures to the public, and demonstrate compliance with applicable standards.

Environmental Restoration – A DOE program that directs the assessment and cleanup of its sites (remediation) and facilities (decontamination and decommissioning) contaminated as a result of nuclear-related activities.

exposure (radiation) – The incidence of radiation on living or inanimate material by accident or intent. Background exposure is the exposure to natural background ionizing radiation. Occupational exposure is exposure to ionizing radiation that takes place at a person’s workplace. Population exposure is the exposure to the total number of persons who inhabit an area.

external radiation – The exposure to ionizing radiation when the radiation source is located outside the body.

gamma ray – High-energy short-wavelength electromagnetic radiation emitted from the nucleus of an excited atom. Gamma rays are identical to X-rays except for the source of the emission.

glove box – An enclosure with built-in sleeves and gloves used by a person to manipulate hazardous materials such as highly enriched uranium without directly exposing the person to the material.

groundwater – Any water found below the land surface.

half-life, radiological – The time required for half of a given number of atoms of a specific radionuclide to decay. Each nuclide has a unique half-life; half-lives can range in duration from less than a second to many millions of years.

industrial solid waste landfill – A type of landfill that exclusively disposes of solid waste generated by manufacturing or industrial operations.

in situ – In its original place; field measurements taken without removing the sample from its original location; remediation performed while the contaminated media (e.g., groundwater or soil) remains below the surface or in place.

interim remedial measure (IRM) – Cleanup activities initiated after it has been determined that contamination or waste disposal practices pose an immediate threat to human health and/or the environment. These measures are implemented until a more permanent solution can be made.

internal radiation – Occurs when radionuclides enter the body, for example, by ingestion of food or liquids or by inhalation.

irradiation – Exposure to external radiation.

isotopes – Forms of an element having the same number of protons but differing numbers of neutrons in their nuclei.

maximally exposed individual – A hypothetical individual who remains in an uncontrolled area and would, when all potential routes of exposure from a facility's operations are considered, receive the greatest possible dose.

maximum contaminant level (MCL) – The maximum permissible level of a contaminant in drinking water provided by a public water system.

migration – The transfer or movement of a material through air, soil, or groundwater.

millirem (mrem) – The dose that is one-thousandth of a rem.

monitoring – Process whereby the quantity and quality of factors that can affect the environment or human health are measured periodically to regulate and control potential impacts.

natural radiation – Radiation from cosmic and other naturally occurring radionuclide sources (such as radon) in the environment.

nuclide – An atom specified by atomic weight, atomic number, and energy state.

outfall – The point of conveyance (e.g., drain or pipe) of wastewater or other effluents into a ditch, pond, or river.

part per billion – A unit measure of concentration equivalent to the weight to volume ratio expressed as microgram per liter ($\mu\text{g/L}$) or the weight to weight ratio of microgram per kilogram ($\mu\text{g/kg}$).

part per million – A unit measure of concentration equivalent to the weight to volume ratio expressed as milligram per liter (mg/L), the weight to weight ratio expressed as milligram per kilogram (mg/kg), or the weight to weight ratio of microgram per gram ($\mu\text{g/g}$).

person-rem – A unit of measure for the collective dose to a population group. For example, a dose of 1 rem to 10 individuals results in a collective dose of 10 person-rem.

pH – A measure of the hydrogen ion concentration in an aqueous solution. Acidic solutions have a pH from 0 to 7, neutral solutions have a pH equal to 7, and basic solutions have a pH from 7 to 14.

polychlorinated biphenyls (PCBs) – Man-made chemicals that range from oily liquids to waxy solids. PCBs were used in hundreds of industrial and commercial applications due to their chemical properties until production in the United States ceased in 1977. PCBs have been demonstrated to cause a variety of adverse health effects in animals and possibly cause cancer and other adverse health effects in humans.

preliminary remediation goal – An initial clean-up goal developed early in the decision-making process that is 1) protective of human health and the environment, and 2) complies with applicable or relevant and appropriate requirements. Preliminary remediation goals are intended to satisfy regulatory cleanup requirements.

quality assurance – Any action in environmental monitoring to demonstrate the reliability of monitoring and measurement data.

quality control – The routine application of procedures within environmental monitoring to obtain the required standards of performance in monitoring and measurement processes.

rad – The unit of absorbed dose deposited in a volume of material.

radioactivity – The spontaneous emission of radiation, generally alpha or beta particles or gamma rays, from the nucleus of an unstable isotope.

radionuclide – A radioactive nuclide capable of spontaneous transformation into other nuclides by changing its nuclear configuration or energy level. This transformation is accomplished by the emission of photons or particles.

release – Any discharge to the environment. “Environment” is broadly defined as any water, land, or ambient air.

rem – The unit of dose (absorbed dose in rads multiplied by the radiation quality factor). Dose is frequently reported in units of millirem (mrem), which is one-thousandth of a rem.

remediation – The correction or cleanup of a site contaminated with waste. See “Environmental Restoration.”

reportable quantity – A release to the environment that exceeds reportable quantities as defined by the Comprehensive Environmental Response, Compensation, and Liability Act.

Resource Conservation and Recovery Act (RCRA) – Federal legislation that regulates the transport, treatment, and disposal of solid and hazardous wastes.

riparian – Related to the banks of a river or wetlands adjacent to rivers and streams.

settleable solids – Material settling out of suspension in a liquid within a defined period of time.

source – A point or object from which radiation or contamination emanates.

Superfund – The program operated under the legislative authority of the Comprehensive Environmental Response, Compensation, and Liability Act and Superfund Amendments and Reauthorization Act that funds and conducts U.S. EPA emergency and long-term removal and remedial actions.

surface water – All water on the surface of the earth, as distinguished from groundwater.

suspended solids – Particles suspended in water, such as silt or clay, that can be trapped by a filter.

terrestrial radiation – Ionizing radiation emitted from radioactive materials in the earth’s soils such as potassium-40, radon, thorium, and uranium. Terrestrial radiation contributes to natural background radiation.

transuranics – Elements such as americium, plutonium, and neptunium that have atomic numbers (the number of protons in the nucleus) greater than 92 (uranium). All transuranics are radioactive.

trichloroethene (TCE) – A colorless liquid used in many industrial applications as a cleaner and/or solvent. One of many chemicals that is classified as a volatile organic compound. High levels of TCE may cause health effects such as liver and lung damage and abnormal heartbeat; moderate levels may cause dizziness or headache. The U.S. Environmental Protection Agency Integrated Risk Information System characterizes TCE as carcinogenic to humans by all routes of exposure. This conclusion is based on convincing evidence of a causal association between TCE exposure in humans and kidney cancer.

trip blank – A quality control sample of water that accompanies sample containers from the analytical laboratory, to the field sampling location where environmental samples are collected, back to the analytical laboratory to determine whether environmental samples have been contaminated during transport, shipment, and/or site conditions.

turbidity – A measure of the concentration of sediment or suspended particles in a liquid.

upgradient – In the opposite direction of groundwater flow; similar to upstream for surface water.

upgradient well – A well installed hydraulically upgradient of a site to provide data to compare to a downgradient well to determine whether the site is affecting groundwater quality.

volatile organic compounds (VOCs) – Organic (carbon-containing) compounds that evaporate readily at room temperature. These compounds are present in solvents, degreasers, paints, thinners, and fuels. Due to a number of factors including widespread industrial use, they are commonly found as contaminants in soil and groundwater. VOCs found at PORTS include TCE, vinyl chloride, benzene, and dichloroethenes.

weighting factor (radiation) – The factor by which an absorbed dose (rad) is multiplied to obtain a quantity that expresses, on a common scale for all ionizing radiation, the biological damage to an exposed person. The weighting factor is used because some types of radiation, such as alpha particles, are more biologically damaging than others.

weighting factor (tissue) – A tissue specific number that represents the fraction of the total potential health risk resulting from uniform, whole body irradiation to the specific organ or tissue (bone marrow, lungs, thyroid, etc.).

wetland – An area that is inundated or saturated by surface or groundwater at a frequency and duration sufficient to support, and under normal circumstances does support, a prevalence of vegetation typically adapted for life in saturated soil conditions. Wetlands generally include swamps, marshes, bogs, floodplains, fens, and similar areas. A jurisdictional wetland is one that falls under state or federal regulatory authority; a non-jurisdictional wetland does not.

EXECUTIVE SUMMARY

PURPOSE

This Annual Site Environmental Report is prepared to summarize environmental monitoring and compliance activities conducted at the U.S. Department of Energy (DOE) Portsmouth Gaseous Diffusion Plant (PORTS) for calendar year 2015. Environmental monitoring is conducted to assess the impact, if any, that site operations may have on public health and the environment. The report fulfills a requirement of DOE Order 231.1B, *Environment, Safety and Health Reporting*, for preparation of an annual summary of environmental data to characterize environmental management performance. The Annual Site Environmental Report also provides the means by which DOE demonstrates compliance with the radiation protection requirements of DOE Order 458.1, *Radiation Protection of the Public and the Environment*.

SITE AND OPERATIONS OVERVIEW

PORTS, which produced enriched uranium via the gaseous diffusion process from 1954 to 2001, is one of three uranium enrichment facilities originally built in the United States; the other two were constructed in Oak Ridge, Tennessee and Paducah, Kentucky, respectively. PORTS is located on 5.9 square miles in Pike County, Ohio. The county has approximately 28,256 residents (U.S. Census Bureau 2016).

DOE is responsible for decontamination and decommissioning (D&D) of the gaseous diffusion process buildings and associated facilities, environmental restoration, waste management, depleted uranium hexafluoride (DUF₆) conversion, and management of other non-leased facilities at PORTS. DOE contractors Fluor-BWXT Portsmouth LLC (FBP), Wastren-EnergX Mission Support, LLC (WEMS), and BWXT Conversion Services, LLC (BWCS) managed DOE programs at PORTS in 2015.

FBP was responsible for the following activities: 1) D&D of the former gaseous diffusion process buildings and associated facilities; 2) environmental restoration of contaminated areas; 3) monitoring and reporting on environmental compliance; 4) disposition of legacy radioactive waste; 5) uranium management; and 6) operation of the site's waste storage facilities.

WEMS provided facility support services including the following: 1) maintenance of facilities, grounds, and roadways; 2) janitorial services; 3) security access for DOE facilities; 4) training; 5) records and fleet management; and 6) information technology/network support for DOE operations.

BWCS was responsible for operations associated with the DUF₆ Conversion Facility, including surveillance and maintenance of DUF₆ cylinders, and environmental compliance and monitoring activities associated with operation of the DUF₆ Conversion Facility. DUF₆, which is a product of the uranium enrichment process, is stored in cylinders on site. The DUF₆ Conversion Facility converts DUF₆ into uranium oxide and aqueous hydrogen fluoride. The uranium oxide is made available for beneficial reuse, storage, or disposal, and the aqueous hydrogen fluoride is sold for reuse.

Centrus Energy Corp. (Centrus), formerly USEC, Inc., has been developing a gaseous centrifuge uranium enrichment plant at PORTS. The Centrus Lead Cascade, which is a small-scale demonstration centrifuge for uranium enrichment, has been operating since 2006 for demonstration and testing purposes. Construction of the commercial scale American Centrifuge Plant (ACP) was on hold at the end of 2015. Both of these facilities (the Lead Cascade and the ACP) are housed in existing buildings at PORTS that are leased from DOE.

With the exception of Chapter 2, Compliance Summary; Chapter 4, Environmental Radiological Program Information; and Chapter 5, Environmental Non-Radiological Program Information, this report does not cover Centrus operations at PORTS because their operations are not subject to DOE Orders. Centrus data

are included in these chapters to provide a more complete picture of the operations in place at PORTS to detect and assess potential impacts to human health and the environment resulting from PORTS activities.

ENVIRONMENTAL MONITORING AND RADIOLOGICAL DOSE SUMMARY

Extensive environmental monitoring is completed at PORTS to comply with environmental regulations, permit requirements, and DOE Orders, and assess the impact, if any, that site operations may have on public health and the environment. The *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a) describes the DOE environmental monitoring programs at PORTS, with the exception of groundwater monitoring. Groundwater monitoring, which also includes related surface water monitoring and residential water supply monitoring, is described in the *Integrated Groundwater Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2014b, DOE 2015d).

Environmental monitoring includes the collection of samples of air, water, soil, sediment, and biota (vegetation, deer, fish, crops, milk, and eggs). Samples are collected at varying frequencies (weekly, monthly, quarterly, annually, or biennially). In 2015, environmental monitoring information was collected for the following programs:

- ambient air
- external radiation
- discharges to surface water
- local surface water
- sediment
- soil
- biota (vegetation, deer, fish, crops, milk, and eggs)
- groundwater.

Samples are analyzed for radionuclides, metals, and/or other chemicals that could be present in the environment due to PORTS activities, although many of these analytes also occur naturally or can be present due to human activities not related to PORTS. Over 3000 samples from these programs are collected on an annual basis.

Potential impacts on human health from radionuclides released by PORTS operations are calculated based on environmental monitoring data. This impact, if any, is calculated in terms of a dose. A dose can be caused by radionuclides released into the air and/or water, or radiation emanating directly from buildings or other objects at PORTS. PORTS complies with the following dose limits:

- The U.S. Environmental Protection Agency (U.S. EPA) has established a dose limit of 10 millirem (mrem)/year from radionuclides released to the air in Title 40 of the *Code of Federal Regulations* (CFR), Part 61, National Emission Standards for Hazardous Air Pollutants (NESHAP), Subpart H, National Emission Standards for Emissions of Radionuclides Other Than Radon from DOE Facilities (40 CFR Part 61, Subpart H).
- The DOE has established a dose limit for members of the general public in DOE Order 458.1, which is as low as reasonably achievable¹, but no more than 100 mrem/year for the dose from radionuclides

¹ “As low as reasonably achievable” is an approach to radiation protection to manage and control releases of radioactive material to the environment, the workforce, and members of the public so that levels are as low as reasonable, taking into account societal, environmental, technical, economic, and public policy considerations. As low as reasonably achievable is not a specific release or dose limit, but a process that has the goal of optimizing control and managing release of radioactive material to the environment and doses so they are as far below the applicable limits as reasonably achievable. This approach optimizes radiation protection.

from all potential pathways of exposure including inhalation, ingestion of water and soil/sediments, consumption of food, and direct radiation.

To aid in comparing sampling results for air and water to the 100 mrem/year dose limit, the 100 mrem/year limit is converted into a derived concentration standard (DOE 2011a). The derived concentration standard is the concentration of a radionuclide in air or water that under conditions of continuous exposure for one year by one exposure mode (ingestion of water or inhalation of air) would result in a dose of 100 mrem. A concentration of 100% of the derived concentration standard would equate to a dose at the DOE limit of 100 mrem/year.

Environmental monitoring data collected in 2015 are consistent with data collected in previous years and indicate that radionuclides, metals, and other chemicals released by PORTS operations have a minimal effect on human health and the environment. The following sections summarize the results of environmental monitoring conducted at PORTS in 2015:

Ambient air. Radionuclides in ambient air are monitored at 15 monitoring stations that are located on site, at the site perimeter, within the local area, and west of PORTS in an area not potentially impacted by PORTS operations (the background location). Samples are analyzed monthly or quarterly for radionuclides that can be associated with PORTS operations. These radionuclides are transuranics (manmade elements greater than atomic number 92 [americium-241, neptunium-237, plutonium-238, plutonium-239/240]), a fission product (technetium-99), uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238).

Uranium, uranium isotopes, and technetium-99 were detected at the ambient air monitoring stations in 2015. Plutonium-238 was also detected in a single sample of more than 180 samples collected at the monitoring stations. With the exception of uranium-233/234, the highest levels of each radionuclide in air were less than 0.1% of the DOE derived concentration standards (DOE 2011a). The highest level of uranium-233/234 was 3% of the derived concentration standard.

The ambient air monitoring data were used to calculate the potential worst case dose from the air pathway to a hypothetical person living at the monitoring station. This approach is unlikely to underestimate the dose because it assumes an individual resides at the location of the monitoring station breathing the air at that location for 24 hours/day, 365 days/year. The highest net dose calculation for the off-site ambient air stations (0.0012 mrem/year) was at stations A28 and A41A, which are west of PORTS on Camp Creek Road and northeast of PORTS at Zahns Corner, respectively. This net dose was calculated by subtracting the dose at the background station from the dose at the monitoring stations closer to PORTS. This hypothetical dose is well below the 10 mrem/year limit applicable to PORTS in NESHAP (40 CFR Part 61, Subpart H).

Discharges to surface water. Discharges of chemicals and other parameters that measure water quality are regulated by the National Pollutant Discharge Elimination System (NPDES) under the Clean Water Act. Water from PORTS is discharged to off-site water bodies through 11 locations called NPDES outfalls. Ohio EPA selects the chemicals monitored at the outfalls based on the chemical characteristics of the water discharged from the outfall. Outfalls are also monitored for radionuclides. Sampling frequencies vary from weekly to quarterly.

Transuranic radionuclides were not detected in any of the samples collected from FBP and Centrus NPDES external outfalls in 2015. Uranium discharges from the FBP and Centrus external outfalls were estimated at 8.9 kg. Total radioactivity (technetium-99 and isotopic uranium) released from the FBP outfalls was estimated at 0.059 Ci.

Water from the NPDES outfalls is discharged to or eventually flows to the Scioto River. Data for radionuclide discharges is used to calculate a potential worst case dose to a hypothetical member of the public who is exposed to water from the Scioto River. Exposure pathways considered were ingestion of water, ingestion of fish, swimming, boating, and shoreline activities. This exposure scenario is unlikely to underestimate the dose because the Scioto River is not used for drinking water downstream of PORTS (97% of the hypothetical dose from liquid effluents is from drinking water). The dose from radionuclides released to the Scioto River in 2015 (0.0017 mrem) is significantly less than the 100 mrem/year DOE limit in DOE Order 458.1 for all radiological releases from a facility.

Discharges of chemicals and other non-radiological parameters that affect water quality are regulated by Ohio EPA in NPDES permits issued to FBP, BWCS, and Centrus. In 2015, the overall FBP NPDES compliance rate with the NPDES permit was 99%. Discharge limitations at the FBP NPDES monitoring locations were exceeded on seven occasions with these exceedances attributed to concentrations of chlorine or other chemicals in cooling tower or sanitary sewage discharges. The overall Centrus and BWCS compliance rates were 100%.

External radiation. External radiation is measured continuously with thermoluminescent dosimeters (TLDs) at five locations near the DUF₆ cylinder storage yards and 19 on-site and off-site locations (12 of the ambient air monitoring stations and seven additional on-site locations). TLDs are placed at the monitoring locations at the beginning of each quarter, remain at the monitoring location throughout the quarter, and are removed from the monitoring location at the end of the quarter and sent to the laboratory for processing. A new TLD replaces the removed device. Radiation is measured as a whole body dose (in mrem), which is the dose that a person would receive if they were continuously present at the monitored location.

The external radiation measured for the PORTS environmental monitoring program includes both external background radiation and radiation emanating from PORTS activities such as storage of DUF₆ cylinders. The total annual dose measured in 2015 at station A29, on the west side of PORTS near the Ohio Valley Electric Corporation (OVEC), was 100 mrem/year. The total dose measured at eight of the off-site/background monitoring stations averaged 92 mrem/year. A net dose calculation was completed for a representative off-site member of the public, such as an office worker at OVEC, based on the 8 mrem/year difference between the average off-site background dose (92 mrem/year) and the dose at station A29 (100 mrem/year). Assuming that the worker was exposed to this radiation for 250 days/year, one hour outdoors and 8 hours indoors, the dose to this worker is 0.96 mrem.

A person living in the United States receives an average dose of approximately 311 mrem/year from natural sources of radiation (National Council on Radiation Protection [NCRP] 2009). The potential estimated dose from external radiation to a member of the public (0.96 mrem/year to a worker near station A29) is approximately 0.3% of the average yearly natural radiation exposure for a person in the United States and is significantly less than the 100 mrem/year limit to a member of the public in DOE Order 458.1 for all radiological releases from a facility.

Local surface water. Samples of surface water are collected semiannually from 14 locations upstream and downstream from PORTS at locations on the Scioto River, Little Beaver Creek, Big Beaver Creek, and Big Run Creek and background locations on local streams approximately 10 miles north, south, east, and west of PORTS. Samples are analyzed for radionuclides.

Technetium-99 was detected in samples collected from Little Beaver Creek (RW-7 and RW-8) and Big Beaver Creek downstream from PORTS (RW-13). Uranium and uranium isotopes were detected at most of the surface water sampling locations. These detected concentrations of radionuclides were less than 1% of the DOE derived concentration standards (DOE 2011a). This derived concentration standard is

based upon direct use of the surface water as drinking water. This comparison is unlikely to underestimate the dose because surface water around PORTS is not used for drinking water.

Sediment. Samples of sediment are collected annually at 17 monitoring locations, which include the 14 locations sampled for the local surface water monitoring program (Scioto River, Little Beaver Creek, Big Beaver Creek, Big Run Creek, and background locations on local streams) and three on-site NPDES outfalls on the east and west sides of PORTS. Samples are analyzed for radionuclides and polychlorinated biphenyls (PCBs).

Neptunium-237 and/or plutonium-239/240 were detected at Little Beaver Creek sampling location RM-7, on-site NPDES Outfall 001 (RM-11), and Big Beaver Creek sampling location RM-13. Technetium-99 was detected in samples collected from Big Beaver Creek at RM-13, Big Run Creek at RM-3, on-site near NPDES outfalls 010 and 013 (RM-10), and downstream locations on Little Beaver Creek (RM-11, RM-7, and RM-8). Uranium and uranium isotopes were also detected at each of the sampling locations, including upstream and background sampling locations..

The dose assessment based on the detections of radionuclides in sediment at the off-site sediment sampling location with the detections of radionuclides that could cause the highest dose to a member of the public (RM-7 on Little Beaver Creek) calculated a dose of 0.035 mrem/year, which is well below the DOE standard of 100 mrem/year in DOE Order 458.1.

PCBs were detected in samples collected from Little Beaver Creek (RM-7, RM-8, and RM-11), Big Beaver Creek (RM-13), Big Run Creek (RM-2 and RM-3), and on-site in the West Drainage (RM-10). None of the detections of PCBs in sediment around PORTS were above the risk-based regional screening level developed by U.S. EPA and utilized by Ohio EPA of 240 micrograms per kilogram ($\mu\text{g}/\text{kg}$) or parts per billion (ppb) (U.S. EPA 2015).

Soil. Soil samples are collected annually at 15 ambient air monitoring locations (on-site, fence line, off-site and background locations) and analyzed for radionuclides.

Plutonium-239/240 was detected at two ambient air monitoring stations: A6 (Piketon) and A9 (southwest of the plant on Old U.S. Route 23). These detections were much less than 0.1 pCi/g and most likely present due to atmospheric fallout from nuclear weapons testing. The detections are much less than the soil screening level for plutonium-239/240 in residential soil (3.78 pCi/g) calculated using the exposure assumptions in the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b).

Uranium, uranium-233/234, uranium-235/236, and/or uranium-238 were detected at each of the sampling locations. Uranium and uranium isotopes are usually detected at similar levels at all the soil sampling locations, including the background location (A37), which suggests that the uranium detected in these samples is due to naturally-occurring uranium.

The dose assessment based on the detections of radionuclides in soil at the off-site ambient air station with the concentrations of radionuclides that could cause the highest dose to a member of the public (station A24, north of PORTS on Shyville Road) calculated a dose of 0.044 mrem/year, which is well below the DOE limit of 100 mrem/year in DOE Order 458.1.

Biota (vegetation, deer, fish, crops, milk, and eggs). Vegetation samples are collected annually at 15 ambient air monitoring locations (on-site, fence line, off-site and background locations). Deer samples are collected annually or as available from deer killed on site in motor vehicle collisions. Fish are collected annually from on-site and off-site streams (Little Beaver Creek, Big Beaver Creek and the

Scioto River, as available). Crops, milk, and eggs are collected annually (as available) from the local community. All samples are analyzed for radionuclides. Fish are also analyzed for PCBs.

Radionuclides were not detected in samples of deer, fish, crops, milk, and eggs collected in 2015. Uranium, uranium-233/234, and uranium-238 were detected in vegetation samples collected in 2015. The dose assessment for a member of the public based on consumption of beef cattle that would eat grass contaminated with radionuclides calculated a dose of 0.0027 mrem/year, which is well below the DOE Order 458.1 limit of 100 mrem/year.

PCBs were detected in the fish samples collected from Little Beaver Creek at 278 µg/kg. PCBs were also detected in upstream and downstream Big Beaver Creek fish samples at 21.8 and 20.8 µg/kg, respectively. These detections were compared to the Ohio Fish Consumption Advisory Chemical Limits provided in the *State of Ohio Cooperative Fish Tissue Monitoring Program Sport Fish Tissue Consumption Advisory Program* (Ohio EPA 2008). These limits are set for the following consumption rates: unrestricted, 1/week, 1/month, 6/year, and do not eat. The concentration of PCBs detected in the fish caught on site in Little Beaver Creek (RW-8) is above the 1/week maximum limit (220 µg/kg) and below the 1/month maximum limit (1000 µg/kg). The concentrations of PCBs detected in fish collected from Big Beaver Creek (20.8 and 21.8 µg/kg) are less than the unrestricted limit (50 µg/kg). Fish were not collected from the Scioto River in 2015.

Groundwater. Groundwater contamination at PORTS is contained on site. More than 300 wells are sampled at varying frequencies to monitor corrective actions, movement of groundwater contaminants, and groundwater quality. Samples are analyzed for volatile organic compounds (VOCs), radionuclides, metals, and other parameters, specific to the contaminants present at the monitoring area. In general, concentrations of contaminants detected within the groundwater plumes at PORTS were stable or decreasing in 2015. No VOCs were detected in any of the seven off-site monitoring wells that monitor the X-749/X-120 groundwater plume near the southern boundary of PORTS. Residential water supplies near PORTS were monitored to verify that site contaminants have not migrated into off-site drinking water wells. Results of this program indicate that PORTS has not affected drinking water wells outside the site boundaries.

Dose. To demonstrate compliance with DOE Order 458.1, this Annual Site Environmental Report includes radiological dose calculations for the dose to the public from radionuclides released to the environment based on environmental monitoring data collected by DOE contractors and Centrus (discussed in the previous paragraphs). Figure 1 provides a comparison of the doses from various common radiation sources.

The maximum dose that a member of the public could receive from radiation released by PORTS in 2015 is 1.1 mrem. This maximum dose assumes that the same individual, or representative person, works at a private company located on the west side of the PORTS reservation, and lives in the immediate vicinity of PORTS.




Figure 1. Comparison of dose from various common radiation sources.

The representative person is assumed to be exposed to the maximum dose calculated from each pathway. The dose is based on:

- 0.0017 mrem from radionuclides released to the Scioto River,
- 0.96 mrem from external radiation at station A29 on the west side of PORTS,
- 0.082 mrem based on exposure to radionuclides detected at off-site monitoring locations in 2015 (sediment [0.035 mrem], soil [0.044 mrem], and biota [0.0027 mrem]), and
- 0.037 mrem from radionuclides released to the air (the dose calculated by the U.S. EPA model required to demonstrate compliance with the NESHAP 10 mrem/year standard [40 CFR Part 61 Subpart H]).

This dose (1.1 mrem) is significantly less than the 100 mrem/year limit set in DOE Order 458.1 for the dose to a member of the public from radionuclides from all potential pathways. The dose to a member of the public from airborne radionuclides released by PORTS (0.037 mrem) is also significantly less than the 10 mrem/year standard set by U.S. EPA in NESHAP (40 CFR Part 61 Subpart H). A person living in the United States receives an average dose of approximately 311 mrem/year from natural sources of radiation (National Council on Radiation Protection [NCRP] 2009).

ENVIRONMENTAL COMPLIANCE

DOE and/or the responsible DOE contractor (FBP or BWCS) have been issued permits for discharge of water to surface streams, air emission permits, and a permit for the storage of hazardous waste.

FBP and BWCS are responsible for preparing a number of reports for compliance with environmental regulations. These reports include: an annual groundwater monitoring report; a biennial hazardous waste report; an annual PCB document log; an annual summary of radionuclide air emissions and the associated dose to the public from these emissions; annual or biennial reports of specified non-radiological air emissions; a monthly report of National Pollutant Discharge Elimination System (NPDES) monitoring data; an annual hazardous chemical inventory; and an annual toxic chemical release inventory.

Centrus is responsible for compliance activities directly associated with the ACP and Lead Cascade including air emission permits associated with the gaseous centrifuge uranium enrichment operations (the proposed ACP and Lead Cascade), NPDES outfalls, and management of wastes generated by their current operations.

DOE/FBP received five Notices of Violation in 2015 as described in the following paragraphs.

FBP received a Notice of Violation on March 2, 2015 from an inspection conducted on February 4, 2015 by the Ohio Public Utilities Commission of a commercial vehicle transporting laundry and respirators to Tennessee. The inspection found that FBP's method of securing the laundry bins and other material within the closed trailer was not adequate. Procedures were revised to provide consistent loading formations for laundry bins and verify proper loading prior to off-site transport. FBP paid a fine of \$1680. No further actions were required.

DOE/FBP received a Notice of Violation on July 6, 2015 from the inspection conducted by U.S. EPA on April 13-14, 2015. The Notice of Violation was for failing to label containers of used oil with the words "used oil" (the containers were labeled "waste oil"). The containers were immediately labeled "used oil". No further action was required.

FBP received a Notice of Violation dated July 17, 2015 from the Ohio Public Utilities Commission due to an incident where radiologically-contaminated rags from a PORTS on-site laboratory were transported off site with ordinary sanitary trash. The rags became contaminated when they were used to wipe out a laboratory fume hood dedicated to non-radiological use that had not been used in over a year. The contamination on the rags likely migrated from the ductwork connected to the hood, although the lab had not been used for radiological work in more than 20 years. The truck had not disposed of the trash. It was verified that no contamination had spread outside of the sealed bag. Procedures were revised to increase radiological surveys of all laboratory fume hoods. FBP paid a fine of \$5250. No further actions were required.

FBP received a Notice of Violation dated July 20, 2015 from the Ohio Environmental Protection Agency (Ohio EPA) due to the detection of total coliform in a drinking water sample collected from the PORTS water supply at an on-site bathroom sink. Total coliform are a type of bacteria naturally present in the environment that may indicate the presence of other potentially harmful bacteria. The cause of the detection was investigated and determined to be a dirty faucet aerator, which was thoroughly disinfected and replaced. The area was posted and follow-up samples were collected as required by Ohio EPA with no additional detections of total coliform. No further actions were required.

FBP received a Notice of Violation from Ohio EPA dated August 18, 2015 for exceedances of NPDES permit limitations for chlorine, water temperature, and acute toxicity between May 2014 and May 2015. The chlorine exceedances were caused by operational issues and were corrected on the day of the exceedances. The temperature exceedance (in 2014) resulted from unusually hot and dry weather. Acute toxicity is a measurement of the characteristics of water discharged from an outfall that could be harmful to aquatic organisms. The toxicity resulted from an operational reduction in water flow to the outfall. The amount of sodium bisulfite, a chemical used to remove chlorine from water, was not properly decreased when the water flow was reduced. The overfeed of sodium bisulfite caused acute toxicity measurements of 1.41 acute toxicity units (TU_a) to two test organisms (fathead minnows and water fleas). The discharge limitations for acute toxicity are 1.0 TU_a for both organisms. The acute toxicity measurement is based on placing the aquatic organisms in diluted and undiluted samples of water from the outfall (or effluent). The discharge limitation (1.0 TU_a) is based on the concentration of the effluent that is lethal to 50% of the aquatic organisms. The sample result of 1.41 TU_a indicates that 50% of the aquatic organisms would be killed by a dilution of 71% effluent. The toxicity lasted no more than 24 hours. FBP reported the violations to Ohio EPA at the time of the occurrences as required by the NPDES permit. No further actions were required.

ENVIRONMENTAL PROGRAMS

D&D, Environmental Restoration, Waste Management, and Public Awareness Programs are conducted at PORTS to protect and inform the local population, improve the quality of the environment, and comply with federal and state regulations.

D&D Program

D&D of the PORTS gaseous diffusion process buildings and associated facilities is proceeding in accordance with the *April 13, 2010 Director's Final Findings and Orders for Removal Action and Remedial Investigation and Feasibility Study and Remedial Design and Remedial Action (which includes the July 16, 2012 Modification thereto)* (D&D DFF&O) (Ohio EPA 2012). The D&D DFF&O is a legal agreement between Ohio EPA and DOE that governs the process for D&D of the buildings/structures that are no longer in use at PORTS.

Ohio EPA concurred with the records of decision for the process buildings and waste disposition in July and June of 2015, respectively. The record of decision for the process buildings and other facilities selected controlled removal of stored waste and materials, demolition of the buildings or structures, and

characterization of materials for disposal or disposition (DOE 2015e). The record of decision for waste disposition selected a combination of on-site and off-site disposal (DOE 2015f), which includes construction of an on-site waste disposal facility (OSWDF).

Implementation of the selected remedial actions began after completion the records of decision. Ohio EPA concurred with Phase I and Phase II of the remedial design/remedial action work plan for the OSWDF (DOE 2015g) in September and October 2015, respectively, which allowed initial site construction activities such as tree clearing, fencing, utility installation, and installation of erosion and sediment controls. These activities began after approval of the work plan and continued in 2016.

Environmental Restoration Program

The Environmental Restoration Program was established by DOE in 1989 to identify, control, and remediate environmental contamination at PORTS. The initial assessment and investigation of PORTS under the RCRA corrective action process was completed in the 1990s. Corrective actions, also called remedial actions, are underway in each quadrant. The Environmental Restoration Program monitors and maintains five closed landfills in accordance with Ohio EPA regulations and operates four groundwater treatment facilities to treat contaminated groundwater from the on-site groundwater plumes that are contaminated with industrial solvents, including trichloroethene (TCE).

With the beginning of D&D, investigation of areas known as “deferred units” is beginning to occur. Deferred units are areas that were in or adjacent to the gaseous diffusion production and operational areas such that remedial activities would have interrupted operations, or were areas that could have become recontaminated from ongoing operations. Ohio EPA deferred investigation/remedial action of soil and groundwater associated with these units until D&D of PORTS (or until the area no longer met the requirements for deferred unit status). Chemical and/or radionuclide contaminants present in the deferred units were contained on site and were not a threat to the public. Ongoing environmental monitoring and on-site worker health and safety programs monitor the contaminants in these areas prior to D&D.

The *Deferred Units Resource Conservation and Recovery Act Facility Investigation/Corrective Measures Study Work Plan*, revised to respond to Ohio EPA comments received in 2013 through 2015, was submitted to Ohio EPA in March 2015 (DOE 2015a). Ohio EPA approved the work plan in June 2015. Soil and groundwater sampling outlined in the work plan started in July 2015 and continued in 2016.

Waste Management Program

The DOE Waste Management Program at PORTS directs the safe storage, treatment, and disposal of waste generated from D&D of facilities that are no longer in use, past plant operations, ongoing plant maintenance, and ongoing environmental restoration projects. In 2015, FBP shipped approximately 9200 tons of waste or other materials to off-site facilities for treatment, disposal, recycling, or reuse.

With the beginning of D&D at PORTS, DOE is placing increased emphasis on the evaluation of materials generated by D&D for reuse or recycling. An agreement between DOE and the Southern Ohio Diversification Initiative (SODI) allows DOE to transfer excess equipment, clean scrap materials, and other assets to SODI. SODI first attempts to reuse the excess equipment and property within the local community. Pursuant to the agreement, if SODI is unable to place the property for reuse in the local community, SODI may sell the property. When SODI sells the property, the proceeds are used to support economic development in the southern Ohio region. In 2015, SODI received approximately 236 tons of materials from PORTS, primarily recyclable metals.

Public Awareness Program

DOE provides a public Environmental Information Center to allow access to all documents used to make decisions on remedial actions being taken at PORTS. The information center is located just north of

PORTS at the Ohio State University Endeavor Center (Room 207), 1862 Shyville Road, Piketon, Ohio 45661. The Information Center is open 9 a.m. to noon Monday and Tuesday, noon to 4 p.m. Wednesday and Thursday, or by appointment (call 740-289-8898). The email address is portseic@pma-iss.com and web site is portsmoutheic.com. Additional information is provided by the DOE Site Office (740-897-5010) and the Office of Public Affairs (740-897-3933). This Annual Site Environmental Report and other information can also be obtained from the DOE web site for PORTS at www.energy.gov/pppo or the FBP web site at www.fbportsmouth.com.

Public update meetings and public workshops on specific topics are also held to keep the public informed and to receive their comments and questions. Periodically, fact sheets about major projects are written for the public. Additionally, notices of document availability and public comment periods, as well as other communications on the program, are regularly distributed to the local newspaper and those on the community relations mailing list, neighbors within 2 miles of the plant, and plant employees.

The PORTS Site Specific Advisory Board, comprised of citizens from the local area, provides public input and recommendations to DOE on environmental remediation, waste management, and related issues at PORTS. Regularly scheduled meetings that are open to the public are held between DOE and the PORTS Site Specific Advisory Board. Additional information about the board can be obtained at www.ports-ssab.energy.gov or by calling 740-289-5249.

The PORTS Envoy Program matches employee volunteers with community stakeholders such as families living next to DOE property, community groups, and local government organizations. The envoys communicate information about PORTS D&D and other site issues to the stakeholders and are available to answer stakeholder questions about PORTS.

An educational outreach program facilitated by a DOE grant administered by Ohio University includes a project in which local high school students produce a summary of the Annual Site Environmental Report for distribution to the public. The DOE Portsmouth/Paducah Project Office web site at www.energy.gov/pppo provides additional information about this project.

DOE has worked with the State Historic Preservation Office, Advisory Council on Historic Preservation, Tribal Nations, and individual members of the public interested in historic preservation to determine how best to document the history associated with the gaseous diffusion process buildings and other areas that are part of D&D. The PORTS Virtual Museum (www.portsvirtualmuseum.org) preserves photos, video, oral histories, and other information associated with operation, remediation, and D&D of PORTS.

1. INTRODUCTION

1.1 SUMMARY

The Portsmouth Gaseous Diffusion Plant (PORTS) is located on a 5.9-square-mile site in a rural area of Pike County, Ohio (see Figure 1.1). U.S. Department of Energy (DOE) activities at PORTS include decontamination and decommissioning (D&D) of the process buildings and associated facilities formerly used for the gaseous diffusion process of uranium enrichment, environmental restoration, waste management, and uranium operations. Fluor-BWXT Portsmouth LLC (FBP) is the DOE contractor responsible for D&D of PORTS, which includes the three gaseous diffusion process buildings and other associated facilities. BWXT Conversion Services, LLC (BWCS) is responsible for operations associated with the Depleted Uranium Hexafluoride (DUF₆) Conversion Facility.

The United States Enrichment Corporation (USEC) operated the gaseous diffusion uranium enrichment facilities at PORTS until 2001. USEC, Inc. (the parent company of USEC) became Centrus Energy Corp. (Centrus) in 2014 after a financial restructuring. Centrus leases facilities at PORTS for the development and planned operation of its gaseous centrifuge uranium enrichment facility – the American Centrifuge Plant (ACP).

In general, activities conducted by Centrus are not covered by this document because their operations are not subject to DOE Orders. However, some Centrus environmental compliance information is provided in Chapter 2 and radiological and non-radiological environmental monitoring program information is discussed in Chapters 4 and 5, respectively. Centrus data are included in these chapters to provide a more complete picture of the programs in place at PORTS to detect and assess potential impacts to human health and the environment resulting from PORTS activities.



Figure 1.1 The Portsmouth Gaseous Diffusion Plant.

1.2 BACKGROUND INFORMATION

PORTS, which produced enriched uranium via the gaseous diffusion process from 1954 through 2001, is owned by DOE. In 1993, DOE leased the uranium production facilities at the site to USEC, which was established by the Energy Policy Act of 1992.

DOE is responsible for D&D of the gaseous diffusion process buildings and associated facilities, environmental restoration, waste management, and uranium operations. DOE contractors FBP, Wastren-EnergX Mission Support, LLC (WEMS), and BWCS managed DOE programs at PORTS in 2015.

FBP was responsible for the following activities: 1) D&D of the former gaseous diffusion process building and associated facilities; 2) environmental restoration of contaminated areas; 3) monitoring and reporting on environmental compliance; 4) disposition of legacy radioactive waste; 5) uranium management; and 6) operation of the site's waste storage facilities.

WEMS provided facility support services including the following: 1) maintenance of facilities, grounds, and roadways; 2) janitorial services; 3) security access for DOE facilities; 4) training; 5) records and fleet management; and 6) information technology/network support for DOE operations.

BWCS was responsible for operations associated with the DUF₆ Conversion Facility, including surveillance and maintenance of DUF₆ cylinders, and environmental compliance and monitoring activities associated with operation of the facility. DUF₆, which is a product of the uranium enrichment process, is stored in cylinders on site. The DUF₆ Conversion Facility converts DUF₆ into uranium oxide and aqueous hydrogen fluoride. The uranium oxide is made available for beneficial reuse, storage, or disposal, and the aqueous hydrogen fluoride is sold for reuse.

Centrus is developing a gaseous centrifuge uranium enrichment plant at PORTS. The gaseous centrifuge uranium enrichment process requires much less electricity than the gaseous diffusion process. Gas centrifuge uranium enrichment uses a rotor that spins at a high speed within a casing to separate uranium-235 from uranium-238 (resulting in enriched uranium). Gaseous diffusion uranium enrichment uses a porous barrier to separate uranium-235 molecules from uranium-238 molecules.

The Centrus Lead Cascade, which is a small-scale demonstration centrifuge for uranium enrichment, has been operating since 2006 for demonstration and testing purposes. Construction of the commercial scale ACP was on hold at the end of 2015. Both of these facilities (the Lead Cascade and the ACP) are housed in existing buildings at PORTS that were constructed for DOE's Gaseous Centrifuge Enrichment Plant, which was cancelled in 1985.

This report is intended to fulfill the requirements of DOE Order 231.1B, *Environment, Safety and Health Reporting*. This DOE Order requires development of an annual site environmental report that includes information on regulatory compliance, environmental programs, radiological and non-radiological monitoring programs, groundwater programs, and quality assurance. The Annual Site Environmental Report also provides the means by which DOE demonstrates compliance with the radiation protection requirements of DOE Order 458.1 *Radiation Protection of the Public and the Environment*.

This report is not intended to present all of the monitoring data at PORTS. Additional data collected for other site purposes, such as environmental restoration and waste management, are presented in other documents that have been prepared in accordance with applicable laws and regulations. These data are presented in other reports, such as the *2015 Groundwater Monitoring Report* (DOE 2016a), which are available at the PORTS Environmental Information Center.

1.3 DESCRIPTION OF SITE LOCALE

PORTS is located in a rural area of Pike County, Ohio, on a 5.9-square-mile site. The site is 2 miles east of the Scioto River in a small valley running parallel to and approximately 120 feet above the Scioto River floodplain. Figure 1.2 depicts the plant site within the State of Ohio and its immediate environs.

Pike County has approximately 28,256 residents (U.S. Census Bureau 2016). Scattered rural development is typical; however, the county contains a number of small villages such as Piketon and Beaver that lie within a few miles of the plant. The county's largest community, Waverly, is about 10 miles north of the plant and has a population of about 4,300 residents (U.S. Census Bureau 2016). The nearest residential center in this area is Piketon, which is about 5 miles north of the plant on U.S. Route 23 with a population of about 2,100 (U.S. Census Bureau 2016). A number of residences are located adjacent to the plant boundary




Figure 1.2. Location of PORTS.

Additional cities within 50 miles of the plant are Portsmouth (population 20,326), 22 miles south; Chillicothe (population 21,738), 27 miles north; and Jackson (population 6,284), 18 miles east (U.S. Census Bureau 2016). The total population within 50 miles of the plant is approximately 677,000 persons.

1.4 DESCRIPTION OF SITE OPERATIONS

DOE, through its managing contractors, is responsible for D&D of the gaseous diffusion uranium enrichment buildings and associated facilities, environmental restoration, and waste management associated with DOE activities. DOE is also responsible for uranium management, which includes the DUF₆ Conversion Facility.

D&D includes the gaseous diffusion process buildings and associated facilities subject to *The April 13, 2010 Director's Final Findings and Orders for Removal Action and Remedial Investigation and Feasibility Study and Remedial Design and Remedial Action, including the July 16, 2012 Modification thereto* (D&D DFF&O) [Ohio Environmental Protection Agency (Ohio EPA) 2012]. D&D activities can consist of deactivation of equipment; removal and cleaning of process residues from equipment, structures, and piping; and dismantlement, demolition, and removal of equipment, structures, piping, and concrete foundations. The D&D Program is also responsible for conducting an evaluation of alternatives for disposition of waste generated by D&D.

Environmental restoration is the investigation and remediation of environmental contamination associated with the past operation of the gaseous diffusion uranium enrichment facilities. Remedial investigations and remedial actions define the nature and extent of environmental contamination, evaluate the potential risk to public health and the environment, remediate areas of environmental contamination, and monitor/evaluate ongoing remedial actions. The goal of the Environmental Restoration Program is to verify that releases from past operations at PORTS are thoroughly investigated and that remedial actions are taken to protect human health and the environment.

Waste management includes managing wastes generated by DOE activities at PORTS, including wastes generated by D&D, environmental restoration, the DUF₆ Conversion Facility, and other DOE site operations. Wastes must be identified and stored in accordance with all environmental regulations. The responsible DOE contractor also arranges the transportation and off-site disposal of wastes. The goal of the Waste Management Program is to manage waste from the time it is generated to its ultimate treatment, recycling, or disposal in accordance with all applicable regulations.

DOE is also responsible for uranium management, which includes management of uranium product, coordination of the DUF₆ program, and warehousing of other uranium materials such as normal uranium hexafluoride, uranium oxides, and uranium metal.

2. COMPLIANCE SUMMARY

2.1 SUMMARY

In 2015, DOE and/or the responsible DOE contractor (FBP or BWCS) held permits for discharge of water to surface streams, air emission permits, and a permit for the storage of hazardous wastes. FBP is responsible for the National Pollutant Discharge Elimination System (NPDES) outfalls and air emission permits that were associated with the gaseous diffusion plant. BWCS is responsible for activities associated with the DUF₆ Conversion Facility.

FBP and BWCS are responsible for preparing a number of reports for compliance with various applicable environmental regulations. These reports include an annual groundwater monitoring report, a biennial hazardous waste report, an annual polychlorinated biphenyl (PCB) document log, an annual summary of radionuclide air emissions and the associated dose to the public from these emissions, annual or biennial reports of specified non-radiological air emissions, a monthly report of NPDES monitoring data, an annual hazardous chemical inventory, and an annual toxic chemical release inventory. Additional information on each of these reports is provided within this chapter.

DOE activities at PORTS are inspected regularly by the federal, state, and local agencies responsible for enforcing environmental regulations at PORTS. DOE/FBP received five Notices of Violation in 2015 as described in the following paragraphs.

FBP received a Notice of Violation on March 2, 2015 from an inspection conducted on February 4, 2015 by the Ohio Public Utilities Commission of a commercial vehicle transporting laundry and respirators to Tennessee. The inspection found that FBP's method of securing the laundry bins and other material within the closed trailer was not adequate. Procedures were revised to provide consistent loading formations for laundry bins and verify proper loading prior to off-site transport. FBP paid a fine of \$1680. No further actions were required.

DOE/FBP received a Notice of Violation on July 6, 2015 from the inspection conducted by the U.S. Environmental Protection Agency (U.S. EPA) on April 13-14, 2015. The Notice of Violation was for failing to label containers of used oil with the words "used oil" (the containers were labeled "waste oil"). The containers were immediately labeled "used oil". No further action was required.

FBP received a Notice of Violation dated July 17, 2015 from the Ohio Public Utilities Commission due to an incident where radiologically-contaminated rags from a PORTS on-site laboratory were transported off site with ordinary sanitary trash. The rags became contaminated when they were used to wipe out a laboratory fume hood dedicated to non-radiological use that had not been used in over a year. The contamination on the rags likely migrated from the ductwork connected to the hood, although the lab had not been used for radiological work in more than 20 years. The truck containing the bag had not disposed of the trash. It was verified that no contamination had spread outside the sealed bag. Procedures were revised to increase radiological surveys of all laboratory fume hoods. FBP paid a fine of \$5250. No further actions were required.

FBP received a Notice of Violation dated July 20, 2015 from Ohio EPA due to the detection of total coliform in a drinking water sample collected from the PORTS water supply at an on-site bathroom sink. Total coliform are a type of bacteria naturally present in the environment that may indicate the presence of other potentially harmful bacteria. The cause of the detection was investigated and determined to be a dirty faucet aerator, which was thoroughly disinfected and replaced. The area was posted and follow-up samples were collected as required by Ohio EPA with no additional detections of total coliform. No further actions were required.

FBP received a Notice of Violation from Ohio EPA dated August 18, 2015 for exceedances of NPDES permit limitations for chlorine, water temperature, and acute toxicity between May 2014 and May 2015. The chlorine exceedances were caused by operational issues and were corrected on the day of the exceedances. The temperature exceedance (in 2014) resulted from unusually hot and dry weather. Acute toxicity is a measurement of the characteristics of water discharged from an outfall that could be harmful to aquatic organisms. The toxicity resulted from an operational reduction in water flow to the outfall. The amount of sodium bisulfite, a chemical used to remove chlorine from water, was not properly decreased when the water flow was reduced. The overfeed of sodium bisulfite caused acute toxicity measurements of 1.41 acute toxicity units (TU_a) to two test organisms (fathead minnows and water fleas). The discharge limitations for acute toxicity are 1.0 TU_a for both organisms. The acute toxicity measurement is based on placing the aquatic organisms in diluted and undiluted samples of water from the outfall (or effluent). The discharge limitation (1.0 TU_a) is based on the concentration of the effluent that is lethal to 50% of the aquatic organisms. The sample result of 1.41 TU_a indicates that 50% of the aquatic organisms would be killed by a dilution of 71% effluent. The toxicity lasted no more than 24 hours. FBP reported the violations to Ohio EPA at the time of the occurrences as required by the NPDES permit. No further actions were required.

2.2 COMPLIANCE INTRODUCTION

DOE is responsible for the D&D Program, Environmental Restoration Program, Waste Management Program, uranium operations, and maintenance of all facilities not leased to Centrus. FBP is responsible for air emission permits and NPDES outfalls associated with the former gaseous diffusion plant operations. BWCS is responsible for activities associated with the DUF₆ Conversion Facility.

Centrus is responsible for compliance activities directly associated with the ACP and Lead Cascade including air emission permits associated with the gaseous centrifuge uranium enrichment operations (the proposed ACP and the Lead Cascade), NPDES outfalls, and management of wastes generated by their current operations.

DOE and/or DOE contractors (FBP or BWCS) held two NPDES permits for discharge of water to surface streams, numerous air emission permits, and a Resource Conservation and Recovery Act (RCRA) Part B permit for the storage of hazardous wastes. Appendix B lists the active environmental permits and registrations held by DOE and/or DOE contractors (FBP and BWCS) at the end of 2015.

Several federal, state, and local agencies are responsible for enforcing environmental regulations at PORTS. Primary regulatory agencies include U.S. EPA and Ohio EPA. These agencies issue permits, review compliance reports, conduct joint monitoring programs, inspect facilities and operations, and oversee compliance with applicable regulations.

DOE and/or DOE contractors conduct self-assessments to identify environmental issues and consult the regulatory agencies to identify the appropriate actions necessary to achieve and maintain compliance.

2.3 COMPLIANCE STATUS

This section discusses the DOE compliance status at PORTS with respect to environmental laws and regulations, DOE Orders, and Executive Orders.

2.3.1 Environmental Restoration and Waste Management

This section discusses the DOE compliance status at PORTS with U.S. EPA and Ohio EPA regulations pertaining to environmental restoration and waste management.

2.3.1.1 Comprehensive Environmental Response, Compensation, and Liability Act

PORTS is not on the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) National Priorities List of sites requiring priority cleanup. However, D&D of PORTS is proceeding in accordance with the D&D DFF&O and CERCLA. The D&D DFF&O describes the regulatory process for D&D of the gaseous diffusion process buildings and associated facilities that are no longer in use. Chapter 3, Section 3.2, provides additional information about the D&D Program.

Environmental remediation, or the cleanup of soil, groundwater and other environmental media contaminated by PORTS operations, is conducted in accordance with the U.S. EPA Administrative Order by Consent, issued on September 29, 1989 (amended in 1994 and 1997), and Consent Decree with the State of Ohio, issued on August 29, 1989. U.S. EPA and Ohio EPA oversee environmental remediation activities at PORTS under the RCRA Corrective Action Program and CERCLA Program. Chapter 3, Section 3.3, provides additional information on the Environmental Restoration Program.

Section 103 of CERCLA requires notification to the National Response Center if hazardous substances are released to the environment in amounts greater than or equal to the reportable quantity. Reportable quantities are listed in CERCLA and vary depending on the type of hazardous substance released. During 2015, DOE contractors had no reportable quantity releases of hazardous substances subject to Section 103 notification requirements.

2.3.1.2 Emergency Planning and Community Right-To-Know Act

The Emergency Planning and Community Right-To-Know Act of 1986, also referred to as the Superfund Amendments and Reauthorization Act Title III, requires reporting of emergency planning information, hazardous chemical inventories, and releases to the environment. Emergency Planning and Community Right-To-Know Act reports are submitted to federal, state, and local authorities.

For emergency planning purposes, facilities must submit information on chemicals present on site above specified quantities (called the threshold planning quantity) to state and local authorities. When a new chemical is brought on site or increased to exceed the threshold planning quantity, information about the new chemical must be submitted to state and local authorities within three months.

Section 304 of the Emergency Planning and Community Right-To-Know Act requires reporting of off-site reportable quantity releases to state and local authorities. During 2015, FBP and BWCS had no off-site reportable quantity releases subject to Section 304 reporting requirements.

The Hazardous Chemical Inventory Report includes the identity, location, storage information, and hazards of the chemicals present on site in amounts above the threshold planning quantities specified by U.S. EPA. This report is submitted annually to state and local authorities. Table 2.1 lists the chemicals reported by the PORTS site, which included DOE contractors or lessees (FBP, WEMS, BWCS, and Centrus) for 2015:

Table 2.1. Chemicals reported in the Hazardous Chemical Inventory Report for 2015

1,2-propanediol	diesel fuel #2 (ultralow sulfur)	methanol	sodium polyacrylate
aluminum oxide	ethylene glycol	mineral oils	sulfuric acid
aluminum oxide hydrate	fluorotrichloromethane (CFC-11)	nitric acid	sulfur dioxide
argon	full range straight run middle distillate	nitrogen	uranium octaoxide
asbestos	gasoline	PCBs	uranium oxide
calcium chloride	hydrogen fluoride	perfluoro-1,3-dimethylcyclohexane	uranium hexafluoride
carbon dioxide	kerosene	petroleum distillates	uranium metal
chlorine	lime calcium oxide	potassium hydroxide	uranium tetrafluoride
citric acid	limestone	sodium chloride	
dichlorotetrafluoroethane (CFC-114)	lubricating oils	sodium hydroxide	

The Toxic Chemical Release Inventory is sent annually to U.S. EPA and Ohio EPA. This report details releases to the environment of specified chemicals when they are manufactured, processed, or otherwise used by the entire site in amounts that exceed threshold quantities specified by U.S. EPA. For this report, U.S. EPA defines a release to include on-site treatment, off-site disposal, and recycling conducted in accordance with regulations.

For 2015, DOE contractors reported the permitted release and/or off-site treatment of three chemicals:

- chlorine: used for water treatment;
- hydrogen fluoride: approximately 9 lbs released to the air from the DUF₆ Conversion Facility; and
- nitrate compounds: approximately 26,000 lbs released to the Scioto River through permitted NPDES outfalls (from water treatment).

2.3.1.3 Resource Conservation and Recovery Act

RCRA regulates the generation, accumulation, storage, transportation, and disposal of solid and hazardous wastes. “Solid wastes,” as defined by Ohio EPA, can be solids, liquids, sludges, or other materials. Hazardous wastes are a subset of solid wastes, and are designated as hazardous by Ohio EPA because of various chemical properties, including ignitability, corrosivity, reactivity, and toxicity.

Hazardous waste. DOE and FBP hold a permit to store hazardous waste at PORTS. The permit, often called a Part B Permit, was issued to DOE and the responsible DOE contractor in 1995, and renewed by Ohio EPA in 2001 and 2011. The permit governs the storage of hazardous waste and includes requirements for waste identification, inspections of storage areas and emergency equipment, emergency procedures, training requirements, and other information required by Ohio EPA.

In 2015, a modification request for the Part B Permit was submitted to Ohio EPA to allow storage of hazardous waste in designated areas of the X-330, X-345, and X-705 buildings. The modification to add new storage areas was needed to relocate hazardous waste currently stored in the X-326 Process Building to other areas as D&D is implemented for the X-326 Process Building.

In accordance with the terms and conditions of the RCRA Part B Permit, DOE and FBP are required to report to Ohio EPA any self-identified activities that are not in compliance with the Part B permit. No permit non-compliances were reported in 2015.

Facilities such as PORTS that generate or store hazardous waste are required to submit a biennial report to Ohio EPA (in even-numbered years) that covers waste shipped in the previous odd-numbered year (i.e., waste shipped in even-numbered years no longer requires reporting). DOE submitted the report for

calendar year 2015 to Ohio EPA in February 2016. This biennial report contains the name and address of each facility that waste was shipped to during the previous calendar year, the name and address of the transporter for each waste shipment, the description and quantity of each waste stream shipped off site, and a description of waste minimization efforts. Chapter 3, Section 3.4, Waste Management Program, provides additional information on wastes from DOE activities at PORTS that were recycled, treated, or disposed in 2015.

RCRA also requires groundwater monitoring at certain hazardous waste management units. As discussed in Chapter 6, groundwater monitoring requirements at PORTS have been integrated into one document, the *Integrated Groundwater Monitoring Plan* (DOE 2014b, DOE 2015d). Hazardous waste management units monitored in accordance with the *Integrated Groundwater Monitoring Plan* include the X-749 Contaminated Materials Disposal Facility (northern portion), X-231B Southwest Oil Biodegradation Plot (Quadrant I Groundwater Investigative [5-Unit] Area), X-701C Neutralization Pit (Quadrant II Groundwater Investigative [7-Unit] Area), X-701B Former Holding Pond, X-701B retention basins, X-744Y Waste Storage Yard (X-701B area), X-230J7 Holding Pond (X-701B area), X-616 Former Chromium Sludge Surface Impoundments, and X-735 RCRA Landfill (northern portion). Chapter 6 discusses the groundwater monitoring requirements for these units.

A groundwater report that summarizes the results of monitoring completed in accordance with the *Integrated Groundwater Monitoring Plan* is submitted annually to Ohio EPA (DOE 2016a). Chapter 6 discusses these monitoring results for 2015.

BWCS is regulated as a small quantity hazardous waste generator. Small quantity hazardous waste generators are subject to requirements for generation and accumulation of hazardous waste. These requirements include proper waste identification, use of appropriate containers, availability of emergency equipment, and specified shipment information.

Solid waste. Groundwater monitoring may be required at closed solid waste disposal facilities, such as landfills. Groundwater monitoring requirements for the closed X-734 Landfills, X-735 Industrial Solid Waste Landfill, and X-749A Classified Materials Disposal Facility are included in the *Integrated Groundwater Monitoring Plan* (DOE 2014b, DOE 2015d). Chapter 6 discusses the groundwater monitoring results for these units in 2015.

2.3.1.4 Federal Facility Compliance Act

Waste that is a mixture of RCRA hazardous waste and low-level radioactive waste (LLW) is currently stored at PORTS. RCRA hazardous waste is subject to Land Disposal Restrictions, which with limited exceptions do not allow the storage of hazardous waste for longer than one year. The Federal Facility Compliance Act, enacted by Congress in 1992, allows for the storage of mixed hazardous/LLW for longer than one year because treatment for this type of waste is not readily available. The Act also requires federal facilities to develop and submit site treatment plans for treatment of mixed wastes. On October 4, 1995, Ohio EPA issued a Director's Final Findings and Orders allowing the storage of mixed waste beyond one year and approving the proposed Site Treatment Plan. An annual update to the Site Treatment Plan is required by these Director's Final Findings and Orders. The annual update to the Site Treatment Plan for fiscal year 2015 was submitted to Ohio EPA in December 2015.

2.3.1.5 Toxic Substances Control Act

The Toxic Substances Control Act (TSCA) regulates the use, storage, and disposal of PCBs, which are most commonly found in older electrical power system components, such as transformers and capacitors. The PCB transformers and capacitors that were present in the gaseous diffusion process buildings have been removed. Five PCB transformers were in service at PORTS in 2015: one in the X-530 Switchyard and four pole-mounted transformers within the facility.

An annual document log is prepared to meet TSCA regulatory requirements. The document log provides an inventory of PCB items in use, in storage as waste, and shipping/disposal information for PCB items disposed in 2015. The *2015 PCB Document Log for the Portsmouth Gaseous Diffusion Plant* was prepared in June 2016. Approximately 15.5 tons of PCB waste (approximately 14,000 kilograms [kg] gross weight) was generated in 2015. Approximately 72.5 tons of PCB waste (gross weight), which includes 11.7 tons of bulk product, was shipped for disposal in 2015. Waste contaminated with PCBs was generated during 2015 through activities in the X-326, X-330 and X-333 Process Buildings and other areas.

A TSCA Federal Facilities Compliance Agreement between DOE and U.S. EPA became effective in 1992 to resolve several PCB compliance issues. These issues included the use of PCBs in systems that are not totally enclosed, storage of wastes containing both PCBs and radionuclides in accordance with nuclear criticality safety requirements, and storage of wastes containing both PCBs and radionuclides for longer than one year. The agreement required installation of troughs under motor exhaust duct gaskets located in the former gaseous diffusion facilities to collect PCB oil leaks. When leaks or spills of PCBs occur, they are managed in accordance with the Federal Facilities Compliance Agreement.

Annual reports of progress made toward milestones specified in the Federal Facilities Compliance Agreement are submitted to U.S. EPA. DOE was in compliance with the requirements and milestones of this Federal Facilities Compliance Agreement during 2015.

The DUF₆ Conversion Facility stores and processes cylinders containing DUF₆ that may have paint containing greater than 50 parts per million (ppm) of PCBs present on the outside of the cylinders. The cylinders are stored in the X-745C, X-745E and X-745G Cylinder Storage Yards. The cylinders are stored in accordance with an agreement with U.S. EPA that includes monitoring of PCBs in surface water and sediment in drainage basins downstream from the cylinder storage yards. Chapter 5, Sections 5.4.2 and 5.5.2 provide the results of this surface water and sediment sampling, respectively.

2.3.1.6 Federal Insecticide, Fungicide, and Rodenticide Act

No restricted-use pesticides were used by DOE contractors in 2015.

2.3.2 Radiation Protection

This section discusses the DOE compliance status with DOE Orders pertaining to radiation protection and management of radioactive waste.

2.3.2.1 DOE Order 458.1, *Radiation Protection of the Public and the Environment*

The purpose of DOE Order 458.1 is to establish requirements to protect the public and the environment against undue risk from radiation associated with radiological activities conducted under the control of the DOE pursuant to the Atomic Energy Act of 1954, as amended. The objectives of DOE Order 458.1 are:

- to conduct DOE radiological activities so that exposure to members of the public is maintained within the dose limits established in the Order and are as low as reasonably achievable, and
- ensure that DOE sites have the capabilities, consistent with the types of radiological activities conducted, to monitor routine and non-routine radiological releases and assess the radiation dose to members of the public.

DOE Order 458.1 requires that off-site radiation doses do not exceed 100 millirem (mrem)/year above background for all exposure pathways. Chapter 4 provides the dose calculations or monitoring results that demonstrate compliance with this DOE Order.

2.3.2.2 DOE Order 435.1, *Radioactive Waste Management*

The objective of DOE Order 435.1 is to ensure that all DOE radioactive waste is managed in a manner that is protective of worker and public health and safety, and the environment. DOE Order 435.1 applies to all high-level waste, transuranic waste, and LLW, including the radioactive component of mixed waste for which DOE is responsible. Only LLW and mixed LLW are found at PORTS. Chapter 3, Section 3.4 provides additional information about the DOE Waste Management Program at PORTS.

An on-site waste disposal facility (OSWDF) has been selected per the record of decision for waste disposal for disposal of waste generated by D&D that meets criteria for on-site disposal (see Chapter 3, Section 3.2.2). The DOE Low-level Waste Disposal Facility Review Group (LFRG) has completed an independent review of the design and planned operation of the OSWDF as presented in a Performance Assessment and Composite Analysis and determined compliance with performance objectives in DOE Order 435.1. Subsequently, on March 13, 2015, PORTS received a Disposal Authorization Statement (DAS) for design and construction of the OSWDF from the DOE Office of Site Restoration. This DAS requires completion of the construction, along with a comparison of the as-built facility to that reviewed, and satisfaction of the conditions in the DAS, as verified by the LFRG, prior to issuance of the DAS for Operations.

2.3.3 Air Quality and Protection

This section discusses the DOE compliance status with U.S. EPA and Ohio EPA regulations pertaining to air emissions (both radionuclides and non-radiological pollutants) and stratospheric ozone protection. Chapter 4, Figure 4.1 is a map of the PORTS ambient air monitoring locations.

2.3.3.1 Clean Air Act

FBP is responsible for numerous air emission sources associated with the former gaseous diffusion production facilities and support facilities. These sources, which included the boilers at the X-600 Steam Plant Complex (prior to demolition in 2013), emitted more than 100 tons per year of non-radiological air pollutants specified by Ohio EPA, which caused DOE to become a major source of air pollutants as defined in 40 CFR Part 70. Ohio EPA issued the final Title V Air Permit to FBP in 2014.

FBP is required to submit quarterly Title V Deviation Reports that document any deviations from requirements of the Title V permit. These quarterly reports are summarized in an annual Title V Compliance Certification. In 2015, FBP did not have any deviations from the Title V Permit requirements.

Ohio EPA requires an annual report called the Ohio EPA Fee Emissions Report to report emissions of selected non-radiological air pollutants. U.S. EPA requires an annual report of greenhouse gas emissions. Chapter 5, Section 5.3.1 provides more information about these reports and the reported emissions for 2015.

BWCS is responsible for four permitted sources associated with the DUF₆ Conversion Facility. In 2015, the Annual Permit Evaluation Report for the BWCS air emission sources did not report any deviations from applicable emission limits or control requirements. Chapter 5, Section 5.3.1, provides more information about air emissions from BWCS in 2015.

Appendix B lists the FBP and BWCS air emission sources at PORTS. Radiological air emissions from the DOE air emission sources are discussed in Chapter 4 and non-radiological air emissions are discussed in Chapter 5.

2.3.3.2 Clean Air Act, Title VI, Stratospheric Ozone Protection

As part of the Stratospheric Ozone Protection Plan, DOE has instituted a record-keeping system consisting of forms and labels to comply with the Title VI record-keeping and labeling requirements. These requirements affect all areas that use ozone-depleting substances. The service record and retrofit or retirement plan forms apply to units with a capacity of more than 50 pounds. The refrigeration equipment disposal log and associated appliance disposal label are used by all units regardless of capacity. The technicians who service equipment under DOE control are trained in accordance with U.S. EPA requirements.

An ozone-depleting substance, specifically dichlorotetrafluoroethane (CFC-114), was used as a coolant in the gaseous diffusion cascade system formerly used to produce enriched uranium. The CFC-114 was removed from the cascade system in 2012 and is stored in tanks within the X-333 Process Building.

2.3.3.3 National Emission Standards for Hazardous Air Pollutants

Title 40 of the *Code of Federal Regulations* (CFR), Part 61, National Emission Standards for Hazardous Air Pollutants (NESHAP), Subpart H, National Emission Standards for Emissions of Radionuclides Other Than Radon from DOE Facilities (40 CFR Part 61, Subpart H) requires DOE to submit an annual report for radiological emissions from DOE air emission sources. DOE contractors FBP and BWCS are both responsible for radiological air emission sources. Chapter 4, Section 4.3.3, provides the radiological dose calculations from these emissions.

FBP sources. In 2015, FBP was responsible for numerous air emission sources including 1) continuously monitored vents in the X-326 and X-330 Process Buildings and the X-344A Uranium Hexafluoride Sampling Building; 2) room ventilation exhausts and/or pressure relief vents associated with the X-700 Chemical Cleaning Facility, X-710 Technical Services Building, X-705 Decontamination Facility, the X-326 L-Cage Glove Box, and the XT-847 Glove Box; and 3) the X-622, X-623, X-624, X-627 Groundwater Treatment Facilities.

Radiological emissions from the vents in the X-326 and X-330 Process Buildings and the X-344A Uranium Hexafluoride Sampling Building were measured by continuous monitoring. Emissions from the room ventilation exhausts and vents (if in use) were estimated based on operating data and U.S. EPA emission factors. Emissions from the groundwater treatment facilities were estimated based on quarterly influent/effluent sampling and quarterly throughput. Total radiological airborne emissions from FBP sources in 2015 were 0.0366 curie (Ci) (3.66E-02 Ci).

BWCS sources. In 2015, BWCS was responsible for emissions from the DUF₆ Conversion Facility. Emissions from the DUF₆ Conversion Facility were based on continuous monitoring of the conversion building stack. Total radiological airborne emissions from the DUF₆ Conversion Facility in 2015 were 0.0000414 Ci (4.14E-05 Ci).

2.3.4 Water Quality and Protection

This section discusses the DOE compliance status with U.S. EPA and Ohio EPA regulations pertaining to water quality and protection.

2.3.4.1 Clean Water Act

DOE contractors FBP and BWCS held NPDES permits during 2015 that allowed discharges of water to surface streams. FBP was responsible for 18 monitoring locations identified in the FBP NPDES permit. Nine outfalls discharge directly to surface water, six outfalls discharge to another outfall before leaving the site, and three other locations that are not outfalls were also monitored. Chapter 4, Section 4.3.5.1, and Chapter 5, Section 5.4.1.1, provide additional information on the FBP NPDES outfalls. Chapter 4, Figure 4.2 is a map of the PORTS NPDES outfalls.

FBP submitted an NPDES permit renewal application to Ohio EPA in June 2012 to replace the FBP NPDES permit that was issued in 2011 and expired at the end of April 2013. In 2015, Ohio EPA issued a new NPDES permit to FBP that became effective on September 1, 2015. FBP monitored the FBP NPDES outfalls in accordance with the 2011 NPDES permit through August 2015 and implemented monitoring in accordance with the new permit in September 2015.

The BWCS NPDES permit allows the discharge of process wastewaters from the DUF₆ Conversion Facility. The BWCS NPDES permit provides monitoring requirements for BWCS Outfall 001 that are only effective when process wastewater is being discharged through the outfall. The permit also includes requirements for BWCS Outfall 602, which are effective when process wastewater is being discharged to the sanitary sewer system that flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). No process wastewater was discharged through BWCS Outfall 001 in 2015. Chapter 4, Section 4.3.5, and Chapter 5, Section 5.4.1.2, provide additional information on the BWCS NPDES outfalls.

Data required to demonstrate compliance with the NPDES permits are submitted to Ohio EPA in monthly discharge monitoring reports (see Chapter 5, Section 5.4.1.1). Seven permit limitations associated with the FBP NPDES permit were exceeded during 2015 (see Chapter 5, Section 5.4.1.1). The overall FBP NPDES compliance rate for 2015 was 99%. There were no exceedances of BWCS permit limitations in 2015; therefore, the overall BWCS NPDES compliance rate for 2015 was 100%.

Most of the FBP NPDES outfalls are also monitored for radionuclides (see Chapter 4, Section 4.3.5). The BWCS outfalls are not monitored for radionuclides.

Stormwater runoff, water from precipitation that flows over land and is not absorbed into the ground, is regulated under the Clean Water Act because it can accumulate debris, chemicals, or other pollutants that affect water quality. Stormwater Pollution Prevention Plans are prepared for the site industrial activities under the FBP NPDES permit. Construction activities are covered by the NPDES Construction Stormwater General Permit. The Stormwater Pollution Prevention Plans include descriptions of the activities and the controls to be used to minimize impacts to stormwater runoff.

Stormwater management and drainage design will be part of site redevelopment after D&D and remediation are completed.

2.3.4.2 Safe Drinking Water Act

In 2015, FBP was responsible for operation of the PORTS drinking water system. Drinking water systems are regulated by the Safe Drinking Water Act, which sets requirements for water testing, treatment, and disinfection, as well as distribution system maintenance and operator training. The Safe Drinking Water Act also sets health-based standards for naturally-occurring and man-made contaminants that may be found in drinking water.

PORTS obtains its drinking water from two water supply well fields west of PORTS in the Scioto River Valley buried aquifer near the Scioto River. Ohio EPA provides the parameters and schedule for sampling the drinking water for various parameters, including nitrate, lead, disinfection byproducts, total coliform, and chlorine. Sampling results are submitted to Ohio EPA in a monthly report.

2.3.5 Other Environmental Statutes

This section discusses the DOE compliance status with other applicable environmental statutes and regulations including underground storage tank regulations and the Endangered Species Act.

2.3.5.1 Underground storage tank regulations

The Underground Storage Tank Program is managed in accordance with the Ohio State Fire Marshal's Bureau of Underground Storage Tank Regulations. Seven underground storage tanks in the former gaseous diffusion plant buildings and associated facilities are owned by DOE (FBP is responsible for five tanks and Centrus is responsible for two tanks). These tanks include six diesel fuel tanks ranging in size from 550 to 20,000 gallons and a 20,000 gallon gasoline tank. The registrations for these tanks are renewed annually.

2.3.5.2 National Environmental Policy Act

The National Environmental Policy Act (NEPA) requires evaluation of the environmental impacts of activities at federal facilities and of activities funded with federal dollars.

DOE has a formal program dedicated to compliance pursuant to DOE Order 451.1, *National Environmental Policy Act Compliance Program*. Restoration actions, waste management, enrichment facilities maintenance, and other activities are evaluated to determine the appropriate level of evaluation and documentation. No environmental impact statements or environmental assessments were completed during 2015.

Routine operation and maintenance activities are also evaluated to assess potential environmental impacts. Activities not regulated under CERCLA may be covered under a categorical exclusion or other NEPA determination as defined in the regulations. These activities are considered routine and have no significant individual or cumulative environmental impacts. DOE has implemented a policy to post online specific classes of categorical exclusions as found in 10 CFR Part 1021, Appendix B to Subpart D. Categorical exclusions for PORTS are posted on the DOE Portsmouth/Paducah Project Office website (www.energy.gov/pppo).

2.3.5.3 Endangered Species Act

The Endangered Species Act of 1973, as amended, provides for the designation and protection of endangered and threatened wildlife and plants, and the habitat on which such species depend. When appropriate, formal consultations are made with the U.S. Fish and Wildlife Service and the Ohio Department of Natural Resources.

A study was conducted in 2013 to identify the potential presence of the federally-endangered Indiana bat (*Myotis sodalis*) and the northern long-eared bat (*Myotis septentrionalis*), in the northeastern area of PORTS that is the planned location for the OSWDF (see Chapter 3, Section 3.2.2). The study did not identify the presence of the federally-endangered Indiana bat in the study area. Both foraging and roosting activities were identified for the northern long-eared bat, which is listed as a threatened species. In 2015, the U.S. Fish and Wildlife Service issued a Biological Opinion that the OSWDF is not likely to jeopardize the continued existence of the northern long-eared bat. Measures will be taken during construction and operation of the OSWDF to minimize potential impacts to bats.

2.3.5.4 National Historic Preservation Act

The National Historic Preservation Act of 1966 is the primary law governing the protection of cultural resources (archaeological and historical properties). Cultural resource reviews are conducted on a case-by-case basis, and consultations with the State Historic Preservation Office and other stakeholders are made as required by Sections 106 and 110 of the Act. The cultural resources of three broad periods of occupation of the PORTS property have been assessed: the prehistoric era (occupation by Native Americans until approximately 1650), the historic era (occupation by Native Americans and early settlers from 1650 through 1952) and the DOE era (the period of occupation by DOE – 1952 to the present).

Fifty-four prehistoric archaeological sites have been identified on PORTS property. Each of these sites was investigated, and four of the sites included sufficient artifacts such as tools, earth ovens, and pottery to be determined eligible for inclusion on the National Register of Historic Places. One of the sites eligible for inclusion on the National Register of Historic Places is located in the northeast corner of PORTS in the support area for the OSWDF. DOE worked with the State Historic Preservation Office and Tribal Nations to develop a data recovery approach for this area so that artifacts and other information could be recovered from the area (approximately 1 acre) prior to construction activities. Field work, including hand excavation of selected areas, was completed in 2015. No significant artifacts were found. A report documenting the activities is being developed.

Sixty-one historic era sites have been identified on PORTS property. Most of these sites were farmstead/residential sites, and investigations of the farmstead/residential sites determined that the sites were not eligible for inclusion on the National Register of Historic Places. Two sites, the Holt Cemetery and Mount Gilead Church and Cemetery, were determined to be eligible for inclusion on the National Register of Historic Places.

DOE has worked with the State Historic Preservation Office, Advisory Council on Historic Preservation, Tribal Nations, and individual members of the public interested in historic preservation to determine how best to document the DOE era of site history, that is, the history associated with the buildings and other areas that are part of D&D. Requirements of the National Historic Preservation Act have been included in the CERCLA process. The PORTS Virtual Museum (www.portsvirtualmuseum.org) preserves photos, video, oral histories, and other information associated with operation, remediation, and D&D of PORTS. The records of decision for process buildings and waste disposition (see Chapter 3, Section 3.2) list the activities selected to preserve the history and cultural resources associated with the PORTS site.

2.3.5.5 Archaeological and Historic Preservation Act and Archaeological Resources Protection Act

The Archaeological and Historic Preservation Act and the Archaeological Resources Protection Act require the Secretary of the Department of Interior to report to Congress on various federal archaeological activities. The Archaeological Resources Protection Act requires federal land managers to provide archaeology program information to the Secretary of the Interior for this report; a questionnaire that provides information for PORTS is completed annually by DOE.

2.3.6 DOE Order 436.1 *Departmental Sustainability*

DOE Order 436.1, *Departmental Sustainability*, requires development and implementation of an Environmental Management System (EMS) in order to protect air, water, land, and other natural or cultural resources potentially impacted by DOE operations.

FBP, WEMS, and BWCS have developed the following EMS criteria, as applicable: site EMS policy statement, EMS implementation training, identification of significant environmental aspects of site operations, establishment of measurable environmental objectives and targets, EMS awareness training (initial and ongoing), and establishment of EMS procedures.

Independent surveillances of the FBP and WEMS EMS programs were completed in the spring of 2014. The review team identified four findings within the FBP EMS program that required corrective actions plans. The findings involved inclusion of site tenants in the EMS program, training (two findings), and the review process for the National Environmental Policy Act. No findings were identified for the WEMS EMS program.

FBP serves as the coordinating contractor for EMS implementation among the DOE site contractors (FBP, WEMS, and BWCS). FBP and WEMS prepare annual EMS reports to document progress, performance, and successes in implementing the EMS at PORTS. The highest priority aspects identified

in the fiscal year 2015 FBP EMS report were waste management, discharges to surface water, and chemical use. The FBP EMS report stated that 50-79% of the established EMS objectives, targets, and programs were on schedule to be met. The highest priority aspects identified in the WEMS EMS report were air emissions, release of liquid effluents, and generation of solid waste. The WEMS report stated that 80% of the established EMS objectives and targets were on schedule to be met.

BWCS has declared readiness for its EMS program, which indicates the program is ready to be audited for conformance to applicable standards. An independent audit of the BWCS EMS program was conducted in 2016. The audit found that the BWCS EMS plan and implementing procedures have the required content to conform to DOE 436.1.

Chapter 3, Section 3.5, provides information about the DOE Environmental Sustainability Program at PORTS.

2.3.7 Executive Orders

Executive Orders are issued by the President to various federal agencies, including DOE. This section discusses the DOE compliance status at PORTS with Executive Orders pertaining to the environment.

2.3.7.1 Executive Order 11988, *Floodplain Management*, and Executive Order 11990, *Protection of Wetlands*

Title 10 of the CFR Part 1022 establishes policy and procedures for compliance with Executive Order 11988, *Floodplain Management*, and Executive Order 11990, *Protection of Wetlands*.

A site-wide wetland survey report was completed and submitted to the Corps of Engineers in 1996. The 1996 survey identified 41 jurisdictional wetlands and four non-jurisdictional wetlands totaling 34.361 acres at PORTS.

A wetland and stream assessment was completed in 2013 for the northeast area of PORTS where the OSWDF will be constructed. DOE is developing mitigation strategies for wetlands and streams that will be impacted by the construction of the OSWDF in accordance with CERCLA applicable or relevant and appropriate requirements.

2.3.7.2 Executive Order 13693, *Planning for Federal Sustainability in the Next Decade*

Executive Order 13693 establishes a framework to maintain federal leadership in sustainability and greenhouse gas emission reductions. Executive Order 13693 revoked both Executive Order 13423 and Executive Order 13514. Existing activities included in the DOE Environmental Sustainability Program at PORTS (see Chapter 3, Section 3.5) support this executive order. These existing activities include improving energy and water use efficiency; encouraging site-wide recycling and material reuse; and increasing the use of alternative fuel and alternative fuel vehicles.

Green and sustainable remediation is the abatement, cleanup, or use of methods to contain, remove, or destroy contaminants while seeking to minimize the environmental, economic, and social costs of the remediation. FBP is incorporating green and sustainable remediation into the D&D activities discussed in Chapter 3. Actions being taken to support green remediation include efficient movement of materials to reduce fuel usage, efforts to minimize water usage and control runoff, and recycling/reuse of materials.

2.4 OTHER MAJOR ENVIRONMENTAL ISSUES AND ACTIONS

This section summarizes environmental inspections of DOE activities at PORTS during 2015 and the results of these inspections.

2.4.1 Environmental Program Inspections

During 2015, eight inspections of DOE activities at PORTS were conducted by federal, state, or local agencies. Table 2.2 lists these inspections.

Table 2.2. Environmental inspections of DOE activities at PORTS for 2015

Date	DOE contractor	Agency	Type	Notices of Violation
January 20	FBP	Ohio EPA	RCRA Corrective Action surveillance and maintenance (X-622 and X-627 Groundwater Treatment Facilities, 5-Unit area)	None
March 26	FBP	Ohio EPA	RCRA Corrective Action surveillance and maintenance (X-616 and X-749 Landfill)	None
April 13-14	FBP	U.S. EPA & Ohio EPA	RCRA compliance	See Section 2.4.2
April 15	FBP	Ohio EPA	RCRA Corrective Action surveillance and maintenance (X-231A/B Oil Degradation Plots, X-749A Landfill, X-720, X-701A, X-701B, X-701C)	None
May 28	FBP	Ohio EPA	RCRA Corrective Action surveillance and maintenance (5-Unit Area extraction well system, X-230J6 and X-230L Holding Ponds)	None
June 1 (letter date)	FBP	Ohio EPA	RCRA Corrective Action surveillance and maintenance (X-700 and X-705 Basement Sumps – information review)	None
June 4	FBP	Ohio EPA/Pike County Health District	Closed solid waste landfills (X-735, X-749, X-749A)	None
September 15	FBP	Ohio EPA	RCRA Hazardous Waste Permit compliance	None

2.4.2 Notices of Violation

DOE and/or FBP received the following Notices of Violation from inspections or reports completed in 2015.

FBP received a Notice of Violation on March 2, 2015 from an inspection conducted on February 4, 2015 by the Ohio Public Utilities Commission of a commercial vehicle transporting laundry and respirators to Tennessee. The inspection found that FBP’s method of securing the laundry bins and other material within the closed trailer was not adequate. Procedures were revised to provide consistent loading formations for laundry bins and verify proper loading prior to off-site transport. FBP paid a fine of \$1680. No further actions were required.

DOE/FBP received a Notice of Violation on July 6, 2015 from the inspection conducted by U.S. EPA on April 13-14, 2015. The Notice of Violation was for failing to label containers of used oil with the words “used oil” (the containers were labeled “waste oil”). The containers were immediately labeled “used oil”. No further action was required.

FBP received a Notice of Violation dated July 17, 2015 from the Ohio Public Utilities Commission due to an incident where radiologically-contaminated rags from a PORTS on-site laboratory were transported off site with ordinary sanitary trash. The rags became contaminated when they were used to wipe out a laboratory fume hood dedicated to non-radiological use that had not been used in over a year. The contamination on the rags likely migrated from the ductwork connected to the hood, although the lab had not been used for radiological work in more than 20 years. The truck had not disposed of the trash. It was verified that no contamination had spread outside the sealed bag. Procedures were revised to increase radiological surveys of all laboratory fume hoods. FBP paid a fine of \$5250. No further actions were required.

FBP received a Notice of Violation dated July 20, 2015 from Ohio EPA due to the detection of total coliform in a drinking water sample collected from the PORTS water supply at an on-site bathroom sink. Total coliform are a type of bacteria naturally present in the environment that may indicate the presence of other potentially harmful bacteria. The cause of the detection was investigated and determined to be a dirty faucet aerator, which was thoroughly disinfected and replaced. The area was posted and follow-up samples were collected as required by Ohio EPA with no additional detections of total coliform. No further actions were required.

FBP received a Notice of Violation from Ohio EPA dated August 18, 2015 for exceedances of NPDES permit limitations for chlorine, water temperature, and acute toxicity between May 2014 and May 2015. The chlorine exceedances were caused by operational issues and were corrected on the day of the exceedances. The temperature exceedance (in 2014) resulted from unusually hot and dry weather. Acute toxicity is a measurement of the characteristics of water discharged from an outfall that could be harmful to aquatic organisms. The toxicity resulted from an operational reduction in water flow to the outfall. The amount of sodium bisulfite, a chemical used to remove chlorine from water, was not properly decreased when the water flow was reduced. The overfeed of sodium bisulfite caused acute toxicity measurements of 1.41 TU_a to two test organisms (fathead minnows and water fleas). The discharge limitations for acute toxicity are 1.0 TU_a for both organisms. The acute toxicity measurement is based on placing the aquatic organisms in diluted and undiluted samples of water from the outfall (or effluent). The discharge limitation (1.0 TU_a) is based on the concentration of the effluent that is lethal to 50% of the aquatic organisms. The sample result of 1.41 TU_a indicates that 50% of the aquatic organisms would be killed by a dilution of 71% effluent. The toxicity lasted no more than 24 hours. FBP reported the violations to Ohio EPA at the time of the occurrences as required by the NPDES permit. No further actions were required.

2.5 UNPLANNED RELEASES

No unplanned releases from DOE activities at PORTS occurred in 2015.

2.6 SUMMARY OF PERMITS

Appendix B lists the permits held by DOE and/or DOE contractors in 2015.

3. ENVIRONMENTAL PROGRAM INFORMATION

3.1 SUMMARY

Ohio EPA concurred with the records of decision for the process buildings and waste disposition in July and June of 2015, respectively. The record of decision for the process buildings and other facilities selected controlled removal of stored waste and materials, demolition of the buildings or structures, and characterization of materials for disposal or disposition (DOE 2015e). The record of decision for waste disposition selected a combination of on-site and off-site disposal (DOE 2015f), which includes construction of an OSWDF.

Soil and groundwater is being investigated and remediated, if necessary, as part of the Environmental Restoration Program at PORTS. Ohio EPA approved the *Deferred Units RCRA Facility Investigation/Corrective Measures Study Work Plan for Solid Waste Management Units* in June 2015 (DOE 2015a). This work plan was developed to investigate “deferred units” at PORTS, which are areas of potential soil and/or groundwater contamination that were in or adjacent to the gaseous diffusion production and operational areas such that remedial activities prior to D&D would have interrupted operations, or were areas that could have become recontaminated from ongoing operations. Soil and groundwater sampling required by the work plan started in July 2015 and continued into 2016.

In 2015, FBP shipped almost 9200 tons of waste or other materials to off-site facilities for treatment, disposal, recycling, or reuse. Activities undertaken by the Environmental Sustainability and Public Awareness programs are also discussed in this chapter.

Chapter 2, Section 2.3.6, provides information on implementation of the DOE EMS at PORTS.

3.2 D&D PROGRAM

On April 13, 2010, Ohio EPA issued the D&D DFF&O, which is an enforceable agreement between Ohio EPA and DOE that governs the process for D&D of the gaseous diffusion process buildings and associated facilities that are no longer in use at PORTS. The D&D DFF&O was revised in 2011 and 2012 to add structures that were inadvertently omitted from the original orders. The D&D DFF&O, which applies to the D&D of buildings down to and including the building slab and disposal of wastes generated by D&D, uses the CERCLA framework for determining appropriate removal and remedial actions. Documents are submitted to Ohio EPA for either concurrence or approval. Chapter 2, Section 2.3.1.1, provides additional information about the D&D DFF&O.

Community involvement is an important part of the CERCLA process and the D&D DFF&O. Opportunities for public comment are built into the D&D process as described in Sections 3.2.1 and 3.2.2. The PORTS Community Relations Plan (DOE 2010, DOE 2012) identifies opportunities to provide information to the public and obtain public input. Additionally, the PORTS Site Specific Advisory Board provides recommendations to DOE based on the concerns of the communities surrounding PORTS. Section 3.6 provides additional information on the PORTS Public Awareness Program.

3.2.1 Process Buildings and Other Facilities

D&D of the process building and other facilities at PORTS is proceeding in accordance with the record of decision for process buildings concurred with by Ohio EPA in July 2015 (DOE 2015e). The record of decision includes:

- Demolition of the buildings or structures;
- Characterization and demolition of underground man-made features;
- Treatment as needed to meet transportation and disposal requirements;

- Packaging of generated waste for final disposal; and
- Transportation and disposal of the waste.

DOE and Ohio EPA met during 2015 to discuss development of remedial design/remedial action documents such as a work plan to discuss general aspects of the work needed for implementation of the record of decision. A sampling and analysis plan for D&D of the X-114A Outdoor Firing Range was submitted to Ohio EPA in July 2015 and concurred with by Ohio EPA in August 2015 (DOE 2015h). Sampling was completed in September 2015. Removal of lead and stabilization of soil to immobilize residual lead in the X-114A Outdoor Firing Range began in 2015 and continued in 2016.

3.2.2 Site-wide Waste Disposition

The record of decision for site-wide waste disposition was concurred with by Ohio EPA in June 2015 (DOE 2015f). The record of decision selected a combination of on-site and off-site disposal, including construction of an OSWDF.

Figure 3.1 shows the location of the planned OSWDF in the northeast portion of PORTS. Ohio EPA concurred with Phase I and Phase II of the remedial design/remedial action work plan for the OSWDF (DOE 2015g) in September and October 2015, respectively, which allowed initial site construction activities such as tree clearing, fencing, utility installation, and installation of erosion and sediment controls. These activities began after approval of the work plan and continued in 2016.

3.3 ENVIRONMENTAL RESTORATION PROGRAM

DOE established the Environmental Restoration Program in 1989 to identify, control, and remediate environmental contamination at PORTS. Environmental restoration is conducted in accordance with the RCRA corrective action process, under U.S. EPA Administrative Order by Consent, issued on September 29, 1989 (amended in 1994 and 1997), and Consent Decree with the State of Ohio, issued on August 29, 1989. With implementation of D&D, removal of facilities and structures down to and including the building slab is controlled by the D&D process (see Section 3.2). Investigation and remediation of environmental contamination is completed under the RCRA corrective action process and in accordance with U.S. EPA Administrative Order by Consent and Consent Decree with the State of Ohio.



Figure 3.1. Location of the OSWDF at PORTS.

In general, the RCRA corrective action process consists of the following:

- 1) an assessment to identify releases of hazardous waste and hazardous constituents and determine the need for further investigation (the RCRA facility assessment),
- 2) an investigation to determine the nature and extent of any contamination (the RCRA facility investigation [RFI]), and
- 3) a study to identify and evaluate remedial alternatives to address contamination (the cleanup alternatives study/corrective measures study [CMS]).

Following the approval of the final cleanup alternative study/CMS, Ohio EPA selects the remedial alternatives that will undergo further review to determine the final remedial actions (the preferred plan). Upon concurrence from U.S. EPA and completion of the public review and comment period, U.S. EPA and Ohio EPA select the final remedial actions. Ohio EPA issues a decision document to select the final remedial actions and the remedial actions are implemented by DOE. Final remedial actions are reviewed by Ohio EPA on a schedule agreed upon by Ohio EPA and DOE (approximately every five years) to ensure that the remedial actions are performing as intended by the decision document and are protective of human health and the environment.

The initial assessment and investigation of PORTS under the RCRA corrective action process was completed in the 1990s. Because PORTS is a large facility, it was divided into quadrants (Quadrant I, II, III, and IV) to facilitate the cleanup process (see Chapter 6, Figure 6.1). Remedial actions have been implemented in each of the PORTS quadrants.

With the beginning of D&D, investigation of areas known as “deferred units” is beginning to occur. Deferred units are areas that were in or adjacent to the gaseous diffusion production and operational areas such that remedial activities prior to D&D would have interrupted operations, or were areas that could have become recontaminated from ongoing operations. Ohio EPA deferred investigation/remedial action of soil and groundwater associated with these units until D&D of PORTS (or until the area no longer met the requirements for deferred unit status). Ongoing environmental monitoring and on-site worker health and safety programs monitor the contaminants in these areas prior to D&D.

The *Deferred Units Resource Conservation and Recovery Act Facility Investigation/Corrective Measures Study Work Plan*, revised to respond to Ohio EPA comments received in 2013 through 2015, was submitted to Ohio EPA in March 2015 (DOE 2015a). Ohio EPA approved the work plan in June 2015. Soil and groundwater sampling in the work plan started in July 2015 and continued in 2016.

As part of the investigation of the deferred units, and to support the overall D&D of PORTS, DOE has prepared a soil background study to determine the concentrations of metals, radionuclides, and other constituents in soil. This background study will be used to 1) assess the extent of possible soil contamination that can be attributed to PORTS operations, 2) support development of risk-based soil preliminary remediation goals, and 3) support real property transfer under CERCLA. The *Final Soil Background Study Sampling and Analysis Report* was submitted to Ohio EPA in May 2015 and was approved by Ohio EPA in June 2015 (DOE 2015b).

The following sections describe the remedial actions underway in each quadrant as well as ongoing activities at any formerly deferred units. Table 3.1 lists remedial activities for the groundwater monitoring areas at PORTS, which include remedial actions required by decision documents and other actions.

3.3.1 Quadrant I

The *Quadrant I Cleanup Alternative Study/Corrective Measures Study* was approved by Ohio EPA in 2000 (DOE 2000). Ohio EPA issued the Decision Document for Quadrant I in 2001, which provided the required remedial actions for the X-749/X-120 groundwater plume and the Quadrant I Groundwater Investigative (5-Unit) Area (the Five-Unit Groundwater Investigative Area and X-231A/X-231B Oil Biodegradation Plots) (Ohio EPA 2001).

Remedial actions required for the X-749B Peter Kiewit Landfill (PK Landfill) were provided in separate Decision Documents issued by Ohio EPA in 1996 (Ohio EPA 1996a) and U.S. EPA in 1997 (U.S. EPA 1997). The following sections discuss the remedial actions required for the X-749/X-120 groundwater plume, PK Landfill, and the Quadrant I Groundwater Investigative (5-Unit) Area. Chapter 6 provides 2015 groundwater monitoring results for the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility, (Section 6.4.1.3 and Figure 6.2), PK Landfill (Section 6.4.2.1 and Figure 6.2) and Quadrant I Groundwater Investigative (5-Unit) Area (Section 6.4.3.1 and Figure 6.3).

3.3.1.1 X-749/X-120 groundwater plume

The remedial actions identified for X-749/X-120 groundwater plume (see Chapter 6, Figure 6.2) include phytoremediation of the groundwater plume, installation of a barrier wall around the eastern and southern portion of the X-749 Landfill, and continued operation of the groundwater collection trenches installed at the PK Landfill and X-749 Landfill. In addition, groundwater extraction wells were installed in 2007, 2008, and 2010 to control migration of the plume and remediate areas of higher trichloroethene (TCE) concentrations within the plume.

Phytoremediation is a process that uses plants to remove, degrade, or contain contaminants in soil and/or groundwater. Phytoremediation at the X-749/X-120 groundwater plume was installed in two phases during 2002 and 2003. The barrier wall around the eastern and southern portion of the X-749 Landfill was completed in 2002.

The *First Five-Year Review for the X-749/X-120 Groundwater Plume*, submitted to Ohio EPA in January 2011, found that the remedial actions implemented for the X-749/X-120 groundwater plume (both the remedial actions required by the Decision Document and the extraction wells installed in 2007 and 2008) were achieving remedial action objectives by preventing migration of contaminants from the X-749 Landfill and controlling migration of the X-749/X-120 groundwater plume (DOE 2011b). However, Ohio EPA and DOE agreed that the phytoremediation system was not as successful as anticipated in reducing concentrations of TCE in groundwater. The extraction wells that began operating in 2007-2008 in the groundwater collection trench on the southwest side of the X-749 Landfill and the X-749 South Barrier Wall Area, as well as the barrier wall on the south and east sides of the landfill (completed in 2002), appeared to be primarily responsible for the reductions in TCE concentrations within the X-749/X-120 groundwater plume. The next review of the remedial actions implemented for the X-749/X-120 groundwater plume was submitted to Ohio EPA in 2016. Ohio EPA approved the review in 2016.

Based on the results of the *First Five-Year Review for the X-749/X-120 Groundwater Plume*, DOE initiated an 18-month evaluation period (through September 2012) to determine whether additional groundwater extraction wells were necessary for remediation of the X-749/X-120 plume. Groundwater modeling completed as part of the 18-month evaluation indicated that the groundwater extraction well system was effective; therefore, no changes have been made to the extraction well system in the X-749/X-120 groundwater plume.

Table 3.1. Remedial actions at PORTS in groundwater monitoring areas

Quadrant/monitoring area	Remedial action/year completed
Quadrant I X-749/X-120 groundwater plume	X-749 multimedia cap – 1992 X-749 barrier wall (north and northwest sides of landfill) – 1992 X-749 subsurface drains and sumps – 1992 South barrier wall – 1994 X-120 horizontal well – 1996 X-625 Groundwater Treatment Facility – 1996 X-749 barrier wall (east and south sides of landfill) – 2002 Phytoremediation (22 acres) – 2002 & 2003 Injection of hydrogen release compounds – 2004 X-749 South Barrier Wall Area extraction wells – 2007 Two additional extraction wells in the groundwater collection trench on the southwest side of the X-749 Landfill – 2008 X-749/X-120 groundwater plume extraction wells – 2010
Quadrant I Peter Kiewit (PK) Landfill (X-749B)	Relocation of Big Run Creek – 1994 Groundwater collection system – 1994 Groundwater collection system expansion – 1997 PK Landfill Subtitle D cap – 1998
Quadrant I Quadrant I Groundwater Investigative (5-Unit) Area	Groundwater extraction wells (3) – 1991 X-622 Groundwater Treatment Facility – 1991 (upgraded in 2001) Interim soil cover at X-231B – 1995 X-231A/X-231B multimedia caps – 2000 Groundwater extraction wells (11) – 2002 Groundwater extraction well (1) – 2009 Removal of contaminated soil at former X-770 Building – 2010
Quadrant I X-749A Classified Materials Disposal Facility	Cap – 1994
Quadrant II Quadrant II Groundwater Investigative (7-Unit) Area	Operation of X-700 and X-705 building sumps – 1989 X-622T Groundwater Treatment Facility – 1992 Removal of X-720 Neutralization Pit – 1998 Removal of X-701C Neutralization Pit – 2001 Removal of contaminated soil near X-720 Neutralization Pit – 2001 X-627 Groundwater Treatment Facility – 2004 (replaced the X-622T facility) Enhanced anaerobic bioremediation – 2011
Quadrant II X-701B Former Holding Pond	X-237 Groundwater Collection System – 1991 X-624 Groundwater Treatment Facility – 1991 (upgraded 2006) Extraction wells (3) – 1993 (removed 2009-2011) X-623 Groundwater Treatment Facility – 1993 X-701B sump – 1995 Groundwater remediation by oxidant injection – 2008 Groundwater and soil remediation by oxidant mixing – 2011

Table 3.1. Remedial actions at PORTS in groundwater monitoring areas (continued)

Quadrant/monitoring area	Remedial action/year completed
Quadrant III X-740 Former Waste Oil Handling Facility Area	Phytoremediation – 1999 Oxidant injections – 2008 Enhanced anaerobic bioremediation – 2011
Quadrant IV X-611A Former Lime Sludge Lagoons	Soil cover – 1996 Prairie vegetation planted – 1997
Quadrant IV X-735 Landfills	Cap on northern portion – 1994 Cap on southern portion – 1998
Quadrant IV X-734 Landfills	Cap on X-734B Landfill (Phase I) – 1999 Cap on X-734 and X-734A Landfills (Phase II) – 2000
Quadrant IV X-533 Former Switchyard Complex	Contaminated soil removal – 2010

During development of the *Deferred Units RCRA RFI/CMS Work Plan for Solid Waste Management Units*, a previously unknown potential source area to the X-749/X-120 groundwater plume was identified north of the X-749 Landfill. This area is being investigated as part of the *Deferred Units RCRA RFI/CMS Work Plan for Solid Waste Management Units* (DOE 2015a).

Chapter 6, Section 6.4.1.3 and Figure 6.2, provide additional information about the 2015 groundwater monitoring results for the X-749/X-120 groundwater plume.

3.3.1.2 PK Landfill

The remedial actions required by the PK Landfill Decision Documents consisted of the continued operation of the eastern groundwater collection system installed in 1994 and construction of an engineered cap that meets the RCRA Subtitle D and related requirements (Ohio EPA 1996a and U.S. EPA 1997). In addition, the southeastern groundwater collection system was constructed in 1997 to contain surface seeps, groundwater from the southern slope of the PK Landfill, and the groundwater plume migrating toward Big Run Creek from the X-749 Landfill.

The second five-year review for the PK Landfill found that the remedial actions implemented at the PK Landfill (the groundwater collection systems and landfill cap) were achieving remedial action objectives by eliminating exposure pathways and reducing the potential for contaminant transport (DOE 2008d). Concentrations of many of the contaminants detected in the PK Landfill wells, sumps, and manholes had decreased significantly from 1999 to 2007. Contaminants detected in the PK Landfill wells, sumps, and manholes were not detected in surface water samples collected from Big Run Creek adjacent to or downstream from PK Landfill. Based on these data, construction of a barrier wall on the upgradient sides of the PK Landfill did not appear to be necessary.

The third five-year review for the PK Landfill found that the corrective actions implemented at the PK Landfill (the groundwater collection systems, landfill cap, and institutional controls) were continuing to achieve corrective action objectives by eliminating exposure pathways and reducing the potential for contaminant transport (DOE 2013f). The next review of the remedial actions implemented at the PK Landfill will be submitted to Ohio EPA in 2018.

Chapter 6, Section 6.4.2.1 and Figure 6.2, provide 2015 groundwater monitoring results for the PK Landfill area.

3.3.1.3 Quadrant I Groundwater Investigative (5-Unit) Area

Remedial actions identified for the Quadrant I Groundwater Investigative (5-Unit) Area (Chapter 6, Figure 6.3) are: 1) installation of multimedia caps over the X-231A and X-231B Oil Biodegradation Plots; and 2) installation of 11 additional groundwater extraction wells to extract contaminated groundwater for treatment in the X-622 Groundwater Treatment Facility (Ohio EPA 2001). The caps were constructed in 2000 and operation of the groundwater extraction wells began in 2002. In 2009, an additional extraction well was installed south of the X-326 Process Building to control and remediate a newly identified source of TCE beneath the building. Table 3.1 lists the remedial actions completed for the Quadrant I Groundwater Investigative (5-Unit) Area.

A five-year review of both the groundwater extraction system for the Quadrant I Groundwater Investigative (5-Unit) Area and the multi-layered caps for the X-231A and X-231B Oil Biodegradation Plots was completed in 2008 (DOE 2008a). This report found that the remedial actions had eliminated potential exposure pathways to contaminants and reduced concentrations of TCE in the groundwater, although more slowly than expected.

The second five-year review of the groundwater extraction system for the Quadrant I Groundwater Investigative (5-Unit) Area and the multi-layered caps for the X-231A and X-231B Oil Biodegradation Plots was submitted to Ohio EPA in 2013 (DOE 2013c). This report found that the remedial actions implemented for the X-231A and X-231B Oil Biodegradation Plots and the Five-Unit Groundwater Investigative Area (the multimedia caps and groundwater extraction system) were continuing to eliminate potential exposure pathways to contaminants, control migration of the groundwater plume, and remove volatile organic compounds (VOCs) from groundwater. The next review of the remedial actions implemented at the Quadrant I Groundwater Investigative (5-Unit) Area and X-231A/B Oil Biodegradation Plots will be submitted to Ohio EPA in 2018.

Chapter 6, Section 6.4.3.1 and Figure 6.3, provide information on the groundwater monitoring completed in the Quadrant I Groundwater Investigative (5-Unit) Area during 2015.

3.3.2 Quadrant II

The *Quadrant II Cleanup Alternative Study/Corrective Measures Study* was approved by Ohio EPA in 2001 (DOE 2001). After approval of the document, however, Ohio EPA requested an amendment to the approved study to address additional remedial alternatives for the X-701B area. Amendments were submitted in 2001 and 2002. In 2003, Ohio EPA informed DOE that a separate Decision Document would be prepared for the X-701B area, and the X-701B Decision Document was issued in 2003 (Ohio EPA 2003).

Chapter 6 provides 2015 groundwater monitoring results for the following areas in Quadrant II that require groundwater monitoring: Quadrant II Groundwater Investigative (7-Unit) Area (Section 6.4.5.1 and Figure 6.4), X-701B Former Holding Pond (Section 6.4.6.1 and Figure 6.5), and X-633 Former Recirculating Cooling Water Complex (Section 6.4.7.1 and Figure 6.6).

3.3.2.1 Quadrant II Groundwater Investigative (7-Unit) Area

A number of deferred units are in the groundwater plume in the Quadrant II Groundwater Investigative (7-Unit) Area (Chapter 6, Figure 6.4). A special investigation conducted in 2009, which sampled soil and groundwater, identified areas of higher TCE concentrations that appeared to be associated with continuing sources of groundwater contamination in the southeastern portion of the plume. In 2010, Ohio EPA approved an interim remedial measure (IRM) for this area called enhanced anaerobic bioremediation.

Enhanced anaerobic bioremediation utilizes injections of fermentable carbon compounds such as sodium lactate (a common ingredient in soaps and face creams) to provide additional food for naturally-occurring microorganisms in soil that degrade TCE to harmless substances. The project began in 2010 and was completed in 2013.

The *Final Report for the 7-Unit Interim Remedial Measure* was submitted to Ohio EPA in 2014 (DOE 2014a). Overall, the results indicated that appropriate conditions can be established at the site to degrade TCE despite the high TCE concentrations in soil and groundwater. Enhanced anaerobic bioremediation successfully reduced TCE to *cis*-1,2-dichloroethene, and with bioaugmentation, some of the *cis*-1,2-dichloroethene was converted to ethane. The report concluded that after the six injection events plus a bioaugmentation event (injection of additional microorganisms that degrade VOCs), overall there was not a measureable reduction in the average concentration of TCE in groundwater, most likely due to the potential presence of dense non-aqueous phase liquid TCE in the area, and the decision was made to conclude the IRM.

DOE and Ohio EPA have agreed that selection of a remedial action for the Quadrant II Groundwater Investigative (7-Unit) Area will be incorporated into the deferred units preferred plan and decision document.

Chapter 6, Section 6.4.5.1 and Figure 6.4, provide information about the groundwater monitoring completed at the Quadrant II Groundwater Investigative (7-Unit) Area during 2015.

3.3.2.2 X-701B Former Holding Pond

Remedial actions required by the Decision Document for X-701B, issued in 2003, include groundwater remediation by injection of a chemical oxidant (Ohio EPA 2003). The oxidant injections required by the Decision Document took place between 2006 and 2008. Following the end of the injections in 2008, an independent review of the X-701B project was completed by DOE Headquarters to evaluate remediation results and provide recommendations for a path forward.

The review of the X-701B oxidant injections determined that the method used to inject oxidant into the contaminated area was not able to address contaminants in the deepest portion of the contaminated soil. If contaminants remained in this portion of the soil, they would continue to be released into the groundwater plume. Therefore, DOE proposed an IRM to excavate soil in the western portion of the X-701B plume area and directly mix oxidant into the contaminated soil. The IRM began in December 2009 and was completed in January 2011. Chapter 6, Section 6.4.6.1 and Figure 6.5, provide information about the groundwater monitoring completed at the X-701B Former Holding Pond during 2015.

3.3.2.3 X-633 Former Recirculating Cooling Water Complex

The X-633 Recirculating Cooling Water Complex was demolished in 2010. A RCRA investigation of soil and groundwater in the area was implemented in 2011. Areas of soil potentially contaminated with metals were identified, but the higher concentrations of metals may have been present in these areas (15 to 20 ft below ground surface) due to naturally-occurring variations in the geology of the area.

Chromium and TCE were detected in groundwater at concentrations above the preliminary remediation goals during the 2011 RCRA investigation for the X-633 area. DOE agreed to sample eight wells around the area annually to continue evaluation of chromium and TCE in groundwater at this area. The *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant* provides the data for this monitoring (DOE 2016a).

3.3.3 Quadrant III

The *Quadrant III Cleanup Alternative Study/Corrective Measures Study* was approved by Ohio EPA in 1998 (DOE 1998a). The Decision Document for Quadrant III, issued in 1999, required phytoremediation of the groundwater plume near the X-740 Waste Oil Handling Facility (Ohio EPA 1999a).

Over 700 hybrid poplar trees were planted on a 2.6-acre area above the X-740 groundwater plume (Chapter 6, Figure 6.8) in 1999. Evaluation reports for this remedial action were completed in 2003 and 2007. The reports concluded that the phytoremediation system had not performed as expected to remove TCE from groundwater in this area (DOE 2003 and DOE 2007b).

In response to Ohio EPA concerns about the performance of the phytoremediation system, DOE implemented additional remedial activities for the X-740 area. Three rounds of oxidant injections were completed in 2008 to remove TCE from the groundwater. Although the oxidant briefly reduced TCE concentrations detected in some of the wells, TCE concentrations in groundwater returned to typical levels in 2009.

In 2010, Ohio EPA approved a pilot study of enhanced anaerobic bioremediation for the X-740 area. Section 3.3.2.1 provides additional information about enhanced anaerobic bioremediation. Emulsified oil, a slow-acting fermentable carbon compound, was injected into the selected portions of the X-740 groundwater plume during December 2010 and January 2011. Collection of groundwater samples to monitor the pilot study continued through 2015. TCE has decreased in wells within the area of the groundwater plume that was treated during the pilot study (see Chapter 6, Section 6.4.9.1 and Figure 6.8). DOE and Ohio EPA have agreed that selection of a new remedy for the X-740 groundwater plume will be incorporated into the deferred units preferred plan and decision document.

Chapter 6 provides 2015 groundwater monitoring results for the following areas in Quadrant III that require groundwater monitoring: X-616 Former Chromium Sludge Surface Impoundments (Section 6.4.8.1 and Figure 6.7) and X-740 Former Waste Oil Handling Facility (Section 6.4.9.1 and Figure 6.8).

3.3.4 Quadrant IV

The *Quadrant IV Cleanup Alternative Study/Corrective Measures Study* was approved by Ohio EPA in 1998 (DOE 1998b). DOE received the Decision Document for Quadrant IV in 2000 (Ohio EPA 2000). No new remedial actions were required in Quadrant IV (remedial actions had already taken place at the X-344D Hydrogen Fluoride Neutralization Pit, X-735 Landfills, X-611A Former Lime Sludge Lagoons, and X-734 Landfills).

Chapter 6 provides 2015 groundwater monitoring results for the following areas in Quadrant IV that require groundwater monitoring: X-611A Former Lime Sludge Lagoons (Section 6.4.10.1 and Figure 6.9), X-735 Landfills (Section 6.4.11.1 and Figure 6.10), X-734 Landfills (Section 6.4.12.1 and Figure 6.11), X-533 Former Switchyard Complex (Section 6.4.13.1 and Figure 6.6), and X-344C Former Hydrogen Fluoride Storage Building (Section 6.4.14.1 and Figure 6.12).

3.3.4.1 X-611A Former Lime Sludge Lagoons

Ohio EPA and U.S. EPA issued a Decision Document for the X-611A area (Chapter 6, Figure 6.9) in 1996, which required a soil cover over the former lagoons and establishment of a prairie habitat (Ohio EPA 1996b). The soil cover and planting of the prairie were completed in 1997. Five-year reviews completed in 2002, 2008, and 2013 (DOE 2002b, DOE 2008c, and DOE 2013e) found that the soil cover and prairie habitat were meeting the remedial action objectives for this unit by eliminating exposure pathways to the contaminants in the sludge at this area. The next review of the remedial actions implemented at the X-611A area will be submitted to Ohio EPA in 2018.

3.3.4.2 X-734 Landfills

Ohio EPA issued a Decision Document for the X-734 Landfills (Chapter 6, Figure 6.11) in 1999 (Ohio EPA 1999b). Remedial actions required by the Decision Document included construction of a multimedia cap over the northern portion of the landfills and a soil cap over the southern portion of the area. These caps were installed in 1999 and 2000.

Five-year reviews completed in 2008 and 2013 found that the landfill caps have achieved remedial action objectives by isolating contaminants in soil and sediment from potential receptors (DOE 2008b and DOE 2013d). The caps were also preventing contaminants from migrating from soil to groundwater and from groundwater to surface water. The next review of the remedial actions implemented at the X-734 Landfills will be submitted to Ohio EPA in 2018.

3.3.4.3 X-630 Former Recirculating Cooling Water Complex

The X-630 Recirculating Cooling Water Complex, located in Quadrant IV within Perimeter Road and west of the X-533 Switchyard Complex, was removed during 2011 as part of D&D. A RCRA investigation of soil and groundwater at the X-630 Recirculating Cooling Water Complex was implemented in 2011.

Areas of soil potentially contaminated with metals were identified, but the higher concentrations of metals may have been present in these areas (15 to 20 ft below ground surface) due to naturally-occurring variations in the geology of the area.

Chromium and TCE were detected in groundwater at concentrations above the preliminary remediation goals during the 2011 RCRA investigation for the X-630 area. DOE agreed to sample four wells around the area annually to continue evaluation of chromium and TCE in groundwater at this area. The *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant* provides the data for this monitoring (DOE 2016a).

3.4 WASTE MANAGEMENT PROGRAM

The DOE Waste Management Program directs the safe storage, treatment, and disposal of waste generated by past and present operations and from current D&D and Environmental Restoration projects at PORTS. Waste managed under the program is divided into the following seven categories, which are defined below:

- *LLW* – radioactive waste not classified as high level or transuranic waste. Some LLW is also classified as bulk survey for release (BSFR) waste. BSFR waste consists of solid materials such as building rubble, soil, paper, or plastics that have extremely low levels of radioactivity. BSFR waste is evaluated by an intermediate facility to ensure it meets criteria for radioactivity and other parameters, and then it is disposed at one of four authorized landfills in Tennessee.
- *Hazardous (RCRA) waste* – waste listed under RCRA or waste that exhibits one or more of the four RCRA hazardous characteristics: ignitability, corrosivity, reactivity, and toxicity. Universal waste, which includes common items such as batteries and light bulbs, is a subset of RCRA waste that is subject to reduced requirements for storage, transportation, and disposal or recycling.
- *PCB wastes* – waste containing PCBs, a class of synthetic organic chemicals. Disposal of PCB-contaminated materials is regulated under TSCA.
- *RCRA/low-level radioactive mixed waste* – waste containing both hazardous and radioactive components. The waste is subject to RCRA, which governs the hazardous components, and to the Atomic Energy Act that governs the radioactive components.

- *PCB/low-level radioactive mixed waste* – waste containing both PCB and radioactive components. The waste is subject to TSCA regulations that govern PCB components, and to the Atomic Energy Act that governs radioactive components.
- *PCB/RCRA/low-level radioactive mixed waste* – waste containing PCB and radioactive components that is also a RCRA hazardous waste. The waste is subject to RCRA regulations, TSCA regulations that govern PCBs, and to the Atomic Energy Act that governs radioactive components.
- *Solid waste* – Waste that includes construction and demolition debris, industrial waste, and sanitary waste, as defined by Ohio regulations. These wastes can include waste from construction or demolition activity and office waste. Waste contaminated with asbestos may also be included in this category if it is not included in any of the categories listed above (PCB, RCRA, and/or LLW).

Waste management requirements are varied and are sometimes complex because of the variety of waste streams generated by DOE activities at PORTS. DOE Orders, Ohio EPA regulations, and U.S. EPA regulations must be satisfied to demonstrate compliance with waste management activities. Additional policies have been implemented for management of radioactive, hazardous, and mixed wastes. These policies include the following:

- minimizing waste generation;
- characterizing and certifying wastes before they are stored, processed, treated, or disposed;
- pursuing volume reduction (such as blending and bulking) as well as on-site storage in preparation for safe and compliant final treatment and/or disposal; and
- recycling.

With the beginning of D&D at PORTS, DOE is placing increased emphasis on the evaluation of materials generated by D&D for reuse or recycling. An agreement between DOE and the Southern Ohio Diversification Initiative (SODI) allows DOE to transfer excess equipment, clean scrap materials and other assets to SODI. SODI first attempts to reuse the excess equipment and property within the local community. Pursuant to the agreement, if SODI is unable to place the property for reuse in the local community, SODI may sell the property. When SODI sells the property, the proceeds are used to support economic development in the southern Ohio region. In 2015, SODI received approximately 236 tons of materials from PORTS, primarily recyclable metals and reusable vehicles.

In 2015, FBP shipped almost 9200 tons of materials to off-site facilities for treatment, disposal, recycling, or reuse (see Table 3.2).

The following materials from FBP were sent off-site for recycling in 2015:

- aluminum cans: 1616 lbs
- batteries: 43,523 lbs
- electronic materials (computer equipment, etc.): 19,260 lbs
- light bulbs: 7884 lbs
- paper/cardboard: 99,655 lbs
- plastic bottles: 7033 lbs
- recyclable metals (including vehicles) (SODI): 236 tons

Table 3.2. Waste Management Program off-site treatment, disposal, and recycling accomplishments for 2015

Waste type	Waste stream	Quantity (lbs ^a)	Treatment or disposal, facility
RCRA	Aerosol cans and other liquids or solids classified as hazardous waste	3448	Environmental Quality Co.
LLW	Uranium materials, scrap metal, sludge, and other debris.	152,721	EnergySolutions Clive, UT
LLW	D&D waste, uranium materials, scrap metal, and other solids	14,448,831	Nevada National Security Site
LLW	Assorted solid debris	12,230	EnergySolutions Bear Creek, TN
LLW/BSFR	Assorted solids (wood, metal, plastic, etc.)	302,030	EnergySolutions Gallaher Rd, TN
RCRA/LLW	Lab wastes and other liquids or solids	2251	Diversified Scientific Solutions
RCRA/LLW	D&D waste, soil, alumina, and other materials	52,003	EnergySolutions Clive, UT
RCRA/LLW	Alumina trap waste, sludge, and other materials	1611	Materials & Energy Corp.
RCRA/LLW	Solids contaminated with RCRA metals	2156	EnergySolutions Bear Creek, TN
RCRA/LLW	Assorted liquids and solids contaminated with RCRA metals	770	Permafix
RCRA/LLW	Solids contaminated with RCRA metals	2530	Waste Control Specialists
LLW/PCB	Oil/water mixture from X-333 and X-330 Buildings	5112	Diversified Scientific Solutions
LLW/PCB	Motors, pallets, plastic, and other solid materials	86,322	Nevada National Security Site
RCRA/LLW/ PCB	Used grease	87	Diversified Scientific Solutions
PCB	PCB ballasts and other solid materials	507	Environmental Quality Co.
Solid waste	D&D waste, concrete, asphalt, metal, and other materials	293,300	Rumpke/Pike Sanitation Landfill
Solid waste	Non-hazardous liquids (antifreeze, asphalt repair)	2176	Environmental Quality Co.
Solid waste	Non-hazardous liquids (non-recyclable oil)	108,900	Clean Harbors
Solid waste	Non-hazardous antifreeze/water mixtures from X-670 Cooling Tower maintenance	2,149,784	Valicor

Table 3.2. Waste Management Program off-site treatment, disposal, and recycling accomplishments for 2015 (continued)

Waste type	Waste stream	Quantity (lbs ^a)	Treatment or disposal, facility
-	Recyclable aluminum cans, batteries, electronic materials, plastic, batteries, metal, light bulbs, etc. (see Section 3.4)	212,260	Various (not including SODI)
-	Recyclable materials transferred to SODI (see Section 3.4)	471,967	-

^aLbs in net weight (waste only).

- tires: 16,320 lbs
- toner cartridges: 3099 lbs
- wooden pallets: 13,870 lbs.

3.5 ENVIRONMENTAL SUSTAINABILITY PROGRAM

DOE is committed to reducing potential environmental risks, costs, wastes, and future liability by effectively integrating environmental sustainability principles into DOE activities at PORTS in a cost effective and environmentally conscious manner. The DOE Environmental Sustainability Program is a balanced, holistic approach that links planning, budgeting, measuring, and improving PORTS overall environmental performance to specific goals and outcomes. The *Fiscal Year 2016 Site Sustainability Plan* describes the Environmental Sustainability Program and integrates the tenets of an EMS (see Chapter 2, Section 2.3.6) (DOE 2015c). The Environmental Sustainability Program includes elements of pollution prevention, waste minimization, affirmative procurement, sustainable design, and energy and water efficiency.

DOE is committed to minimizing and/or eliminating the amounts and types of wastes generated and to achieving reduced life cycle costs for managing and dispositioning property and wastes during all of DOE projects and activities at PORTS.

Effective environmental sustainability management begins with an integrated strategy. In order to achieve the objectives and targets of the Environmental Sustainability Program, DOE has developed and implemented a well-defined strategy for setting, updating, and achieving objectives and targets in line with the EMS and in conjunction with DOE pollution prevention goals. The broad objectives are core elements of the Environmental Sustainability Program. These objectives, presented below, are both qualitative and quantitative and reduce the life cycle cost and liability of DOE programs and operations at PORTS:

- eliminating, minimizing, or recycling wastes that would otherwise require storage, treatment, disposal, and long-term monitoring and surveillance;
- eliminating or minimizing use of toxic chemicals and associated environmental releases that would otherwise require control, treatment, monitoring, and reporting;

- maximizing the use (procurement) of recycled-content materials and environmentally preferable products and services, thereby minimizing the economic and environmental impacts of managing by-products and wastes generated in the conduct of mission-related activities; and
- reducing the life-cycle cost of managing personal property at PORTS.

DOE continued energy reduction programs at PORTS that focused on accomplishing the goals of Executive Order 13693, *Planning for Federal Sustainability in the Next Decade*. Executive Order 13693 provides goals for greenhouse gas emission reductions and environmental sustainability (including energy and water efficiency; waste and pollution prevention; and electronics stewardship).

In support of this Executive Order, the *Fiscal Year 2016 Site Sustainability Plan for the Portsmouth Gaseous Diffusion Plant* provides goals and progress through fiscal year 2015 for reductions in greenhouse gas emissions, water consumption, recycling/waste diversion, electronic stewardship, and other areas (DOE 2015c). The following accomplishments were listed for fiscal year 2015:

- a decrease of 45% in greenhouse gas emissions (primarily associated for electricity consumption) versus the fiscal year 2008 baseline emissions.
- a decrease in water consumption of 7.9% in fiscal year 2015 versus fiscal year 2014.
- 13.4% of electricity consumption from renewable energy sources, which exceeds the goal of 7.5%.
- an increase in alternative fuel vehicles (either flex-fuel or hybrid vehicles) to 73% of the total vehicle fleet. All new vehicles are alternate fuel vehicles.

PORTS received a 3-Star EPEAT Purchasing Award from the Green Electronics Council in fiscal year 2015 for its policies and procedures for the purchase of EPEAT-certified products. PORTS also received a GreenBuy Silver Award from DOE for fiscal year 2015 for buying products that save energy, conserve water, and reduce health and environmental impacts.

3.6 PUBLIC AWARENESS PROGRAM

A comprehensive community relations and public participation program is in place at PORTS. The purpose of the program is to foster a spirit of openness and credibility between PORTS officials and local citizens, elected officials, business, media, and various segments of the public. The program also provides the public with opportunities to become involved in the decisions affecting environmental issues at PORTS.

The PORTS Site Specific Advisory Board, comprised of citizens from the local area, provides public input and recommendations to DOE on D&D, environmental remediation, waste management, and related issues at PORTS. Regularly scheduled meetings that are open to the public are held between DOE and the PORTS Site Specific Advisory Board. Additional information about the PORTS Site Specific Advisory Board can be obtained at www.ports-ssab.energy.gov or by calling 740-289-5249.

The PORTS Envoy Program matches employee volunteers with community stakeholders such as families living next to DOE property, community groups, and local government organizations. The envoys communicate information about PORTS D&D and other site issues to the stakeholders and are available to answer stakeholder questions about PORTS.

DOE also maintains a public Environmental Information Center to provide public access to documents used to make decisions on remedial actions being taken at PORTS. The Information Center is located just

north of PORTS at the Ohio State University Endeavor Center (Room 207), 1862 Shyville Road, Piketon, Ohio 45661. The email address is portseic@pma-iss.com and web site is portsmouthic.com. Hours for the Information Center are 9 a.m. to noon Monday and Tuesday, noon to 4 p.m. Wednesday and Thursday, or by appointment (call 740-289-8898). Other information, including this Annual Site Environmental Report, can also be obtained from the DOE Portsmouth/Paducah Project Office web site at www.energy.gov/pppo or the FBP web site at www.fbportsmouth.com.

Public update meetings and public workshops on specific topics are also held to keep the public informed and to receive their comments and questions. Periodically, fact sheets about major projects are written for the public. Additionally, notices of document availability and public comment periods, as well as other communications on the program, are regularly distributed to the local newspaper and those on the community relations mailing list, neighbors within 2 miles of the plant, and plant employees.

An educational outreach program facilitated by a DOE grant administered by Ohio University includes a project in which local high school students produce a summary of the Annual Site Environmental Report for distribution to the public. The DOE Portsmouth/Paducah Project Office web site at www.energy.gov/pppo provides additional information about this project.

Points of contact have been established for the public to obtain information or direct questions regarding the Environmental Management Program. The DOE Site Office may be contacted at 740-897-5010. The Office of Public Affairs (740-897-3933) also provides information on the program.

This page intentionally left blank.

4. ENVIRONMENTAL RADIOLOGICAL PROGRAM INFORMATION

4.1 SUMMARY

Environmental monitoring at PORTS measures both radiological and chemical parameters in air, water, soil, sediment, and biota (animals, vegetation, and crops). This chapter discusses the radiological component of environmental monitoring programs at PORTS; Chapter 5 discusses the non-radiological parameters for the monitoring programs.

Environmental monitoring programs are required by state and federal regulations, permits, and DOE Orders. These programs may also be developed to address public concerns about plant operations. In 2015, environmental monitoring information was collected by DOE contractors (FBP and BWCS) and Centrus. This chapter includes information on air emissions and water discharges from Centrus to provide a more complete summary of environmental monitoring at PORTS.

Environmental monitoring data collected at PORTS are used to assess potential impacts to human health and the environment from radionuclides released by current and historical PORTS operations. This impact, called a dose, can be caused by radionuclides released to air and/or water, or radiation emanating directly from buildings or other objects at PORTS. U.S. EPA sets a 10 mrem/year limit for the dose from radionuclides released to the air in the NESHAP (40 CFR Part 61, Subpart H). DOE sets a dose limit as low as reasonably achievable¹, but no more than 100 mrem/year for the dose from radionuclides from all potential pathways in DOE Order 458.1. A person living in the United States receives an average dose of approximately 311 mrem/year from natural sources of radiation (National Council on Radiation Protection [NCRP] 2009).

This chapter includes radiological dose calculations for the dose to the public from radionuclides released to the air and surface water (the Scioto River), from external radiation, and from radionuclides detected by environmental monitoring programs. The maximum dose a member of the public could receive from radiation released by PORTS in 2015 or detected by environmental monitoring programs in 2015 is 1.1 mrem/year. This summary of the dose calculations assumes that the same individual, or representative person, works at a private company located on the west side of the PORTS reservation and lives in the immediate vicinity of PORTS. The representative person is assumed to be exposed to the maximum dose calculated from each pathway. Table 4.1 summarizes this dose information.

Table 4.1. Summary of potential doses to the public from PORTS in 2015

Source of dose	Dose (mrem/year)
Airborne radionuclides (off-site individual)	0.037 ^a
Radionuclides released to the Scioto River	0.0017
External radiation at station A29 (west side of PORTS)	0.96
Radionuclides detected by environmental monitoring programs	0.082
Total	1.1^b

^a10 mrem/year is U.S. EPA limit for airborne radionuclides in the NESHAP (40 CFR Part 61, Subpart H).

^b100 mrem/year is the DOE limit for all potential pathways in DOE Order 458.1.

¹ “As low as reasonably achievable” is an approach to radiation protection to manage and control releases of radioactive material to the environment, the workforce, and members of the public so that levels are as low as reasonable, taking into account societal, environmental, technical, economic, and public policy considerations. As low as reasonably achievable is not a specific release or dose limit, but a process that has the goal of optimizing control and managing release of radioactive material to the environment and doses so they are as far below the applicable limits as reasonably achievable. This approach optimizes radiation protection.

4.2 ENVIRONMENTAL RADIOLOGICAL PROGRAM INTRODUCTION

Environmental monitoring programs at PORTS are designed to detect the effects (if any) of PORTS operations on human health and the environment. Multiple samples are collected throughout the year and analyzed for radionuclides that could be present from PORTS activities. The results of these monitoring programs are used to gauge the environmental impact of PORTS operations and to set priorities for environmental improvements.

Environmental regulations, permits, DOE Orders, and public concerns are all considered in developing environmental monitoring programs. State and federal regulations drive some of the monitoring conducted at PORTS such as limitations on discharges to air and water. DOE Orders 231.1B, *Environment Safety and Health Reporting*, and 458.1, *Radiation Protection of the Public and the Environment*, also address environmental monitoring requirements.

The DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* describes the environmental monitoring programs for DOE activities at PORTS (DOE 2013a). Specific radionuclides monitored at PORTS are selected based on the materials handled at PORTS and on historic monitoring data. For example, samples are analyzed for uranium and isotopic uranium because of the uranium enrichment process. Samples are analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240) and technetium-99 because these radionuclides are produced during the fission process in nuclear reactors and were introduced to PORTS via the use of recycled uranium beginning in the late 1950s.

In 2015, environmental monitoring data were collected by DOE contractors (FBP and BWCS) and Centrus. This chapter provides information on the Centrus NPDES monitoring program and air emissions of radionuclides from Centrus sources. Centrus data are provided for informational purposes only; DOE cannot ensure the quality of Centrus data.

Data from the following environmental monitoring programs are included in this chapter:

- airborne discharges
- ambient air
- external radiation
- discharges to surface water
- surface water
- sediment
- soil
- biota.

DOE also conducts an extensive groundwater monitoring program at PORTS. Chapter 6 provides information on the groundwater monitoring program, associated surface water monitoring, and water supply monitoring.

As discussed in this chapter, dose is a measure of the potential biological damage that could be caused by exposure to and subsequent absorption of radiation to the body. Because there are many natural sources of radiation, a person living in the United States receives an average dose of approximately 311 mrem/year from sources of natural radiation (NCRP 2009). Appendix A provides additional information on radiation and dose.

Releases of radionuclides from PORTS activities can result in a dose to a member of the public in addition to the dose received from natural sources of radiation. PORTS activities that release radionuclides are regulated by U.S. EPA and DOE. Airborne releases of radionuclides from DOE

facilities are regulated by U.S. EPA under the NESHAP (40 CFR Part 61, Subpart H). These regulations set an annual dose limit of 10 mrem/year to any member of the public as a result of airborne radiological releases.

DOE regulates radionuclide emissions to all environmental media through DOE Orders 436.1, *Departmental Sustainability*, and 458.1, *Radiation Protection of the Public and the Environment*. DOE Order 458.1 sets a dose limit as low as reasonably achievable, but no more than 100 mrem/year to any member of the public from all radionuclide releases from a facility. The annual dose limit in NESHAP (10 mrem/year) applies only to airborne radiological releases.

To aid in comparing sampling results for air and water to the 100 mrem/year dose limit, the 100 mrem/year limit is converted into a derived concentration standard (DOE 2011a). The derived concentration standard is the concentration of a radionuclide in air or water that under conditions of continuous exposure for one year by one exposure mode (ingestion of water or inhalation of air) would result in a dose of 100 mrem.

Small quantities of radionuclides were released to the environment from PORTS operations during 2015. This chapter describes the methods used to estimate the potential doses that could result from radionuclides released from PORTS operations. In addition, this chapter assesses the potential doses that could result from radionuclides historically released by PORTS and detected in 2015 by environmental monitoring programs.

4.3 RADIOLOGICAL EMISSIONS AND DOSES

Exposure to radioactive materials can occur from releases to the atmosphere, surface water, or groundwater and from exposure to external radiation emanating from buildings or other objects. For 2015, doses are estimated for exposure to atmospheric releases, external radiation, and releases to surface water (the Scioto River).

Doses are also estimated for exposure to radionuclides from PORTS operations that were detected in 2015 as part of the DOE environmental monitoring programs for sediment, soil, residential drinking water (well water – excluding naturally-occurring detections of uranium isotopes) and selected biota (vegetation, deer, fish, crops, and dairy products). Analytical data from the environmental monitoring programs are assessed to determine whether radionuclides were detected at locations accessible to the public. If radionuclides were detected at locations accessible to the public, a dose assessment is completed based on the monitoring data. Exposure to radionuclides detected in groundwater at PORTS is not included because contaminated groundwater at PORTS is not a source of drinking water.

In 2015, doses are estimated for exposure to radionuclides detected by the monitoring programs for sediment, soil, and vegetation. Radionuclides were not detected in 2015 in samples of residential drinking water, deer, fish, crops, and dairy products.

In addition, DOE Order 458.1 sets absorbed dose rate limits for aquatic animals, riparian animals, terrestrial plants, and terrestrial animals. This chapter discusses the dose calculations completed to demonstrate compliance with these limits.

DOE staff, DOE contractors, and visitors to DOE areas who may be exposed to radiation are also monitored. These results are also provided in this chapter.

4.3.1 Dose Terminology

Most consequences associated with radionuclides released to the environment are caused by interactions between human tissue and various types of radiation emitted by the radionuclides. These interactions

involve the transfer of energy from radiation to tissue, potentially resulting in tissue damage. Radiation may come from radionuclides outside the body (in or on environmental media or objects) or from radionuclides deposited inside the body (by inhalation, ingestion, and, in a few cases, absorption through the skin). Exposures to radiation from radionuclides outside the body are called external exposures, and exposures to radiation from radionuclides inside the body are called internal exposures. This distinction is important because external exposure occurs only as long as a person is near the external radionuclide; simply leaving the area of the source will stop the exposure. Internal exposure continues as long as the radionuclide remains inside the body.

The three naturally-occurring uranium isotopes (uranium-234, uranium-235, and uranium-238) and technetium-99 are the most commonly detected radionuclides in environmental media samples collected around PORTS. Other radioactive isotopes (americium-241, neptunium-237, plutonium-238, plutonium-239/240, and uranium-236) are occasionally detected at PORTS and may be included in the calculations to ensure the potential dose from PORTS operations is not underestimated. Technetium-99 and transuranic radionuclides (americium-241, plutonium-238, and plutonium-239/240) are present in the world-wide environment in very small amounts due to radioactive fallout in the atmosphere from nuclear weapons testing by various countries around the world.

A number of specialized measurement units have been defined for characterizing exposures to ionizing radiation. Because the damage associated with exposure to radiation results primarily from the exposure of tissue to ionizing radiation, the units are defined in terms of the amount of ionizing radiation absorbed by human (or animal) tissue and in terms of the biological consequences of the absorbed energy. These units include the following:

- *Absorbed dose* – the quantity of ionizing radiation energy absorbed by an organ divided by the organ’s mass. The unit of absorbed dose is the rad, equal to 0.01 joule per kilogram in any medium (1 rad = 0.01 gray).
- *Equivalent dose* – the product of the absorbed dose (rad) in tissue and a radiation weighting factor. Equivalent dose is expressed in units of rem or sievert (1 rem = 0.01 sievert).
- *Effective dose* – the sum of the doses received by all organs or tissues of the body after each one has been multiplied by the appropriate tissue weighting factor. It includes the dose from radiation sources internal and/or external to the body. Effective dose is expressed in units of rem (or sievert). In this report, the term “effective dose” is often shortened to “dose.”
- *Collective dose* – the sum of the effective doses to all persons in a specified population received in a specified period of time. Collective dose is expressed in units of person-rem or person-sievert. The collective dose is also frequently called the “population dose.”

4.3.2 Airborne Emissions

Airborne discharges of radionuclides from PORTS are regulated under the NESHAP (40 CFR Part 61, Subpart H). Releases of radionuclides are used to calculate a dose to members of the public, which is reported annually to U.S. EPA and Ohio EPA. Section 4.3.3 discusses the results of this dose calculation.

In 2015, FBP was responsible for air emission sources associated with the former gaseous diffusion plant operations, including continuously monitored vents in the X-326 Process Building and the X-344A Uranium Hexafluoride Sampling Building. The vents in the X-326 were in use to support D&D activities. The X-344A vents were in use for ongoing sampling activities of uranium product. Vents in the X-330 and X-333 Process Buildings and X-343 Feed Vaporization and Sampling Building that were continuously monitored when the gaseous diffusion plant was operating were inactive during 2015.

Other radionuclide air emission sources included room ventilation exhausts and/or pressure relief vents associated with the X-700 Chemical Cleaning Facility (inactive), X-710 Technical Services Building, X-705 Decontamination Facility, X-326 L-cage Glove Box (inactive), and the XT-847 Glove Box (inactive). These emission sources were not continuously monitored; emissions from these sources (when in use) were estimated based on operating data and U.S. EPA emission factors. The X-622, X-623, X-624, and X-627 Groundwater Treatment Facilities treated groundwater contaminated with radionuclides or other site water (in accordance with the FBP NPDES permit). Emissions from the groundwater treatment facilities were calculated based on quarterly influent and effluent sampling at each facility and quarterly throughput. Total emissions from the DOE/FBP airborne sources in 2015 were calculated to be 0.0366 Ci (3.66E-02 Ci).

BWCS was responsible for air emission sources associated with the DUF₆ Conversion Facility. Emissions from the DUF₆ Conversion Facility were based on continuous monitoring of the conversion building stack. Total emissions from the DOE/BWCS airborne sources in 2015 were calculated to be 0.0000414 Ci (4.14E-05 Ci).

Total emissions from all DOE airborne sources in 2015 were calculated to be 0.0366 Ci (3.66E-02 Ci). Centrus reported total emissions of 0.0000153 Ci (1.53E-05 Ci) from airborne sources that are part of the Lead Cascade.

4.3.3 Dose Calculation Based on Airborne Emissions

A dose calculation for atmospheric, or airborne, radionuclides is required by U.S. EPA under NESHAP and is provided to U.S. EPA in an annual report. The effect of radionuclides released to the atmosphere by PORTS during 2015 was characterized by calculating the effective dose to the maximally exposed person (the individual who resides at the most exposed point near the plant) and to the entire population (approximately 677,000 residents) within 50 miles of the plant. Dose calculations were made using a computer program called CAP88-PC Version 4.0, which was developed under sponsorship of U.S. EPA for use in demonstrating compliance with the radionuclide NESHAP. The program uses models to calculate levels of radionuclides in the air, on the ground, and in food (e.g., vegetables, meat, and milk) and subsequent intakes by individuals. The program also uses meteorological data collected at PORTS such as wind direction, wind speed, atmospheric stability, rainfall, and average air temperature.

Radionuclide emissions were modeled for each of the air emission sources discussed in Section 4.3.2. The dose calculations assumed that each person remained unprotected, resided at home (actually outside the house) during the entire year, and obtained food according to the rural pattern defined in the NESHAP background documents. This pattern specifies that 70% of the vegetables and produce, 44% of the meat, and 40% of the milk consumed by each person are produced in the local area (e.g., in a home garden). The remaining portion of each food is assumed to be produced within 50 miles of PORTS. These assumptions most likely result in an overestimate of the dose received by a member of the public, since it is unlikely that a person spends the entire year outside at home and consumes food from the local area as described above.

The maximum potential dose to an off-site individual from radiological releases from DOE air emission sources at PORTS in 2015 was 0.037 mrem/year. The combined dose from Centrus (the Lead Cascade) and DOE sources is also 0.037 mrem/year. The dose from the Centrus sources is negligible compared to DOE sources. This dose is well below the 10-mrem/year limit applicable to PORTS and the approximate 311-mrem/year dose that the average individual in the United States receives from natural sources of radiation (NCRP 2009).

The collective dose (or population dose) is the sum of the individual doses to the entire population within 50 miles of PORTS. In 2015, the population dose from PORTS emissions was 0.224 person-rem/year.

The population dose based on PORTS emissions was insignificant; for example, the average population dose to all people within 50 miles of PORTS from the ingestion of naturally-occurring radionuclides in water and food was approximately 19,630 person-rem/year based on an average dose of approximately 29 mrem/year to an individual (NCRP 2009).

4.3.4 Dose Calculation Based on Ambient Air Monitoring

DOE collects samples from 15 ambient air monitoring stations (see Figure 4.1) and analyzes them for the radionuclides that could be present in ambient air due to PORTS activities. These radionuclides are isotopic uranium (uranium-233/234, uranium-235/236, and uranium-238), technetium-99, and selected transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240). The ambient air monitoring stations measure radionuclides released from DOE and Centrus point sources (the sources described in Section 4.3.2), fugitive air emissions (emissions that are not associated with a specific release point such as a stack), and background levels of radiation (radiation that occurs naturally in the environment and is not associated with PORTS operations).

The CAP88 model generates a dose conversion factor that was used to calculate a dose for a given level of each radionuclide in air. The following assumptions were made to calculate the dose at each station: 1) the highest level of each radionuclide detected in 2015 was assumed to be present for the entire year; or 2) if a radionuclide was not detected, the radionuclide was assumed to be present for the entire year at half the highest undetected result.

The dose associated with each radionuclide at each ambient air monitoring station was added to obtain the gross dose for each station. The net dose for each station was obtained by subtracting the dose measured at the background station (A37). The net dose for each station ranged from 0 at stations with a lower dose than the background station to 0.0012 mrem/year at stations A28 and A41A, which are off-site west of PORTS on Camp Creek Road and northeast of PORTS at Zahns Corner, respectively (see Figure 4.1).

The highest net dose measured at the ambient air monitoring stations (0.0012 mrem/year at stations A28 and A41A) is 3% of the dose calculated from the combined DOE and Centrus point source emissions (0.037 mrem/year). This dose is significantly less than the 10 mrem/year NESHAP limit for airborne radiological releases (40 CFR Part 61, Subpart H) and 100 mrem/year DOE limit in DOE Order 458.1 for all radiological releases from a facility.

4.3.5 Discharges of Radionuclides from NPDES Outfalls

FBP, BWCS, and Centrus were responsible for NPDES outfalls at PORTS during 2015. The BWCS NPDES outfall is not monitored for radionuclides; therefore, it is not discussed in this section. A description of the FBP and Centrus outfalls and the discharges of radionuclides from these outfalls during 2015 are included in this section.

4.3.5.1 FBP outfalls

In 2015, FBP was responsible for 18 monitoring locations identified in the FBP NPDES permit. Nine outfalls discharge directly to surface water, six outfalls discharge to another outfall before leaving the site, and three other locations that are not outfalls are also monitored (see Figure 4.2). A brief description of each FBP outfall or monitoring location at PORTS follows.

FBP NPDES Outfall 001 (X-230J7 East Holding Pond) – The X-230J7 East Holding Pond receives non-contact cooling water, steam condensate, foundation drainage, storm runoff, hydro-testing water from cylinders, and sanitary water for eyewash/shower station testing and flushing. The pond provides an area where materials suspended in the influent can settle, chlorine can dissipate, oil can be diverted/contained, and pH can be adjusted. Water from this holding pond is discharged to a tributary that flows to Little Beaver Creek.






Figure 4.1. DOE ambient air and radiation monitoring locations.



Legend

- State or U.S. route
- Road
- Railroad
- Stream or river
- DOE boundary
- Cylinder yard
- Building
- Pond or impoundment
- ▲ NPDES outfall
- FBP cylinder yard sampling location
- BWCS cylinder yard sampling location

Figure 4.2. PORTS NPDES outfalls/monitoring points and cylinder storage yards sampling locations.

FBP NPDES Outfall 002 (X-230K South Holding Pond) – The X-230K South Holding Pond receives non-contact cooling water, boiler blowdown, steam condensate, foundation drainage, treated runoff from the former coal pile area, storm runoff, fire-fighting training and fire suppression system water, and sanitary water for eyewash/shower station testing and flushing. The pond provides an area where materials suspended in the influent can settle, chlorine can dissipate, oil can be contained, and pH can be adjusted. Water from this holding pond is discharged to Big Run Creek.

FBP NPDES Outfall 003 (X-6619 Sewage Treatment Plant) – The X-6619 Sewage Treatment Plant treats PORTS sewage, some of Pike County sewage, and process wastewater from BWCS as well as water discharged from DOE groundwater treatment facilities, the X-700 Bionitrification Facility, the X-705 Decontamination Microfiltration System, and miscellaneous waste streams. The X-6619 Sewage Treatment Plant uses screening, aeration, clarification, and filtering followed by disinfection to treat wastewater prior to release to the Scioto River.

FBP NPDES Outfall 004 (Cooling Tower Blowdown) – Outfall 004 is located within the X-680 Blowdown Sample and Treatment Building at PORTS. It monitors blowdown water from cooling towers on site prior to being discharged to the Scioto River.

FBP NPDES Outfall 005 (X-611B Lime Sludge Lagoon) – The X-611B Lime Sludge Lagoon is used to settle lime sludge used in a water-softening process. The X-611B also receives rainwater runoff. Currently the lagoon only discharges during periods of excess precipitation.

FBP NPDES Outfall 009 (X-230L North Holding Pond) – The X-230L North Holding Pond receives non-contact cooling water, steam condensate, storm runoff, fire suppression system water, and sanitary water for eyewash/shower station testing and flushing. The pond provides an area where materials suspended in the influent can settle, chlorine can dissipate, oil can be contained, and pH can be adjusted. Water from this holding pond is discharged to a tributary that flows to Little Beaver Creek.

FBP NPDES Outfall 010 (X-230J5 Northwest Holding Pond) – The X-230J5 Northwest Holding Pond receives non-contact cooling water, steam condensate, storm runoff, fire-fighting training and fire suppression system water, and sanitary water for eyewash/shower station testing and flushing. The pond provides an area where materials suspended in the influent can settle, chlorine can dissipate, oil can be diverted/contained, and pH can be adjusted. Water from this holding pond is discharged to a tributary commonly referred to as the West Ditch, which flows to the Scioto River.

FBP NPDES Outfall 011 (X-230J6 Northeast Holding Pond) – The X-230J6 Northeast Holding Pond receives non-contact cooling water, steam condensate, storm runoff, fire suppression system water, and sanitary water for eyewash/shower station testing and flushing. The pond provides an area where materials suspended in the influent can settle, chlorine can dissipate, oil can be diverted/contained, and pH can be adjusted. Water from this holding pond is discharged to a tributary that flows to Little Beaver Creek.

FBP NPDES Outfall 015 (X-624 Groundwater Treatment Facility) – The X-624 Groundwater Treatment Facility removes VOCs from contaminated groundwater collected in the X-237 Groundwater Collection System in the X-701B Holding Pond area. This collection system was constructed to control the migration of groundwater contaminated with VOCs toward Little Beaver Creek. Treated water is released to a tributary that flows to Little Beaver Creek.

FBP NPDES Outfall 602 (X-621 Coal Pile Runoff Treatment Facility) – Prior to D&D of the X-600 Steam Plant Complex, the X-621 Coal Pile Runoff Treatment Facility treated storm water runoff from the coal pile at the X-600 Steam Plant Complex. The X-600 Steam Plant Complex was removed in 2013.

The X-621 Treatment Facility currently operates intermittently to treat precipitation runoff from the area of the former facility. The treated water is discharged to the X-230K South Holding Pond (FBP NPDES Outfall 002).

FBP NPDES Outfall 604 (X-700 Bionitrification Facility) – The X-700 Bionitrification Facility receives solutions from plant operations that are high in nitrate. At the X-700, these solutions are diluted and treated biologically using bacteria prior to being discharged to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003).

FBP NPDES Outfall 605 (X-705 Decontamination Microfiltration System) – The X-705 Decontamination Microfiltration System treats process wastewater using microfiltration and pressure filtration technology. The treated water is discharged to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003).

FBP NPDES Outfall 608 (X-622 Groundwater Treatment Facility) – The X-622 Groundwater Treatment Facility removes VOCs from contaminated groundwater originating from site remediation activities in the southern portion of the site, which is Quadrant I in the RCRA Corrective Action Program (see Chapter 3, Section 3.3.1). Treated water is discharged to the sanitary sewer and then through FBP NPDES Outfall 003.

FBP NPDES Outfall 610 (X-623 Groundwater Treatment Facility) – The X-623 Groundwater Treatment Facility formerly treated contaminated groundwater from extraction wells in the X-701B groundwater plume. The groundwater extraction wells were removed between 2009 and 2011. Currently, the facility removes VOCs from miscellaneous water associated with site activities (in accordance with the FBP NPDES permit). Treated water is discharged to the sanitary sewer and then through FBP NPDES Outfall 003.

FBP NPDES Outfall 611 (X-627 Groundwater Treatment Facility) – The X-627 Groundwater Treatment Facility removes VOCs from groundwater collecting in sumps located in the basements of the X-700 and X-705 buildings, which are part of Quadrant II. Treated water is discharged to the sanitary sewer and then through FBP NPDES Outfall 003.

FBP is also responsible for three additional monitoring points that are not discharge points as described in the previous paragraphs. FBP NPDES Station Number 801 is a surface water background monitoring location on the Scioto River upstream from FBP NPDES Outfalls 003 and 004 that is used for biotoxicity studies. FBP NPDES Station Number 902 is a monitoring location on Little Beaver Creek downstream from FBP NPDES Outfall 001, and FBP NPDES Station Number 903 is a monitoring location on Big Run Creek downstream from FBP NPDES Outfall 002. Water temperature is the only parameter measured at FBP NPDES Station Numbers 902 and 903.

FBP NPDES Outfalls 001, 002, 003, 004, 005, 009, 010, 011, 015, 608, 610, and 611 were monitored for radiological discharges by collecting water samples and analyzing the samples for uranium, uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238), technetium-99, and transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240).

Discharges of radionuclides in liquids through FBP NPDES outfalls have no significant impact on public health and the environment. In 2015, uranium discharges from the FBP external outfalls (Outfalls 001, 002, 003, 004, 005, 009, 010, 011, and 015) were estimated at 8.3 kg. Total radioactivity (technetium-99 and isotopic uranium) released from the same outfalls was estimated at 0.059 Ci.

Discharges of radionuclides were calculated using monthly monitoring data from the NPDES outfalls. Analytical results below the detection limit were assigned a value of zero in the calculations to determine

the quantities of uranium and technetium-99 discharged through the outfalls. Discharges of radionuclides from the outfalls are used in the dose calculation for releases to surface water (Section 4.3.6). The dose calculated with these data is significantly less than the 100 mrem/year limit in DOE Order 458.1 for all radiological releases from a facility.

No transuranics (americium-241, neptunium-237, plutonium-238, and plutonium-239/240) were detected in samples collected from the external FBP outfalls (Outfalls 001, 002, 003, 004, 005, 009, 010, 011, and 015) during 2015.

4.3.5.2 Centrus outfalls

In 2015, Centrus was responsible for three NPDES outfalls through which water is discharged from the site (see Figure 4.2). Two outfalls discharge directly to surface water, and one discharges to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003) before leaving the site. A brief description of each Centrus NPDES outfall follows.

Centrus NPDES Outfall 012 (X-2230M Southwest Holding Pond) – The X-2230M Southwest Holding Pond accumulates precipitation runoff, non-contact cooling water, and steam condensate from the southwestern portion of PORTS. The pond provides an area where solids can settle, chlorine can dissipate, and oil can be separated from the water prior to its release to an unnamed stream that flows to the Scioto River.

Centrus NPDES Outfall 013 (X-2230N West Holding Pond) – The X-2230N West Holding Pond accumulates precipitation runoff, non-contact cooling water, and steam condensate from the western portion of PORTS. The pond provides an area where solids can settle, chlorine can dissipate, and oil can be separated from the water prior to its release to a tributary commonly referred to as the West Ditch, which flows to the Scioto River.

Centrus NPDES Outfall 613 (X-6002 Particulate Separator) – The X-6002 Particulate Separator removes suspended solids from water used in the X-6002 Recirculating Hot Water Plant, which provides heat to a number of buildings at PORTS. The treated water is discharged to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003).

Centrus Outfalls 012 and 013 were monitored for radiological discharges by collecting water samples and analyzing the samples for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, and uranium.

Transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240) and technetium-99 were not detected in any of the samples collected from Centrus NPDES outfalls in 2015.

Uranium discharges in 2015 from external Centrus NPDES outfalls (Outfalls 012 and 013) were estimated at 0.605 kg. These values were calculated using quarterly discharge monitoring reports for the Centrus NPDES outfalls. Analytical results below the detection limit were assigned a value of zero in the calculations to determine the quantities of uranium discharged through the Centrus NPDES outfalls.

Discharges of radionuclides from Centrus Outfalls 012 and 013 are used in the dose calculation for releases to surface water (Section 4.3.6). The dose calculated with these data and data from external FBP outfalls is significantly less than the 100 mrem/year limit in DOE Order 458.1 for all radiological releases from a facility.

4.3.6 Dose Calculation for Releases to Surface Water

Radionuclides are measured at the FBP and Centrus NPDES external outfalls (nine FBP outfalls and two Centrus outfalls). Water from these external outfalls is either directly discharged to the Scioto River or eventually flows into the Scioto River from Little Beaver Creek, Big Run Creek, or unnamed tributaries to these water bodies. A hypothetical dose to a member of the public was calculated using the measured radiological discharges and the annual flow rate of the Scioto River.

Activity (in picocuries per liter [pCi/L]) for americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, and isotopic uranium (uranium-233/234, uranium-235/236, and uranium-238) were measured in the water discharged from the FBP outfalls. Uranium mass (in micrograms per liter [$\mu\text{g/L}$]) and activity (in pCi/L) for americium-241, neptunium-237, plutonium-238, plutonium-239/240, and technetium-99 were measured in the water discharged from the Centrus outfalls. Radionuclides that were not detected were assumed to be present at the detection limit. Uranium measured at the Centrus outfalls was assumed to be 5.2% uranium-235, 94% uranium-238, and 0.8% uranium-234 based on the highest enrichment of uranium produced by PORTS in the years prior to shutdown of the gaseous diffusion uranium enrichment operations. The maximum individual dose was calculated using the above-mentioned measured radionuclide discharges from the plant outfalls and the annual flow rate of the Scioto River.

The dose calculations were derived from the procedures developed for a similar DOE facility: *LADTAP XL: An Improved Electronic Spreadsheet Version of LADTAP II* (Hamby 1991) and *LADTAP-PA: A Spreadsheet for Estimating Dose Resulting from E-Area Groundwater Contamination at the Savannah River Site* (Jannik and Dixon 2006), which updates the 1991 LADTAP XL. Specific exposure scenarios provided in the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b) were also used when available. Environmental pathways considered were ingestion of water, ingestion of fish, swimming, boating, and shoreline activities. This exposure scenario is unlikely to underestimate the dose because the Scioto River is not used for drinking water downstream of PORTS (97% of the hypothetical dose from liquid effluents is from drinking water). The dose from radionuclides released to the Scioto River in 2015 (0.0017 mrem) is significantly less than the 100 mrem/year DOE limit in DOE Order 458.1 for all radiological releases from a facility.

4.3.7 Radiological Dose Calculation for External Radiation

Radiation is emitted from DUF_6 cylinders stored on site at PORTS in the cylinder storage yards located in the northwest portion of the site near Perimeter Road. External radiation is measured at five locations along Perimeter Road near the boundaries of the cylinder storage yards in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a). External radiation is measured using thermoluminescent dosimeters (TLDs), which measure both external background radiation and radiation emanating from the DUF_6 cylinders. Section 4.6.2 and Figure 4.3 provide more information about the external radiation monitoring program.

Data from radiation monitoring at the cylinder yards are used to assess potential exposure to a representative on-site member of the public that drives on Perimeter Road. The radiological exposure to an on-site member of the general public is estimated as the time that a person drives on Perimeter Road past the cylinder yards, which is estimated at 8.7 hours per year (1 minute per trip, 2 trips per day, 5 work-days per week, and 52 weeks per year). In 2015, the average annual dose (8736 hours) recorded at the cylinder yards near Perimeter Road was 777 mrem/year, based on TLD measurements for an entire year at locations #41, #868, #874, #882, and #890 (see Section 4.6.2 and Figure 4.3). Based on these assumptions, exposure to an on-site member of the public from radiation from the cylinder yards is approximately 0.77 mrem/year.

External radiation is also measured using TLDs at 19 locations that include 12 of the ambient air monitoring stations and seven additional on-site locations in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a). The total annual dose measured in 2015 at station A29, near the Ohio Valley Electric Corporation (OVEC), was 100 mrem/year (see Section 4.6.2 and Figure 4.3). The total dose measured at eight of the off-site or background monitoring stations averaged 92 mrem/year. A dose calculation was completed for a representative off-site member of the public, such as a worker at OVEC, based on the 8 mrem/year difference between the average off-site background dose (92 mrem/year) and the dose at station A29 (100 mrem/year). Assuming that the worker was exposed to this radiation for 250 days/year, one hour outdoors and 8 hours indoors, the dose to this worker is 0.96 mrem.

A person living in the United States receives an average dose of approximately 311 mrem/year from natural sources of radiation (National Council on Radiation Protection [NCRP] 2009). The higher potential estimated dose from external radiation to a member of the public (0.96 mrem/year to a worker near station A29 versus 0.77 mrem/year to a delivery person on Perimeter Road) is approximately 0.3 percent of the average yearly natural radiation exposure for a person in the United States and is significantly less than the 100 mrem/year limit in DOE Order 458.1 for all radiological releases from a facility.

4.3.8 Radiological Dose Results for DOE Workers and Visitors

The DOE Radiological Protection Organization at PORTS monitors external radiation levels in active DOE facilities at PORTS on a continual basis. This radiation monitoring assists in determining the radiation levels that workers are exposed to and in identifying changes in radiation levels. These measurements provide 1) information for worker protection, 2) a means to trend radiological exposure data for specified facilities, and (3) a means to estimate potential public exposure to radiation from DOE activities at PORTS.

The Radiation Exposure Monitoring System report is an electronic file created annually to comply with DOE Order 231.1B. This report contains exposure results for all monitored DOE employees, DOE contractors, and visitors to DOE areas at PORTS with a positive exposure during the previous calendar year. The 2015 Radiation Exposure Monitoring System report indicated that no visitors received a measurable dose (1 mrem or more).

More than 2500 DOE employees and DOE contractors were monitored throughout 2015. These workers received an average dose of 1.85 mrem. Less than 3% of the monitored workers, primarily workers handling DUF₆ cylinders, received a measurable dose (1 mrem total effective dose or more). No administrative guidelines or regulatory dose limits were exceeded in 2015.

4.3.9 Radiological Dose Calculations for Off-site Environmental Monitoring Data

Environmental monitoring at PORTS includes collecting samples at off-site locations around PORTS and analyzing the samples for radionuclides that could be present due to PORTS operations. Radiological monitoring programs at PORTS include ambient air, surface water, sediment, soil, residential drinking water (well water), and biota (vegetation, deer, fish, crops, milk, and eggs).

Samples are analyzed for uranium, uranium isotopes, technetium-99, and/or selected transuranics (americium-241, neptunium-237, plutonium-238, and plutonium-239/240). Uranium occurs naturally in the environment; therefore, detections of uranium cannot necessarily be attributed to PORTS operations. Technetium-99 and transuranics could come from PORTS operations because they were present in recycled uranium processed by PORTS during the Cold War. Technetium-99 and transuranic radionuclides could also come from sources other than PORTS because they are generally present in the

world-wide environment in very small amounts due to radioactive fallout in the atmosphere from nuclear weapons testing by various countries around the world.

DOE sets a limit as low as reasonably achievable, but no more than 100 mrem/year in DOE Order 458.1 for a potential dose to a member of the public via exposure to all radionuclide releases from a DOE facility. To ensure that PORTS meets this standard, dose calculations may be completed for environmental media.

Dose calculations for ambient air and surface water were presented in Sections 4.3.4 and 4.3.6, respectively. Dose calculations are also completed for detections of radionuclides in sediment, soil, residential drinking water (well water – excluding naturally-occurring detections of uranium isotopes), and biota (vegetation, deer, fish, crops, and dairy products) at off-site sampling locations. If radionuclides are not detected in the samples, a dose assessment is not completed. Off-site sampling locations are selected based on detections of radionuclides that could cause the highest dose to a member of the public. Detections of radionuclides in sediment and soil on the PORTS facility are not used to assess potential risk because the public does not have access to the sampled areas of the facility.

The summary of these dose calculations assumes that the same individual is exposed to the maximum dose calculated from each pathway. In 2015, dose calculations were completed for public exposure to radionuclides detected in sediment, soil, and vegetation. Radionuclides were not detected in 2015 in samples of residential drinking water, deer, fish, crops, and dairy products.

The following sections provide brief descriptions of the dose calculations for sediment, soil, and vegetation. Methodologies used to complete each risk calculation are based on information developed and approved by U.S. EPA including the *Exposure Factors Handbook* (U.S. EPA 1997) and *Federal Guidance Report No. 11 (FGR 11) Limiting Values of Radionuclide Intake and Air Concentration and Dose Conversion Factors for Inhalation, Immersion, and Ingestion* (U.S. EPA 1988).

In addition, specific exposure scenarios provided in the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b) were used when available. This document integrates the results of technical meetings between U.S. EPA, Ohio EPA, and DOE and provides methods for completing risk analyses at PORTS to promote consistency in the risk approach.

Table 4.2 summarizes the results of each dose calculation. Potential doses to the public from radionuclides detected by the PORTS environmental monitoring program in 2015 are significantly less than the 100 mrem/year limit in DOE Order 458.1.

Table 4.2. Summary of potential doses to the public from radionuclides detected by DOE environmental monitoring programs in 2015

Source of dose	Dose (mrem/year) ^a
Sediment	0.035
Soil	0.044
Vegetation	0.0027
Total	0.082

^a100 mrem/year is the limit for all potential pathways in DOE Order 458.1.

4.3.9.1 Dose calculation for sediment

The dose calculation for sediment is based on the following detections of radionuclides in the sample collected in 2015 from monitoring location RM-7, an off-site sampling location on Little Beaver Creek (see Section 4.6.5 and Figure 4.4):

- neptunium-237: 0.0295 picocuries per gram (pCi/g)
- plutonium-239/240: 0.0146 pCi/g
- technetium-99: 16.3 pCi/g
- uranium-233/234: 4.05 pCi/g
- uranium-235/236: 0.2 pCi/g
- uranium-238: 1.37 pCi/g.

Based on an incidental ingestion rate of 200 milligrams (mg)/day (0.0007 ounces/day) and an exposure frequency of 100 days/year, which are consistent with the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b), and exposure factors in U.S. EPA's *Exposure Factors Handbook* (U.S. EPA 1997), the dose that could be received by an individual from sediment contaminated at these levels is 0.035 mrem/year. Section 4.6.5 provides additional information on the sediment monitoring program as well as a map of sediment sampling locations.

4.3.9.2 Dose calculation for soil

The dose calculation for soil is based on the detections of the following uranium isotopes in the soil sample collected at the ambient air monitoring station A24, north of PORTS on Shyville Road (see Section 4.6.7 and Figure 4.1):

- uranium-233/234: 1.13 pCi/g
- uranium-235/236: 0.0647 pCi/g
- uranium-238: 1.16 pCi/g.

Based on an incidental ingestion rate of 200 mg/day (0.0007 ounces/day) and an exposure frequency of 350 days/year, which are consistent with the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b), and exposure factors in U.S. EPA's *Exposure Factors Handbook* (U.S. EPA 1997), the dose that could be received by an individual from soil contaminated at these levels is 0.044 mrem/year. Section 4.6.7 provides additional information on the soil monitoring program.

4.3.9.3 Dose calculation for vegetation

The dose calculation for vegetation is based on the following detections of radionuclides in vegetation (primarily grass) and soil at ambient air monitoring station A12 (east of PORTS on McCorkle Road – see Section 4.6.8.1 and Figure 4.1):

Vegetation

- uranium-233/234: 0.00877 pCi/g
- uranium-238: 0.00665 pCi/g

Soil

- uranium-233/234: 0.993 pCi/g
- uranium-235/236: 0.0532 pCi/g
- uranium-238: 1.01 pCi/g.

The dose calculation is based on human consumption of beef cattle that would eat grass (and soil) containing these radionuclides. Based on an ingestion rate for beef of 2 ounces/day and an exposure

frequency of 350 days/year, which are consistent with the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b) and U.S. EPA's *Exposure Factors Handbook* (U.S. EPA 1997), the dose that could be received by an individual eating beef from cattle that grazed on vegetation and soil contaminated at these levels is 0.0027 mrem/year. Section 4.6.8.1 provides additional information on the vegetation monitoring program.

4.4 PROTECTION OF BIOTA

DOE Order 458.1 sets absorbed dose rate limits for aquatic animals, riparian animals (animals that live on the banks of a river or in wetlands adjacent to a body of water), terrestrial plants, and terrestrial animals. DOE Technical Standard A *Graded Approach for Evaluating Radiation Doses to Aquatic and Terrestrial Biota* (DOE 2002a) was used to demonstrate compliance with these limits.

4.4.1 Aquatic and Riparian Animals

Analytical data for surface water and sediment samples collected during 2015 from the east side of the PORTS reservation [surface water sampling location EDD-SW01 (see Chapter 6, Section 6.4.15 and Figure 6.13) and sediment sampling location RM-11 (see Section 4.6.5 and Figure 4.4)] were used to assess the dose limits for aquatic and riparian animals (1 rad/day to aquatic animals and 0.1 rad/day to riparian animals). These locations were selected because levels of radionuclides detected in surface water and sediment from these locations were among the highest detected in samples collected in 2015. Section 4.6.5 and Chapter 6, Section 6.4.15 provide more information about these sediment and surface water sampling programs, respectively.

The maximum levels of radionuclides (plutonium-239/240 [sediment only], technetium-99, and uranium isotopes) were as follows:

Radionuclide	EDD-SW01	RM-11
Plutonium-239/240	–	0.0189 pCi/g
Technetium-99	17.3 pCi/L	3.9 pCi/g
Uranium-233/234	9.16 pCi/L	6.23 pCi/g
Uranium-235/236	0.428 pCi/L	0.258 pCi/g
Uranium-238	1.72 pCi/L	1.52 pCi/g.

These values were entered into the RESRAD-BIOTA software that is designed to implement the DOE Technical Standard (DOE 2002a). The software provides a screening method with generic limiting concentrations of radionuclides in environmental media. If the measured maximum levels of radionuclides detected at the selected PORTS sampling locations result in an output from the software calculations of less than 1, the doses to aquatic and riparian animals are within the dose limits (1 rad/day to aquatic animals and 0.1 rad/day to riparian animals).

In 2015, the RESRAD-BIOTA software output for the maximum levels of radionuclides detected at sampling locations EDD-SW01 (surface water) and RM-11 (sediment) was 0.0571, which is less than 1. Therefore, the assessment indicates that the levels of radionuclides detected in water and sediment at these locations did not result in a dose of more than 1 rad/day to aquatic animals and 0.1 rad/day to riparian animals.

4.4.2 Terrestrial Plants and Animals

Analytical data for surface water and soil samples collected during 2015 from the northern side of the PORTS reservation [surface water sampling location LBC-SW04 (see Chapter 6, Section 6.4.15 and Figure 6.13) and soil sampling location A8 (see Figure 4.1)] were used to assess the dose limits for terrestrial plants and animals. These locations were selected because levels of radionuclides detected in

surface water and soil from these locations were among the highest detected in samples collected in 2015. Section 4.6.7 and Chapter 6, Section 6.4.15 provide additional information about these soil and surface water sampling programs, respectively.

No transuranic radionuclides were detected in 2015 from samples collected LBC-SW04 (surface water) and A8 (soil). The maximum levels of technetium-99 (surface water only) and uranium isotopes were as follows:

<u>Radionuclide</u>	<u>LBC-SW04</u>	<u>A8</u>
Technetium-99	12.1 pCi/L	–
Uranium-233/234	6.98 pCi/L	1.59 pCi/g
Uranium-235/236	0.253 pCi/L	0.0889 pCi/g
Uranium-238	1.4 pCi/L	1.59 pCi/g.

These values were entered into the RESRAD-BIOTA software that is designed to implement the DOE Technical Standard (DOE 2002a). The software provides a screening method with generic limiting concentrations of radionuclides in environmental media. If the measured maximum levels of radionuclides detected at the selected PORTS sampling locations result in an output from the software calculations of less than 1, the doses to terrestrial plants and animals are within the dose limits (1 rad/day to terrestrial plants and 0.1 rad/day to terrestrial animals).

In 2015, the RESRAD-BIOTA software output for the maximum levels of radionuclides detected at sampling locations LBC-SW04 (surface water) and A8 (soil) was 0.00137, which is less than 1. Therefore, the assessment indicates that the levels of radionuclides detected in water and soil at these locations did not result in a dose of more than 1 rad/day to terrestrial plants and 0.1 rad/day to terrestrial animals.

4.5 UNPLANNED RADIOLOGICAL RELEASES

No unplanned releases of radionuclides took place at PORTS in 2015.

4.6 ENVIRONMENTAL RADIOLOGICAL MONITORING

This section discusses the radiological monitoring programs at PORTS: ambient air monitoring, external radiation, surface water, sediment, settleable solids, soil, vegetation, and biota (deer, fish, crops, milk, and eggs).

4.6.1 Ambient Air Monitoring

The ambient air monitoring stations measure radionuclides released from 1) DOE and Centrus point sources (the sources discussed in Section 4.3.2), 2) fugitive air emissions (emissions from PORTS that are not associated with a stack or pipe such as remediation sites or normal building ventilation), and 3) background levels of radionuclides (radionuclides that occur naturally, such as uranium). These radionuclides are isotopic uranium (uranium-233/234, uranium-235/236, and uranium-238), technetium-99, and selected transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240).

In 2015, samples were collected from 15 ambient air monitoring stations located within and around PORTS (see Section 4.3.4, Figure 4.1), including a background ambient air monitoring station (A37) located approximately 13 miles southwest of the plant. The analytical results from air sampling stations closer to the plant are compared to the background measurements.

With the exception of plutonium-238, no transuranic radionuclides were detected at the ambient air monitoring stations in 2015. Maximum activities of detected radionuclides are listed below:

<u>Radionuclide</u>	<u>Maximum activity (pCi/m³)</u>	<u>Location</u>	<u>Derived Concentration Standard (DCS) (DOE 2011a)</u>	<u>Percentage of DCS</u>
Plutonium-238	0.000026	A15	0.088	0.03%
Technetium-99	0.059	A41A, A28	920	0.006%
Uranium-233/234	0.031	T7	1.1	3%
Uranium-235/236	0.00079	T7	1.2	0.07%
Uranium-238	0.00081	A3	1.3	0.06%

To confirm that air emissions from PORTS are within regulatory requirements and are not harmful to human health, the ambient air monitoring data were used to calculate a dose to a hypothetical person living at the monitoring station. The highest net dose calculation for the off-site ambient air stations (0.0012 mrem/year) was at stations A28 and A41A, are west of PORTS on Camp Creek Road and northeast of PORTS at Zahns Corner, respectively. This hypothetical dose is well below the 10 mrem/year limit applicable to PORTS in NESHAP (40 CFR Part 61, Subpart H). Section 4.3.4 provides additional information about this dose calculation.

4.6.2 External Radiation

External radiation is measured continuously with TLDs at five locations near the DUF₆ cylinder storage yards (see Figure 4.3), 19 locations that include 12 of the ambient air monitoring stations (see Section 4.3.4, Figure 4.1), and seven additional on-site locations (see Figure 4.3). TLDs are placed at the monitoring locations at the beginning of each quarter, remain at the monitoring location throughout the quarter, and are removed from the monitoring location at the end of the quarter and sent to the laboratory for processing. A new TLD replaces the removed device. Radiation is measured in millirems as a whole body dose, which is the dose that a person would receive if they were continuously present at the monitored location.

External radiation is measured at five locations around the northwest corner of PORTS just inside Perimeter Road near the cylinder storage yards (see Figure 4.3). The average annual dose for these five locations (#41, #868, #874, #882, and #890) is 777 mrem. Section 4.3.7 provides a dose calculation for the representative on-site member of the public, such as a delivery person, that is allowed on the portion of Perimeter Road near the cylinder storage yards (the general public is not allowed on the portion of Perimeter Road near the cylinder storage yards). The potential estimated dose from the cylinder yards to a delivery person (0.77 mrem/year) is significantly less than DOE's 100 mrem/year dose limit to the public for radionuclides from all potential pathways.

In 2015, the average annual dose measured at eight off-site or background locations (A3, A6, A9, A12, A15, A23, A24, and A28) was 92 mrem. Three locations within PORTS measured levels of radiation approximately 50% higher or more than the average off-site radiation (92 mrem): location #874 (605 mrem) near the X-745C Cylinder Storage Yard; location #862 (130 mrem) south of the cylinder yards and west of the X-530A Switchyards; and location #933 (154 mrem) east of the X-744G building in the X-701B Holding Pond groundwater monitoring area. Three other on-site locations (A8, A29, and A40A) measured radiation at levels slightly higher than the average background (ranging from 1 mrem to 10 mrem above average).

The on-site locations with higher doses than the off-site average are not used by the general public, with the exception of location #874 near the cylinder yards and station A29, near OVEC. The dose calculation for the representative on-site member of the public exposed to the cylinder yards is discussed above and





Figure 4.3. On-site radiation and cylinder yard dose monitoring locations.

in Section 4.3.7. Section 4.3.7 also includes a dose calculation for the representative off-site member of the public who works at OVEC near station A29. The potential estimated dose to this off-site worker (0.96 mrem/year) is significantly less than the 100 mrem/year dose limit to the public for radionuclides from all potential pathways in DOE Order 458.1.

Section 4.3.8 provides dose results for DOE workers, including workers in the cylinder yards. No administrative guidelines or regulatory dose limits were exceeded in 2015.

4.6.3 Surface Water from Cylinder Storage Yards

In 2015, FBP collected surface water samples from the X-745B, X-745D, and X-745F Cylinder Storage Yards. BWCS collected surface water samples at the cylinder yards associated with the DUF₆ Conversion Facility (X-745C, X-745E, and X-745G Cylinder Storage Yards). Sections 4.6.3.1 and 4.6.3.2 provide the results of sampling completed in 2015 by FBP and BWCS, respectively.

4.6.3.1 FBP cylinder storage yards

In 2015, FBP collected surface water samples from seven locations at the X-745B, X-745D, and X-745F Cylinder Storage Yards. Figure 4.2 shows the sampling locations. Samples were analyzed for alpha activity, beta activity, and uranium. Samples were collected monthly if water was available.

Maximum levels of alpha activity, beta activity, and uranium were detected as follows:

Alpha activity: 97.9 pCi/L (X-745B2, October 2015)

Beta activity: 187 pCi/L (X-745B1, October 2015)

Uranium: 154 µg/L (X-745B2, October 2015).

Surface water from the cylinder storage yards flows to FBP NPDES outfalls prior to discharge from the site; therefore, releases of radionuclides from the cylinder yards are monitored by sampling conducted at the FBP outfalls. Radionuclides detected at FBP outfalls (see Section 4.3.5.1) are used in the dose calculation for releases to surface water (see Section 4.3.6). The dose from radionuclides released to surface water (the Scioto River) in 2015 (0.0017 mrem) is significantly less than the 100 mrem/year limit for all radiological releases from a facility in DOE Order 458.1.

4.6.3.2 BWCS cylinder storage yards

Ohio EPA requires monthly collection of surface water samples from seven locations at the X-745C, X-745E, and X-745G Cylinder Storage Yards. Figure 4.2 shows the sampling locations. Samples were analyzed for alpha activity, beta activity, and uranium.

Maximum levels of alpha activity, beta activity, and uranium were detected as follows:

Alpha activity: 12.6 pCi/L (X-745C2, October 2015)

Beta activity: 10.1 pCi/L (X-745E1, October 2015)

Uranium: 13 µg/L (X-745C2, April 2015).

Surface water from the cylinder storage yards flows to FBP NPDES outfalls prior to discharge from the site; therefore, releases of radionuclides from the cylinder yards are monitored by sampling conducted at the FBP outfalls. Radionuclides detected at FBP outfalls (see Section 4.3.5.1) are used in the dose calculation for releases to surface water (see Section 4.3.6). The dose from radionuclides released to surface water (the Scioto River) in 2015 (0.0017 mrem) is significantly less than the 100 mrem/year limit for all radiological releases from a facility in DOE Order 458.1.

4.6.4 Local Surface Water

In 2015, local surface water samples were collected from 14 locations upstream and downstream from PORTS. These samples were taken from the Scioto River, Little Beaver Creek, Big Beaver Creek, and Big Run Creek (see Figure 4.4). As background measurements, samples were also collected from local streams approximately 10 miles north, south, east, and west of PORTS.

Samples were collected semiannually and analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238) in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a).

No transuranic radionuclides were detected in the local surface water samples collected during 2015. Technetium-99 was detected in samples collected from Little Beaver Creek (RW-7 and RW-8) and Big Beaver Creek downstream from PORTS (RW-13).

Maximum detections of technetium-99 and uranium isotopes in local surface water samples are listed below:

<u>Radionuclide</u>	<u>Maximum activity (pCi/L)</u>	<u>Location</u>	<u>Derived Concentration Standard (DCS) (DOE 2011a)</u>	<u>Percentage of DCS</u>
Technetium-99	18	RW-13	44,000	0.04%
Uranium-233/234	4.07	RW-7	680	0.6%
Uranium-235/236	0.216	RW-7	720	0.03%
Uranium-238	0.853	RW-8	750	0.1%

4.6.5 Sediment

Sediment samples are collected from the same locations upstream and downstream from PORTS where local surface water samples are collected and at the NPDES outfalls on the east and west sides of PORTS (see Figure 4.4). Samples are collected annually and analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238) in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a).

Americium-241 and plutonium-238 were not detected in any of the sediment samples collected in 2015. Neptunium-237 and plutonium-239/240 were detected at 0.0295 pCi/g and 0.0146 pCi/g, respectively at Little Beaver Creek sampling location RM-7. Plutonium-239/240 was detected at 0.0189 pCi/g at RM-11 (NPDES Outfall 001), and neptunium-237 was detected at 0.00919 pCi/g at Big Beaver Creek sampling location RM-13.

Uranium and uranium isotopes are naturally occurring, but may also be present due to PORTS activities. Maximum detections of uranium and uranium isotopes in sediment samples were detected at background sampling location RM-10W and on-site sampling location RM-11 (discharge from the X-230J7 East Holding Pond). Uranium was detected at 6.49 micrograms per gram ($\mu\text{g/g}$) (RM-10W), uranium-233/234 was detected at 6.23 pCi/g (RM-11), uranium-235/236 was detected at 0.258 pCi/g (RM-11), and uranium-238 was detected at 2.16 pCi/g (RM-10W). Uranium and uranium isotopes detected in the 2015 samples have been detected at similar levels in previous sampling events from 2002 through 2014.





Figure 4.4. Local surface water and sediment monitoring locations.

Technetium-99 is often detected in sediment samples collected at locations downstream from PORTS. In 2015, technetium-99 was detected in the sample collected from Big Beaver Creek at RM-13, downstream location on Big Run Creek at RM-3, the location downstream from NPDES outfalls 010 and 013 (RM-10), and downstream locations on Little Beaver Creek (RM-11, RM-7, and RM-8). The highest detection (16.3 pCi/g) was at location RM-7 (Little Beaver Creek). These detections of technetium-99 are consistent with data from previous sampling events (2002 through 2014).

Section 4.3.9.1 provides a dose assessment to a member of the public based on detections of radionuclides at sampling location RM-7 on Little Beaver Creek. This off-site sampling location had the following levels of radionuclides detected in 2015 that would cause the highest dose to a member of the public: 0.0295 pCi/g of neptunium-237, 0.0146 pCi/g of plutonium-239/240, 16.3 pCi/g of technetium-99, 4.05 pCi/g of uranium-233/234, 0.2 pCi/g of uranium-235/236, and 1.37 pCi/g of uranium-238. The total potential dose to a member of the public resulting from PORTS operations (1.1 mrem/year), which includes this dose calculation (0.035 mrem/year), is well below the DOE standard of 100 mrem/year in DOE Order 458.1.

4.6.6 Settleable Solids

DOE collects semiannual water samples from nine effluent locations and three background locations (see Figure 4.5) to determine the concentration of radioactive material that is present in the sediment suspended in the water sample. The data are used to determine compliance with DOE Order 458.1, *Radiation Protection of the Public and the Environment*, which states that operators of DOE facilities discharging or releasing liquids containing radionuclides from DOE activities must ensure that the discharges do not exceed an annual average (at the point of discharge) of either of the following:


- 5 pCi/g above background of settleable solids for alpha-emitting radionuclides, and
- 50 pCi/g above background for beta-emitting radionuclides.

When a low concentration of settleable solids is detected in a water sample, accurate measurement of the alpha and beta activity in the settleable solids portion of the sample is not practical due to the small sample size. A DOE memo (DOE 1995) states that settleable solids of less than 40 milligrams per liter (mg/L) are in *de facto* compliance with the DOE Order 458.1 limits (5 pCi/g above background for alpha activity and 50 pCi/g above background for beta activity). In 2015, settleable solids were not detected at concentrations above 40 mg/L at any of the monitoring locations; therefore, monitoring results for the settleable solids monitoring program are in compliance with DOE Order 458.1. Detections of settleable solids that monitor PORTS effluent ranged from 4 to 14.3 mg/L.

4.6.7 Soil

Soil samples are collected annually from ambient air monitoring locations (see Figure 4.1) and analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238) in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a).

Plutonium-239/240 was detected at two ambient air monitoring stations: A6 (Piketon) at 0.0197 pCi/g and A9 (southwest of the plant on Old U.S. Route 23) at 0.0178 pCi/g. These detections are much less than the soil screening level for plutonium-239/240 in residential soil (3.78 pCi/g) calculated using the exposure assumptions in the *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant* (DOE 2013b). No other transuranics were detected in any of the soil samples collected during 2015.



Legend

- State or U.S. route
- Stream or river
- Cylinder yard
- Settleable solids monitoring location
- Road
- - - DOE boundary
- Building
- Railroad
- Pond or impoundment

Figure 4.5. DOE settleable solids monitoring locations.

Technetium-99 was not detected in any of the soil samples collected during 2015. Uranium, uranium-233/234, uranium-235/236, and/or uranium-238 were detected at each of the sampling locations. Uranium and uranium isotopes are usually detected at similar levels at all the soil sampling locations, including the background location (A37), which suggests that the uranium detected in these samples is due to naturally-occurring uranium.

Section 4.3.9.2 provides a dose assessment based on the detections of uranium-233/234 (1.13 pCi/g), uranium-235/236 (0.0647 pCi/g), and uranium-238 (1.16 pCi/g) in soil at the off-site ambient air station with the detections of radionuclides that could cause the highest dose to a member of the public (station A24, north of PORTS on Shyville Road). The total potential dose to a member of the public resulting from PORTS operations (1.1 mrem/year), which includes this dose calculation (0.044 mrem/year), is well below the DOE limit of 100 mrem/year in DOE Order 458.1.

4.6.8 Biological Monitoring

The DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a) requires biological monitoring to assess the uptake of radionuclides into selected local biota (vegetation, deer, fish, crops, milk, and eggs).

4.6.8.1 Vegetation

To assess the uptake of radionuclides into plant material, vegetation samples (primarily grass) are collected in the same areas where soil samples are collected at the ambient air monitoring stations (see Figure 4.1). Samples are collected annually and analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238) in accordance with the DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a).

Uranium, uranium-233/234, and uranium-238 were detected in vegetation samples collected in 2015. Uranium and uranium isotopes are detected occasionally in vegetation samples, and have been detected at similar levels in previous sampling. Section 4.3.9.3 provides a dose assessment for a member of the public based on consumption of beef cattle that would eat grass contaminated with radionuclides. The total potential dose to a member of the public resulting from PORTS operations (1.1 mrem/year), which includes this dose calculation (0.0027 mrem/year), is well below the DOE Order 458.1 limit of 100 mrem/year.

4.6.8.2 Deer

Samples of liver, kidney, and muscle from deer killed on site in motor vehicle collisions are collected annually, if available. Samples are analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238). Deer samples were collected in January, March, May, September, and November of 2015. No radionuclides were detected in any of the deer samples collected in 2015.

4.6.8.3 Fish

Fish samples are collected annually (if available) from locations on Little Beaver Creek (RW-8), Big Beaver Creek (RW-13 and RW-15), and the Scioto River (RW-1 and RW-6) as shown on Figure 4.4. In 2015, fish were caught at Little Beaver Creek (RW-8) and Big Beaver Creek (RW-13 and RW-15). Fish were not collected from the Scioto River in 2015. The samples were analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238). No radionuclides were detected in the fish samples collected during 2015.

4.6.8.4 Crops

In 2015, crop samples, including corn, tomatoes, and beans, were collected from five off-site locations near PORTS. The samples were analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238). No radionuclides were detected in the crop samples collected during 2015.

4.6.8.5 Milk and eggs

Samples were collected in 2015 of milk and eggs produced near PORTS. The samples were analyzed for transuranic radionuclides (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238). No radionuclides were detected in the milk and egg samples collected during 2015.

4.7 RELEASE OF PROPERTY CONTAINING RESIDUAL RADIOACTIVE MATERIAL

DOE Order 458.1 establishes limits for unconditional release of personal and real property from DOE facilities. Real property is defined as land and anything permanently affixed to the land such as buildings, fences, and those things attached to the buildings, such as light fixtures, plumbing, and heating fixtures, or other such items, that would be personal property if not attached. Personal property is defined as property of any kind, except for real property.

No real property was released from PORTS in 2015. Sections 4.7.1 and 4.7.2 provide information about personal property released from FBP and BWCS, respectively.

4.7.1 FBP releases

FBP uses pre-approved authorized limits established by DOE Orders to evaluate and release materials defined as personal property. In 2015, FBP authorized 2263 release requests for materials/items of personal property. Table 4.3 summarizes the items/materials released through these release requests.

Table 4.3 Summary of FBP personal property releases in 2015

Items/materials	Number of release requests	Items/materials	Number of release requests
<i>Waste/recycling/reuse</i>		<i>Equipment/other materials</i>	
Trash	53	Vehicles	132
Construction waste	15	Equipment	336
Light bulbs	42	Hand equipment	96
Aerosol cans	17	Samples	43
Fuel	6	Portable restroom	20
Batteries	35	Personal protective equipment	363
Recyclables	31	Records	637
Used oil	30	Electronics	25
Cylinders	94	Dosimeters	29
Water bottles	46	Dry ice boxes	49
Office furniture	27	Miscellaneous	122
Tires	15		

4.7.2 BWCS releases

In 2015, BWCS continued off-site shipment of aqueous hydrogen fluoride produced by the DUF₆ Conversion Facility, which converts DUF₆ into uranium oxide and aqueous hydrogen fluoride. Each shipment must meet the release limit of less than 3 picocuries/milliliter (pCi/mL) of total uranium activity. Approximately 188,250 gallons of aqueous hydrogen fluoride were shipped off site during 2015. The average total uranium activity of all the shipments was 0.006 pCi/mL.

5. ENVIRONMENTAL NON-RADIOLOGICAL PROGRAM INFORMATION

5.1 SUMMARY

Non-radiological environmental monitoring at PORTS includes air, water, sediment, and fish. Monitoring of non-radiological parameters is required by state and federal regulations and/or permits, but is also performed to reduce public concerns about plant operations.

Non-radiological data collected in 2015 are similar to data collected in previous years.

5.2 ENVIRONMENTAL NON-RADIOLOGICAL PROGRAM INTRODUCTION

Environmental monitoring programs at PORTS usually monitor both radiological and non-radiological constituents that could be released to the environment as a result of PORTS activities. The radiological components of each monitoring program were discussed in the previous chapter. The DOE *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a) specifies non-radiological monitoring requirements for ambient air, surface water, sediment, and fish. Non-radiological data are not collected for all sampling locations or all monitoring programs.

Environmental permits issued by Ohio EPA to FBP, BWCS, or Centrus specify discharge limitations, monitoring requirements, and/or reporting requirements for air emissions and water discharges. Centrus data for NPDES water discharges are included in this section to provide a more complete picture of environmental monitoring at PORTS. Centrus information for discharges to water is provided for informational purposes only; DOE is not certifying the accuracy of the Centrus data.

Data from the following environmental monitoring programs are included in this chapter:

- air
- surface water
- sediment
- biota (fish).

DOE also conducts an extensive groundwater monitoring program at PORTS that includes both radiological and non-radiological constituents. Chapter 6 provides information on the groundwater monitoring program, associated surface water monitoring, and water supply monitoring.

5.3 AIR

Permitted air emission sources at PORTS emit non-radiological air pollutants. In addition, the DOE ambient air monitoring program measures fluoride at monitoring stations within PORTS boundaries and in the surrounding area. Chapter 4, Figure 4.1 is a map of the PORTS ambient air monitoring locations.

5.3.1 Airborne Discharges

FBP is responsible for numerous air emission sources associated with the former gaseous diffusion production facilities and support facilities. These sources, which included the boilers at the X-600 Steam Plant Complex (prior to demolition in 2013), emitted more than 100 tons per year of non-radiological air pollutants specified by Ohio EPA, which caused DOE to become a major source of air pollutants as defined in 40 CFR Part 70.

FBP is required to submit an annual report called the Ohio EPA Fee Emissions Report to report emissions of selected non-radiological air pollutants. FBP reported the following emissions of non-radiological air pollutants for 2015: 11.03 tons of particulate matter, 1.96 tons of organic compounds, and 1.78 tons of

nitrogen oxides. Emissions for 2015 are associated with the X-627 Groundwater Treatment Facility, X-330 Dry Air Plant Emergency Generator, and plant roads/parking areas.

The DUF₆ Conversion Facility emits only a small quantity of non-radiological air pollutants. Because of these small emissions, Ohio EPA requires a Fee Emissions Report only once every two years. BWCS reported less than 10 tons/year of specified non-radiological air pollutants for 2015 (the report requires reporting in increments of emissions: zero, less than 10 tons, 10-50 tons, more than 50 tons, and more than 100 tons). BWCS reported 9 lbs of hydrogen fluoride emitted to the air in the Toxic Chemical Release Inventory for 2015 (see Chapter 2, Section 2.3.1.2).

U.S. EPA also requires annual reporting of greenhouse gas emissions (carbon dioxide, methane, and nitrous oxide). In 2015, FBP reported emissions of 13,703 metric tons of carbon dioxide, 0.26 metric ton of methane, and 0.026 metric ton of nitrous oxide. These emissions result from combustion of natural gas used at the X-690 Boilers.

Another potential air pollutant present at PORTS is asbestos released by D&D of plant facilities. Asbestos emissions are controlled by a system of work practices. The amount of asbestos removed and disposed is reported to Ohio EPA. In 2015, 8.8 tons of asbestos-containing materials (net weight) were shipped from PORTS.

5.3.2 Ambient Air Monitoring

In addition to the radionuclides discussed in Chapter 4, DOE ambient air monitoring stations also measure fluoride. Fluoride detected at the ambient air monitoring stations could be present due to background concentrations (fluoride occurs naturally in the environment), activities associated with the former gaseous diffusion process, and operation of the DUF₆ Conversion Facility.

In 2015, samples for fluoride were collected weekly from 15 ambient air monitoring stations in and around PORTS (see Chapter 4, Figure 4.1), including a background ambient air monitoring station (A37) located approximately 13 miles southwest of the plant.

In 2015, fluoride was not detected in 82 percent of the samples collected for the ambient air monitoring program. If fluoride is not detected in a sample, the ambient concentration of fluoride is calculated assuming that fluoride is present at the detection limit. The average ambient concentration of fluoride measured in samples collected at background station A37 was 0.014 microgram per cubic meter ($\mu\text{g}/\text{m}^3$). Average ambient concentrations of fluoride measured at the stations around PORTS ranged from 0.014 $\mu\text{g}/\text{m}^3$ at station A36 (on site at the X-611 Water Filtration Plant) and station A15 (east-southeast of PORTS on Loop Road) to 0.023 $\mu\text{g}/\text{m}^3$ at off-site station A3 (south of PORTS). There is no standard for fluoride in ambient air. The data indicate that ambient concentrations of fluoride at off-site and background locations are not appreciably different from concentrations at PORTS.

5.4 WATER

Surface water and groundwater are monitored at PORTS. Groundwater monitoring is discussed in Chapter 6, along with surface water monitoring conducted as part of the groundwater monitoring program. Non-radiological surface water monitoring primarily consists of sampling water discharges associated with the FBP, BWCS, and Centrus NPDES-permitted outfalls. PCBs are monitored in surface water downstream from the cylinder storage yards.

5.4.1 Water Discharges (NPDES Outfalls)

In 2015, DOE contractors (FBP and BWCS) were responsible for 21 NPDES discharge points (outfalls) or sampling points at PORTS. Centrus was responsible for three outfalls. This section describes non-radiological discharges from these outfalls during 2015.

5.4.1.1 FBP NPDES outfalls

In 2015, FBP was responsible for 18 outfalls or sampling points. Nine outfalls discharge directly to surface water, and six outfalls discharge to another outfall before leaving the site. FBP also monitors three additional sampling points that are not discharge locations. Chapter 4, Section 4.3.5.1, provides a brief description of each FBP outfall or sampling point and provides a site diagram showing each FBP NPDES outfall/sampling point (see Chapter 4, Figure 4.2).

Ohio EPA selects the chemical parameters that must be monitored at each outfall based on the chemical characteristics of the water that flows into the outfall and sets discharge limitations for some of these parameters. For example, some of the FBP outfalls discharge water from the groundwater treatment facilities; therefore, the outfalls are monitored for selected VOCs (*trans*-1,2-dichloroethene and/or TCE) because the groundwater treatment facilities treat water contaminated with VOCs. Chemicals and water quality parameters monitored at each FBP outfall in 2015 are as follows:

- FBP NPDES Outfall 001 (X-230J7 East Holding Pond) – cadmium, chlorine, copper, dissolved solids, fluoride, mercury, oil and grease, pH, silver, suspended solids, and zinc.
- FBP NPDES Outfall 002 (X-230K South Holding Pond) – cadmium, fluoride, mercury, ammonia-nitrogen, oil and grease, pH, selenium, silver, suspended solids, and thallium.
- FBP NPDES Outfall 003 (X-6619 Sewage Treatment Plant) – acute toxicity, ammonia-nitrogen, carbonaceous biochemical oxygen demand, chlorine (May-October only), copper, E. coli (May-October only), fecal coliform (May-October only), mercury, nitrite + nitrate, oil and grease, pH, silver, thallium, suspended solids, and zinc.
- FBP NPDES Outfall 004 (Cooling Tower Blowdown) – acute toxicity, chlorine, copper, dissolved solids, mercury, oil and grease, pH, suspended solids, and zinc.
- FBP NPDES Outfall 005 (X-611B Lime Sludge Lagoon) – lead, mercury, pH, selenium, and suspended solids.
- FBP NPDES Outfall 009 (X-230L North Holding Pond) – bis(2-ethylhexyl)phthalate, cadmium, copper, fluoride, mercury, oil and grease, pH, silver, suspended solids, and zinc.
- FBP NPDES Outfall 010 (X-230J5 Northwest Holding Pond) – cadmium, lead, mercury, oil and grease, pH, selenium, suspended solids, and zinc.
- FBP NPDES Outfall 011 (X-230J6 Northeast Holding Pond) – cadmium, chlorine, copper, fluoride, oil and grease, pH, suspended solids, thallium, and zinc.
- FBP NPDES Outfall 015 (X-624 Groundwater Treatment Facility) – arsenic, barium, total PCBs, pH, silver, and TCE.
- FBP NPDES Outfall 602 (X-621 Coal Pile Runoff Treatment Facility) – iron, manganese, pH, and suspended solids.
- FBP NPDES Outfall 604 (X-700 Bionitrification Facility) – copper, iron, nickel, nitrate-nitrogen, pH, and zinc.

- FBP NPDES Outfall 605 (X-705 Decontamination Microfiltration System) – ammonia-nitrogen, chromium, hexavalent chromium, copper, iron, Kjeldahl nitrogen, nickel, nitrate-nitrogen, nitrite-nitrogen, oil and grease, pH, sulfate, suspended solids, TCE, and zinc.
- FBP NPDES Outfall 608 (X-622 Groundwater Treatment Facility) – TCE, pH, and *trans*-1,2-dichloroethene.
- FBP NPDES Outfall 610 (X-623 Groundwater Treatment Facility) – TCE, pH, and *trans*-1,2-dichloroethene.
- FBP NPDES Outfall 611 (X-627 Groundwater Treatment Facility) – pH and TCE.

The FBP NPDES Permit also identifies additional monitoring points that are not discharge points as described in the previous paragraphs. FBP NPDES Station Number 801 is a surface water background monitoring location on the Scioto River upstream from FBP NPDES Outfalls 003 and 004. Samples are collected from this monitoring point to measure toxicity to minnows and another aquatic organism, *Ceriodaphnia*.

FBP NPDES Station Number 902 is a monitoring location on Little Beaver Creek downstream from FBP NPDES Outfall 001. FBP NPDES Station Number 903 is a monitoring location on Big Run Creek downstream from FBP NPDES Outfall 002. Water temperature is the only parameter measured at each of these monitoring points.

The monitoring data detailed in the previous paragraphs are submitted to Ohio EPA in a monthly discharge monitoring report.

In 2015, discharge limitations at the FBP NPDES monitoring locations were exceeded on seven occasions.

In March 2015, the maximum limits for acute toxicity for fathead minnows (*Pimephales promelas*) and *Ceriodaphnia dubia* (an aquatic organism called a water flea), were exceeded at Outfall 004 (Cooling Tower Blowdown). Acute toxicity is a measurement of the characteristics of water discharged from an outfall that could be harmful to aquatic organisms. The toxicity resulted from an operational reduction in water flow to the outfall. The amount of sodium bisulfite, a chemical used to remove chlorine from water, was not properly decreased when the water flow was reduced. The overfeed of sodium bisulfite caused acute toxicity measurements of 1.41 TU_a to two test organisms (fathead minnows and water fleas). The discharge limitations for acute toxicity are 1.0 TU_a for both organisms. The acute toxicity measurement is based on placing the aquatic organisms in diluted and undiluted samples of water from the outfall (or effluent). The discharge limitation (1.0 TU_a) is based on the concentration of the effluent that is lethal to 50% of the aquatic organisms. The sample result of 1.41 TU_a indicates that 50% of the aquatic organisms would be killed by a dilution of 71% effluent. The toxicity lasted no more than 24 hours.

The maximum daily concentration limit for chlorine (0.05 mg/L) was exceeded four times at Outfall 004 (Cooling Tower Blowdown) and once at Outfall 003 (X-6619 Sewage Treatment Plant) in 2015. Chlorine was detected at 0.12 to 0.3 mg/L in samples collected in January, February, May, and September from Outfall 004. Chlorine was detected at 0.06 mg/L in the sample collected on August 3, 2015, at Outfall 003. The exceedances were caused by operational issues and were corrected on the day of the exceedance.

In 2015, the overall FBP NPDES compliance rate with the NPDES permit was 99%.

5.4.1.2 BWCS NPDES outfalls

BWCS is responsible for the NPDES permit for the discharge of process wastewaters from the DUF₆ Conversion Facility. The BWCS NPDES permit provides monitoring requirements for two outfalls: BWCS Outfall 001 and BWCS Outfall 602. Chapter 4, Figure 4.2 shows the location of the BWCS NPDES outfalls. Monitoring requirements for BWCS Outfall 001 are only effective when process wastewater is being discharged through the outfall. No process waste water was discharged through Outfall 001 in 2015; therefore, no monitoring was required.

BWCS Outfall 602 monitors the discharge of BWCS process wastewater to the sanitary sewer, which flows to the X-6619 Sewage Treatment Plant that discharges through FBP NPDES Outfall 003. Process wastewater discharged from BWCS Outfall 602 was monitored for pH and total flow.

The monitoring data collected in accordance with the BWCS permit are submitted to Ohio EPA in a monthly discharge monitoring report. No exceedances of permit limitations at BWCS Outfall 602 occurred during 2015; therefore, the overall BWCS compliance rate with the NPDES permit was 100%.

5.4.1.3 Centrus NPDES outfalls

Centrus is responsible for three NPDES outfalls through which water is discharged from the site (see Chapter 4, Figure 4.2). Two outfalls discharge directly to surface water, and one outfall discharges to FBP NPDES Outfall 003 before leaving the site. Chapter 4, Section 4.3.5.2, provides a brief description of each Centrus NPDES outfall. Chemicals and water quality parameters monitored at each Centrus outfall are as follows:

- Centrus NPDES Outfall 012 (X-2230M Southwest Holding Pond) – chlorine, iron, oil and grease, pH, suspended solids, total PCBs, and TCE.
- Centrus NPDES Outfall 013 (X-2230N West Holding Pond) – chlorine, oil and grease, pH, suspended solids, and total PCBs.
- Centrus NPDES Outfall 613 (X-6002A Recirculating Hot Water Plant particle separator) – chlorine, pH, and suspended solids.

The monitoring data are submitted to Ohio EPA in a monthly discharge monitoring report. No exceedances of permit limitations at Centrus Outfalls 012, 013 and 613 occurred during 2015; therefore, the overall Centrus compliance rate with the NPDES permit was 100%.

5.4.2 Surface Water Monitoring Associated with BWCS Cylinder Storage Yards

Surface water samples (filtered and unfiltered) are collected quarterly from four locations in the drainage basins downstream from the BWCS X-745C, X-745E, and X-745G Cylinder Storage Yards (UDS X01, RM-8, UDS X02, and RM-10 – see Chapter 4, Figure 4.2) and analyzed for PCBs. PCBs were not detected in any of the surface water samples (filtered or unfiltered) collected during 2015. Section 5.5.2 presents the results for sediment samples collected as part of this program.

5.5 SEDIMENT

In 2015, sediment monitoring at PORTS included local streams and the Scioto River upstream and downstream from PORTS and drainage basins downstream from the BWCS cylinder storage yards.

5.5.1 Local Sediment Monitoring

Sediment samples are collected annually at the same locations upstream and downstream from PORTS where local surface water samples are collected and at the NPDES outfalls on the east and west sides of

PORTS (see Chapter 4, Figure 4.4). In 2015, samples were analyzed for 20 metals and PCBs, in addition to the radiological parameters discussed in Chapter 4.

PCBs were detected in sediment samples collected downstream from PORTS. PCBs were detected in samples collected from Little Beaver Creek (RM-7, RM-8, and RM-11), Big Beaver Creek (RM-13), Big Run Creek (RM-2 and RM-3), and the West Drainage Ditch near FBP NPDES Outfall 010 and Centrus NPDES Outfall 013 (RM-10).

None of the detections of PCBs in sediment around PORTS were above the risk-based regional screening level for PCB-1254/1260 developed by U.S. EPA and utilized by Ohio EPA: 240 micrograms per kilogram ($\mu\text{g}/\text{kg}$) or parts per billion (ppb) (U.S. EPA 2015). The highest detection of PCBs (159 $\mu\text{g}/\text{kg}$) was in Little Beaver Creek just upstream from Big Beaver Creek (RM-7). Investigation and remediation of PCBs in soil and sediment at PORTS will be addressed as part of the environmental remediation of PORTS.

The results of metals sampling conducted in 2015 indicate that no appreciable differences are evident in the concentrations of metals present in sediment samples taken upstream from PORTS, at background sampling locations, and downstream from PORTS. Metals occur naturally in the environment. Accordingly, the metals detected in the samples most likely did not result from activities at PORTS.

5.5.2 Sediment Monitoring Associated with BWCS Cylinder Storage Yards

Sediment samples are collected quarterly from four locations in the drainage basins downstream from the BWCS X-745C, X-745E, and X-745G Cylinder Storage Yards (UDS X01, RM-8, UDS X02, and RM-10) and analyzed for PCBs. These locations are on site at PORTS and not accessible to the public.

In 2015, PCBs were detected in at least one of the sediment samples collected at each location. The maximum concentration of PCBs (100 $\mu\text{g}/\text{kg}$) was detected at sampling location UDS X02. The concentrations of PCBs detected in 2015 are below the 1 ppm (1000 ppb) reference value set forth in the U.S. EPA Region 5 *TSCA Approval for Storage for Disposal of PCB Bulk Product (Mixed) Waste*, which applies to the storage of DUF₆ cylinders at PORTS that may have paint on the exterior of the cylinders that contains more than 50 ppm PCBs. None of the samples contained PCBs above the risk-based regional screening level for PCB-1254/1260 developed by U.S. EPA and utilized by Ohio EPA: 240 $\mu\text{g}/\text{kg}$ (ppb) (U.S. EPA 2015).

Section 5.4.2 presents the results for surface water samples collected as part of this program.

5.6 BIOLOGICAL MONITORING - FISH

Fish samples are collected annually (if available) from locations on Little Beaver Creek (RW-8), Big Beaver Creek (RW-13 and RW-15), and the Scioto River (RW-1 and RW-6). In 2015, fish were caught in Little Beaver Creek (RW-8) and Big Beaver Creek (RW-13 and RW-15). Chapter 4, Figure 4.4, shows the surface water monitoring locations where the fish were caught.

Fish samples were analyzed for PCBs, in addition to the radiological parameters discussed in Chapter 4. Fish samples collected for this program included only the fish fillet, that is, only the portion of the fish that would be eaten by a person. The fish sample collected from Big Beaver Creek at RW-13 was sunfish. The samples collected at Little Beaver Creek (RW-8) and Big Beaver Creek (RW-15) were bass.

PCBs were detected in each of the fish samples at concentrations ranging from 20.8 to 278 $\mu\text{g}/\text{kg}$ (in the bass sample collected from Little Beaver Creek at RW-8). These detections were compared to the Ohio Fish Consumption Advisory Chemical Limits provided in the *State of Ohio Cooperative Fish Tissue Monitoring Program Sport Fish Tissue Consumption Advisory Program* (Ohio EPA 2008). These limits

are set for the following consumption rates: unrestricted, 1/week, 1/month, 6/year, and do not eat. The concentration of PCBs detected in the bass caught on site in Little Beaver Creek (RW-8) is above the 1/week maximum limit (220 $\mu\text{g}/\text{kg}$) and below the 1/month maximum limit (1000 $\mu\text{g}/\text{kg}$). The concentrations of PCBs detected in fish collected from Big Beaver Creek (20.8 and 21.8 $\mu\text{g}/\text{kg}$) are less than the unrestricted limit (50 $\mu\text{g}/\text{kg}$). Fish were not collected from the Scioto River in 2015.

The Ohio Sport Fish Consumption Advisory, available from Ohio EPA, Division of Surface Water, advises the public on consumption limits for sport fish caught from all water bodies in Ohio and should be consulted before eating any fish caught in Ohio waters.

This page intentionally left blank.

6. GROUNDWATER PROGRAMS

6.1 SUMMARY

Groundwater monitoring at PORTS is required by a combination of state and federal regulations, legal agreements with Ohio EPA and U.S. EPA, and DOE Orders. More than 400 monitoring wells are used to track the flow of groundwater and to identify and measure groundwater contaminants. Groundwater programs also include on-site surface water monitoring and water supply monitoring.

Groundwater plumes that consist of VOCs, primarily TCE, are found at five of the PORTS monitoring areas: X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility, Quadrant I Groundwater Investigative (5-Unit) Area, Quadrant II Groundwater Investigative (7-Unit) Area, X-701B Former Holding Pond, and X-740 Former Waste Oil Handling Facility. In general, concentrations of contaminants detected within these plumes were stable or decreasing during 2015.

The groundwater plume at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility is near the southern boundary of PORTS. In 2015, no VOCs were detected in any of the seven off-site monitoring wells. TCE has not been detected in groundwater beyond the DOE property boundary at concentrations that exceed the Ohio EPA drinking water standard of 5 µg/L. Data collected in 2015 indicate that the groundwater extraction wells installed in the X-749/X-120 groundwater plume in 2010 are succeeding in reducing TCE concentrations within the plume.

The *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant* provides further details on the groundwater plumes at PORTS, specific monitoring well identifications, and analytical results for monitoring wells (DOE 2016a). This document and other documents referenced in this chapter are available in the PORTS Environmental Information Center.

6.2 GROUNDWATER PROGRAMS INTRODUCTION

This chapter provides an overview of groundwater monitoring at PORTS and the results of the groundwater monitoring program for 2015. The following sections provide an overview of the PORTS groundwater monitoring program followed by a review of the history and 2015 monitoring data for each area. Chapter 3, Section 3.3, provides additional information about the remedial actions implemented at a number of the areas discussed in this chapter to reduce or eliminate groundwater contamination.

This chapter also includes information on the groundwater treatment facilities at PORTS. These facilities receive contaminated groundwater from the groundwater monitoring areas and treat the water prior to discharge through the permitted FBP NPDES outfalls.

6.3 OVERVIEW OF GROUNDWATER MONITORING AT PORTS

This section provides an overview of the regulatory basis for groundwater monitoring at PORTS, groundwater use and geology, and monitoring activities and issues.

6.3.1 Regulatory Programs

Groundwater monitoring at PORTS was initiated in the 1980s. Groundwater monitoring has been conducted in response to state and/or federal regulations, regulatory documents prepared by DOE, agreements between DOE and Ohio EPA or U.S. EPA, and DOE Orders.

Because of the numerous regulatory programs applicable to groundwater monitoring at PORTS, an *Integrated Groundwater Monitoring Plan* was developed to address all groundwater monitoring requirements for PORTS. The initial plan was approved by Ohio EPA and implemented at PORTS starting in April 1999. The *Integrated Groundwater Monitoring Plan* is periodically revised by DOE and

approved by Ohio EPA. An annual groundwater report is submitted to Ohio EPA in accordance with the *Integrated Groundwater Monitoring Plan*.

Groundwater monitoring in January through June of 2015 was completed in accordance with the *Integrated Groundwater Monitoring Plan* dated May 2014 (DOE 2014b). Groundwater monitoring in July through December of 2015 was completed in accordance with the *Integrated Groundwater Monitoring Plan* dated July 2015 (DOE 2015d). The 2015 *Integrated Groundwater Monitoring Plan* incorporated minor revisions to the groundwater monitoring program, such as adding wells to the monitoring programs for the Quadrant I Groundwater Investigative (5-Unit) Area and X-701B Former Holding Pond.

Groundwater monitoring is also conducted to meet DOE Order requirements. Exit pathway monitoring assesses the effect of PORTS on off-site groundwater quality. DOE Orders are the basis for radiological monitoring of groundwater at PORTS.

6.3.2 Groundwater Use and Geology

Two water-bearing zones are present beneath the industrialized portion of PORTS: the Gallia and Berea formations. The Gallia is the uppermost water-bearing zone and contains most of the groundwater contamination at PORTS. The Berea is deeper than the Gallia and is usually separated from the Gallia by the Sunbury shale, which acts as a barrier to impede groundwater flow between the Gallia and Berea formations. Additional information about site hydrogeology is available in the PORTS Environmental Information Center.

Groundwater directly beneath PORTS is not used as a domestic, municipal, or industrial water supply, and contaminants in the groundwater beneath PORTS do not affect the quality of the water in the Scioto River Valley buried aquifer. PORTS is the largest industrial user of water in the vicinity and obtains water from water supply well fields north or west of PORTS in the Scioto River Valley buried aquifer. DOE has filed a deed notification at the Pike County Auditor's Office that restricts the use of groundwater beneath the PORTS site.


6.3.3 Monitoring Activities

Groundwater monitoring at PORTS includes several activities. Samples of water are collected from groundwater monitoring wells and analyzed to obtain information about contaminants and naturally-occurring compounds in the groundwater. Monitoring wells are also used to obtain other information about groundwater. When the level of water, or groundwater elevation, is measured in a number of wells over a short period of time, the groundwater elevations, combined with information about the subsurface soil, can be used to estimate the rate and direction of groundwater flow. The rate and direction of groundwater flow can be used to predict the movement of contaminants in the groundwater and to develop ways to control or remediate groundwater contamination.

6.4 GROUNDWATER MONITORING AREAS

The *Integrated Groundwater Monitoring Plan* requires groundwater monitoring of the following areas within the quadrants of the site designated by the RCRA Corrective Action Program (DOE 2014b, DOE 2015d). These areas (see Figure 6.1) are:

- Quadrant I
 - X-749 Contaminated Materials Disposal Facility /X-120 Former Training Facility,
 - PK Landfill,
 - Quadrant I Groundwater Investigative (5-Unit) Area,
 - X-749A Classified Materials Disposal Facility,



Legend

- State or U.S. route
- Stream or river
- Cylinder yard
- Groundwater monitoring area
- Road
- DOE boundary
- Building
- Railroad
- Quad Boundary
- Pond or impoundment

Figure 6.1. Groundwater monitoring areas at PORTS.

- Quadrant II
 - Quadrant II Groundwater Investigative (7-Unit) Area,
 - X-701B Former Holding Pond,
 - X-633 Former Recirculating Cooling Water Complex,
- Quadrant III
 - X-616 Former Chromium Sludge Surface Impoundments,
 - X-740 Former Waste Oil Handling Facility,
- Quadrant IV
 - X-611A Former Lime Sludge Lagoons,
 - X-735 Landfills,
 - X-734 Landfills,
 - X-533 Former Switchyard Complex, and
 - X-344C Former Hydrogen Fluoride Storage Building.

The *Integrated Groundwater Monitoring Plan* also contains requirements for 1) surface water monitoring in creeks and drainage ditches at PORTS that receive groundwater discharge; and 2) water supply monitoring (DOE 2014b, DOE 2015d).

In general, samples are collected from wells (or surface water locations) at each area listed above and are analyzed for metals, VOCs, and/or radionuclides. Table 6.1 lists the analytical requirements for each groundwater monitoring area and other monitoring programs described in this chapter. Constituents detected in the groundwater are then compared to standards called preliminary remediation goals to assess the potential for each constituent to affect human health and the environment. Preliminary remediation goals are initial clean-up goals developed early in the decision-making process that are 1) protective of human health and the environment, and 2) comply with applicable or relevant and appropriate requirements. Preliminary remediation goals are intended to satisfy regulatory cleanup requirements.

Five areas of groundwater contamination, commonly called groundwater plumes, have been identified at PORTS. Groundwater contamination consists of VOCs (primarily TCE) and radionuclides such as technetium-99. The areas that contain groundwater plumes are X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility, Quadrant I Groundwater Investigative (5-Unit) Area, Quadrant II Groundwater Investigative (7-Unit) Area, X-701B Former Holding Pond, and X-740 Former Waste Oil Handling Facility. Other areas are monitored to evaluate groundwater contaminated with metals, to ensure past uses of the area (such as a landfill) have not caused groundwater contamination, or to monitor remediation that has taken place in the area.

The following sections describe the history of each groundwater monitoring area and groundwater monitoring results for each area in 2015.

6.4.1 X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility

In the southernmost portion of PORTS in Quadrant I, groundwater concerns focus on three contaminant sources: X-749 Contaminated Materials Disposal Facility (also called the X-749 Landfill), X-120 Former Training Facility, and PK Landfill. A contaminant plume consisting of VOCs, primarily TCE, is associated with the X-749 Contaminated Materials Disposal Facility and X-120 Former Training Facility. The PK Landfill, located immediately northeast of the X-749 Landfill, is not a contaminant source to the X-749/X-120 groundwater plume.

Table 6.1. Analytical parameters for monitoring areas and programs at PORTS in 2015

Monitoring Area or Program		Analytes
X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility ^{a,b}	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu	technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d total metals ^d : Be, Cd, Cr, Mn, Ni
PK Landfill ^b	VOCs ^c	total metals ^d : Be, Cd, Cr, Mn, Ni
Quadrant I Groundwater Investigative (5-Unit) Area ^{a,b}	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu	technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d total metals ^d : Be, Cd, Cr, Mn, Ni
X-749A Classified Materials Disposal Facility	VOC ^e technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^c alkalinity chloride sulfate chemical oxygen demand total dissolved solids	total metals ^d : Sb, As, Ba, Be, Cd, Ca, Cr, Co, Cu, Fe, Pb, Mg, Mn, Ni, K, Se, Ag, Na, Tl, V, Zn nitrate/nitrite ammonia
Quadrant II Groundwater Investigative (7-Unit) Area ^{a,b}	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu	technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d total metals ^d : Be, Cd, Cr, Mn, Ni
X-701B Former Holding Pond ^{a,b}	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d	alkalinity chloride sulfate total dissolved solids total metals ^d : Be, Cd, Cr, Mn, Ni
X-633 Former Recirculating Cooling Water Complex	total metals ^d : Cr	
X-616 Former Chromium Sludge Surface Impoundments	VOCs ^c	total metals ^d : Be, Cd, Cr, Mn, Ni
X-740 Former Waste Oil Handling Facility ^{a,b}	VOCs ^c EAB/GC ^f	
X-611A Former Lime Sludge Lagoons	total metals ^d : Be, Cr	
X-735 Landfills	VOC ^e technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d alkalinity chloride sulfate chemical oxygen demand total dissolved solids	total metals ^d : Sb, As, Ba, Be, Cd, Ca, Cr, Co, Cu, Fe, Hg, Pb, Mg, Mn, Ni, K, Se, Ag, Na, Tl, V, Zn nitrate/nitrite ammonia

Table 6.1. Analytical parameters for monitoring areas and programs at PORTS in 2015 (continued)

Monitoring Area or Program	Analytes
X-734 Landfills	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d alkalinity chloride total metals ^d : Be, Cd, Cr, Mn, Ni, Na ammonia chemical oxygen demand nitrate/nitrite sulfate total dissolved solids
X-533 Former Switchyard Complex	total metals ^d : Cd, Ni
X-344C Former Hydrogen Fluoride Storage Building	VOCs ^c
Surface Water	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d
Water Supply	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d alpha activity
Exit Pathway	VOCs ^c transuranics ^d : ²⁴¹ Am, ²³⁷ Np, ²³⁸ Pu, ^{239/240} Pu technetium-99 U, ^{233/234} U, ^{235/236} U, ²³⁸ U ^d

^aSelected well(s) in this area are sampled once every two years for a comprehensive list of more than 200 potential contaminants (40 CFR Part 264 Appendix IX – Appendix to Ohio Administrative Code Rule 3745-54-98).

^bNot all wells in this area are analyzed for all listed analytes.

^cAcetone, benzene, bromodichloromethane, bromoform, carbon disulfide, carbon tetrachloride, chlorobenzene, chloroethane, chloroform, dibromochloromethane, 1,2-dichlorobenzene, 1,4-dichlorobenzene, 1,1-dichloroethane, 1,2-dichloroethane, 1,1-dichloroethene, cis-1,2-dichloroethene, trans-1,2-dichloroethene, ethylbenzene, bromomethane, chloromethane, methylene chloride, 2-butanone (methyl ethyl ketone), 4-methyl-2-pentanone (methyl isobutyl ketone), 1,1,2,2-tetrachloroethane, tetrachloroethene, toluene, 1,1,1-trichloroethane, 1,1,2-trichloroethane, TCE, trichlorofluoromethane (CFC-11), vinyl chloride, xylenes (m,p-xylenes).

^dAppendix C lists the symbols for metals and transuranic radionuclides.

^eVOCs listed in footnote c plus: acrylonitrile, bromochloromethane, 1,2-dibromo-3-chloropropane, 1,2-dibromoethane, trans-1,4-dichloro-2-butene, 1,2-dichloropropane, cis-1,3-dichloropropene, trans-1,3-dichloropropene, 2-hexanone (methyl butyl ketone), dibromomethane, iodomethane, styrene, 1,1,1,2-tetrachloroethane, 1,2,3-trichloropropane, and vinyl acetate.

^fEnhanced anaerobic bioremediation (EAB) parameters and gene copies of EAB bacteria: Chloride, nitrate, sulfate, nitrate/nitrite as nitrogen, chemical oxygen demand, ethane, ethylene, methane, alkalinity, dehalococoides spp, functional gene RDase BAV1, functional gene RDase VS, and reductase-encoding tceA gene.

6.4.1.1 X-749 Contaminated Materials Disposal Facility

The X-749 Contaminated Materials Disposal Facility is a landfill located in the south-central section of the facility in Quadrant I. The landfill covers approximately 11.5 acres and was built in an area of highest elevation within the southern half of PORTS. The landfill operated from 1955 to 1990, during which time buried wastes were generally contained in metal drums or other containers compatible with the waste.

The northern portion of the X-749 Landfill contains waste contaminated with industrial solvents, waste oils from plant compressors and pumps, sludges classified as hazardous, and low-level radioactive materials. The southern portion of the X-749 Landfill contains non-hazardous, low-level radioactive scrap materials.

The initial closure of the X-749 Landfill in 1992 included installation of 1) a multimedia cap; 2) a barrier wall along the north side and northwest corner of X-749 Landfill; and 3) subsurface groundwater drains on the northern half of the east side and the southwest corner of the landfill, including one sump within each of the groundwater drains. The barrier wall and subsurface drains extended down to bedrock. An additional barrier wall on the south and east sides of the X-749 Landfill was constructed in 2002. The groundwater drain and sump on the east side of the landfill were removed for construction of this barrier wall. Groundwater from the remaining subsurface drain is treated at the X-622 Groundwater Treatment Facility and discharged through FBP NPDES Outfall 608, which flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003).

The leading edge of the contaminated groundwater plume emanating from the X-749 Landfill is near the southern boundary of PORTS. In 1994, a subsurface barrier wall was completed across a portion of this southern boundary of PORTS. The X-749 South Barrier Wall was designed to inhibit migration of the plume off plant property prior to the implementation of a final remedial measure; however, VOCs moved beyond the wall. In 2007, four groundwater extraction wells were installed in the X-749 South Barrier Wall Area, and in 2008, two extraction wells were installed in the groundwater collection system on the southwest side of the landfill. These extraction wells are controlling migration of the plume off plant property and reducing concentrations of TCE in groundwater. Two additional groundwater extraction wells were installed in 2010 to further control migration of the X-749/X-120 groundwater plume and remediate areas of higher TCE concentrations within the plume. A third extraction well was installed in the X-120 area of the plume (see Section 6.4.1.2). Chapter 3, Section 3.3.1.1, provides additional information about the remedial actions implemented to address the X-749/X-120 groundwater plume.

Ninety-eight wells and one sump/extraction well were sampled during 2015 to monitor the X-749/X-120 area. Table 6.1 lists the analytical parameters for the wells and sump in this area.

6.4.1.2 X-120 Former Training Facility

The X-120 Former Training Facility (originally called the Goodyear Training Facility and also called the X-120 Old Training Facility), which is west and north of the X-749 Contaminated Materials Disposal Facility, covered an area of approximately 11.5 acres west of the present-day XT-847 building. The X-120 Former Training Facility included a machine shop, metal shop, paint shop, and several warehouses used during the construction of PORTS in the 1950s.

Groundwater in the vicinity of this facility is contaminated with VOCs, primarily TCE. In 1996, a horizontal well was installed along the approximate axis of the X-120 plume. Contaminated groundwater flowed from this well to the X-625 Groundwater Treatment Facility. In 2003, operation of the X-625 Groundwater Treatment Facility and horizontal well ceased with the approval of Ohio EPA due to the limited amount of groundwater collected by the well. A groundwater extraction well was installed in 2010 in the area west of the X-120 Former Training Facility to remediate the higher concentrations of

TCE in groundwater in this area. Chapter 3, Section 3.3.1.1, provides additional information about the remedial actions implemented to address the X-749/X-120 groundwater plume.

Ninety-eight wells and one sump/extraction well were sampled during 2015 to monitor the X-749/X-120 area. Table 6.1 lists the analytical parameters for the wells and sump in this area.

6.4.1.3 Monitoring results for the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility in 2015

The most extensive and most concentrated constituents associated with the X-749/X-120 plume (see Figure 6.2) are VOCs, particularly TCE.

In general, concentrations of TCE were stable or decreasing within the X-749/X-120 groundwater plume. The area within the plume where TCE concentrations are less than 5 µg/L became larger in 2015 compared to 2014 based on the decrease in TCE detected in well X749-29G. The concentration of TCE detected in well X749-29G in the last five years has fluctuated above and below 5 µg/L (see Figure 6.2). Concentrations of TCE remained less than 5 µg/L in 2015 in the other three wells that define the area (X120-05G, X749-PZ07G, and X749-36G).

The area of the plume with higher TCE concentrations (100 µg/L to 1000 µg/L) to the south and west of the X-749 Landfill remained separated from the higher TCE concentrations within or just outside of the X-749 Landfill. In other words, wells with TCE concentrations higher than 5 µg/L (the definition of the plume perimeter) but less than 100 µg/L are between the landfill and the higher TCE concentrations west and south of the landfill. These results indicate that the extraction wells in the groundwater collection system at the southwest side of the X-749 Landfill are functioning as intended to prevent migration of TCE from the X-749 Landfill.

The boundary of the eastern portion of X-749 groundwater plume that emanates from the east side of the X-749 Landfill remained similar to previous years. Concentrations of TCE remained stable or continued to decrease within the eastern portion of the plume (wells X749-PZ10G, X749-20G, X749-21G, and X749-35G).

Extraction well X749-EW09G was installed in 2010 to remediate higher concentrations of TCE associated with the former X-120 facility in the northern portion of the X-749/X-120 groundwater plume. The concentration of TCE detected in well X120-11G, which is immediately north of X749-EW09G, is consistently high (230 and 240 µg/L in 2015). The average concentration of TCE detected in 2015 in well X120-11G is similar to 2014 and 2013, and has decreased from 2012 and 2011 (see Figure 6.2). These results indicate that extraction well X749-EW09G is functioning as intended to reduce concentrations of TCE in this area.

Groundwater extraction well X749-EW07G was installed in 2010 to remediate areas of higher TCE concentrations south of the X-749 Landfill. Wells X749-67G (approximately 350 ft south of extraction well X749-EW07G) and X749-110G (approximately 125 ft south of X749-EW07G) monitor the performance of extraction well X749-EW07G. The average concentration of TCE detected in 2015 in well X749-67G (268 µg/L) has decreased from the average annual concentrations detected in 2011–2014 (see Figure 6.2). The average concentration of TCE detected in 2015 in well X749-110G (28 µg/L) has decreased from the average annual concentrations detected in 2011–2014 (see Figure 6.2). These results indicate that extraction well X749-EW07G is functioning as intended to reduce concentrations of TCE south of the X-749 Landfill.




Figure 6.2. TCE-contaminated Gallia groundwater plume at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015.

The concentrations of TCE detected in on-site monitoring wells downgradient of the X-749 South Barrier Wall area groundwater extraction wells (wells X749-EW01G, EW02G, EW03G, and EW04G) have decreased to below 5 µg/L in most sampling events since 2011, with the exception of well X749-67G (discussed in the previous paragraph). No VOCs were detected in any of the seven off-site monitoring wells.

Samples from selected wells that monitor the X-749/X-120 groundwater plume were analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and/or uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.4.2 PK Landfill

The PK Landfill is located west of Big Run Creek just south of the X-230K Holding Pond in Quadrant I and northeast of the X-749 Landfill. PK Landfill, which began operations in 1952, was used as a salvage yard, burn pit, and trash area during the construction of PORTS. After the initial construction, the disposal site was operated as a sanitary landfill until 1968, when soil was graded over the site and the area was seeded with native grasses.

During site investigations, intermittent seeps were observed emanating from the PK Landfill into Big Run Creek. In 1994, a portion of Big Run Creek was relocated approximately 50 feet to the east. A groundwater collection system was installed in the old creek channel to capture the seeps emanating from the landfill. A second collection system was constructed in 1997 on the southeastern landfill boundary to contain the groundwater plume migrating toward Big Run Creek from the southern portion of the PK Landfill. Although the PK Landfill is adjacent to the X-749 Landfill and X-749/X-120 groundwater plume, it is not a source of contaminants detected in the X-749/X-120 groundwater plume. A cap was constructed over the landfill in 1998. Chapter 3, Section 3.3.1.2, provides additional information about the remedial actions implemented at PK Landfill.

In 2015, nine wells, two sumps, and two manholes were sampled to monitor the PK Landfill area. Table 6.1 lists the analytical parameters for the wells, sumps, and manholes in this area.

6.4.2.1 Monitoring results for the PK Landfill in 2015

The PK Landfill is not part of the X-749/X-120 groundwater plume, although some of the wells associated with the PK Landfill are contaminated with low levels of VOCs, including TCE (see Figure 6.2). Most of the detections of VOCs in the PK Landfill monitoring wells are below preliminary remediation goals. In 2015, vinyl chloride was detected in samples collected from wells PK-17B and PK-21B at concentrations ranging from 5.3 to 22 µg/L, which exceed the preliminary remediation goal of 2 µg/L. Vinyl chloride is typically detected in these wells at concentrations above the preliminary remediation goal. No other VOCs were detected in the PK Landfill monitoring wells at concentrations that exceeded the preliminary remediation goals.

6.4.3. Quadrant I Groundwater Investigative (5-Unit) Area

The Quadrant I Groundwater Investigative (5-Unit) Area consists of a groundwater plume resulting from a number of potential sources of groundwater contamination in the northern portion of Quadrant I: the X-231A and X-231B Oil Biodegradation Plots, X-600 Former Steam Plant Complex, X-600A Former Coal Pile Yard, X-621 Coal Pile Runoff Treatment Facility, X-710 Technical Services Building, the X-760 Former Pilot Investigation Building, and the X-770 Former Mechanical Testing Facility. The X-231B Southwest Oil Biodegradation Plot was monitored prior to implementation of the *Integrated Groundwater Monitoring Plan*.

Three groundwater extraction wells were installed in 1991 as part of an IRM for the X-231B Southwest Oil Biodegradation Plot. Eleven additional groundwater extraction wells were installed in 2001-2002 as part of the remedial actions required by the Quadrant I Decision Document. These wells began operation in 2002. An additional extraction well south of the X-326 Process Building began operating in 2009. The extracted groundwater is treated at the X-622 Groundwater Treatment Facility and discharged through FBP NPDES Outfall 608, which flows into the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). Multimedia landfill caps were installed over the X-231B area and a similar area, X-231A, in 2000 to minimize water infiltration and control the spread of contamination. Chapter 3, Section 3.3.1.3, provides additional information about the remedial actions implemented in the Quadrant I Groundwater Investigative (5-Unit) Area.

Thirty-four wells were sampled in 2015 as part of the monitoring program for the Quadrant I Groundwater Investigative (5-Unit) Area. Table 6.1 lists the analytical parameters for the wells in this area.

6.4.3.1 Monitoring results for the Quadrant I Groundwater Investigative (5-Unit) Area in 2015

A contaminated groundwater plume consisting primarily of TCE is associated with the Quadrant I Groundwater Investigative (5-Unit) Area (see Figure 6.3). Other VOCs are also present in the plume.

The eastern and northwestern edges of the groundwater plume moved inwards in 2015. On the eastern edge of the plume, TCE was detected at 3.8 µg/L in X231A-01G and 4.5 µg/L in well X749A-18G. TCE has been detected above and below the preliminary remediation goal (5 µg/L) in well X749A-18G; TCE was detected at 14 µg/L in 2014. On the northwestern edge of the plume, TCE decreased to 3.9 µg/L in well X231B-29G (see Figure 6.3). TCE is increasing in well X231B-36G, which monitors the northern portion of the plume (see Figure 6.3). No other significant changes in TCE concentrations were identified in wells that monitor the Quadrant I Groundwater Investigative (5-Unit) Area in 2015.

Samples from selected wells that monitor the Quadrant I Groundwater Investigative (5-Unit) Area were analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and/or uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.4.4 X-749A Classified Materials Disposal Facility

The 6-acre X-749A Classified Materials Disposal Facility (also called the X-749A Landfill) is a landfill that operated from 1953 through 1988 for the disposal of wastes classified under the Atomic Energy Act (see Figure 6.3). Potential contaminants include PCBs, asbestos, radionuclides, and industrial waste. Closure of the landfill, completed in 1994, included the construction of a multilayer cap and the installation of a drainage system to collect surface water runoff. The drainage system discharges via the X-230K South Holding Pond (FBP NPDES Outfall 002). Although the X-749A Classified Materials Disposal Facility is located at the eastern edge of the Quadrant I Groundwater Investigative (5-Unit) Area groundwater plume, the X-749A Landfill is not the source of the VOCs detected in some of the X-749A monitoring wells at the eastern edge of the Quadrant I Groundwater Investigative (5-Unit) Area groundwater plume.

Ten wells associated with the landfill were sampled in 2015. Table 6.1 lists the analytical parameters for the wells in this area.




Figure 6.3. TCE-contaminated Gallia groundwater plume at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015.

6.4.4.1 Monitoring results for the X-749A Classified Materials Disposal Facility in 2015

Under the detection monitoring program for the X-749A Landfill, concentrations of alkalinity, ammonia, calcium, chloride, iron, nitrate/nitrite, sodium, and sulfate in downgradient Gallia wells were evaluated using two statistical procedures to monitor potential impacts to groundwater and trends in concentrations of these parameters. Ohio EPA is notified when the statistical control limit for any of the indicator parameters using the first statistical procedure is exceeded at any of the downgradient Gallia wells in two consecutive semiannual sampling events. The second statistical procedure monitors long-term trends in concentrations of the indicator parameters and does not require Ohio EPA notification.

None of the control limits used to determine a statistically significant change in the indicator parameters requiring Ohio EPA notification was exceeded in the X-749A wells in 2015.

6.4.5 Quadrant II Groundwater Investigative (7-Unit) Area

The Quadrant II Groundwater Investigative (7-Unit) Area consists of an area of groundwater contamination with several potential sources. One of these sources, the X-701C Neutralization Pit, was monitored prior to implementation of the *Integrated Groundwater Monitoring Plan*. The X-701C Neutralization Pit was an open-topped neutralization pit that received process effluents and basement sump wastewater such as acid and alkali solutions and rinse water contaminated with TCE and other VOCs from metal-cleaning operations. The X-701C Neutralization Pit was located within a TCE plume centered around the X-700 and X-705 buildings. The pit was removed in 2001. In 2010, Ohio EPA approved an IRM to remediate contaminant source areas within the southeastern portion of the groundwater plume, which was completed in 2013. Chapter 3, Section 3.3.2.1 provides additional information about the Quadrant II Groundwater Investigative (7-Unit) Area.

The natural groundwater flow direction in this area is to the east toward Little Beaver Creek. The groundwater flow pattern has been changed in this area by use of sump pumps in the basements of the X-700 and X-705 buildings. Thus, the groundwater plume in this area does not spread but instead flows toward the sumps where it is collected and then treated at the X-627 Groundwater Treatment Facility. This facility discharges through FBP NPDES Outfall 611, which flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). Twenty-four wells are part of the routine monitoring program for this area. Table 6.1 lists the analytical parameters for the wells in this area.

6.4.5.1 Monitoring results for the Quadrant II Groundwater Investigative (7-Unit) Area in 2015

A contaminated groundwater plume consisting primarily of TCE is associated with the Quadrant II Groundwater Investigative (7-Unit) Area (see Figure 6.4).

Concentrations of TCE detected in the Quadrant II Groundwater Investigative (7-Unit) Area plume were generally stable or decreasing in 2015, with the exception of X701-45G on the southern perimeter of the plume. TCE has increased to 6.2 µg/L in 2015 in well X701-45G (see Figure 6.4).

Wells at the eastern or southeastern boundary of the monitoring area, X700-03G, X701-26G, and X701-27G, were sampled semiannually to monitor movement of the east side of the Quadrant II Groundwater Investigative (7-Unit) Area plume towards the X-701B Former Holding Pond Area. TCE was not detected in any of the samples collected from well X700-03G. Concentrations of TCE detected in wells X701-26G and X701-27G were similar to or less than TCE concentrations detected in 2014 (see Figure 6.4).




Figure 6.4. TCE-contaminated Gallia groundwater plume at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015.

Samples from selected wells that monitor the Quadrant II Groundwater Investigative (7-Unit) Area were analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and/or uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.4.6 X-701B Former Holding Pond

In the eastern portion of Quadrant II, groundwater concerns focus on three areas: the X-701B Former Holding Pond, the X-230J7 Holding Pond, and the X-744Y Waste Storage Yard.

The X-701B Former Holding Pond was used from the beginning of plant operations in 1954 until 1988. The pond was designed for neutralization and settlement of acid waste from several sources. TCE and other VOCs were also discharged to the pond. Two surface impoundments (sludge retention basins) were located west of the holding pond. The X-230J7 Holding Pond received wastewater from the X-701B Former Holding Pond. The X-744Y Waste Storage Yard is south of the X-701B Former Holding Pond. The yard was approximately 15 acres and surrounded the X-744G Bulk Storage Building. RCRA hazardous waste was managed in this area.

A contaminated groundwater plume extends from the X-701B Former Holding Pond towards Little Beaver Creek. Three groundwater extraction wells were installed in 1993 southeast of the X-701B Former Holding Pond and a sump was installed in 1995 in the bottom of the pond as part of the RCRA closure of the unit. These wells and sump were designed to intercept contaminated groundwater emanating from the holding pond area before it could join the existing groundwater contaminant plume. The extraction wells and sump were removed between 2009 and 2011 because of the X-701B IRM (see Chapter 3, Section 3.3.2.2).

Two groundwater interceptor trenches (French drains) are used to intercept TCE-contaminated groundwater in the eastern portion of the monitoring area. These interceptor trenches, called the X-237 Groundwater Collection System, control TCE migration into Little Beaver Creek. The 660-foot-long primary trench has two sumps in the backfill and a 440-foot-long secondary trench intersects the primary trench. The extracted groundwater is treated at the X-624 Groundwater Treatment Facility and discharges through FBP NPDES Outfall 015, which flows to Little Beaver Creek.

Groundwater remediation in the X-701B Former Holding Pond Area was initiated in 2006 (see Chapter 3, Section 3.3.2.2). Oxidant was injected into the subsurface in the western portion of the area from 2006 through 2008 to remediate VOCs in soil and groundwater. The X-701B IRM was initiated in December 2009 and completed in 2011 to further address contaminants remaining in soil and groundwater following the oxidant injections. Contaminated soil in the X-701B IRM area was removed and mixed with oxidant, with additional oxidant mixed into soil remaining at the bottom of the excavation.

Sixty-two wells that monitor the X-701B Former Holding Pond area were sampled in 2015. Table 6.1 lists the analytical parameters for the wells that are part of the *Integrated Groundwater Monitoring Plan* (DOE 2015d).

6.4.6.1 Monitoring results for the X-701B Former Holding Pond in 2015

In general, concentrations of TCE detected in wells within the X-701B plume in 2015 were similar to previous years. Concentrations of TCE remain elevated in wells X701-BW2G and X701-130G that monitor the western portion of the plume, west of the IRM treatment area (see Figure 6.5). TCE is decreasing in well X701-EW121G, which is downgradient (east) of the IRM treatment area (see Figure 6.5).




Figure 6.5. TCE-contaminated Gallia groundwater plume at the X-701B Former Holding Pond – 2015.

In the third quarter, TCE was detected at 160 µg/L in well X701-01G in the southwestern portion of the monitoring area. The TCE concentrations in the wells that define this area of the plume have rebounded since the completion of the IRM in 2011, which ended the dewatering of the IRM area (see Figure 6.5).

Samples from 48 wells that monitor the X-701B Holding Pond were analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and/or uranium-238). Technetium-99 or uranium were detected above Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium) in eight wells near the former X-701B Pond and east retention basin and in wells installed within the IRM area. Concentrations of radionuclides present in groundwater in the X-701B area can be affected by the oxidant used in the X-701B IRM and the oxidant injections conducted in 2006 through 2008 that were part of the X-701B groundwater remedy. The oxidant, which affects the oxidation/reduction potential and pH of the soil and/or groundwater, temporarily causes metals in soil to be mobilized into the groundwater. It is expected that the metals will move downgradient with groundwater flow for a short distance and then be re-adsorbed into the soil matrix as the geochemistry of the soil and groundwater returns to ambient conditions.

Samples from five wells that monitor the area near the X-744G Bulk Storage Building and X-744Y Storage Yard were analyzed for cadmium and nickel, which were detected above preliminary remediation goals in three of the five wells (X701-01G, X744G-01G, and X744G-02G). These results are typical for the X-744 area wells. Nickel was also detected at concentrations equal to or above the preliminary remediation goal in samples collected from wells X701-20G and X701-127G, which monitor the center of the plume downgradient from the IRM treatment area and the area in which oxidant was injected from 2006 through 2008. This area is likely affected by the oxidant used in the X-701B IRM and the oxidant injections conducted in 2006 through 2008.

6.4.7 X-633 Former Recirculating Cooling Water Complex

The X-633 Former Recirculating Cooling Water Complex in Quadrant II consisted of a recirculating water pumphouse and four cooling towers with associated basins. Chromium-based corrosion inhibitors were added to the cooling water until the early 1990s, when the system was converted to a phosphate-based inhibitor. D&D of the facilities was completed in 2010. Chapter 3, Section 3.3.2.3 provides additional information about the RCRA investigation of soils and groundwater in this area.

The X-633 Former Recirculating Cooling Water Complex was identified as an area of concern for potential metals contamination in 1996 based on historical analytical data for groundwater wells in this area. Samples from wells in this area were collected in 1998 and 1999 to assess the area for metals contamination. Based on detections of chromium above the preliminary remediation goal, this area was added to the PORTS groundwater monitoring program. Two wells are sampled semiannually for chromium as part of the monitoring program for this area.

6.4.7.1 Monitoring results for the X-633 Former Recirculating Cooling Water Complex in 2015

Chromium was detected in both of the X-633 monitoring wells in 2015. Samples collected from well X633-07G contained chromium at concentrations above the preliminary remediation goal of 100 µg/L: 450 µg/L (second quarter) and 630 µg/L (fourth quarter). Samples collected from well X633-PZ04G also contained chromium but at concentrations well below the preliminary remediation goal. These results are typical for these wells. Figure 6.6 shows the chromium concentrations detected in the X-633 Former Recirculating Cooling Water Complex wells.




Figure 6.6. Metal concentrations in groundwater at the X-633 Former Recirculating Cooling Water Complex and X-533 Former Switchyard Complex – 2015.

6.4.8 X-616 Former Chromium Sludge Surface Impoundments

The X-616 Former Chromium Sludge Surface Impoundments in Quadrant III were two unlined surface impoundments used from 1976 to 1985 for storage of sludge generated by the treatment of water from the PORTS process cooling system. A corrosion inhibitor containing chromium was used in the cooling water system. Sludge containing chromium was produced by the water treatment system and was pumped into and stored in the X-616 impoundments. The sludge was removed from the impoundments and remediated as an interim action in 1990 and 1991. The unit was certified closed in 1993. Sixteen wells are sampled as part of the monitoring program for this area. Table 6.1 lists the analytical parameters for the wells in this area.

6.4.8.1 Monitoring results for the X-616 Former Chromium Sludge Surface Impoundments in 2015

Chromium is of special concern at X-616 because of the previous use of the area. In 2015, chromium was detected above the preliminary remediation goal of 100 µg/L in one well that monitors the X-616 area: well X616-05G (on the northeastern boundary of the area). Chromium is typically detected above the preliminary remediation goal in this well. Nickel was detected above the preliminary remediation goal (100 µg/L for Gallia wells) in two wells (X616-05G and X616-25G). Nickel is typically detected above the preliminary remediation goal in these two wells. Figure 6.7 shows the concentrations of chromium and nickel in wells at the X-616 Former Chromium Sludge Surface Impoundments.

TCE was detected above the preliminary remediation goal of 5 µg/L in three wells west of the former surface impoundments: wells X616-09G, X616-13G, and X616-20B. TCE has been detected above 5 µg/L in wells X616-09G and X616-20B since 2004 or earlier. Concentrations of TCE increased to above 5 µg/L in well X616-13G in 2013. Figure 6.7 shows the concentrations of TCE detected in the X-616 wells in 2015.

6.4.9 X-740 Former Waste Oil Handling Facility

The X-740 Former Waste Oil Handling Facility, which was demolished in 2006, was located on the western half of PORTS south of the X-530A Switchyard in Quadrant III. The X-740 facility, which operated from 1983 until 1991, was used as an inventory and staging facility for waste oil and waste solvents that were generated from various plant operational and maintenance activities. A sump within the building was used between 1986 and 1990 to collect residual waste oil and waste solvents from containers crushed in a hydraulic drum crusher at the facility. The facility and sump were initially identified as hazardous waste management units in 1991. The X-740 Former Waste Oil Handling Facility (both the facility and sump identified as hazardous waste management units) underwent closure, and closure certification was approved by Ohio EPA in 1998.

In 1999, poplar trees were planted in a 2.6-acre phytoremediation area above the groundwater plume near the X-740 Former Waste Oil Handling Facility. Because phytoremediation did not work as anticipated to reduce the concentrations of VOCs in groundwater in this area, three rounds of oxidant injections were completed during 2008. Additional alternatives for groundwater remediation in this area were evaluated in 2009, and a pilot study of enhanced anaerobic bioremediation began in 2010. DOE and Ohio EPA have agreed that selection of a new remedy for the X-740 groundwater plume will be incorporated into the deferred units preferred plan and decision document. Chapter 3, Section 3.3.3, provides additional information about the remedial activities for the X-740 area.

Twenty-three wells that monitor the X-740 Former Waste Oil Handling Facility were sampled during 2015.




Figure 6.7. TCE and metal concentrations in groundwater at the X-616 Former Chromium Sludge Surface Impoundments – 2015.

6.4.9.1 Monitoring results for the X-740 Former Waste Oil Handling Facility in 2015

A contaminated groundwater plume consisting primarily of TCE is located near the X-740 Former Waste Oil Handling Facility in Quadrant III. Figure 6.8 shows the TCE groundwater plume in 2015 for the X-740 area. The perimeter of the X-740 groundwater plume did not change in 2015. However, concentrations of TCE are decreasing in Gallia wells that monitor the pilot study (X740-18G, X740-19G, X740-20G, X740-21G, and X740-22G – see Figure 6.8). TCE has also decreased in wells X740-03G and X740-09B, which had the highest concentrations of TCE in the X-740 groundwater plume prior to the pilot study.

6.4.10 X-611A Former Lime Sludge Lagoons

The X-611A Former Lime Sludge Lagoons in Quadrant IV were comprised of three adjacent unlined sludge retention lagoons constructed in 1954 and used for disposal of lime sludge waste from the site water treatment plant from 1954 to 1960. The lagoons covered a surface area of approximately 18 acres and were constructed in a low-lying area that included Little Beaver Creek. As a result, approximately 1500 feet of Little Beaver Creek were relocated to a channel just east of the lagoons.

As part of the RCRA Corrective Action Program, a prairie habitat has been developed in this area by placing a soil cover over the north, middle, and south lagoons. A soil berm was also constructed outside the northern boundary of the north lagoon to facilitate shallow accumulation of water in this low-lying area. Chapter 3, Section 3.3.4.1, provides more information about this remediation. Six wells are sampled semiannually as part of the monitoring program for this area. Table 6.1 lists the analytical parameters for the wells in this area.

6.4.10.1 Monitoring results for the X-611A Former Lime Sludge Lagoons in 2015

The six monitoring wells at X-611A are sampled and analyzed for beryllium and chromium. In 2015, chromium was detected in the samples collected from two of the six wells in this area at concentrations between 2.7 and 12 µg/L, which are below the preliminary remediation goal (100 µg/L).

In 2015, beryllium was detected in three of the six wells in this area at concentrations of 1.9 µg/L or less, which are less than the preliminary remediation goals (6.5 µg/L for Gallia wells and 7 µg/L for Berea wells). Figure 6.9 shows the concentrations of beryllium and chromium detected in the X-611A wells in 2015.

6.4.11 X-735 Landfills

Several distinct waste management units are contained within the X-735 Landfills area in Quadrant IV. The main units consist of the hazardous waste landfill, referred to as the X-735 RCRA Landfill, and the X-735 Industrial Solid Waste Landfill. The X-735 Industrial Solid Waste Landfill includes the industrial solid waste cells, asbestos disposal cells, and the chromium sludge monocells A and B. The chromium sludge monocells contain a portion of the chromium sludge generated during the closure of the X-616 Chromium Sludge Surface Impoundments.

Initially, a total of 17.9 acres was approved by Ohio EPA and Pike County Department of Health for landfill disposal of conventional solid wastes. The landfill began operation in 1981. During operation of the landfill, PORTS investigations indicated that wipe rags contaminated with solvents had inadvertently been disposed in the northern portion of the landfill. The contaminated rags were considered a hazardous waste. Waste disposal in the northern area ended in 1991, and Ohio EPA determined that the area required closure as a RCRA hazardous waste landfill. Consequently, this unit of the sanitary landfill was identified as the X-735 RCRA Landfill.




Figure 6.8. TCE-contaminated Gallia groundwater plume near the X-740 Former Waste Oil Handling Facility – 2015.




Figure 6.9. Metal concentrations in groundwater at the X-611A Former Lime Sludge Lagoons – 2015.

A buffer zone was left unexcavated to provide space for groundwater monitoring wells and a space between the RCRA landfill unit and the remaining southern portion, the X-735 Industrial Solid Waste Landfill. Routine groundwater monitoring has been conducted at the X-735 Landfills since 1991.

The industrial solid waste portion of the X-735 Landfills included a solid waste section and an asbestos waste section. The X-735 Industrial Solid Waste Landfill, not including the chromium sludge monocells, encompasses a total area of approximately 4.1 acres. Operation of the X-735 Industrial Solid Waste Landfill ceased in 1997; this portion of the landfill was capped in 1998.

The *Integrated Groundwater Monitoring Plan* incorporates monitoring requirements for the hazardous and solid waste portions of the X-735 Landfills (DOE 2014b, DOE 2015d). In addition, the *Corrective Measures Plan for the X-735 Landfill* was approved by Ohio EPA in 2008 (DOE 2007a). This plan provides the monitoring requirements for Gallia wells that monitor the X-735 Landfill. Corrective measures monitoring was implemented because Ohio EPA determined that assessment monitoring of the landfill, completed between 2005 and 2007, identified that a small release of leachate constituents is occurring or has occurred from the X-735 Landfills. Eighteen wells were sampled in 2015 as part of the monitoring programs for this area. Table 6.1 lists the analytical parameters and Figure 6.10 shows the monitoring wells in this area.

6.4.11.1 Monitoring results for the X-735 Landfills in 2015

The monitoring program at the X-735 Landfills includes corrective measures monitoring for Gallia wells and detection monitoring for Berea wells. As required by the corrective measures monitoring program, concentrations of three metals (cobalt, mercury, and nickel) and five indicator parameters (alkalinity, chloride, sodium, sulfate, and total dissolved solids) detected in downgradient Gallia wells are compared to concentration limits based on drinking water standards or site background concentrations. None of these concentration limits were exceeded in 2015.

The detection monitoring program for X-735 Berea wells continued in 2015. Concentrations of alkalinity, ammonia, calcium, chloride, iron, nitrate/nitrite, potassium, sodium, and sulfate in downgradient Berea wells were evaluated to monitor potential impacts to groundwater and trends in concentrations of these parameters. None of the control limits used to determine a statistically significant change in the indicator parameters requiring Ohio EPA notification was exceeded in the X-735 Berea wells in 2015.

Samples from the X-735 monitoring wells were also analyzed for radionuclides (technetium-99, uranium, uranium-233/234, uranium-235/236, and uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.4.12 X-734 Landfills

The X-734 Landfills in Quadrant IV consisted of three landfill units that were used until 1985. Detailed records of materials disposed in the landfills were not kept. However, wastes known to be disposed at the landfills included trash and garbage, construction spoils, wood and other waste from clearing and grubbing, and empty drums. Other materials reportedly disposed in the landfills may have included waste contaminated with metals, empty paint cans, and uranium-contaminated soil from the X-342 area.

The X-734 Landfills were closed in accordance with regulations in effect at that time, and no groundwater monitoring of the area was required. However, the RCRA Facility Investigation conducted in the early 1990s identified the presence of VOCs, metals, and radionuclides in soil and/or groundwater in the area. The X-734 Landfills were capped in 1999-2000 as part of the remedial actions required for Quadrant IV. Chapter 3, Section 3.3.4.2, provides more information about the remedial actions for this area.




Figure 6.10. Monitoring wells at the X-735 Landfills.

Fifteen wells (see Figure 6.11) are sampled semiannually as part of the monitoring program for this area. Table 6.1 lists the monitoring parameters for the wells in this area.

6.4.12.1 Monitoring results for the X-734 Landfills in 2015

VOCs are routinely detected in a number of the wells that monitor the X-734 Landfills, but generally at concentrations below preliminary remediation goals. In 2015, no VOCs were detected at concentrations above the preliminary remediation goals in the samples collected from the X-734 monitoring wells.

Samples from the X-734 monitoring wells were also analyzed for five metals (beryllium, cadmium, chromium, manganese, and nickel). None of the samples contained metals at concentrations above the respective preliminary remediation goal.

Samples from the X-734 monitoring wells were also analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.4.13 X-533 Former Switchyard Complex

The X-533 Former Switchyard Complex in Quadrant IV consisted of a switchyard containing electrical transformers and circuit breakers, associated support buildings, and a transformer cleaning pad. The groundwater area of concern is located north of the switchyard and associated support buildings near the transformer cleaning pad. D&D of the facilities began in 2010 and was completed in 2011. Soil contaminated with PCBs or metals was removed from three areas within the complex in 2010; however, none of the soil removal areas were located near the groundwater area of concern (the north side of the area near the transformer cleaning pad).

The X-533 Former Switchyard Complex was identified as an area of concern for potential metals contamination in 1996 based on historical analytical data for groundwater wells in this area. Samples from wells in this area were collected in 1998 and 1999 to assess the area for metals contamination. The area was added to the PORTS groundwater monitoring program because the sampling identified metals that may have contaminated groundwater in this area. Three wells are sampled semiannually for cadmium and nickel.

6.4.13.1 Monitoring results for the X-533 Former Switchyard Complex in 2015

Three wells that monitor the X-533 Former Switchyard Complex (F-03G, TCP-01G, and X533-03G) were sampled in the second and fourth quarters of 2015 and analyzed for cadmium and nickel. Each of the well samples contained these metals at concentrations above the preliminary remediation goals (6.5 µg/L for cadmium and 100 µg/L for nickel). Concentrations of cadmium detected in the wells ranged from 14 to 46 µg/L, and concentrations of nickel detected in the wells ranged from 170 to 450 µg/L. Figure 6.6 shows the concentrations of metals detected in the X-533 wells in 2015.

6.4.14 X-344C Former Hydrogen Fluoride Storage Building

The X-344C Former Hydrogen Fluoride Storage Building and associated hydrogen fluoride storage tanks were demolished and removed in 2006. In 2009, an investigation of soils and groundwater near the former building determined that groundwater in one monitoring well south of the former building contained two VOCs (*cis*-1,2-dichloroethene and *trans*-1,2-dichloroethene) at concentrations well below the preliminary remediation goals.

This area was added to the PORTS groundwater monitoring program in 2010. One well is sampled annually for VOCs under the monitoring program for this area (see Figure 6.12).




Figure 6.11. Monitoring wells at the X-734 Landfills.




Figure 6.12. Monitoring well at the X-344C Former Hydrogen Fluoride Storage Building.

6.4.14.1 Monitoring results for the X-344C Former Hydrogen Fluoride Storage Building in 2015

Four VOCs, *cis*-1,2-dichloroethene, *trans*-1,2-dichloroethene, TCE, and vinyl chloride, were detected in the sample collected in the first quarter of 2015 at low concentrations less than 2 µg/L, which are less than the preliminary remediation goals. These detections are consistent with the data collected at this well in 2009 through 2014.

6.4.15 Surface Water Monitoring

Surface water monitoring is conducted in conjunction with groundwater assessment monitoring to determine if contaminants present in groundwater are detected in surface water samples. Surface water is collected quarterly from 14 locations (see Figure 6.13). Surface water samples are analyzed for the parameters listed in Table 6.1. The purpose for each surface water monitoring location is described as follows:

- Little Beaver Creek and East Drainage Ditch sample locations LBC-SW01, LBC-SW02, and EDD-SW01 assess possible X-701B area groundwater discharges.
- Little Beaver Creek sample locations LBC-SW02 and LBC-SW03 assess potential contamination from the X-611A Former Lime Sludge Lagoons.
- Big Run Creek sample location BRC-SW01 assesses potential groundwater discharges from the Quadrant I Groundwater Investigative (5-Unit) Area.
- Big Run Creek sample location BRC-SW05 monitors potential discharges from the X-749/PK Landfill groundwater collection system on the east side of the landfills, as well as the Quadrant I Groundwater Investigative (5-Unit) Area.
- Big Run Creek sample location BRC-SW02 (downstream from BRC-SW01 and BRC-SW05) monitors potential discharges from the Quadrant I Groundwater Investigative (5-Unit) Area, X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility, and PK Landfill.
- Southwestern Drainage Ditch sample locations UND-SW01 and UND-SW02 assess potential groundwater releases to this creek and the X-2230M Southwest Holding Pond from the western portion of the X-749/X-120 groundwater plume.
- North Holding Pond sample location NHP-SW01 and Little Beaver Creek sample location LBC-SW04 assess potential groundwater discharges from the X-734 Landfill and other Quadrant IV sources.
- Western Drainage Ditch sample locations WDD-SW01, WDD-SW02, and WDD-SW03 assess potential groundwater discharges from the X-616 and X-740 areas to the Western Drainage Ditch and the X-2230N West Holding Pond.

6.4.15.1 Monitoring results for surface water in 2015

Trihalomethanes are a category of VOCs that are byproducts of water chlorination and include bromodichloromethane, bromoform, chloroform, and dibromochloromethane. These compounds are detected at most of the surface water sampling locations because the streams receive discharges that contain chlorinated water from the PORTS NPDES outfalls. These detections were well below the Ohio EPA non-drinking water quality criteria for the protection of human health in the Ohio River drainage basin (bromodichloromethane – 460 µg/L; bromoform – 3600 µg/L; chloroform – 4700 µg/L; and dibromochloromethane – 340 µg/L).





Figure 6.13. Surface water monitoring locations.

Since the 1990s, TCE has been detected regularly at low levels in samples collected from the Southwestern Drainage Ditch (UND-SW01, located inside Perimeter Road). In 2015, TCE was detected at 0.7 to 5.3 µg/L in each of the four samples collected from the Southwestern Drainage Ditch at UND-SW01. *Cis*-1,2-dichloroethene and 1,1-dichloroethene were also detected at estimated concentrations less than 0.5 µg/L in samples collected at UND-SW01. VOCs were not detected in the samples collected from the Southwestern Drainage Ditch at UND-SW02. The detections of TCE were well below the Ohio EPA non-drinking water quality criterion for TCE (810 µg/L) for the protection of human health in the Ohio River drainage basin.

TCE and *cis*-1,2-dichloroethene were detected in samples collected from the East Drainage Ditch and Little Beaver Creek at a maximum concentration of 3.8 µg/L. TCE and other VOCs are routinely detected in East Drainage Ditch and Little Beaver Creek at low concentrations. TCE was also detected at an estimated concentration of 0.33 µg/L in the second quarter sample collected from the West Drainage Ditch at WDD-SW02. All detections of TCE were well below the Ohio EPA non-drinking water quality criterion for TCE (810 µg/L) for the protection of human health in the Ohio River drainage basin.

Samples collected in the second and fourth quarters of 2015 were analyzed for selected transuranics (americium-241, neptunium-237, plutonium-238, and plutonium-239/240). No transuranics were detected in the surface water samples collected during 2015.

Technetium-99 was detected at levels up to 33.1 pCi/L in samples collected from the East Drainage Ditch (EDD-SW01), Little Beaver Creek (LBC-SW01, LBC-SW02, LBC-SW03, and LBC-SW04), and the West Drainage Ditch (WDD-SW01 and WDD-SW03). These detections are within the historical range of technetium-99 detected in surface water at PORTS, and are 0.08% or less of derived concentration standard for technetium-99 in water (44,000 pCi/L – DOE 2011a).

Uranium was routinely detected in the 2015 surface water samples at levels similar to those detected in previous years. Because uranium occurs naturally in rocks and soil, some or all of the uranium detected in these samples may be due to naturally-occurring uranium.

6.4.16 Water Supply Monitoring

Routine monitoring of private residential drinking water sources is completed at PORTS in accordance with the requirements of Section VIII of the September 1989 Consent Decree between the State of Ohio and DOE and the *Integrated Groundwater Monitoring Plan* (DOE 2014b, DOE 2015d).

The purpose of the program is to determine whether PORTS has had any impact on the quality of the private residential drinking water sources. Although this program may provide an indication of contaminant transport off site, it should not be interpreted as an extension of the on-site groundwater monitoring program, which bears the responsibility for detection of contaminants and determining the rate and extent of contaminant movement. Data from this program will not be used in environmental investigations due to the lack of knowledge of how residential wells were constructed and due to the presence of various types of pumps (which may not be ideal equipment for sampling).

Four residential drinking water sources participated in the program in 2015. Two residential drinking water sources that are included in the water supply monitoring program (RES-004 and RES-005) were not able to be sampled in 2015 because the well pumps were not operable. The PORTS water supply is also sampled as part of this program. Figure 6.14 shows the drinking water sources that were part of the monitoring program in 2015. Sampling locations may be added or deleted if requested by a resident and




Figure 6.14. Water supply monitoring locations.

as program requirements dictate. Typically, sampling locations are deleted when a resident obtains a public water supply. Wells are sampled semiannually with samples analyzed for the parameters listed in Table 6.1.

In the first and third quarters of 2015, TCE was detected at estimated concentrations of 0.4 µg/L and 0.65 µg/L, respectively, in the samples collected from RES-017, which is south of PORTS on Big Run Road. No other VOCs were detected in the samples at this location. Since this residential water supply was added to the monitoring program in 2009, TCE has routinely been detected in the water supply samples at concentrations up to 1 µg/L. These detections are less than the drinking water standard for TCE (5 µg/L). Big Run Creek is located between RES-017 and the affected water-bearing formation (i.e., Gallia groundwater) located in the southern portion of the plant site west of Big Run Creek. The Gallia groundwater drains into Big Run Creek.

Chlorination byproducts called trihalomethanes (bromodichloromethane, bromoform, chloroform, and dibromochloromethane), which are common residuals in treated drinking water, were detected in the first and third quarter samples collected from residential sampling location RES-015. The total concentration of these trihalomethanes was less than the Ohio EPA drinking water standard (80 µg/L for total trihalomethanes).

Each sample was analyzed for transuranics (americium-241, neptunium-237, plutonium-238, and plutonium-239/240), technetium-99, uranium, and uranium isotopes (uranium-233/234, uranium-235/236, and uranium-238). No transuranics or technetium-99 were detected in any of the water supply samples collected in 2015. Low levels of uranium and uranium isotopes detected in some of the wells are consistent with naturally-occurring concentrations found in groundwater in the area.

6.5 DOE ORDER MONITORING PROGRAMS

One of the DOE surveillance monitoring programs at PORTS is exit pathway monitoring. Exit pathway monitoring assesses the effect of the facility on off-site surface water and groundwater quality.

6.5.1 Exit Pathway Monitoring

Selected locations on local streams and drainage channels near the PORTS boundary are sampling points of the exit pathway monitoring program because surface water from PORTS NPDES outfalls and groundwater discharge to these surface waters. Monitoring wells near the PORTS boundary are also used in the exit pathway monitoring program. Figure 6.15 shows the sampling locations for exit pathway monitoring and Table 6.1 lists the analytical parameters.

Surface water sampling points on Big Run Creek (BRC-SW02), Little Beaver Creek (LBC-SW04), Southwestern Drainage Ditch (UND-SW02), and Western Drainage Ditch (WDD-SW03) are part of the exit pathway monitoring program (see Figure 6.13). TCE was detected at 0.29 µg/L in the fourth quarter sample collected from Little Beaver Creek at LBC-SW04 (see Section 6.4.15.1). This detection was well below the Ohio EPA non-drinking water quality criterion for TCE (810 µg/L) for the protection of human health in the Ohio River drainage basin.

Trihalomethanes (bromodichloromethane, bromoform, chloroform, and dibromochloromethane), which are common residuals in chlorinated drinking water, were detected in samples collected from the Western Drainage Ditch and Little Beaver Creek at concentrations well below Ohio EPA non-drinking water quality criteria for trihalomethanes for the protection of human health in the Ohio River drainage basin (see Section 6.4.15.1).




Figure 6.15. Exit pathway monitoring locations.

Technetium-99 was detected at levels up to 19.3 pCi/L in samples collected at the surface water exit pathway monitoring locations on Little Beaver Creek (LBC-SW04) and Western Drainage Ditch (WDD-SW03). These detections were 0.04% or less of derived concentration standard for technetium-99 in water (44,000 pCi/L – DOE 2011a).

VOCs were also detected in several on-site groundwater monitoring wells that are part of the exit pathway monitoring program. TCE and other VOCs were detected in several wells that monitor the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility (see Section 6.4.1.3). Detections of TCE and other VOCs in the exit pathway monitoring wells were below Ohio EPA drinking water standards.

Samples from exit pathway monitoring wells were analyzed for radionuclides (americium-241, neptunium-237, plutonium-238, plutonium-239/240, technetium-99, uranium, uranium-233/234, uranium-235/236, and/or uranium-238). If detected, radionuclides were present at levels below Ohio EPA drinking water standards (900 pCi/L for technetium-99 based on a 4 mrem/year dose from beta emitters, and 30 µg/L for uranium).

6.6 GROUNDWATER TREATMENT FACILITIES

In 2015, a combined total of approximately 33.7 million gallons of water were treated at the X-622, X-623, X-624, and X-627 Groundwater Treatment Facilities. Approximately 26 gallons of TCE were removed from the water. All processed water is discharged through NPDES outfalls before exiting PORTS. Facility information is summarized in Table 6.2.

Table 6.2. Summary of TCE removed by PORTS groundwater treatment facilities in 2015^a

Facility	Gallons of water treated	Gallons of TCE removed
X-622	19,877,210	2
X-623	30,245	0.01
X-624	2,875,600	10
X-627	10,946,405	14

^aSource: 2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant (DOE 2016a)

6.6.1 X-622 Groundwater Treatment Facility

The X-622 Groundwater Treatment Facility consists of an air stripper with aqueous-phase activated carbon filtration. This facility processes groundwater from the following systems in Quadrant I (see Figures 6.2 and 6.3):

- groundwater collection system with associated sump (X749-WPW) and extraction wells X749-EW05G and X749-EW06G on the southwest boundary of the X-749 Landfill;
- groundwater extraction wells X749-EW01G, X749-EW02G, X749-EW03G, and X749-EW04G installed in 2007 in the X-749 South Barrier Wall area;
- groundwater extraction wells (X749-EW07G, X749-EW08G, and X749-EW09G) installed in 2010 in the X-749/X-120 groundwater plume;

- groundwater collection system and associated sumps (PK-PL6 and PK-PL6A) on the eastern boundary of the PK Landfill; and
- fifteen extraction wells located in the Quadrant I Groundwater Investigative (5-Unit) Area.

The facility processed approximately 20 million gallons of groundwater during 2015, thereby removing approximately 2 gallons of TCE from the water. Treated water from the facility discharges through FBP NPDES Outfall 608, which flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). No NPDES permit limitations were exceeded at Outfall 608 in 2015.

6.6.2 X-623 Groundwater Treatment Facility

The X-623 Groundwater Treatment Facility consists of an air stripper with offgas activated carbon filtration and aqueous-phase activated carbon filtration. Prior to implementation of the X-701B IRM in 2009, the X-623 Groundwater Treatment Facility treated TCE-contaminated groundwater from a sump in the bottom of the X-701B Former Holding Pond and three groundwater extraction wells (X623-EW01G, X623-EW02G, and X623-EW03G) east of the holding pond. The sump and extraction wells were removed in 2009-2011 to facilitate implementation of the IRM.

During 2015, the X-623 Groundwater Treatment Facility operated intermittently to treat miscellaneous water associated with site activities in accordance with the NPDES permit. The X-623 Groundwater Treatment Facility did not operate in January, February, April, May, August, September, and October of 2015.

The facility treated 30,245 gallons of water during 2015, thereby removing approximately 0.01 gallon of TCE from the water. Treated water from the facility discharges through FBP NPDES Outfall 610, which flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). No NPDES permit limitations were exceeded at Outfall 610 in 2015.

6.6.3 X-624 Groundwater Treatment Facility

At the X-624 Groundwater Treatment Facility, groundwater is treated via an air stripper with offgas activated carbon filtration and aqueous-phase activated carbon filtration. This facility processes TCE-contaminated groundwater from the X-237 Groundwater Collection System on the east side of the X-701B groundwater plume. The X-237 Groundwater Collection System consists of north-south and east-west collection trenches and two sumps/pumping wells (see Figure 6.5).

The X-624 Groundwater Treatment Facility treated approximately 2.9 million gallons of water in 2015, thereby removing approximately 10 gallons of TCE from the water. Treated water from the facility discharges through FBP NPDES Outfall 015, which discharges to Little Beaver Creek. No NPDES permit limitations were exceeded at Outfall 015 in 2015.

6.6.4 X-627 Groundwater Treatment Facility

The X-627 Groundwater Treatment Facility consists of an air stripper with offgas activated carbon filtration and aqueous phase activated carbon filtration. The X-700 and X-705 buildings are located above the Quadrant II Groundwater Investigative (7-Unit) Area plume, and contaminated water is collected in the sumps located in the basement of each building (see Figure 6.4).

Almost 11 million gallons of groundwater were processed during 2015, thereby removing 14 gallons of TCE from the water. Treated water from the facility discharges through FBP NPDES Outfall 611, which flows to the X-6619 Sewage Treatment Plant (FBP NPDES Outfall 003). No NPDES permit limitations were exceeded at Outfall 611 in 2015.

7. QUALITY ASSURANCE

7.1 SUMMARY

Quality assurance and quality control are essential components of DOE environmental monitoring programs at PORTS. Quality is integrated into sample preservation, field data and sample collection, sample transportation, and sample analysis. Numerous program assessment activities in the field and within the facilities are conducted at regular intervals to demonstrate that quality is built into and maintained in all DOE programs. Analytical laboratories used by DOE contractors during 2015 participated in the DOE Consolidated Audit Program and Mixed-Analyte Performance Evaluation Program.

7.2 QUALITY ASSURANCE INTRODUCTION

Quality assurance, an integral part of environmental monitoring, requires systematic control of the processes involved in sampling the environment and in analyzing the samples. To demonstrate accurate results, DOE uses the following planned and systematic controls:

- implementation of standard operating procedures for sample collection and analysis;
- training and qualification of surveyors and analysts;
- implementation of sample tracking and chain-of-custody procedures to demonstrate traceability and integrity of samples and data;
- participation in external quality control programs;
- frequent calibration and routine maintenance of measuring and test equipment;
- maintenance of internal quality control programs;
- implementation of good measurement techniques and good laboratory practices; and
- frequent assessments of field sampling, measurement activities, and laboratory processes.

Environmental sampling is conducted by DOE contractors at PORTS in accordance with state and federal regulations and DOE Orders. Sampling plans and procedures are prepared, and appropriate sampling instruments or devices are selected in accordance with practices recommended by U.S. EPA, the American Society for Testing and Materials, or other authorities. Chain-of-custody forms document sample custody from sample collection through receipt by the analytical laboratory. The samples remain in the custody of the sampling group until the samples are received at the laboratory. Samples shipped to an off-site laboratory are sealed within the shipping container to prevent tampering until they are received by the sample custodian at the off-site laboratory.

The analytical data are reviewed to determine compliance with applicable regulations and permits. The data are used to identify locations and concentrations of contaminants of concern, to evaluate the rate and extent of contamination at the site, and to help determine the need for remedial action. Adequate and complete documentation generated as a result of these efforts supports the quality standards established by DOE. Quality Assurance Project Plans were used by FBP and BWCS during 2015 to ensure a consistent system for collecting, assessing, and documenting environmental data of known and documented quality.

7.3 FIELD SAMPLING AND MONITORING

Personnel involved in field sampling and monitoring are properly trained through a combination of classroom, on-line, and/or on-the-job training as required by environmental, health, and safety regulations and DOE contract requirements. Procedures are developed from guidelines and regulations created by DOE or other regulatory agencies that have authority over PORTS activities. These procedures specify sampling protocol, sampling devices, containers, and preservatives to be used. Chain-of-custody procedures (used with all samples) are documented, and samples are controlled and protected from the point of collection to the generation of analytical results.

Data generated from field sampling can be greatly influenced by the methods used to collect and transport the samples. A quality assurance program provides the procedures for proper sample collection so that the samples represent the conditions that exist in the environment at the time of sampling. The DOE quality assurance program at PORTS mandates compliance with written sampling procedures, use of clean sampling devices and containers, use of approved sample preservation techniques, and collection of field blanks, trip blanks, and duplicate samples. Chain-of-custody procedures are strictly followed to maintain sample integrity. In order to maintain sample integrity, samples are delivered to the laboratory as soon as practicable after collection.

7.4 ANALYTICAL QUALITY ASSURANCE

DOE contractors at PORTS only use analytical laboratories that demonstrate compliance in the following areas through participation in independent audits and surveillance programs:

- compliance with federal waste disposal regulations,
- data quality,
- materials management,
- sample control,
- data management,
- electronic data management,
- implementation of a laboratory quality assurance plan, and
- review of external and internal performance evaluation program.

After analytical laboratory data are received by DOE contractors, they are independently evaluated using a systematic process that compares the data to established quality assurance/quality control criteria. An independent data validator checks documentation produced by the analytical laboratory to verify that the laboratory has provided data that meet established criteria.

In 2015, samples collected for DOE environmental monitoring programs at PORTS such as NPDES monitoring, groundwater monitoring required by the *Integrated Groundwater Monitoring Plan* (DOE 2014b, DOE 2015d), and environmental monitoring required by the *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant* (DOE 2013a), were sent to analytical laboratories that participated in DOE programs to ensure data quality. The DOE Consolidated Audit Program implements annual performance qualification audits of environmental laboratories. The DOE Mixed-Analyte Performance Evaluation Program provides semiannual performance testing and evaluation of analytical laboratories.

8. REFERENCES

- American Nuclear Society 1986. *Glossary of Terms in Nuclear Science and Technology*, LaGrange Park, IL.
- Biological Effects of Ionizing Radiations 1990. *Health Effects of Exposure to Low Levels of Ionizing Radiation*, Committee on the Biological Effects of Ionizing Radiations (BEIR V), National Research Council, National Academy of Sciences, National Academy Press, Washington, D.C.
- DOE 1995. Memorandum, Pelletier to Pearson: *Requirements for Control of Settleable Solids, Air, Water and Radiation Division: EH-412*, Washington D.C., December 6.
- DOE 1998a. *Quadrant III Cleanup Alternatives Study/Corrective Measures Study Final Report for Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/OR/12-1360&D3, POEF-ER-4619&D3, U.S. Department of Energy, Piketon, OH, April.
- DOE 1998b. *Quadrant IV Cleanup Alternatives Study/Corrective Measures Study Final Report for Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/OR/12-1332&D3, POEF-ER-4609&D3, U.S. Department of Energy, Piketon, OH, August.
- DOE 2000. *Quadrant I Cleanup Alternatives Study/Corrective Measures Study Final Report for Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/OR/12-1248&D6, U.S. Department of Energy, Piketon, OH, May.
- DOE 2001. *Quadrant II Cleanup Alternatives Study/Corrective Measures Study Final Report for Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/OR/12-1223&D5, U.S. Department of Energy, Piketon, OH, February.
- DOE 2002a. *A Graded Approach for Evaluating Radiation Doses to Aquatic and Terrestrial Biota*, DOE-STD-1153-2002, U.S. Department of Energy, Washington, D.C., July.
- DOE 2002b. *X-611A Prairie and X-749B Peter Kiewit Landfill Five-Year Evaluation Report for the Portsmouth Gaseous Diffusion Plant*, DOE/OR/11-3110&D1, U.S. Department of Energy, Piketon, OH, August.
- DOE 2003. *Five-Year Evaluation Report for the X-740 Phytoremediation Project at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/OR/11-3135&D1, U.S. Department of Energy, Piketon, OH, October.
- DOE 2007a. *Corrective Measures Plan for the X-735 Landfill at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0019&D4, U.S. Department of Energy, Piketon, OH, October.
- DOE 2007b. *Supplemental Evaluation to the 2003 Five Year Evaluation Report for the X-740 Phytoremediation Area at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0038&D1, U.S. Department of Energy, Piketon, OH, January.
- DOE 2008a. *First Five-Year Review for the Five-Unit Groundwater Investigative Area and X-231A/X-231B Oil Biodegradation Plots at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0054&D2, U.S. Department of Energy, Piketon, OH, April.

- DOE 2008b. *First Five-Year Review for the X-734 Landfill Area at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0073&D2, U.S. Department of Energy, Piketon, OH, December.
- DOE 2008c. *Second Five-Year Review for the X-611A Prairie at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0072&D2, U.S. Department of Energy, Piketon, OH, December.
- DOE 2008d. *Second Five-Year Review for the X-749B Peter Kiewit Landfill at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0053&D2, U.S. Department of Energy, Piketon, OH, March.
- DOE 2010. *Community Relations Plan for the U.S. Department of Energy's Decontamination and Decommissioning Project at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0128&D1, U.S. Department of Energy, Piketon, OH, June.
- DOE 2011a. *Derived Concentration Technical Standard*, DOE-STD-1196-2011, U.S. Department of Energy, Washington, D.C., April.
- DOE 2011b. *First Five-Year Review for the X-749/X-120 Groundwater Plume at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0187V1&D1, DOE/PPPO/03-0187V2&D1, U.S. Department of Energy, Piketon, OH, January.
- DOE 2012. *Addendum to the Community Relations Plan for the U.S. Department of Energy's Decontamination and Decommissioning Project at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0128&D2/A1, U.S. Department of Energy, Piketon, OH, September.
- DOE 2013a. *Environmental Monitoring Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0009&D4, U.S. Department of Energy, Piketon, OH, February.
- DOE 2013b. *Methods for Conducting Human Health Risk Assessments and Risk Evaluations at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0127&D7, U.S. Department of Energy, Piketon, OH, December.
- DOE 2013c. *Second Five-Year Review for the Five-Unit Groundwater Investigative Area and X-231A/X-231B Oil Biodegradation Plots at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0490&D1, U.S. Department of Energy, Piketon, OH, September.
- DOE 2013d. *Second Five-Year Review for the X-734 Landfill Area at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0559&D1, U.S. Department of Energy, Piketon, OH, December.
- DOE 2013e. *Third Five-Year Review for the X-611A Prairie at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0482&D2, U.S. Department of Energy, Piketon, OH, July.
- DOE 2013f. *Third Five-Year Review for the X-749B Peter Kiewit Landfill at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0489&D1, U.S. Department of Energy, Piketon, OH, September.
- DOE 2014a. *Final Report for the 7-Unit Interim Remedial Measure at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0606&D1, U.S. Department of Energy, Piketon, OH, October.

- DOE 2014b. *Integrated Groundwater Monitoring Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0032&D7, U.S. Department of Energy, Piketon, OH, May.
- DOE 2015a. *Deferred Units Resource Conservation and Recovery Act Facility Investigation/Corrective Measures Study Work Plan at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0252&D3, U.S. Department of Energy, Piketon, OH, March.
- DOE 2015b. *Final Soil Background Report for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0667&D1, U.S. Department of Energy, Piketon, OH, April.
- DOE 2015c. *Fiscal Year 2016 Site Sustainability Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0742&D1, U.S. Department of Energy, Piketon, OH, December.
- DOE 2015d. *Integrated Groundwater Monitoring Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0032&D8, U.S. Department of Energy, Piketon, OH, July.
- DOE 2015e. *Record of Decision for Process Buildings and Complex Facilities Decontamination and Decommissioning Evaluation Project at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0425&D2, U.S. Department of Energy, Piketon, OH, July.
- DOE 2015f. *Record of Decision for the Site-wide Waste Disposition Evaluation Project at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0513&D2, U.S. Department of Energy, Piketon, OH, June.
- DOE 2015g. *Remedial Design/Remedial Action Work Plan for the On-site Waste Disposal Facility Initial Site Preparation and Construction Activities at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0691&D1, U.S. Department of Energy, Piketon, OH, September.
- DOE 2015h. *Sampling and Analysis Plan for the X-114A Outdoor Firing Range Structures at the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0680&D1, U.S. Department of Energy, Piketon, OH, July.
- DOE 2016a. *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0746&D1, U.S. Department of Energy, Piketon, OH, March.
- Hamby, D. M. 1991. *LADTAP XL: An Improved Electronic Spreadsheet Version of LADTAP II*, DE93003179, Westinghouse Savannah River Company, Aiken, SC.
- Health Physics Society 2010. *Environmental Radiation* (Fact Sheet – Adopted January 2010), available at www.hps.org (accessed March 2, 2016).
- Jannik and Dixon 2006. *LADTAP-PA: A Spreadsheet for Estimating Dose Resulting from E-Area Groundwater Contamination at the Savannah River Site*, Savannah River National Laboratory, Aiken, SC.
- McGraw-Hill 1989. *McGraw-Hill Dictionary of Scientific and Technical Terms*, 4th ed., McGraw-Hill, Inc., NY.
- National Council on Radiation Protection 2009. *Ionizing Radiation Exposure of the Population of the United States*, NCRP Report No. 160, National Council on Radiation Protection and Measurements, Bethesda, MD.

- Ohio EPA 1996a. *Decision Document Peter Kiewit Landfill, U.S. DOE Portsmouth, Pike County, Ohio*, Ohio Environmental Protection Agency, Columbus, OH, May.
- Ohio EPA 1996b. *Decision Document X-611A Solid Waste Management Unit U.S. DOE Portsmouth, Pike County, Ohio*, Ohio Environmental Protection Agency, Columbus, OH, June.
- Ohio EPA 1999a. *Ohio Environmental Protection Agency's Decision Document for Quadrant III of the Portsmouth Gaseous Diffusion Plant*, Ohio Environmental Protection Agency, Columbus, OH, March.
- Ohio EPA 1999b. *The Decision Document for the X-734 Landfill Area in Quadrant IV of the Portsmouth Gaseous Diffusion Plant*, Ohio Environmental Protection Agency, Columbus, OH, September.
- Ohio EPA 2000. *U.S. DOE Portsmouth QIV Decision Document*, Ohio Environmental Protection Agency, Columbus, OH, September.
- Ohio EPA 2001. *U.S. DOE Portsmouth Quadrant I Decision Document Portsmouth Gaseous Diffusion Plant*, Ohio Environmental Protection Agency, Columbus, OH, March.
- Ohio EPA 2003. *Ohio EPA's Decision Document for the X-701B SWMU in Quadrant II of the U.S. DOE Portsmouth Facility, Piketon, Ohio*, Ohio Environmental Protection Agency, Columbus, OH, December.
- Ohio EPA 2008. *State of Ohio Cooperative Fish Tissue Monitoring Program Sport Fish Tissue Consumption Advisory Program*, February 2008, State of Ohio, Columbus, OH.
- Ohio EPA 2012. *The April 13, 2010 Director's Final Findings and Orders for Removal Action and Remedial Investigation and Feasibility Study and Remedial Design and Remedial Action, including the July 16, 2012 Modification thereto*, Ohio EPA, Columbus, OH, July 16.
- U.S. Census Bureau 2016. U.S. Census Bureau, www.census.gov, population estimates for 2014, (accessed March 2, 2016).
- U.S. EPA 1988. *Federal Guidance Report No. 11 (FGR 11) Limiting Values of Radionuclide Intake and Air Concentration and Dose Conversion Factors for Inhalation, Immersion, and Ingestion*, EPA-520/1-88-020, U.S. Environmental Protection Agency, Washington, D.C.
- U.S. EPA 1997. *Exposure Factors Handbook*, EPA/600/P-95/002Fa, U.S. Environmental Protection Agency, Washington, D.C.
- U.S. EPA 2015. Regional Screening Level (RSL) Summary Table (TR=1E-06, HQ=1) November 2015, Screening level for PCB-1254/PCB-1260 in residential soil, www.epa.gov/risk/risk-based-screening-table-generic-tables (accessed March 1, 2016).
- Westinghouse Savannah River Company 1994. *Savannah River Site Environmental Report for 1993, Summary Pamphlet*, Savannah River, GA.

APPENDIX A
RADIATION

This page intentionally left blank.

This appendix presents basic facts concerning radiation. The information is intended as a basis for understanding the dose associated with releases from PORTS, not as a comprehensive discussion of radiation and its effects on the environment and biological systems. *The McGraw-Hill Dictionary of Scientific and Technical Terms* defines radiation and radioactivity as follows:

radiation—1) The emission and propagation of waves transmitting energy through space or through some medium; for example, the emission and propagation of electromagnetic, sound, or elastic waves. 2) The energy transmitted through space or some medium; when unqualified, usually refers to electromagnetic radiation. Also known as radiant energy. 3) A stream of particles, such as electrons, neutrons, protons, alpha particles, or high-energy photons, or a mixture of these (McGraw-Hill 1989).

radioactivity—A particular type of radiation emitted by a radioactive substance, such as alpha radioactivity (McGraw-Hill 1989).

Radiation occurs naturally; it was not invented but discovered. People are constantly exposed to radiation. For example, radon in air, potassium in food and water, and uranium, thorium, and radium in the earth’s crust are all sources of radiation. The following discussion describes important aspects of radiation, including atoms and isotopes; types, sources, and pathways of radiation; radiation measurement; and dose information.

A.1 ATOMS AND ISOTOPES

All matter is made up of atoms. An atom is “a unit of measure consisting of a single nucleus surrounded by a number of electrons equal to the number of protons in the nucleus” (American Nuclear Society 1986). The number of protons in the nucleus determines an element’s atomic number, or chemical identity. With the exception of hydrogen, the nucleus of each type of atom also contains at least one neutron. Unlike protons, the number of neutrons may vary among atoms of the same element. The number of neutrons and protons determines the atomic weight. Atoms of the same element with a different number of neutrons are called isotopes. In other words, isotopes have the same chemical properties but different atomic weights. Figure A.1 depicts isotopes of the element hydrogen.

Another example is the element uranium, which has 92 protons; all isotopes of uranium, therefore, have 92 protons. However, each uranium isotope has a different number of neutrons. Uranium-238 (also denoted ²³⁸U) has 92 protons and 146 neutrons; uranium-235 has 92 protons and 143 neutrons; uranium-234 has 92 protons and 142 neutrons.




Figure A.1. Isotopes of the element hydrogen

Some isotopes are stable, or nonradioactive; some are radioactive. Radioactive isotopes are called radioisotopes, or radionuclides. In an attempt to become stable, radionuclides “throw away,” or emit, rays or particles. This emission of rays and particles is known as radioactive decay. Each radionuclide has a “radioactive half-life,” which is the average time that it takes for half of a specified number of atoms to decay. Half-lives can be very short (less than a second) or very long (millions of years), depending on the radionuclide. Appendix C presents the half-lives of radionuclides of interest at PORTS.

A.2 RADIATION

Radiation, or radiant energy, is energy in the form of waves or particles moving through space. Visible light, heat, radio waves, and alpha particles are examples of radiation. When people feel warmth from the sunlight, they are actually absorbing the radiant energy emitted by the sun.

Electromagnetic radiation is radiation in the form of electromagnetic waves; examples include gamma rays, ultraviolet light, and radio waves. Particulate radiation is radiation in the form of particles; examples include alpha and beta particles. Radiation also is characterized as ionizing or nonionizing radiation by the way in which it interacts with matter.

A.2.1 Ionizing Radiation

Normally, an atom has an equal number of protons and electrons; however, atoms can lose or gain electrons in a process known as ionization. Some forms of radiation can ionize atoms by “knocking” electrons off atoms. Examples of ionizing radiation include alpha, beta, and gamma radiation.

Ionizing radiation is capable of changing the chemical state of matter and subsequently causing biological damage and thus is potentially harmful to human health. Figure A.2 shows the penetrating potential of different types of ionizing radiation.




Figure A.2. Penetrating power of radiation.

A.2.2 Nonionizing Radiation

Nonionizing radiation bounces off or passes through matter without displacing electrons. Examples include visible light and radio waves. Currently, it is unclear whether nonionizing radiation is harmful to human health. In the discussion that follows, the term radiation is used to describe ionizing radiation.

A.3 SOURCES OF RADIATION

Radiation is everywhere. Most occurs naturally, but a small percentage is human-made. Naturally occurring radiation is known as background radiation.

A.3.1 Background Radiation

Many materials are naturally radioactive. In fact, this naturally occurring radiation is the major source of radiation in the environment. Although people have little control over the amount of background radiation to which they are exposed, this exposure must be put into perspective. Background radiation remains relatively constant over time; background radiation present in the environment today is much the same as it was hundreds of years ago.

Sources of background radiation include uranium in the earth, radon in the air, and potassium in food. Background radiation is categorized as space, terrestrial, or internal, depending on its origin.

A.3.1.1 Space radiation

Energetically charged particles from outer space continuously hit the earth's atmosphere. These particles and the secondary particles and photons they create are called space or cosmic radiation. Because the atmosphere provides some shielding against space radiation, the intensity of this radiation increases with altitude above sea level. For example, a person in Denver, Colorado, is exposed to more space radiation than a person in Death Valley, California.

A.3.1.2 Terrestrial radiation

Terrestrial radiation refers to radiation emitted from radioactive materials in the earth's rocks, soils, and minerals. Radon (Rn); radon progeny, the relatively short-lived decay products of radium-226 (^{226}Ra); potassium (^{40}K); isotopes of thorium (Th); and isotopes of uranium (U) are the elements responsible for most terrestrial radiation.

A.3.1.3 Internal radiation

Radioactive material in the environment can enter the body through the air people breathe and the food they eat; it also can enter through an open wound. Natural radionuclides that can be inhaled and ingested include isotopes of uranium, thorium, radium, radon, polonium, bismuth, and lead in the ^{238}U and ^{232}Th decay series. In addition, the body contains isotopes of potassium (^{40}K), rubidium (^{87}Rb), and carbon (^{14}C).

A.3.2 Human-made Radiation

Most people are exposed to human-made sources of radiation. Examples include consumer products, medical sources, and industrial or occupational sources. About one-half of 1% of the U.S. population performs work in which radiation in some form is present. Atmospheric testing of atomic weapons was a source of human-made radiation, but testing has been suspended in the United States and most parts of the world. Fallout from atmospheric weapons testing is not currently a significant contributor to background radiation (Health Physics Society 2010).

A.3.2.1 Consumer products and activities

Some consumer products are sources of radiation. In some consumer products, such as smoke detectors, watches, or clocks, radiation is essential to the performance of the device. In other products or activities, such as smoking tobacco products or building materials, the radiation occurs incidentally to the product function. Commercial air travel is another consumer activity that results in exposure to radiation (from space radiation).

A.3.2.2 Medical sources

Radiation is an important tool of diagnostic medicine and treatment, and, in this use, is the main source of exposure to human-made radiation. Exposure is deliberate and directly beneficial to the patients exposed. Generally, medical exposures result from beams directed to specific areas of the body. Thus, all body organs generally are not irradiated uniformly. Radiation and radioactive materials are also used in a wide variety of pharmaceuticals and in the preparation of medical instruments, including the sterilization of heat-sensitive products such as plastic heart valves. Nuclear medicine examinations and treatment involve the internal administration of radioactive compounds, or radiopharmaceuticals, by injection, inhalation, consumption, or insertion. Even then, radionuclides are not distributed uniformly throughout the body.

A.3.2.3 Industrial and occupational sources

Other sources of radiation include emissions of radioactive materials from nuclear facilities such as uranium mines, fuel processing plants, and nuclear power plants; emissions from mineral extraction facilities; and the transportation of radioactive materials. Workers in certain occupations may also be

exposed to radiation due to their jobs. These occupations include positions in medicine, aviation, research, education, and government.

A.4 PATHWAYS OF RADIATION

Radiation and radioactive materials in the environment can reach people through many routes (see Figure A.3). Potential routes for radiation are referred to as pathways. For example, radioactive material in the air could fall on a pasture. The grass could then be eaten by cows, and the radioactive material on the grass would be present in the cow's milk. People drinking the milk would thus be exposed to this radiation. Or people could simply inhale the radioactive material in the air. The same events could occur with radioactive material in water. Fish living in the water would be exposed; people eating the fish would then be exposed to the radiation in the fish. Or people swimming in the water would be exposed.




Figure A.3. Possible radiation pathways.

A.5 MEASURING RADIATION

To determine the possible effects of radiation on the environment and the health of people, the radiation must be measured. More precisely, its potential to cause damage must be determined.

A.5.1 Activity

When measuring the amount of radiation in the environment, what is actually being measured is the rate of radioactive decay, or activity. The rate of decay varies widely among the various radionuclides. For that reason, 1 gram of a radioactive substance may contain the same amount of activity as several tons of another material. This activity is expressed in a unit of measure known as a curie (Ci). More specifically, 1 Ci = 3.7E+10 (37,000,000,000) atom disintegrations per second (dps). In the international system of units, 1 dps = 1 becquerel (Bq). Table A.1 provides units of radiation measure and applicable conversions.

Table A.1. Units of radiation measures

Current System	International System	Conversion
curie (Ci)	Becquerel (Bq)	1 Ci = 3.7 x 10 ¹⁰ Bq
rad (radiation absorbed dose)	Gray (Gy)	1 rad = 0.01 Gy
rem (roentgen equivalent man)	Sievert (Sv)	1 rem = 0.01 Sv

A.5.2 Absorbed Dose

The total amount of energy absorbed per unit mass as a result of exposure to radiation is expressed in a unit of measure known as a rad. In the international system of units, 100 rad equals 1 gray (Gy). In terms of human health, however, it is the effect of the absorbed energy that is important, not the actual amount.

A.5.3 Dose

The measure of potential biological damage caused by exposure to and subsequent absorption of radiation is expressed in a unit of measure known as a rem. One rem of any type of radiation has the same total damaging effect. Because a rem represents a fairly large dose, dose is expressed as a millirem (mrem) or 1/1000 of a rem. In the international system of units, 100 rem equals 1 sievert (Sv); 100 mrem equals 1 millisievert (mSv). Specific types of dose are defined as follows:

- **equivalent dose** – The product of the absorbed dose (rad) in tissue and a radiation weighting factor. Equivalent dose is expressed in units of rem (or sievert) (1 rem = 0.01 sievert).
- **committed equivalent dose** – The calculated equivalent dose to a tissue or organ over a 50-year period after known intake of a radionuclide into the body. Contributions from external dose are not included. Committed equivalent dose is expressed in units of rem (or sievert).
- **committed effective dose** – The sum of the committed equivalent doses to various tissues in the body, each multiplied by the appropriate tissue weighting factor. Committed effective dose is expressed in units of rem (or sievert).
- **effective dose** – The sum of the doses received by all organs or tissues of the body after each one has been multiplied by the appropriate tissue weighting factor. It includes the dose from radiation sources internal and/or external to the body. Effective dose is expressed in units of rem (or sievert). In this report, the term “effective dose” is often shortened to “dose”.
- **collective dose** – The sum of the effective doses to all persons in a specified population received in a specified period of time. Collective dose is expressed in units of person-rem (or person-sievert). This dose is also called the population dose.

A.6 DOSE

Determining dose is an involved process using complex mathematical equations based on several factors, including the type of radiation, the rate of exposure, weather conditions, and typical diet. Basically, ionizing radiation is generated from radioactive decay, or activity. People absorb some of the energy to which they are exposed. This absorbed energy is calculated as part of an individual’s dose. Whether radiation is natural or human-made, its effects on people are the same.

A.6.1 Comparison of Dose Levels

Table A.2 presents a scale of dose levels. Included is an example of the type of exposure that may cause such a dose or the special significance of such a dose. This information is intended to familiarize the reader with the type of doses individuals may receive.

A.6.1.1 Dose from space radiation

The average annual dose received by residents of the United States from space radiation is about 33 mrem (0.33 mSv) (NCRP 2009). The average dose to a person living in Honolulu, Hawaii (at sea level and near the equator) is about 20 mrem (0.2 mSv), while the average dose to a person living in Colorado Springs, Colorado (high altitude and latitude) is about 70 mrem (0.7 mSv) (Health Physics Society 2010).

Table A.2. Comparison and description of various dose levels^a

Dose level	Description
0.85 mrem (0.0085 mSv)	Approximate daily dose from natural background radiation, including radon
1.92 mrem (0.0192 mSv)	Cosmic dose to a person on a one-way airplane flight from Washington D.C. to Seattle
10 mrem (0.10 mSv)	Annual exposure limit, set by U.S. EPA, for exposures from airborne emissions from operations of nuclear fuel cycle facilities, including power plants and uranium mines and mills
36 mrem (0.36 mSv)	Average annual dose to a person who smokes one pack of cigarettes per day
36 mrem (0.36 mSv)	Mammogram (two views)
46 mrem (0.46 mSv)	Estimate of the largest dose any off-site person could have received from the March 28, 1979, Three Mile Island nuclear power plant accident
60 mrem (0.60 mSv)	X-ray (single exposure) of abdomen or hip
100 mrem (1.00 mSv)	Annual limit of dose from all DOE facilities to a member of the public who is not a radiation worker
244 mrem (2.44 mSv)	Average dose from an upper gastrointestinal diagnostic X-ray series
300 mrem (3.00 mSv)	Average annual dose to a person in the United States from all sources of medical radiation
311 mrem (3.11 mSv)	Average annual dose to a person in the United States from all sources of natural background radiation
700 mrem (7.0 mSv)	Computed tomography – chest
1-5 rem (0.01-0.05 Sv)	U.S. EPA protective action guideline calling for public officials to take emergency action when the dose to a member of the public from a nuclear accident will likely reach this range
5 rem (0.05 Sv)	Annual limit for occupational exposure of radiation workers set by the Nuclear Regulatory Commission and DOE
10 rem (0.10 Sv)	The Biological Effects of Ionizing Radiation V report estimated that an acute dose at this level would result in a lifetime excess risk of death from cancer of 0.8% (Biological Effects of Ionizing Radiation 1990)
25 rem (0.25 Sv)	U.S. EPA guideline for voluntary maximum dose to emergency workers for non-lifesaving work during an emergency
75 rem (0.75 Sv)	U.S. EPA guideline for maximum dose to emergency workers volunteering for lifesaving work
50-600 rem (0.50-6.00 Sv)	Doses in this range received over a short period of time will produce radiation sickness in varying degrees. At the lower end of this range, people are expected to recover completely, given proper medical attention. At the top of this range, most people would die within 60 days

^aAdapted from Savannah River Site Environmental Report for 1993, Summary Pamphlet, WSRC-TR-94-076, Westinghouse Savannah River Company, 1994 and NCRP Report No. 160, *Ionizing Radiation Exposure of the Population of the United States* (NCRP 2009).

A.6.1.2 Dose from terrestrial radiation

The average annual dose received from terrestrial gamma radiation is about 21 mrem (0.21 mSv) in the United States (NCRP 2009). Similar to space radiation, this dose varies geographically across the country with the lowest doses on the Atlantic and Gulf coastal plains and highest doses in the mountains in the western United States.

A.6.1.3 Dose from internal radiation

Inhalation of the short-lived decay products of radon are the major contributors to the annual dose equivalent for internal radionuclides (mostly ^{222}Rn). They contribute an average dose of about 228 mrem (2.28 mSv) per year (NCRP 2009). The average dose from ingestion of radionuclides is about 29 mrem (0.29 mSv) per year, which can be attributed to the naturally occurring radioisotope of potassium, ^{40}K ; and radioisotopes of thorium (Th), uranium (U), and their decay series (NCRP 2009).

A.6.1.4 Dose from consumer products

The U.S. average annual dose received by an individual from consumer products is about 13 mrem (0.13 mSv) (NCRP 2009). Almost 90 percent of this dose results from smoking cigarettes, commercial air travel, and building materials (radionuclides present in brick, masonry, cement, concrete, and other materials).

A.6.1.5 Dose from medical sources

Medical exams and procedures account for the largest portion of the average annual dose received from human-made sources. These procedures include x-rays, computed tomography (a more sophisticated type of x-ray), and fluoroscopy, and nuclear medicine. The increase in the use of medical imaging procedures, especially computed tomography, over the last 25 years has resulted in a marked increase in the average annual dose from medical sources received by a person in the United States: 53 mrem/year in the early 1980s to 300 mrem/year in 2006 (NCRP 2009). The actual doses received by individuals who complete such medical exams can be much higher than the average value because not everyone receives such exams each year.

A.6.1.6 Doses from industrial and occupational sources

Small doses received by individuals occur as a result of emissions of radioactive materials from nuclear facilities, emissions from certain mineral extraction facilities, and transportation of radioactive materials. The combination of these sources contributes less than 1 mrem (0.01 mSv) per year to the average dose to an individual (NCRP 2009).

This page intentionally left blank.

APPENDIX B
ENVIRONMENTAL PERMITS

This page intentionally left blank.

Table B.1. DOE environmental permits and registrations at PORTS

Permit/registered source	Source no.	Issue date	Expiration date	Status
	<i>FBP– Clean Air Act Permits</i>			
Title V Permit	P0109662	4/28/2014	5/19/2019	Active
Permit to Install X-627 Groundwater Treatment Facility (06-07283)	P474, T104, T105	3/15/2005	None	Active
Permit to Install and Operate X-326 L-cage Glove Box (P0104170)	P022	11/12/2008	11/12/2018	Active
Permit to Install and Operate X-735 Landfill Cap and Venting System (northern portion) (P0104170)	P023	11/12/2008	11/12/2018	Active
Permit to Install X-670A Cooling Tower (P0106292)	P539	07/29/2010	None	Active
Permit to Install X-333 Low Assay Withdrawal Seal Exhaust System (06-07984)	P117	01/10/2006	None	Inactive
Permit to Install Biodegradation Vent #1 (06-07928)	P040	11/03/2005	None	Active
Permit to Install Biodegradation Vent #2 (06-07928)	P041	11/03/2005	None	Active
Permit to Install Biodegradation Vent #3 (06-07928)	P042	11/03/2005	None	Active
Permit to Install X-700 Radiation Calibration Lab Fume Hood (06-07928)	P045	11/03/2005	None	Active
Permit to Install X-705 Calciners (B Area) (06-07928)	P053	11/03/2005	None	Active
Permit to Install X-720 Instrument Cleaning Room Hood 4 (06-07928)	P065	11/03/2005	None	Active
Permit to Install X-720 Motor Shop Steam Cleaning Booth (06-07928)	P067	11/03/2005	None	Active
Permit to Install X-344 Pigtail Gulper (06-07760)	P430	05/17/2005	None	Active
Permit to Install X-701B In Situ Chemical Oxidation with Recirculation Treatment System (06-07666)	P475, T106	03/15/2005	None	Inactive
Permit to Install X-720 Instrument Cleaning Room Glove Box (06-07000)	P474	11/19/2002	None	Active
Permit to Install X-705 Dry Ice Blaster with HEPA Filter (06-06752)	P473	04/11/2002	None	Active
Permit to Install X-705 8 inch, 12 inch, and 2.5 Ton Uranium Cylinders, Cleaned for Reuse or Disposal (06-06703)	P470	04/11/2002	None	Active
Permit to Install X-344 Toll Transfer Facility (06-06303)	P469	12/12/2000	None	Active
Permit to Install X-343 Feed Vaporization and Sampling (06-06302)	P468	12/12/2000	None	Inactive
Permit to Install 85 Horsepower Trash Pump (06-06170)	P467	05/24/2000	None	Active
Permit to Install X-847 Glove Box (06-5682)	P466	07/21/1999	None	Active

Table B.1. DOE environmental permits and registrations at PORTS (continued)

Permit/registered source	Source no.	Issue date	Expiration date	Status
<i>FBP– Clean Air Act Permits (continued)</i>				
X-624 Groundwater Treatment Facility (now considered a <i>de minimis</i> source)	P019	10/28/1992	None	Active
Permit to Install X-623 Groundwater Treatment Facility (06-4613)	P018	01/08/1992	None	Active
Permit to Install X-749 Contaminated Materials Disposal Facility (06-2999)	P027	04/17/1991	None	Active
Permit to Install Gasoline Dispensing Facility (06-02906)	G001	10/31/1990	None	Active
<i>BWCS – Clean Air Act Permits</i>				
Permit No. P0109511 to Install and Operate Process Line 1 (DUF ₆ Conversion Facility)	P001	3/23/2012	3/23/2022	Active
Permit No. P0109511 to Install and Operate Process Line 2 (DUF ₆ Conversion Facility)	P002	3/23/2012	3/23/2022	Active
Permit No. P0109511 to Install and Operate Process Line 3 (DUF ₆ Conversion Facility)	P003	3/23/2012	3/23/2022	Active
Permit No. P0109511 to Install and Operate HVAC System (DUF ₆ Conversion Facility)	P004	3/23/2012	3/23/2022	Active
<i>FBP – Clean Water Act/Safe Drinking Water Act Permits</i>				
NPDES Permit	OIO00000*LD	7/23/2015	8/31/2020	Active
Safe Drinking Water Act – License to Operate a Public Water System	OH6632414		Renewed annually	Active
Permit to Install X-622 Groundwater Treatment Facility	06-2951	11/20/1990	None	Active
Permit to Install X-623 Groundwater Treatment Facility	06-3528	1/9/19/1996	None	Active
Permit to Install X-624 Groundwater Treatment Facility	06-3556	10/28/1992	None	Active
Permit to Install X-627 Groundwater Treatment Facility	06-07283	1/13/2004	None	Active
<i>BWCS – Clean Water Act Permit</i>				
NPDES Permit	OIS00034*BD	5/13/2014	5/31/2019	Active
<i>FBP – Hazardous Waste Permit</i>				
RCRA Part B Permit (DOE/FBP)	Ohio Permit No. 04-66-0680	3/25/2011	3/25/2021	Active
<i>FBP – Registrations</i>				
Underground Storage Tank Registration	66005107		Renewed annually	Active

APPENDIX C

RADIONUCLIDE AND CHEMICAL NOMENCLATURE

This page intentionally left blank.

Table C.1. Nomenclature for elements and chemical constituents

Constituent	Symbol
Aluminum	Al
Ammonia	NH ₃
Antimony	Sb
Arsenic	As
Barium	Ba
Beryllium	Be
Cadmium	Cd
Calcium	Ca
Chromium	Cr
Cobalt	Co
Copper	Cu
Iron	Fe
Lead	Pb
Lithium	Li
Magnesium	Mg
Manganese	Mn
Mercury	Hg
Nickel	Ni
Nitrogen	N
Nitrate ion	NO ₃ ⁻
Nitrite ion	NO ₂ ⁻
Phosphorus	P
Phosphate ion	PO ₄ ²⁻
Potassium	K
Selenium	Se
Silver	Ag
Sodium	Na
Sulfate ion	SO ₄ ⁻
Sulfur dioxide	SO ₂
Thallium	Tl
Uranium	U
Vanadium	V
Zinc	Zn

Table C.2. Nomenclature and half-life for radionuclides

Radionuclide	Symbol	Half-life (years)
Americium-241	^{241}Am	432.2
Neptunium-237	^{237}Np	2,140,000
Plutonium-238	^{238}Pu	87.75
Plutonium-239	^{239}Pu	24,100
Plutonium-240	^{240}Pu	6,569
Technetium-99	^{99}Tc	213,000
Uranium-233	^{233}U	159,200
Uranium-234	^{234}U	244,500
Uranium-235	^{235}U	703,800,000
Uranium-236	^{236}U	23,415,000
Uranium-238	^{238}U	4,468,000,000

Source: *Radioactive Decay Tables: A Handbook of Decay Data for Application to Radioactive Dosimetry and Radiological Assessments* (DOE/TIC-11026), as reported in the *Oak Ridge Reservation Annual Site Environmental Report for 2005* (DOE/ORO-2218).

RECORD COPY DISTRIBUTION

File—FBP RMDC—RC




U.S. Department of Energy Portsmouth Gaseous Diffusion Plant



At the X-611A prairie on the east side of PORTS, periodic burning supports the establishment of prairie grasses and flowers

Annual Site Environmental Data – 2015



**U.S. Department of Energy
Portsmouth Gaseous Diffusion Plant
Annual Site Environmental Data – 2015
Piketon, Ohio**



**U.S. Department of Energy
DOE/PPPO/03-0766&D1**

January 2017

**By
Fluor-BWXT Portsmouth LLC, under Contract DE-AC30-10CC40017**

FBP-ER-RCRA-WD-RPT-0237, Revision 2

This document has been approved for public release:

Samuel Eldridge (signature on file)

3/3/2017

Classification Office

Date

This page intentionally left blank.

CONTENTS

TABLES	iii
ACRONYMS AND ABBREVIATIONS	v
1. INTRODUCTION.....	1-1
2. ENVIRONMENTAL MONITORING.....	2-1
3. DOSE	3-1
4. GROUNDWATER.....	4-1
5. REFERENCES.....	5-1

This page intentionally left blank.

TABLES

2.1	Radionuclide concentrations in FBP and Centrus NPDES outfall water samples – 2015	2-2
2.2	FBP NPDES permit summary January 2015 – August 2015.....	2-5
2.3	FBP NPDES permit summary September 2015 – December 2015	2-9
2.4	BWCS NPDES permit summary – 2015	2-14
2.5	FBP NPDES discharge and compliance rates – 2015.....	2-15
2.6	BWCS NPDES discharge and compliance rates – 2015.....	2-20
2.7	Centrus NPDES discharge monitoring results – 2015	2-21
2.8	Radionuclides in surface water runoff samples from FBP and BWCS cylinder storage yards – 2015.....	2-22
2.9	Drainage basin monitoring of surface water and sediment for BWCS cylinder storage yards – 2015.....	2-24
2.10	Ambient air monitoring program summary for radionuclides and fluoride – 2015.....	2-25
2.11	External radiation monitoring program (mrem) – 2015.....	2-29
2.12	External radiation monitoring (mrem) at locations near cylinder storage yards – 2015.....	2-30
2.13	Settleable solids monitoring results – 2015	2-31
2.14	Local surface water monitoring program results – 2015	2-32
2.15	Sediment monitoring program results – 2015.....	2-36
2.16	Soil and biota (vegetation) monitoring at ambient air monitoring stations – 2015.....	2-41
2.17	Biota (fish) monitoring program results – 2015.....	2-44
2.18	Biota (crops) monitoring program results – 2015	2-45
2.19	Biota (deer) monitoring program results – 2015.....	2-47
2.20	Biota (off-site dairy) monitoring – 2015.....	2-49
3.1	Emissions (Ci/year) from DOE air emission sources – 2015	3-1
3.2	Predicted radiation doses from airborne releases at PORTS – 2015	3-2
3.3	Dose calculations for ambient air monitoring stations – 2015.....	3-2

4.1	VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015.....	4-4
4.2	Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015.....	4-14
4.3	VOCs detected at the PK Landfill – 2015.....	4-20
4.4	VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015.....	4-21
4.5	Results for radionuclides at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015 ..	4-25
4.6	VOCs detected at the X-749A Classified Materials Disposal Facility – 2015	4-26
4.7	Results for radionuclides at the X-749A Classified Materials Disposal Facility – 2015.....	4-27
4.8	VOCs detected at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015.....	4-28
4.9	Results for radionuclides at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015.	4-31
4.10	VOCs detected at the X-701B Former Holding Pond – 2015.....	4-33
4.11	Results for radionuclides at the X-701B Former Holding Pond – 2015	4-39
4.12	Results for chromium at the X-633 Former Recirculating Cooling Water Complex – 2015.....	4-46
4.13	VOCs detected at the X-616 Former Chromium Sludge Surface Impoundments – 2015	4-47
4.14	Results for chromium at the X-616 Former Chromium Sludge Surface Impoundments – 2015.....	4-48
4.15	VOCs detected at the X-740 Former Waste Oil Handling Facility – 2015.....	4-49
4.16	Results for beryllium and chromium at the X-611A Former Lime Sludge Lagoons – 2015.....	4-52
4.17	VOCs detected at the X-735 Landfills – 2015.....	4-53
4.18	Results for radionuclides at the X-735 Landfills – 2015	4-54
4.19	VOCs detected at the X-734 Landfills – 2015.....	4-56
4.20	Results for radionuclides at the X-734 Landfills – 2015	4-57
4.21	Results for cadmium and nickel at the X-533 Former Switchyard Complex – 2015	4-60
4.22	VOCs detected at the X-344C Former Hydrogen Fluoride Storage Building – 2015	4-61
4.23	VOCs detected at surface water monitoring locations – 2015.....	4-62
4.24	Results for radionuclides at surface water monitoring locations – 2015	4-64

ACRONYMS AND ABBREVIATIONS

#/100 mL	number per 100 mL
ACP	American Centrifuge Plant
BWCS	BWXT Conversion Services, LLC
°C	degrees Celsius
Ci	curie
cm	centimeter
DOE	U.S. Department of Energy
DUF ₆	depleted uranium hexafluoride
FBP	Fluor-BWXT Portsmouth LLC
°F	degrees Fahrenheit
g	gram
GPD	gallons per day
in.	inch
kg	kilogram
L	liter
m	meter
m ³	cubic meter
µg	microgram
mg	milligram
MGD	million gallons per day
mrem	millirem
ND	not detected
ng	nanogram
NPDES	National Pollutant Discharge Elimination System
Ohio EPA	Ohio Environmental Protection Agency
OVEC	Ohio Valley Electric Corporation
PCB	polychlorinated biphenyl
pCi	picocurie
PK	Peter Kiewit
PORTS	Portsmouth Gaseous Diffusion Plant
SU	standard unit
TUa	acute toxicity unit
VOC	volatile organic compound

This page intentionally left blank.

1. INTRODUCTION

Environmental monitoring at the Department of Energy (DOE) Portsmouth Gaseous Diffusion Plant (PORTS) is conducted throughout the year. Monitoring demonstrates the site is a safe place to work, plant operations do not adversely affect neighboring communities, and activities comply with federal and state regulations.

This document is a compilation of the environmental monitoring data for calendar year 2015 and is intended as a tool for analysts in environmental monitoring, environmental restoration, and other related disciplines. The data in this document form the basis for the summary information in the *Portsmouth Gaseous Diffusion Plant Annual Site Environmental Report – 2015* (DOE 2017).

Radiological monitoring data presented in this Data Report and discussed in the *Annual Site Environmental Report for 2015* indicate that the maximum dose a member of the public could receive from radionuclides released by PORTS in 2015 or detected by environmental monitoring programs in 2015 is 1.1 millirem (mrem). This dose is significantly less than the 100 mrem limit set in DOE Order 458.1, *Radiation Protection of the Public and the Environment*.

Other non-radiological chemicals such as polychlorinated biphenyls (PCBs), metals, and volatile organic compounds (VOCs) are also monitored. Discharges of metals and other chemicals to surface water are controlled by National Pollutant Discharge Elimination System (NPDES) permits. Emissions of non-radiological air pollutants are controlled by air emission permits issued by Ohio Environmental Protection Agency (Ohio EPA). The *Portsmouth Gaseous Diffusion Plant Annual Site Environmental Report – 2015* (DOE 2017) provides more information about non-radiological chemicals released from PORTS or detected by PORTS monitoring programs during 2015.

This page intentionally left blank.

2. ENVIRONMENTAL MONITORING

This section provides environmental monitoring data collected in 2015 by DOE contractors Fluor-BWXT Portsmouth LLC (FBP) and BWXT Conversion Services, LLC (BWCS). Data collected by Centrus for NPDES outfalls associated with the American Centrifuge Plant (ACP) and Lead Cascade are also reported in this section.

The following tables are provided in this section:

- Table 2.1. Radionuclide concentrations in FBP and Centrus NPDES outfall water samples – 2015
- Table 2.2. FBP NPDES permit summary January 2015 – August 2015
- Table 2.3. FBP NPDES permit summary September 2015 – December 2015
- Table 2.4. BWCS NPDES permit summary – 2015
- Table 2.5. FBP NPDES discharge and compliance rates – 2015
- Table 2.6. BWCS NPDES discharge and compliance rates – 2015
- Table 2.7. Centrus NPDES discharge monitoring results – 2015
- Table 2.8. Radionuclides in surface water runoff samples from FBP and BWCS cylinder storage yards – 2015
- Table 2.9. Drainage basin monitoring of surface water and sediment for BWCS cylinder storage yards – 2015
- Table 2.10. Ambient air monitoring program summary for radionuclides and fluoride – 2015
- Table 2.11. External radiation monitoring program (mrem) – 2015
- Table 2.12. External radiation monitoring (mrem) at locations near cylinder storage yards – 2015
- Table 2.13. Settleable solids monitoring results – 2015
- Table 2.14. Local surface water monitoring program results – 2015
- Table 2.15. Sediment monitoring program results – 2015
- Table 2.16. Soil and biota (vegetation) monitoring at ambient air monitoring stations – 2015
- Table 2.17. Biota (fish) monitoring program results – 2015
- Table 2.18. Biota (crops) monitoring program results – 2015

- Table 2.19. Biota (deer) monitoring program results – 2015
- Table 2.20. Biota (off-site dairy) monitoring program results – 2015.

**Table 2.1. Radionuclide concentrations in FBP and Centrus
 NPDES outfall water samples – 2015**

NPDES outfall ^a	Parameter ^b	Number of samples ^c	Minimum ^d	Maximum ^d	Average ^e
<i>FBP Outfalls</i>					
001	Americium-241	4(4)	< 0.0132	< 0.0265	
	Neptunium-237	4(4)	0	< 0.0226	
	Plutonium-238	4(4)	0	< 0.00585	
	Plutonium-239/240	4(4)	< 0.00585	< 0.0256	
	Technetium-99	12(0)	10.5	101	29.0
	Uranium	12(0)	0.434	11	2.56
	Uranium-233/234	12(0)	0.702	20.6	4.48
	Uranium-235/236	12(7)	< 0.0349	0.832	
002	Uranium-238	12(0)	0.136	3.57	0.829
	Americium-241	4(4)	< 0.00871	< 0.0259	
	Neptunium-237	4(4)	0	< 0.032	
	Plutonium-238	4(4)	0	< 0.0251	
	Plutonium-239/240	4(4)	< 0.01	< 0.027	
	Technetium-99	12(12)	0	< 4.56	
	Uranium	12(1)	< 0.466	1.34	0.82
	Uranium-233/234	12(0)	0.6	3.42	1.14
003	Uranium-235/236	12(11)	< 0.012	0.21	
	Uranium-238	12(1)	< 0.149	0.431	0.266
	Americium-241	4(4)	< 0.00888	< 0.0382	
	Neptunium-237	4(4)	0	< 0.0181	
	Plutonium-238	4(4)	0	< 0.0179	
	Plutonium-239/240	4(4)	< 0.0146	< 0.0387	
	Technetium-99	12(0)	25.9	112	60.6
	Uranium	12(0)	0.747	3.74	2.12
004	Uranium-233/234	12(0)	0.676	6.84	2.96
	Uranium-235/236	12(6)	< 0.0338	0.244	
	Uranium-238	12(0)	0.243	1.22	0.691
	Americium-241	4(4)	< 0.00938	< 0.0324	
	Neptunium-237	4(4)	< 0.00492	< 0.0181	
	Plutonium-238	4(4)	0	< 0.0173	
	Plutonium-239/240	4(4)	< 0.00577	< 0.0283	
	Technetium-99	12(12)	0	3.44	
	Uranium	12(9)	< 0.123	2.92	
	Uranium-233/234	12(4)	< 0.04	1.72	
	Uranium-235/236	12(12)	0	< 0.0871	
	Uranium-238	12(9)	< 0.0413	0.967	

**Table 2.1. Radionuclide concentrations in FBP and Centrus
 NPDES outfall water samples – 2015 (continued)**

NPDES outfall ^a	Parameter ^b	Number of samples ^c	Minimum ^d	Maximum ^d	Average ^e
<i>FBP Outfalls</i>					
005	Americium-241	3(3)	< 0.0157	< 0.0265	
	Neptunium-237	3(3)	0	< 0.00867	
	Plutonium-238	3(3)	0	< 0.0121	
	Plutonium-239/240	3(3)	< 0.00606	< 0.0253	
	Technetium-99	3(3)	< 0.0918	< 2.43	
	Uranium	3(3)	< 0.0624	< 0.225	
	Uranium-233/234	3(3)	< 0.02	< 0.0845	
	Uranium-235/236	3(3)	0	< 0.0122	
009	Uranium-238	3(3)	< 0.02	< 0.0736	
	Americium-241	4(4)	0	< 0.0512	
	Neptunium-237	4(4)	0	< 0.0047	
	Plutonium-238	4(4)	0	< 0.028	
	Plutonium-239/240	4(4)	< 0.00504	< 0.0334	
	Technetium-99	12(12)	0	< 3.49	
	Uranium	12(0)	4.09	7.43	5.43
	Uranium-233/234	12(1)	1.53	3.09	2.22
010	Uranium-235/236	12(7)	< 0.0726	0.206	
	Uranium-238	12(0)	1.36	2.47	1.81
	Americium-241	4(4)	< 0.00475	< 0.0359	
	Neptunium-237	4(4)	0	< 0.0359	
	Plutonium-238	4(4)	0	< 0.0206	
	Plutonium-239/240	4(4)	0	< 0.0158	
	Technetium-99	12(12)	0	< 6.73	
	Uranium	12(0)	1.55	5.4	2.83
011	Uranium-233/234	12(0)	0.746	3.54	1.59
	Uranium-235/236	12(10)	< 0.0512	0.174	
	Uranium-238	12(0)	0.513	1.79	0.937
	Americium-241	4(4)	0	< 0.0414	
	Neptunium-237	4(4)	0	< 0.0139	
	Plutonium-238	4(4)	0	< 0.00975	
	Plutonium-239/240	4(4)	< 0.0105	< 0.0244	
	Technetium-99	12(12)	0	< 2.6	
015	Uranium	12(0)	0.979	2.43	1.68
	Uranium-233/234	12(0)	0.44	1.13	0.801
	Uranium-235/236	12(12)	0	< 0.0784	
	Uranium-238	12(0)	0.323	0.81	0.557
	Americium-241	4(4)	< 0.0135	< 0.0397	
	Neptunium-237	4(4)	0	< 0.0147	
	Plutonium-238	4(4)	0	< 0.00593	
	Plutonium-239/240	4(4)	< 0.0106	< 0.0327	
015	Technetium-99	12(4)	< 0.444	610	
	Uranium	12(0)	0.614	1.81	1.06
	Uranium-233/234	12(0)	0.565	1.69	0.977
	Uranium-235/236	12(12)	< 0.012	< 0.0829	
	Uranium-238	12(0)	0.204	0.595	0.349

**Table 2.1. Radionuclide concentrations in FBP and Centrus
 NPDES outfall water samples – 2015 (continued)**

NPDES outfall ^a	Parameter ^b	Number of samples ^c	Minimum ^d	Maximum ^d	Average ^e	
<i>FBP Outfalls</i>						
608	Americium-241	4(4)	0	< 0.0235		
	Neptunium-237	4(4)	0	< 0.0189		
	Plutonium-238	4(4)	0	< 0.00538		
	Plutonium-239/240	4(4)	< 0.0215	< 0.0326		
	Techneium-99	12(0)	104	446	229	
	Uranium	12(0)	0.487	2.15	0.840	
	Uranium-233/234	12(0)	0.18	1.09	0.405	
	Uranium-235/236	12(12)	< 0.00559	< 0.0708		
610	Uranium-238	12(0)	0.16	0.712	0.277	
	Americium-241	4(4)	< 0.0139	< 0.0443		
	Neptunium-237	4(4)	0	< 0.00469		
	Plutonium-238	4(4)	0	< 0.0136		
	Plutonium-239/240	4(4)	< 0.00902	< 0.0233		
	Techneium-99	5(0)	47.2	441	130	
	Uranium	5(0)	0.26	15.5	4.15	
	Uranium-233/234	5(0)	0.331	19.5	5.36	
611	Uranium-235/236	5(3)	< 0.00597	1.28		
	Uranium-238	5(1)	< 0.0864	5.03		
	Americium-241	4(4)	0	< 0.0281		
	Neptunium-237	4(4)	< 0.0196	< 0.0299		
	Plutonium-238	4(4)	0	0		
	Plutonium-239/240	4(4)	< 0.0106	< 0.0273		
	Techneium-99	12(0)	419	728	628	
	Uranium	12(0)	4.68	14.6	6.33	
012	Uranium-233/234	12(0)	4.5	25.3	9.27	
	Uranium-235/236	12(0)	0.199	1.36	0.475	
	Uranium-238	12(0)	1.53	4.69	2.05	
	<i>Centrus Outfalls</i>					
	012	Americium-241	4(4)	< 0.043	< 0.079	
		Neptunium-237	4(4)	< 0.073	< 0.106	
		Plutonium-238	4(4)	< 0.031	< 0.181	
		Plutonium-239/240	4(4)	< 0.079	< 0.134	
Techneium-99		52(52)	< 6.37	< 8.04		
013	Uranium	52(0)	0.50	9.86	1.43	
	Americium-241	4(4)	< 0.042	< 0.069		
	Neptunium-237	4(4)	< 0.059	< 0.116		
	Plutonium-238	4(4)	< 0.042	< 0.153		
	Plutonium-239/240	4(4)	< 0.026	< 0.153		
013	Techneium-99	52(52)	< 6.45	< 7.87		
	Uranium	52(0)	0.34	2.2	0.98	

^aFBP internal NPDES Outfalls 608, 610, and 611 discharge to NPDES Outfall 003 (X-6619 Sewage Treatment Plant).

^bUranium is reported in µg/L; all other radionuclides are reported in pCi/L.

^cNumber in parentheses is the number of samples that were below the detection limit.

^dMinimum or maximum values reported as "0" may actually be negative results. Because of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out. These negative value results are reported as "0" in the table for simplicity.

^eAverages were not calculated for outfalls that had greater than 15% of the results below the detection limit. For outfalls with less than 15% of the results below the detection limit, any result below the detection limit was assigned a value at the detection limit to calculate the average for the parameter.

Table 2.2. FBP NPDES permit summary January 2015 – August 2015

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 001 (X-230J7 East Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/month	24-hr composite		
Chlorine, total residual	mg/L	1/week	Grab		
Dissolved solids	mg/L	1/week	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/month	24-hr composite		
Oil & grease	mg/L	1/week	Grab	10	15
pH	SU	1/week	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Silver, total recoverable	µg/L	1/month	24-hr composite		
Total suspended solids ^b	mg/L	1/week	24-hr composite	20	45
Zinc, total recoverable	µg/L	1/month	24-hr composite		
<i>FBP Outfall 002 (X-230K South Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/month	24-hr composite		
Mercury, total	ng/L	1/month	Grab	12 (0.000074)	1700 (0.0105)
pH	SU	1/week	Grab		6.5–9.0
Oil & grease	mg/L	1/week	Grab		10
Silver, total recoverable	µg/L	1/week	24-hr composite	1.3 (0.0080)	11 (0.068)
Thallium, total recoverable	µg/L	1/week	24-hr composite	6.3 (0.039)	79 (0.49)
Total suspended solids ^b	mg/L	1/week	24-hr composite	20	45
<i>FBP Outfall 003 (X-6619 Sewage Treatment Plant)</i>					
Acute toxicity, <i>Ceriodaphnia dubia</i>	TUa	1/2 months	24-hr composite		
Acute toxicity, <i>Pimephales promelas</i>	TUa	1/2 months	24-hr composite		
Carbonaceous biochemical oxygen demand, 5-day	mg/L	1/week	24-hr composite	10 (15.1)	15 (22.7)
Chlorine, total residual ^c	mg/L	Daily	Grab		0.038
Copper, total recoverable	µg/L	1/month	24-hr composite		
Fecal coliform ^c	#/100 mL	1/week	Grab	1000	2000
Flow rate	MGD	Daily	24-hr total		
Mercury, total	ng/L	1/month	Grab		
Nitrogen, ammonia (NH ₃)	mg/L	1/2 weeks	24-hr composite		
Nitrite plus nitrate	mg/L	1/month	24-hr composite		
Oil & grease	mg/L	1/quarter	Grab		
pH	SU	3/week	Grab		6.5–9.0
Silver, total recoverable	µg/L	1/month	24-hr composite		
Total suspended solids	mg/L	1/week	24-hr composite	12 (18.2)	18 (27.3)
Zinc, total recoverable	µg/L	1/month	24-hr composite		

Table 2.2. FBP NPDES permit summary January 2015 – August 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 004 (Cooling Tower Blowdown)</i>					
Acute toxicity, <i>Ceriodaphnia dubia</i>	TUa	1/2 months	24-hr composite		1.00
Acute toxicity, <i>Pimephales promelas</i>	TUa	1/2 months	24-hr composite		1.00
Chlorine, total residual	mg/L	1/week	Grab		0.038
Copper, total recoverable	µg/L	1/month	24-hr composite		
Dissolved solids	mg/L	1/week	24-hr composite	3500 (14,784)	4000 (16,896)
Flow rate	MGD	Daily	24-hr total		
Mercury, total	ng/L	1/month	Grab		
Oil & grease	mg/L	1/month	Grab	15	20
pH	SU	1/2 weeks	Grab		6.5–9.0
Total suspended solids	mg/L	1/month	24-hr composite	18 (76)	27 (114)
Zinc, total recoverable	µg/L	1/month	24-hr composite		
<i>FBP Outfall 005 (X-611B Lime Sludge Lagoons)</i>					
Flow rate	MGD	3/week	24-hr total (estimate)		
pH	SU	1/week	Grab		6.5–10.0
Total suspended solids ^b	mg/L	1/week	Grab	10	15
<i>FBP Outfall 009 (X-230L North Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/month	Grab		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/month	Grab		
Oil & grease	mg/L	1/month	Grab	10	15
pH	SU	1/week	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Total suspended solids ^b	mg/L	1/week	Grab	30	45
Zinc, total recoverable	µg/L	1/month	Grab		
<i>FBP Outfall 010 (X-230J5 Northwest Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Mercury, total	ng/L	1/month	Grab		
Oil & grease	mg/L	1/month	Grab	10	15
pH	SU	1/2 weeks	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Total suspended solids ^b	mg/L	1/2 weeks	24-hr composite	30	45
Zinc, total recoverable	µg/L	1/month	24-hr composite		

Table 2.2. FBP NPDES permit summary January 2015 – August 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 011 (X-230J6 Northeast Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/month	Grab		
Chlorine, total residual	mg/L	1/2 weeks	Grab		
Copper, total recoverable	µg/L	1/month	Grab		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/month	Grab		
Oil & grease	mg/L	1/2 weeks	Grab	10	15
pH	SU	1/2 weeks	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Total suspended solids ^b	mg/L	1/2 weeks	Grab	30	45
Zinc, total recoverable	µg/L	1/month	Grab		
<i>FBP Outfall 015 (X-624 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
PCBs	µg/L	1/quarter	Grab		<i>d</i>
pH	SU	1/2 weeks	Grab		6.5–9.0
Trichloroethene	µg/L	1/2 weeks	Grab	10	10
<i>FBP Outfall 602 (X-621 Coal Pile Runoff Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total (estimate)		
Iron, total ^b	µg/L	1/2 weeks	Grab	3500	7000
Manganese, total ^b	µg/L	1/2 weeks	Grab	2000	4000
pH	SU	1/2 weeks	Grab		6.0–10.0
Precipitation, total	in.	Daily	24-hr total		
Total suspended solids ^b	mg/L	1/2 weeks	Grab	35	50
<i>FBP Outfall 604 (X-700 Bionitrification Facility)</i>					
Copper, total	µg/L	1/month	24-hr composite		
Iron, total	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Nickel, total	µg/L	1/month	24-hr composite		
Nitrogen, nitrate	mg/L	1/month	24-hr composite		
pH	SU	1/month	Grab		6.5–9.0
Zinc, total	µg/L	1/month	24-hr composite		
<i>FBP Outfall 605 (X-705 Microfiltration Treatment System)</i>					
Chromium, hexavalent	µg/L	1/month	Grab		
Chromium, total	µg/L	1/month	24-hr composite		
Copper, total	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Iron, total	µg/L	1/month	24-hr composite		

Table 2.2. FBP NPDES permit summary January 2015 – August 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 605 (X-705 Microfiltration Treatment System)</i>					
Nickel, total	µg/L	1/month	24-hr composite		
Nitrogen, ammonia (NH ₃)	mg/L	1/month	24-hr composite		
Nitrogen, nitrate	mg/L	1/month	24-hr composite		
Nitrogen, nitrite	mg/L	1/month	24-hr composite		
Nitrogen, Kjeldahl	mg/L	1/month	24-hr composite		
Oil & grease	mg/L	1/month	Grab		
pH	SU	1/month	Grab		6.5–10.0
Sulfate (SO ₄)	mg/L	1/month	24-hr composite		
Total suspended solids	mg/L	1/month	24-hr composite	20	30
Trichloroethene	µg/L	1/month	Grab		
Zinc, total	µg/L	1/month	24-hr composite		
<i>FBP Outfall 608 (X-622 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
<i>trans</i> -1,2-dichloroethene	µg/L	1/2 weeks	Grab	25	66
Trichloroethene	µg/L	1/2 weeks	Grab		10
<i>FBP Outfall 610 (X-623 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
<i>trans</i> -1,2-dichloroethene	µg/L	1/2 weeks	Grab	25	66
Trichloroethene	µg/L	1/2 weeks	Grab	10	10
<i>FBP Outfall 611 (X-627 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
Trichloroethene	µg/L	1/2 weeks	Grab	10	10
<i>FBP Monitoring Station 902 (Downstream Far Field Monitoring)</i>					
Water temperature	°C	2/week	24-hr maximum	<i>e</i>	<i>e</i>
<i>FBP Monitoring Station 903 (Downstream Far Field Monitoring)</i>					
Water temperature	°C	2/week	24-hr maximum	<i>e</i>	<i>e</i>
<i>FBP Monitoring Station 801 (Upstream Monitoring)</i>					
48-hr acute toxicity, <i>Ceriodaphnia dubia</i>	% affected	1/2 months	Grab		
96-hr acute toxicity, <i>Pimephales promelas</i>	% affected	1/2 months	Grab		

^aIf provided in the permit, the loading limit, in kg/day or kg/month, is provided in parentheses.

^bLimitations do not apply if flow increases as a result of a precipitation or snow melt event and conditions specified in the permit are met.

^cSummer only (May through October).

^dNo detectable PCBs.

^eMaximum daily and monthly average limits vary according to month.

Table 2.3. FBP NPDES permit summary September 2015 – December 2015

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 001 (X-230J7 East Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/quarter	24-hr composite		
Chlorine, total residual	mg/L	1/week	Grab		
Copper, total recoverable	µg/L	1/quarter	24-hr composite		
Dissolved solids	mg/L	1/week	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/quarter	24-hr composite		
Mercury, total (low level)	ng/L	1/month	Grab	12	
Oil & grease	mg/L	1/week	Grab	10	15
pH	SU	1/week	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Silver, total recoverable	µg/L	1/month	24-hr composite		
Total suspended solids ^b	mg/L	1/week	24-hr composite	20	45
Zinc, total recoverable	µg/L	1/quarter	24-hr composite		
<i>FBP Outfall 002 (X-230K South Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/quarter	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/quarter	24-hr composite		
Mercury, total (low level)	ng/L	1/quarter	Grab		
pH	SU	1/week	Grab		6.5–9.0
Nitrogen, ammonia (NH ₃)	mg/L	1/month	24-hr composite		
Oil & grease	mg/L	1/week	Grab		10
Selenium, total recoverable	µg/L	1/month	24-hr composite		
Silver, total recoverable	µg/L	1/quarter	24-hr composite		
Thallium, total recoverable	µg/L	1/quarter	24-hr composite		
Total suspended solids ^b	mg/L	1/week	24-hr composite	20	45
<i>FBP Outfall 003 (X-6619 Sewage Treatment Plant)</i>					
Acute toxicity, <i>Ceriodaphnia dubia</i>	TUa	1/quarter	24-hr composite		
Acute toxicity, <i>Pimephales promelas</i>	TUa	1/quarter	24-hr composite		
Carbonaceous biochemical oxygen demand, 5-day	mg/L	1/week	24-hr composite	10 (15.1)	15 (22.7)
Chlorine, total residual ^c	mg/L	Daily	Grab		0.038
Copper, total recoverable	µg/L	1/quarter	24-hr composite		
E. coli ^c	#/100 mL	1/week	Grab		
Fecal coliform ^c	#/100 mL	1/week	Grab	1000	2000
Flow rate	MGD	Daily	24-hr total		
Mercury, total	ng/L	1/month	Grab	66 (0.000098)	1700 (0.0025)

Table 2.3. FBP NPDES permit summary September 2015 – December 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 003 (X-6619 Sewage Treatment Plant)</i>					
Nitrogen, ammonia (NH ₃)	mg/L	1/2 weeks	24-hr composite		
Nitrite plus nitrate	mg/L	1/quarter	24-hr composite		
Oil & grease	mg/L	1/quarter	Grab		
pH	SU	3/week	Grab		6.5–9.0
Silver, total recoverable	µg/L	1/quarter	24-hr composite		
Thallium, total recoverable	µg/L	1/quarter	24-hr composite		
Total suspended solids	mg/L	1/week	24-hr composite	12 (18.2)	18 (27.3)
Zinc, total recoverable	µg/L	1/quarter	24-hr composite		
<i>FBP Outfall 004 (Cooling Tower Blowdown)</i>					
Acute toxicity, <i>Ceriodaphnia dubia</i>	TUa	1/quarter	24-hr composite		
Acute toxicity, <i>Pimephales promelas</i>	TUa	1/quarter	24-hr composite		
Chlorine, total residual	mg/L	1/week	Grab		0.038
Copper, total recoverable	µg/L	1/month	24-hr composite		
Dissolved solids	mg/L	1/week	24-hr composite	3500 (8480)	4000 (9690)
Flow rate	MGD	Daily	24-hr total		
Mercury, total	ng/L	1/quarter	Grab		
Oil & grease	mg/L	1/month	Grab	15	20
pH	SU	1/month	Grab		6.5–9.0
Total suspended solids	mg/L	1/month	24-hr composite	15 (43)	27 (65)
Zinc, total recoverable	µg/L	1/quarter	24-hr composite		
<i>FBP Outfall 005 (X-611B Lime Sludge Lagoons)</i>					
Flow rate	MGD	3/week	24-hr total (estimate)		
Lead, total recoverable	µg/L	1/month	Grab		
Mercury, total	ng/L	1/month	Grab		
pH	SU	1/week	Grab		6.5–10.0
Selenium, total recoverable	µg/L	1/month	Grab		5
Total suspended solids ^b	mg/L	1/week	Grab	10	15
<i>FBP Outfall 009 (X-230L North Holding Pond)</i>					
Bis(2-ethylhexyl)phthalate	µg/L	1/month	Composite	8.4	1105
Copper, total recoverable	µg/L	1/month	Grab		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/quarter	Grab		
Mercury, total	ng/L	1/quarter	Grab		
Oil & grease	mg/L	1/month	Grab	10	15
pH	SU	1/week	Grab		6.5–9.0

Table 2.3. FBP NPDES permit summary September 2015 – December 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 009 (X-230L North Holding Pond)</i>					
Silver, total recoverable	µg/L	1/month	Grab	1.3	2.7
Total suspended solids ^b	mg/L	1/week	Grab	30	45
Zinc, total recoverable	µg/L	1/quarter	Grab		
<i>FBP Outfall 010 (X-230J5 Northwest Holding Pond)</i>					
Flow rate	MGD	Daily	24-hr total		
Lead, total recoverable	µg/L	1/month	24-hr composite		
Mercury, total	ng/L	1/quarter	Composite		
Oil & grease	mg/L	1/month	Grab	10	15
pH	SU	1/2 weeks	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Selenium, total recoverable	µg/L	1/month	24-hr composite		5.6
Total suspended solids ^b	mg/L	1/2 weeks	24-hr composite	30	45
Zinc, total recoverable	µg/L	1/month	24-hr composite		
<i>FBP Outfall 011 (X-230J6 Northeast Holding Pond)</i>					
Cadmium, total recoverable	µg/L	1/quarter	Grab		
Chlorine, total residual	mg/L	1/2 weeks	Grab		
Copper, total recoverable	µg/L	1/month	Grab		
Flow rate	MGD	Daily	24-hr total		
Fluoride, total	mg/L	1/quarter	Grab		
Oil & grease	mg/L	1/2 weeks	Grab	10	15
pH	SU	1/2 weeks	Grab		6.5–9.0
Precipitation, total	in.	Daily	24-hr total		
Selenium, total recoverable	µg/L	1/month	Grab		
Thallium, total recoverable	µg/L	1/quarter	Grab		
Total suspended solids ^b	mg/L	1/2 weeks	Grab	30	45
Zinc, total recoverable	µg/L	1/month	Grab		
<i>FBP Outfall 015 (X-624 Groundwater Treatment Facility)</i>					
Arsenic, total recoverable	µg/L	1/quarter	Grab		
Barium, total recoverable	µg/L	1/quarter	Grab		
Flow rate	MGD	Daily	24-hr total		
PCBs	µg/L	1/quarter	Grab		<i>d</i>
pH	SU	1/2 weeks	Grab		6.5–9.0
Silver, total recoverable	µg/L	1/month	Grab	1.3	6.8
Trichloroethene	µg/L	1/2 weeks	Grab	10	10

Table 2.3. FBP NPDES permit summary September 2015 – December 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 602 (X-621 Coal Pile Runoff Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total (estimate)		
Iron, total ^b	µg/L	1/2 weeks	Grab	3500	7000
Manganese, total ^b	µg/L	1/2 weeks	Grab	2000	4000
pH	SU	1/2 weeks	Grab		6.0–10.0
Precipitation, total	in.	Daily	24-hr total		
Total suspended solids ^b	mg/L	1/2 weeks	Grab	35	50
<i>FBP Outfall 604 (X-700 Bionitrification Facility)</i>					
Copper, total	µg/L	1/month	24-hr composite		
Iron, total	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Nickel, total	µg/L	1/month	24-hr composite		
Nitrogen, nitrate	mg/L	1/month	24-hr composite		
pH	SU	1/month	Grab		6.5–9.0
Zinc, total	µg/L	1/month	24-hr composite		
<i>FBP Outfall 605 (X-705 Microfiltration Treatment System)</i>					
Chromium, hexavalent	µg/L	1/month	Grab		
Chromium, total	µg/L	1/month	24-hr composite		
Copper, total	µg/L	1/month	24-hr composite		
Flow rate	MGD	Daily	24-hr total		
Nickel, total	µg/L	1/month	24-hr composite		
Nitrogen, ammonia (NH ₃)	mg/L	1/month	24-hr composite		
Nitrogen, nitrate	mg/L	1/month	24-hr composite		
Nitrogen, nitrite	mg/L	1/month	24-hr composite		
Nitrogen, Kjeldahl	mg/L	1/month	24-hr composite		
Oil & grease	mg/L	1/month	Grab		
pH	SU	1/month	Grab		6.5–10.0
Sulfate (SO ₄)	mg/L	1/month	24-hr composite		
Total suspended solids	mg/L	1/month	24-hr composite	20	30
Trichloroethene	µg/L	1/month	Grab		
Zinc, total	µg/L	1/month	24-hr composite		
<i>FBP Outfall 608 (X-622 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
<i>trans</i> -1,2-dichloroethene	µg/L	1/2 weeks	Grab	25	66
Trichloroethene	µg/L	1/2 weeks	Grab	10	10

Table 2.3. FBP NPDES permit summary September 2015 – December 2015 (continued)

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration/Loading ^a	
				Monthly	Daily
<i>FBP Outfall 610 (X-623 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
<i>trans</i> -1,2-dichloroethene	µg/L	1/2 weeks	Grab	25	66
Trichloroethene	µg/L	1/2 weeks	Grab	10	10
<i>FBP Outfall 611 (X-627 Groundwater Treatment Facility)</i>					
Flow rate	MGD	Daily	24-hr total		
pH	SU	1/2 weeks	Grab		
Trichloroethene	µg/L	1/2 weeks	Grab	10	10
<i>FBP Monitoring Station 801 (Upstream Monitoring)</i>					
48-hr acute toxicity, <i>Ceriodaphnia dubia</i>	% affected	1/quarter	Grab		
96-hr acute toxicity, <i>Pimephales promelas</i>	% affected	1/quarter	Grab		
<i>FBP Monitoring Station 902 (Downstream Far Field Monitoring)</i>					
Water temperature	°C	2/week	24-hr maximum	27.8 ^c	29.4 ^c
<i>FBP Monitoring Station 903 (Downstream Far Field Monitoring)</i>					
Water temperature	°C	2/week	24-hr maximum	27.8 ^c	29.4 ^c

^aIf provided in the permit, the loading limit, in kg/day or kg/month, is provided in parentheses.

^bLimitations do not apply if flow increases as a result of a precipitation or snow melt event and conditions specified in the permit are met.

^cSummer only (May through October).

^dNo detectable PCBs.

Table 2.4. BWCS NPDES permit summary – 2015

Effluent characteristics		Monitoring requirements		Discharge limitations	
Parameter	Units	Measurement frequency	Sampling type	Concentration	
				Monthly	Daily
<i>BWCS Outfall 001^a</i>					
Biochemical oxygen demand, 5-day	mg/L	1/week	24-hr composite		
Chlorine, total residual	mg/L	Daily	Grab		0.05
Dissolved solids, sum of	mg/L	1/week	24-hr composite		1500
Flow rate	GPD	Daily	24-hr total		
Nitrogen, ammonia	mg/L	1/week	24-hr composite		
Oil and grease, total	mg/L	1/month	Grab		
pH	SU	Daily	Grab		6.5–9.0
Phosphorus, total	mg/L	1/week	24-hr composite		
Total suspended solids ^b	mg/L	1/week	24-hr composite	30	45
Water temperature	°F	Daily	Maximum	<i>c</i>	<i>c</i>
<i>BWCS Outfall 602</i>					
Flow rate	GPD	Daily	24-hr total		
pH	SU	Daily	Grab		

^aThese monitoring requirements and limits apply only when process water is being discharged through the outfall.

^bLimitations do not apply if flow increases as a result of a precipitation or snow melt event and conditions specified in the permit are met.

^cMaximum daily and monthly average limits vary according to month.

Table 2.5. FBP NPDES discharge and compliance rates – 2015

Parameter	NPDES compliance rate (%) ^a	Number of measurements ^b	Concentration (and loading if applicable)			Units
			Minimum	Maximum	Average ^c	
<i>Outfall 001 (X-230J7 East Holding Pond)</i>						
Cadmium, total recoverable	-	9(5)	0.0335	0.18		µg/L
Chlorine, total residual	-	49(6)	< 0.02	0.06	0.03	mg/L
Copper, total recoverable		1(0)	3			µg/L
Dissolved solids	-	48(0)	160	2000	291	mg/L
Flow rate	-	365	0.013	2.656	0.598	MGD
Fluoride, total	-	9(0)	0.0765	1.45	0.28	mg/L
Mercury, total (low level)		4(0)	6.94	11.7	9.67	ng/L
Oil & grease	100	48(39)	0.85	3.7		mg/L
monthly average ^d	100	12	0	1.7		mg/L
pH	100	49	7.20	8.90	7.98	SU
Precipitation, total	-	365	0	2.39	0.13	in.
Silver, total recoverable	-	12(8)	0.0155	0.0415		µg/L
Total suspended solids	100	48(9)	0.6	20		mg/L
monthly average ^d	100	12	0.4	10		mg/L
Zinc, total recoverable	-	9(0)	7.6	64.5	27	µg/L
<i>Outfall 002 (X-230K South Holding Pond)</i>						
Cadmium, total recoverable	-	9(9)	< 0.04	< 0.04		µg/L
Flow rate	-	365	0.008	1.802	0.495	MGD
Fluoride, total	-	9(0)	0.089	0.17	0.14	mg/L
Mercury, total (low level)	100	9(0)	1.02	7.49	3.44	ng/L
monthly average ^d	100	8	1.02	7.49	3.44	ng/L
Mercury, total (loading)	100	8	1.09E-06	3.83E-05	1.15E-05	kg/day
monthly average ^d	100	8	9.61E-07	2.69E-05	9.43E-06	kg/day
Nitrogen, ammonia (NH ₃)		4(3)	< 0.022	0.025		mg/L
Oil & grease	100	48(40)	1.05	2.4		mg/L
monthly average ^d	-	12	0	1.35		mg/L
pH	100	48	7.11	8.76	7.92	SU
Selenium, total recoverable		4(3)	< 1	2.1		µg/L
Silver, total recoverable	100	33(21)	0.016	0.052		µg/L
monthly average ^d	100	8	0	0.031		µg/L
Silver, total recoverable (loading)	100	33	0	0.00016		kg/day
monthly average ^d	100	8	0	0.000088		kg/day
Thallium, total recoverable	100	33(19)	0.0395	0.19		µg/L
monthly average ^d	100	8	0	0.085		µg/L
Thallium, total recoverable (loading)	100	33	0	0.000529		kg/day
monthly average ^d	100	8	0	0.000297		kg/day
Total suspended solids	100	48(0)	1.2	15	5.5	mg/L
monthly average ^d	100	12	2.4	11	5.5	mg/L
<i>Outfall 003 (X-6619 Sewage Treatment Plant)</i>						
Acute toxicity, <i>Ceriodaphnia dubia</i>	-	5(5)	< 1.00	< 1.00		TUa
Acute toxicity, <i>Pimephales promelas</i>	-	5(5)	< 1.00	< 1.00		TUa

Table 2.5. FBP NPDES discharge and compliance rates – 2015 (continued)

Parameter	NPDES compliance rate (%) ^a	Number of measurements ^b	Concentration (and loading if applicable)			Units
			Minimum	Maximum	Average ^c	
<i>Outfall 003 (X-6619 Sewage Treatment Plant)</i>						
Carbonaceous biochemical oxygen demand, 5-day monthly average ^d	100	48(39)	2.55	8.7		mg/L
	100	12	0	5.3		mg/L
Carbonaceous biochemical oxygen demand, 5-day (loading) monthly average ^d	100	48	0	10.1		kg/day
	100	12	0	5.9		kg/day
Chlorine, total residual ^b	99	99(16)	< 0.02	0.06		mg/L
Copper, total recoverable	-	9(0)	1.3	2.8	2.0	µg/L
E. coli ^b	-	8(0)	4	194	65	#/100 mL
Fecal coliform ^b	100	24(0)	2	590	56	#/100 mL
monthly average ^d	100	6	13	194	56	#/100 mL
Flow rate	-	365	0.126	0.631	0.273	MGD
Mercury, total (low level)	-	13(0)	4.94	230	41.6	ng/L
Nitrogen, ammonia (NH ₃)	-	24(9)	0.019	5.9		mg/L
Nitrite plus nitrate	-	9(0)	4.4	9.4	7.1	mg/L
Oil & grease	-	4(3)	< 1.7	2.5		mg/L
pH	100	196	6.62	8.18	7.42	SU
Silver, total recoverable	-	9(6)	< 0.02	0.040		µg/L
Thallium, total recoverable	-	1(0)	0.072			µg/L
Total suspended solids monthly average ^d	100	48(7)	< 1.1	7.4	2.4	mg/L
	100	12	1.5	3.3	2.2	mg/L
Total suspended solids (loading) monthly average ^d	100	48	0	8.1	2.6	kg/day
	100	12	1.3	3.4	2.3	kg/day
Zinc, total recoverable	-	9(0)	7.6	27	18	µg/L
<i>Outfall 004 (Cooling Tower Blowdown)</i>						
Acute toxicity, <i>Ceriodaphnia dubia</i>	83	6(5)	< 1.00	1.41		TUa
Acute toxicity, <i>Pimephales promelas</i>	83	6(5)	< 1.00	1.41		TUa
Chlorine, total residual	92	48(25)	< 0.02	0.3		mg/L
Copper, total recoverable	-	12(0)	3.3	31	16	µg/L
Dissolved solids monthly average ^d	100	12(0)	170	380	240	mg/L
	100	12	170	380	240	mg/L
Dissolved solids (loading) monthly average ^d	100	12	74	300	190	kg/day
	100	12	72	305	199	kg/day
Flow rate	-	365	0.072	0.435	0.249	MGD
Mercury, total (low level)	-	9(0)	0.498	2.37	1.30	ng/L
Oil & grease monthly average ^d	100	12(11)	< 1.7	2.4		mg/L
	100	12	0	2.4		mg/L
pH	100	13	7.10	8.28	7.63	SU
Total suspended solids monthly average ^d	100	12(4)	0.8	2.4		mg/L
	100	12	0	2.4		mg/L
Total suspended solids (loading) monthly average ^d	100	12	0	3		kg/day
	100	12	0	2.7		kg/day
Zinc, total recoverable	-	9(0)	7.3	39	22	µg/L

Table 2.5. FBP NPDES discharge and compliance rates – 2015 (continued)

Parameter	NPDES compliance rate (%) ^a	Number of measurements ^b	Concentration (and loading if applicable)			Units
			Minimum	Maximum	Average ^c	
<i>Outfall 005 (X-611B Lime Sludge Lagoons)</i>						
Flow rate	-	28	0.001	9.963	1.535	MGD
Lead, total recoverable		1(0)	0.89			µg/L
Mercury, total (low level)		1(0)	3.28			ng/L
pH	100	7	7.09	8.72	7.90	SU
Selenium, total recoverable		1(1)	< 1			µg/L
Total suspended solids	100	4(0)	1.6	9.6	5.5	mg/L
monthly average ^d	100	2	5.4	5.6	5.5	mg/L
<i>Outfall 009 (X-230L North Holding Pond)</i>						
Bis(2-ethylhexyl)phthalate		4(4)	< 0.6	< 0.62		µg/L
Cadmium, total recoverable	-	8(5)	< 0.04	0.064		µg/L
Copper, total recoverable		4(0)	0.77	2.3	1.3	µg/L
Flow rate	-	365	0.038	2.750	0.520	MGD
Fluoride, total	-	9(0)	0.098	0.215	0.16	mg/L
Mercury, total		1(0)	3.76			ng/L
Oil & grease	100	12(11)	0.9	< 2		mg/L
monthly average ^d	100	12	0	0.9		mg/L
pH	100	123	7.00	8.62	7.66	SU
Precipitation, total	-	243	0	2.39	0.15	in.
Silver, total recoverable		4(2)	< 0.02	0.04		µg/L
Total suspended solids	100	46(2)	1.2	34	9.8	mg/L
monthly average ^d	100	12	1.6	18	10	mg/L
Zinc, total recoverable	-	9(0)	5.6	56.5	21.6	µg/L
<i>Outfall 010 (X-230J5 Northwest Holding Pond)</i>						
Cadmium, total recoverable	-	8(4)	< 0.04	0.11		µg/L
Flow rate	-	365	0.0713	0.881	0.274	MGD
Lead, total recoverable		4(1)	< 0.1	1.1		µg/L
Mercury, total	-	9(0)	0.587	11.6	3.13	ng/L
Oil & grease	100	18(17)	< 1.7	< 2		mg/L
monthly average ^d	100	12	0	1.8		mg/L
pH	100	28	7.21	8.53	7.74	SU
Precipitation, total	-	365	0	2.39	0.13	in.
Selenium, total recoverable		4(3)	< 1	2		µg/L
Total suspended solids	100	23(2)	0.6	28	6.8	mg/L
monthly average ^d	100	12	1	24	7.5	mg/L
Zinc, total recoverable	-	12(0)	3.3	110	30	µg/L
<i>Outfall 011 (X-230J6 Northeast Holding Pond)</i>						
Cadmium, total recoverable	-	9(2)	< 0.04	0.15		µg/L
Chlorine, total residual	-	25(5)	< 0.02	0.10		mg/L
Copper, total recoverable	-	12(0)	0.26	3.5	1.3	µg/L
Flow rate	-	365	0.001	0.263	0.032	MGD
Fluoride, total	-	9(0)	0.086	0.21	0.16	mg/L
Oil & grease	100	24(20)	< 1.6	2.8		mg/L
monthly average ^d	100	12	0	1.4		mg/L
pH	100	34	7.11	8.91	7.89	SU
Precipitation, total	-	365	0	2.39	0.13	in.
Selenium, total recoverable		4(3)	< 1	2.5		µg/L

Table 2.5. FBP NPDES discharge and compliance rates – 2015 (continued)

Parameter	NPDES compliance rate (%) ^a	Number of measurements ^b	Concentration (and loading if applicable)			Units
			Minimum	Maximum	Average ^c	
<i>Outfall 011 (X-230J6 Northeast Holding Pond)</i>						
Thallium, total recoverable	-	1(0)	0.12			µg/L
Total suspended solids	100	24(3)	0.8	6.4	2.3	mg/L
monthly average ^d	100	12	0.5	5	2.3	mg/L
Zinc, total recoverable	-	12(0)	4.2	130	34	µg/L
<i>Outfall 015 (X-624 Groundwater Treatment Facility)</i>						
Arsenic, total recoverable	-	1(1)	< 0.5			µg/L
Barium, total recoverable	-	1(0)	33			µg/L
Flow rate	-	303	0	0.0363	0.0095	MGD
PCBs	-	4(4)	< 0.099	< 0.11		µg/L
pH	100	26	7.21	8.08	7.57	SU
Silver, total recoverable	-	4(4)	< 0.02	< 0.02		µg/L
Trichloroethene	100	24(0)	0.54	4.9	1.75	µg/L
monthly average ^d	100	12	0.82	3.9	1.75	µg/L
<i>Outfall 602 (X-621 Coal Pile Runoff Treatment Facility)</i>						
Flow rate	-	28	0.01	0.213	0.118	MGD
Iron, total	100	8(0)	160	570	310	µg/L
monthly average ^d	100	6	160	530	290	µg/L
Manganese, total	100	8(0)	60	270	160	µg/L
monthly average ^d	100	6	76	260	160	µg/L
pH	100	8	7.91	9.46	8.93	SU
Precipitation, total	-	212	0	1.99	0.17	in.
Total suspended solids	100	8(0)	7.2	27	13	mg/L
monthly average ^d	100	6	7.2	22	13	mg/L
<i>Outfall 604 (X-700 Bionitrification Facility)</i>						
Copper, total	-	7(0)	1.2	10	4	µg/L
Iron, total	-	7(0)	83	750	280	µg/L
Flow rate	-	72	0.0048	0.0111	0.0104	MGD
Nickel, total	-	7(0)	0.36	1.1	0.84	µg/L
Nitrogen, nitrate	-	7(0)	2.6	70	25	mg/L
pH	100	7	7.78	8.23	8.01	SU
Zinc, total	-	7(0)	2.8	17	8.3	µg/L
<i>Outfall 605 (X-705 Microfiltration Treatment System)</i>						
Chromium, hexavalent	-	5(5)	< 0.01	< 0.01		µg/L
Chromium, total	-	5(4)	< 0.88	1.3		µg/L
Copper, total	-	5(0)	0.57	25	11	µg/L
Flow rate	-	23	0.0038	0.0134	0.0076	MGD
Iron, total	-	1(1)	< 22			µg/L
Nickel, total	-	5(0)	2.9	35	13	µg/L
Nitrogen, ammonia (NH ₃)	-	5(1)	< 0.22	0.67		mg/L
Nitrogen, nitrate	-	5(0)	0.43	27.3	11	mg/L
Nitrogen, nitrite	-	5(5)	< 0.1	< 0.2		mg/L
Nitrogen, Kjeldahl	-	5(5)	< 0.18	< 0.18		mg/L
Oil & grease	-	5(5)	< 1.7	< 1.9		mg/L
pH	100	5	7.56	8.6	8.29	SU
Sulfate (SO ₄)	-	5(0)	47	69	59	mg/L
Total suspended solids	100	5(4)	< 1.1	1.2		mg/L
monthly average ^d	100	5	0	1.2		mg/L
Trichloroethene	-	5(5)	< 0.16	< 0.16		µg/L
Zinc, total	-	5(0)	2.4	9.6	5.7	µg/L

Table 2.5. FBP NPDES discharge and compliance rates – 2015 (continued)

Parameter	NPDES compliance rate (%) ^a	Number of measurements ^b	Concentration (and loading if applicable)			Units
			Minimum	Maximum	Average ^c	
<i>Outfall 608 (X-622 Groundwater Treatment Facility)</i>						
Flow rate	-	363	0	0.104	0.0548	MGD
pH	-	26	7.07	8.18	7.79	SU
Trichloroethene	100	24(0)	0.90	4.9	2.1	µg/L
1,2- <i>trans</i> -dichloroethene	100	24(24)	< 0.15	< 0.15		µg/L
monthly average ^d	100	12	0	0		µg/L
<i>Outfall 610 (X-623 Groundwater Treatment Facility)</i>						
Flow rate	-	6	0.0012	0.0114	0.005	MGD
pH	-	5	6.65	7.22	6.87	SU
Trichloroethene	100	5(0)	0.37	0.63		µg/L
monthly average ^d	100	5	0.37	0.63		µg/L
1,2- <i>trans</i> -dichloroethene	100	5(5)	< 0.15	< 0.15		µg/L
monthly average ^d	100	5	0	0		µg/L
<i>Outfall 611 (X-627 Groundwater Treatment Facility)</i>						
Flow rate	-	365	0.0014	0.0600	0.0300	MGD
pH	-	26	7.45	8.36	7.91	SU
Trichloroethene	100	24(1)	< 0.16	9	2.6	µg/L
monthly average ^d	100	12	0.19	6.9	2.6	µg/L
<i>Monitoring Station 801 (Upstream Monitoring)</i>						
48-hr acute toxicity, <i>Ceriodaphnia dubia</i>	-	6(6)	0	0		% affected
96-hr acute toxicity, <i>Pimephales promelas</i>	-	6(6)	0	0		% affected
<i>Monitoring Station 902 (Downstream Far Field Monitoring)</i>						
Water temperature	100	86	2	28	17	°C
monthly average	100	11	3.8	26	17	°C
<i>Monitoring Station 903 (PDownstream Far Field Monitoring)</i>						
Water temperature	100	80	2	28	16	°C
monthly average	100	11	3.6	25	16	°C

^aCompliance rates are provided only for those parameters with a limit specified in the NPDES permit (many parameters require monitoring only). At all outfalls except Outfalls 003, 004, and 605, permit limitations do not apply to total suspended solids (and iron and manganese at Outfall 605) if flow increases as a result of precipitation or snow melt and conditions set in the permit are met.

^bNumber in parentheses is the number of samples that were below the detection limit.

^cAverages were not calculated for outfalls that had greater than 15% of the results below the detection limit. For outfalls with less than 15% of the results below the detection limit, any result below the detection limit was assumed to be zero for calculating the average for the parameter.

^dTo compute the monthly average, parameters that were undetected were assumed to be zero. Exceedances due to flow increases from precipitation or snow melt (see footnote a) were not included in the monthly average calculation.

Note: Some measurements are provided in scientific notation. The number and sign (+ or -) to the right of the “E” indicate the number of places to the right or left of the decimal point. For example, 3.4E-04 is 0.00034 (the decimal point moves four places to the left); 2.1E+02 is 210 (the decimal point moves two places to the right).

Table 2.6. BWCS NPDES discharge and compliance rates – 2015

Parameter	NPDES compliance rate (%)	Number of measurements	Result			Units
			Minimum	Maximum	Average	
<i>Outfall 001^a</i>						
<i>Outfall 602</i>						
Flow rate	100	335	695	14,465	9885	GPD
pH	100	234	5.98	7.12	6.76	SU

^aThis outfall was not used for process water discharges in 2015; therefore, monitoring was not required.

Table 2.7. Centrus NPDES discharge monitoring results – 2015

Parameter	Number of samples ^a	Concentration			Units
		Minimum	Maximum	Average ^b	
<i>Outfall 012 (X-230M Southwest Holding Pond)</i>					
Cadmium	12(3)	< 0.04	0.55		µg/L
Chlorine	24(3)	0	0.12	0.04	mg/L
Copper	12(1)	0.20	3.2	1.3	µg/L
Flow rate	365	0.0215	2.884	0.237	MGD
Iron	12(0)	120	1300	522	µg/L
Oil and grease	24(21)	< 1.7	3.7		mg/L
PCBs, total	1(1)	< 0.1			µg/L
pH	24	6.97	8.55	8.04	SU
Selenium	12(11)	< 1	1.9		µg/L
Silver	12(9)	< 0.02	0.13		µg/L
Suspended solids	24(0)	1.2	16	5.3	mg/L
Thallium	12(7)	< 0.066	0.16		µg/L
Trichloroethene	12(12)	< 0.16	< 0.16		µg/L
<i>Outfall 013 (X-230N West Holding Pond)</i>					
Antimony	12(0)	0.34	1.1	0.61	µg/L
Arsenic	12(2)	< 0.5	4.5		µg/L
Chlorine	24(2)	0	0.13	0.04	mg/L
Copper	12(0)	0.67	7.2	2.4	µg/L
Flow rate	365	0.0052	2.240	0.224	MGD
Oil and grease	24(20)	< 1.6	2.3		mg/L
PCBs, total	1(1)	< 0.1			µg/L
pH	24	7.00	8.64	7.98	SU
Suspended solids	24(4)	< 1.1	8		mg/L
Thallium	12(11)	< 0.066	0.25		µg/L
Zinc	12(0)	5.8	63	24	µg/L
<i>Outfall 613 (X-6002 Particulate Separator)</i>					
Chlorine	19(0)	0.02	0.19	0.07	mg/L
Flow rate	303	0	0.012	0.0002	MGD
Suspended solids	19(2)	< 1.1	42	6.6	mg/L

^aNumber in parentheses is the number of samples that were below the detection limit.

^bAverages were not calculated for outfalls that had greater than 15% of the results below the detection limit. For outfalls with less than 15% of the results below the detection limit, any result below the detection limit was assigned a value at the detection limit for calculating an average for the parameter.

Table 2.8. Radionuclides in surface water runoff samples from FBP and BWCS cylinder storage yards – 2015

Sample location	Parameter	Units	Number of samples ^a	Minimum ^b	Maximum	Average ^c
<i>FBP cylinder storage yards</i>						
X745-B1	Alpha activity	pCi/L	9(9)	< 0.223	< 217	
	Beta activity	pCi/L	9(7)	< 1	187	
	Uranium	µg/L	9(0)	0.05	8.62	1.38
X745-B2	Alpha activity	pCi/L	9(2)	< 1.36	97.9	
	Beta activity	pCi/L	9(2)	< 0.404	99.9	
	Uranium	µg/L	9(0)	1.59	154	24.6
X745-B3	Alpha activity	pCi/L	9(3)	< 0.856	39	
	Beta activity	pCi/L	9(1)	< 1.16	51.4	18.0
	Uranium	µg/L	9(1)	< 0.0432	1.91	0.92
X745-D1	Alpha activity	pCi/L	12(7)	< 0.339	4.83	
	Beta activity	pCi/L	12(2)	< 3.09	13.1	
	Uranium	µg/L	12(0)	0.36	3.83	2.0
X745-F1	Alpha activity	pCi/L	12(10)	0	3.43	
	Beta activity	pCi/L	12(4)	< 1.73	6.46	
	Uranium	µg/L	12(0)	0.06	2.88	0.7
X745-F2	Alpha activity	pCi/L	12(6)	< 0.894	23.7	
	Beta activity	pCi/L	12(0)	4.63	53.5	16.3
	Uranium	µg/L	12(0)	0.73	6.82	3.5
X745-F3	Alpha activity	pCi/L	12(11)	< 0.565	4.22	
	Beta activity	pCi/L	12(3)	2.43	31.8	
	Uranium	µg/L	12(0)	0.11	5.93	2.5
<i>BWCS cylinder storage yards</i>						
X745-C1	Alpha activity	pCi/L	12(0)	0.696	4.22	2.38
	Beta activity	pCi/L	12(0)	1.64	5.84	3.68
	Uranium	µg/L	12(0)	0.28	6.0	3.1
X745-C2	Alpha activity	pCi/L	13(0)	1.41	12.6	4.80
	Beta activity	pCi/L	13(0)	1.65	9.79	3.89
	Uranium	µg/L	13(0)	0.78	13	7.7
X745-C3	Alpha activity	pCi/L	12(1)	0	5.47	2.02
	Beta activity	pCi/L	12(0)	1.47	5.40	2.95
	Uranium	µg/L	12(1)	0	4.0	2.2
X745-C4	Alpha activity	pCi/L	12(0)	1.53	11.4	4.25
	Beta activity	pCi/L	12(0)	1.76	6.91	3.55
	Uranium	µg/L	12(0)	0.75	11	5.6
X745-E1	Alpha activity	pCi/L	13(3)	0	7.24	
	Beta activity	pCi/L	13(0)	1.66	10.1	5.77
	Uranium	µg/L	13(0)	0.23	3.4	1.4

Table 2.8. Radionuclides in surface water runoff samples from FBP and BWCS cylinder storage yards – 2015 (continued)

Sample location	Parameter	Units	Number of samples ^a	Minimum ^b	Maximum	Average ^c
<i>BWCS cylinder storage yards (continued)</i>						
X745-G1A	Alpha activity	pCi/L	12(1)	0	4.85	2.16
	Beta activity	pCi/L	12(0)	1.28	8.50	4.57
	Uranium	µg/L	12(0)	0.81	5.5	2.2
X745-G2	Alpha activity	pCi/L	12(0)	0.71	5.36	2.45
	Beta activity	pCi/L	12(0)	1.45	7.19	3.76
	Uranium	µg/L	12(0)	0.23	3.5	1.7

^aNumber in parentheses is the number of samples that were below the detection limit.

^bMinimum values reported as "0" may actually be negative results. Because of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out. These negative value results are reported as "0" in the table for simplicity.

^cAverages were not calculated for locations that had greater than 15% of the results below the detection limit. For locations with less than 15% of the results below the detection limit, any result below the detection limit was assigned a value at the detection limit to calculate the average for the parameter.

Table 2.9. Drainage basin monitoring of surface water and sediment for BWCS cylinder storage yards – 2015

Location	Parameter ^a	First quarter ^b			Second quarter ^b		
		SW-F	SW-UF	Sed	SW-F	SW-UF	Sed
UDS X01	Total PCB	0.16U	0.16U	13U	0.16U	0.16U	28
RM-8	Total PCB	0.16U	0.16U	10U	0.16U	0.16U	10U
UDS X02	Total PCB	0.16U	0.16U	9.4U	0.16U	0.16U	50
RM-10	Total PCB	0.16U	0.16U	9.9U	0.16U	0.16U	16

Location	Parameter ^a	Third quarter ^b			Fourth quarter ^b		
		SW-F	SW-UF	Sed	SW-F	SW-UF	Sed
UDS X01	Total PCB	0.16U	0.16U	44J	0.16U	0.16U	20J
RM-8	Total PCB	0.16U	0.16U	10U	0.16U	0.16U	9.8U
UDS X02	Total PCB	0.16U	0.16U	100	0.16U	0.16U	25J
RM-10	Total PCB	0.16U	0.16U	10U	0.16U	0.16U	9.6U

^aResults for surface water (SW) are reported in µg/L; results for sediment (Sed) are reported in µg/kg.

^bAbbreviations and data qualifiers are as follows: SW-F – filtered surface water; SW-UF – unfiltered surface water; Sed – sediment; J – the reported value is an estimated concentration greater than the method detection limit but less than the practical quantitation limit; U – undetected.

Table 2.10. Ambient air monitoring program summary for radionuclides and fluoride – 2015

Sampling Location	Parameter ^a	No. of measurements ^b	Minimum ^{c, d}	Maximum ^c	Average ^{c, e}
<i>On-site air samplers</i>					
A8	Americium-241	4(4)	6.2E-07	4.1E-06	
	Fluoride	48(43)	1.0E-02	4.7E-02	
	Neptunium-237	4(4)	0	7.4E-07	
	Plutonium-238	4(4)	0	2.6E-06	
	Plutonium-239/240	4(4)	7.9E-07	2.0E-06	
	Techneium-99	12(0)	2.6E-04	5.2E-02	1.5E-02
	Uranium	12(2)	2.8E-05	7.4E-04	
	Uranium-233/234	12(1)	7.4E-07	6.3E-04	1.2E-04
	Uranium-235/236	12(11)	1.4E-06	3.4E-05	
	Uranium-238	12(3)	8.7E-06	2.4E-04	
A10	Americium-241	4(4)	6.6E-07	2.4E-06	
	Fluoride	49(47)	1.2E-02	1.9E-02	
	Neptunium-237	4(4)	0	5.3E-06	
	Plutonium-238	4(4)	0	1.5E-06	
	Plutonium-239/240	4(4)	1.2E-06	2.9E-06	
	Techneium-99	12(0)	1.4E-04	4.9E-02	1.6E-02
	Uranium	12(0)	3.3E-05	7.7E-04	1.4E-04
	Uranium-233/234	12(1)	6.5E-06	3.2E-04	1.0E-04
	Uranium-235/236	12(8)	2.1E-06	1.9E-05	
	Uranium-238	12(0)	1.1E-05	2.6E-04	4.9E-05
A29	Americium-241	4(4)	7.7E-07	2.2E-06	
	Fluoride	50(37)	7.8E-03	5.0E-02	
	Neptunium-237	4(4)	0	6.8E-07	
	Plutonium-238	4(4)	0	7.4E-07	
	Plutonium-239/240	4(4)	5.9E-07	4.7E-06	
	Techneium-99	12(1)	6.0E-05	3.4E-02	1.3E-02
	Uranium	12(1)	2.2E-05	1.5E-04	6.4E-05
	Uranium-233/234	12(1)	8.6E-07	1.2E-04	4.1E-05
	Uranium-235/236	12(11)	0	1.3E-05	
	Uranium-238	12(0)	7.1E-06	5.1E-05	2.3E-05
A36	Americium-241	4(4)	1.2E-06	5.0E-06	
	Fluoride	49(46)	6.2E-03	1.8E-02	
	Neptunium-237	4(4)	0	1.9E-06	
	Plutonium-238	4(4)	0	2.0E-06	
	Plutonium-239/240	4(4)	2.4E-06	3.8E-06	
	Techneium-99	12(0)	4.8E-04	3.1E-02	1.3E-02
	Uranium	12(0)	2.5E-05	1.3E-03	1.9E-04
	Uranium-233/234	12(1)	5.1E-06	5.3E-04	1.5E-04
	Uranium-235/236	12(8)	1.0E-06	2.9E-05	
	Uranium-238	12(0)	8.2E-06	4.4E-04	6.4E-05
A40A	Fluoride	52(41)	2.0E-03	7.0E-02	

Table 2.10. Ambient air monitoring program summary for radionuclides and fluoride – 2015 (continued)

Sampling Location	Parameter ^a	No. of measurements ^b	Minimum ^{c, d}	Maximum ^c	Average ^{c, e}
<i>On-site air samplers</i>					
T7	Americium-241	4(4)	1.3E-06	4.1E-06	
	Neptunium-237	4(4)	0	1.8E-06	
	Plutonium-238	4(4)	0	1.4E-06	
	Plutonium-239/240	4(4)	2.0E-06	4.1E-06	
	Techneium-99	12(0)	1.9E-04	3.6E-02	1.2E-02
	Uranium	12(2)	1.4E-05	1.3E-03	
	Uranium-233/234	12(1)	7.7E-07	3.1E-02	2.6E-03
	Uranium-235/236	12(10)	0	7.9E-04	
	Uranium-238	12(3)	7.8E-06	3.0E-04	
<i>Off-site air samplers</i>					
A3	Americium-241	4(4)	1.3E-06	3.9E-06	
	Fluoride	46(23)	1.0E-02	6.1E-02	
	Neptunium-237	4(4)	0	1.2E-06	
	Plutonium-238	4(4)	0	1.2E-06	
	Plutonium-239/240	4(4)	6.8E-07	3.7E-06	
	Techneium-99	12(0)	2.9E-04	4.8E-02	1.5E-02
	Uranium	12(0)	3.6E-05	2.4E-03	2.6E-04
	Uranium-233/234	12(1)	3.6E-06	8.3E-04	1.2E-04
	Uranium-235/236	12(10)	7.3E-07	4.4E-05	
A6	Uranium-238	12(0)	1.2E-05	8.1E-04	8.8E-05
	Americium-241	4(4)	0	5.0E-06	
	Fluoride	46(40)	1.2E-02	1.9E-02	
	Neptunium-237	4(4)	0	1.5E-06	
	Plutonium-238	4(4)	0	4.0E-06	
	Plutonium-239/240	4(4)	1.9E-06	4.0E-06	
	Techneium-99	12(1)	9.5E-05	5.6E-02	1.6E-02
	Uranium	12(2)	1.5E-05	1.6E-04	
	Uranium-233/234	12(1)	0	6.0E-05	2.8E-05
A9	Uranium-235/236	12(11)	0	1.4E-05	
	Uranium-238	12(3)	7.7E-06	5.4E-05	
	Americium-241	4(4)	5.8E-07	2.9E-06	
	Fluoride	46(50)	7.1E-03	7.3E-02	
	Neptunium-237	4(4)	6.2E-07	7.9E-07	
	Plutonium-238	4(4)	0	2.6E-06	
	Plutonium-239/240	4(4)	2.5E-06	5.8E-06	
	Techneium-99	12(2)	4.7E-05	5.8E-02	
	Uranium	12(0)	2.6E-05	2.0E-03	2.5E-04
Uranium-233/234	12(1)	3.4E-06	6.8E-04	9.7E-05	
Uranium-235/236	12(10)	1.1E-06	3.6E-05		
Uranium-238	12(0)	1.3E-05	6.8E-04	8.8E-05	

Table 2.10. Ambient air monitoring program summary for radionuclides and fluoride – 2015 (continued)

Sampling Location	Parameter ^a	No. of measurements ^b	Minimum ^{c, d}	Maximum ^c	Average ^{c, e}
A12	Americium-241	4(4)	2.6E-06	4.6E-06	
	Fluoride	51(33)	8.5E-03	1.5E-01	
	Neptunium-237	4(4)	0	2.4E-06	
	Plutonium-238	4(4)	0	0	
	Plutonium-239/240	4(4)	0	4.7E-06	
	Techneium-99	12(0)	5.3E-04	3.7E-02	1.6E-02
	Uranium	12(0)	3.5E-05	8.0E-04	1.2E-04
	Uranium-233/234	12(1)	2.4E-06	3.9E-04	9.1E-05
	Uranium-235/236	12(10)	2.0E-06	2.7E-05	
	Uranium-238	12(0)	1.1E-05	2.6E-04	4.3E-05
A15	Americium-241	4(4)	0	3.2E-06	
	Fluoride	44(40)	9.0E-03	2.3E-02	
	Neptunium-237	4(4)	0	7.4E-07	
	Plutonium-238	4(3)	7.8E-07	2.6E-05	
	Plutonium-239/240	4(4)	0	7.8E-06	
	Techneium-99	12(0)	2.2E-04	4.8E-02	1.5E-02
	Uranium	12(1)	2.8E-05	1.5E-03	1.8E-04
	Uranium-233/234	12(2)	8.2E-07	5.1E-04	
	Uranium-235/236	12(10)	0	3.1E-05	
	Uranium-238	12(1)	9.1E-06	5.1E-04	6.2E-05
A23	Americium-241	4(4)	6.2E-07	5.8E-06	
	Fluoride	42(35)	1.2E-02	2.6E-02	
	Neptunium-237	4(4)	0	1.8E-06	
	Plutonium-238	4(4)	0	1.4E-06	
	Plutonium-239/240	4(4)	8.0E-07	4.6E-06	
	Techneium-99	12(0)	3.0E-04	5.4E-02	1.7E-02
	Uranium	12(0)	5.4E-05	5.6E-04	1.4E-04
	Uranium-233/234	12(1)	2.6E-06	5.9E-04	1.4E-04
	Uranium-235/236	12(9)	5.0E-07	2.4E-05	
	Uranium-238	12(0)	1.8E-05	1.8E-04	4.9E-05
A24	Americium-241	4(4)	6.0E-07	3.8E-06	
	Fluoride	39(30)	1.3E-02	2.5E-02	
	Neptunium-237	4(4)	0	1.3E-06	
	Plutonium-238	4(4)	0	7.4E-07	
	Plutonium-239/240	4(4)	2.6E-06	4.9E-06	
	Techneium-99	12(0)	2.2E-04	5.6E-02	1.6E-02
	Uranium	12(0)	3.0E-05	4.5E-04	1.2E-04
	Uranium-233/234	12(1)	2.8E-06	2.7E-04	1.0E-04
	Uranium-235/236	12(11)	7.4E-07	1.3E-05	
	Uranium-238	12(0)	2.0E-05	1.5E-04	4.3E-05

Table 2.10. Ambient air monitoring program summary for radionuclides and fluoride – 2015 (continued)

Sampling Location	Parameter ^a	No. of measurements ^b	Minimum ^{c, d}	Maximum ^{c, d}	Average ^{c, e}
A28	Americium-241	4(4)	1.8E-06	2.9E-06	
	Fluoride	50(46)	1.1E-02	5.7E-02	
	Neptunium-237	4(4)	0	1.2E-06	
	Plutonium-238	4(4)	0	6.8E-07	
	Plutonium-239/240	4(4)	2.0E-06	3.8E-06	
	Technetium-99	12(0)	1.5E-04	5.9E-02	1.9E-02
	Uranium	12(0)	3.0E-05	1.4E-04	6.6E-05
	Uranium-233/234	12(1)	4.9E-06	4.6E-05	2.5E-05
	Uranium-235/236	12(11)	7.3E-07	2.5E-05	
A37 (background)	Uranium-238	12(0)	9.8E-06	7.6E-05	2.7E-05
	Americium-241	4(4)	5.9E-07	5.5E-06	
	Fluoride	51(47)	1.2E-02	3.1E-02	
	Neptunium-237	4(4)	0	6.7E-07	
	Plutonium-238	4(4)	6.4E-07	4.7E-06	
	Plutonium-239/240	4(4)	1.4E-06	4.3E-06	
	Technetium-99	12(1)	1.2E-04	4.8E-02	1.4E-02
	Uranium	12(1)	1.9E-05	1.4E-04	5.7E-05
	Uranium-233/234	12(1)	4.2E-06	4.2E-05	2.1E-05
A41A	Uranium-235/236	12(11)	0	1.7E-05	
	Uranium-238	12(0)	1.2E-05	5.3E-05	2.3E-05
	Americium-241	4(4)	6.8E-07	4.8E-06	
	Fluoride	50(28)	1.5E-02	2.8E-02	
	Neptunium-237	4(4)	0	1.3E-06	
	Plutonium-238	4(4)	0	2.7E-06	
	Plutonium-239/240	4(4)	0	2.1E-06	
	Technetium-99	12(0)	2.2E-04	5.9E-02	2.0E-02
	Uranium	12(0)	1.1E-05	1.0E-04	6.2E-05
Uranium-233/234	12(1)	2.2E-06	6.5E-05	3.2E-05	
Uranium-235/236	12(11)	0	1.9E-05		
Uranium-238	12(0)	1.2E-05	5.8E-05	2.5E-05	

^aAll parameters are measured in pCi/m³ with the exception of uranium and fluoride which are measured in µg/m³.

^bRadiological samples for technetium-99, uranium, and uranium isotopes are analyzed monthly, samples for americium-241, neptunium-237, plutonium-238, and plutonium-239/240 are analyzed one month per quarter, and samples for fluoride are analyzed weekly. Number in parentheses is the number of samples that were below the detection limit. If the analytical result for a sample was below the detection limit, the ambient air concentration was calculated based on the detection limit for the sample.

^cResults are provided in scientific notation. The number and sign (+ or -) to the right of the “E” indicate the number of places to the right or left of the decimal point. For example, 3.4E-04 is 0.00034 (the decimal point moves four places to the left); 2.1E+02 is 210 (the decimal point moves two places to the right).

Ambient concentrations of uranium and uranium isotopes reported from June through December of 2015 may be slightly elevated and should be considered estimated. Uranium and uranium isotopes were detected in quality control samples associated with the ambient air samples and subsequently in unused filters obtained from the manufacturer that are placed at the ambient air stations to collect samples. The presence of uranium and uranium isotopes in the unused filters may have caused slightly elevated analytical results for uranium and uranium isotopes. Levels of these constituents in ambient air are calculated based on the analytical results and therefore may be slightly elevated as well. Reported minimum, maximum, and average values include these estimated results.

^dValues reported as “0” may actually be negative results. Because of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out. These negative value results are reported as “0” in the table for simplicity.

^eAverages are not calculated for locations that had greater than 15% of the results below the detection limit.

Table 2.11. External radiation monitoring program (mrem) – 2015

Location	First quarter	Second quarter	Third quarter	Fourth quarter	Cumulative annual whole body dose ^a
#1404A	24	23	23	20	90
#518	24	23	21	19	87
#862	31	35	35	29	130
#874	150	162	162	131	605
#906	20	21	21	18	80
#933	42	40	40	32	154
A12	22	24	24	21	91
A15	24	26	25	22	97
A23	24	23	24	21	92
A24	26	26	26	22	100
A28	20	23	23	20	86
A29	25	27	26	22	100
A3	23	22	24	19	88
A36	25	24	23	20	92
A40A	24	24	24	21	93
A6	23	24	23	21	91
A8	25	27	27	23	102
A9	23	24	24	20	91
X230J2	24	25	23	20	92

^aThe annual occupational whole body dose limit set by Title 10 of the *Code of Federal Regulations* Part 20 is 5000 mrem.

Table 2.12. External radiation monitoring (mrem) at locations near cylinder storage yards – 2015

Location	First quarter ^a			Second quarter ^a		
	Deep ^b	N ^c	Shallow ^d	Deep ^b	N ^c	Shallow ^d
#41	161	14	161	179	21	179
#868	302	8	302	320	ND	320
#874	171	17	171	169	20	169
#882	261	10	261	290	30	290
#890	92	29	92	79	14	79

Location	Third quarter ^a			Fourth quarter ^a			Annual (total) ^a		
	Deep ^b	N ^c	Shallow ^d	Deep ^b	N ^c	Shallow ^d	Deep ^b	N ^c	Shallow ^d
#41	150	ND	150	130	ND	130	620	ND	620
#868	342	ND	342	303	54	303	1267	32	1267
#874	171	ND	171	140	ND	140	651	ND	651
#882	267	ND	267	223	ND	223	1041	26	1041
#890	68	ND	68	65	8	65	304	33	304

^aND – not detected above the minimum reportable dose.

^bDeep dose (dose equivalent at a tissue depth of 1 centimeter [cm]) applies to external whole body exposure. Dose is reported for photon energies from approximately 10 kilo-electron volts (keV) to 6 mega-electron volts (MeV) and includes neutron dose (if present).

^cNeutron component of deep dose.

^dShallow dose (dose equivalent at a tissue depth of 0.007 cm averaged over an area of 1 square cm) applies to exposure of the skin or an extremity. It includes the dose for beta particles and photons. Extremity doses are based on 662 keV photons. Neutron dose is included if present.

Table 2.13. Settleable solids monitoring results – 2015

Sampling location	Parameter ^a	Unit	Results ^b			
			April	November		
<i>Little Beaver Creek</i>						
EDD-SW01 (FBP Outfalls 001& 015)	Settleable solids	mg/L	4.4	6.2	4UJ ^c	
	Suspended solids	mg/L	4.8	6.2	5.8 ^c	
FBP Outfall 005	Settleable solids	mg/L	4U		4U	
	Suspended solids	mg/L	7.2		10.5	
FBP Outfall 009	Settleable solids	mg/L	6.3		4U	
	Suspended solids	mg/L	8.4		4U	
FBP Outfall 011	Settleable solids	mg/L	4.9		5.2	
	Suspended solids	mg/L	4U		5.2	
<i>Big Run Creek</i>						
FBP Outfall 002	Settleable solids	mg/L	7.2	8 ^c	7.6J	
	Suspended solids	mg/L	6.6	6.5 ^c	7.6	
<i>Scioto River</i>						
ACP NPDES Outfall 012	Settleable solids	mg/L	7.8		4.2	
	Suspended solids	mg/L	7.6		4.2	
WDD-SW03 (FBP Outfall 010 & ACP Outfall 013)	Settleable solids	mg/L	4		4U	
	Suspended solids	mg/L	4.2		4U	
FBP Outfall 003	Settleable solids	mg/L	4U		14.3	
	Suspended solids	mg/L	13		18.5	
FBP Outfall 004	Settleable solids	mg/L	4U		4U	
	Suspended solids	mg/L	4U		4U	
<i>Background locations</i>						
RW-6 (Scioto River)	Settleable solids	mg/L	19.7	18.9 ^c	9.1J	4UJ ^c
	Suspended solids	mg/L	31.7	29.2 ^c	9.1	7.3 ^c
RW-5 (Big Beaver Creek)	Settleable solids	mg/L	4U		4U	
	Suspended solids	mg/L	4U		4U	
LBC-SW12 (Little Beaver Creek)	Settleable solids	mg/L	4U		29.2	
	Suspended solids	mg/L	4U		34.5	

^aSuspended solids are the solids in a water sample (such as silt or clay particles) that can be trapped by a filter. Settleable solids are a component of suspended solids defined as the particles that settle out of suspension in water within a defined time period.

^bAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^cThis result is for the duplicate sample collected from this location. A duplicate sample is a sample collected from the same location at the same time and using the same sampling device (if possible) as the regular sample.

Table 2.14. Local surface water monitoring program results – 2015

Location	Parameter ^a	Second quarter ^{b,c}		Fourth quarter ^{b,c}
Scioto River RW-1 (downstream)	Americium-241	0.0417U		-0.00918U
	Neptunium-237	0U		-0.00434U
	Plutonium-238	0U		0.015U
	Plutonium-239/240	0.0242U		0.0299U
	Technetium-99	-0.932U		2.1U
	Uranium	2.3		1.26
	Uranium-233/234	0.658		0.441
	Uranium-235/236	0.0367U		0.0231U
Scioto River RW-6 (upstream)	Uranium-238	0.767		0.418
	Americium-241	0.00453U		0.00478U
	Neptunium-237	0U		0U
	Plutonium-238	0.0158U		0.00517U
	Plutonium-239/240	0.0315U		0.0207U
	Technetium-99	-4.1U		-1.21U
	Uranium	1.78		1.49J
	Uranium-233/234	0.673		0.462
Little Beaver Creek RW-7 (downstream)	Uranium-235/236	-0.00603U		0.0484UJ
	Uranium-238	0.601		0.492
	Americium-241	0.0229U		0.0206U
	Neptunium-237	0.0221U		0.00409U
	Plutonium-238	-0.00542U		0.0107U
	Plutonium-239/240	0.00542U		0.0376U
	Technetium-99	9.04		14.1
	Uranium	0.813		2.44
RW-8 (downstream)	Uranium-233/234	1.13		4.07
	Uranium-235/236	0.0632U		0.183
	Uranium-238	0.263		0.791
	Americium-241	0.0179U		0.0246U
	Neptunium-237	0U		0.00848U
	Plutonium-238	0U		0U
	Plutonium-239/240	0.0143U		0.0257U
	Technetium-99	5.11U		7.99
RW-12 (upstream)	Uranium	0.82		2.64
	Uranium-233/234	0.913		3.8
	Uranium-235/236	0.0397U		0.216
	Uranium-238	0.269		0.853
	Americium-241	0.00901U	0.0223U ^d	0.015U
	Neptunium-237	-0.00431U	0.00438U ^d	-0.00454U
	Plutonium-238	0U	0U ^d	-0.0107U
	Plutonium-239/240	0.0165U	0.0407U ^d	0U
Technetium-99	-3.23U	-1.77U ^d	1.01U	
Uranium	0.083U	0.056U ^d	0.0454U	
Uranium-233/234	0.0315U	0.0376U ^d	0.0559UJ	
Uranium-235/236	0.0056U	0U ^d	0U	
Uranium-238	0.027U	0.0188U ^d	0.0152U	

Table 2.14. Local surface water monitoring program results – 2015 (continued)

Location	Parameter ^a	Second quarter ^{b,c}		Fourth quarter ^{b,c}
Big Beaver Creek RW-13 (downstream)	Americium-241	0.0546U	0.0152U	0.0191U ^d
	Neptunium-237	0.00939U	0.0124U	0.0182U ^d
	Plutonium-238	-0.01U	-0.00491U	0U ^d
	Plutonium-239/240	0.0352U	0.0295U	0.00523U ^d
	Technetium-99	2.03U	11.8J	18J ^d
	Uranium	0.303	1.91	1.72 ^d
	Uranium-233/234	0.638	3.52	3.31 ^d
	Uranium-235/236	0.047U	0.138	0.115 ^d
RW-5 (upstream)	Uranium-238	0.0945	0.619	0.559 ^d
	Americium-241	0.00451U		0.0248U
	Neptunium-237	-0.00475U		0.00464U
	Plutonium-238	0.0161U		-0.00551U
	Plutonium-239/240	0.0269U		0.00552U
	Technetium-99	-3.17U		-0.296U
	Uranium	0.226U		0.475J
	Uranium-233/234	0.0531U		0.125
Big Run Creek RW-2 (downstream)	Uranium-235/236	0.0055U		0.0172U
	Uranium-238	0.0752U		0.157
	Americium-241	0.00439U	0.0219U ^d	0.00973U
	Neptunium-237	0U	0U ^d	0.00498U
	Plutonium-238	0.0172U	-0.00513U ^d	0.0104U
	Plutonium-239/240	0U	0.0205U ^d	0.00521U
	Technetium-99	-2.28U	-2.44U ^d	1.19U
	Uranium	0.239U	0.166U ^d	0.365J
RW-3 (downstream)	Uranium-233/234	0.192	0.148 ^d	0.202
	Uranium-235/236	0.0171U	0U ^d	0.0111U
	Uranium-238	0.0778U	0.0557U ^d	0.121
	Americium-241	0.0324U		0.0518U
	Neptunium-237	0.00433U		0.00445U
	Plutonium-238	0.0101U		-0.00516U
	Plutonium-239/240	0.0354U		0U
	Technetium-99	2.96U		2.42U
	Uranium	1.1		0.33J
	Uranium-233/234	2.26		0.236
	Uranium-235/236	0.144		0.03U
	Uranium-238	0.347		0.106

Table 2.14. Local surface water monitoring program results – 2015 (continued)

Location	Parameter ^a	Second quarter ^{b,c}	Fourth quarter ^{b,c}	
Big Run Creek (continued) RW-33 (upstream)	Americium-241	0.0185U	0.0416U	
	Neptunium-237	-0.00882U	0U	
	Plutonium-238	0U	0.00548U	
	Plutonium-239/240	0.0423U	0.0164U	
	Technetium-99	-4.92U	0.388U	
	Uranium	0.162U	2.13	
	Uranium-233/234	0.0274U	0.807	
	Uranium-235/236	0.0284U	0.0181U	
Background creeks RW-10N	Uranium-238	0.0502U	0.715	
	Americium-241	0.0276U	0.0204U	
	Neptunium-237	0.00435U	0.00473U	
	Plutonium-238	0U	0U	
	Plutonium-239/240	0.0226U	0.0146U	
	Technetium-99	-1.28U	0.841U	
	Uranium	0.458	0.298J	
	Uranium-233/234	0.168	0.0935J	
RW-10S	Uranium-235/236	0U	0.0116U	
	Uranium-238	0.154	0.0982J	
	Americium-241	0.043U	0.00484U	0.0248U ^d
	Neptunium-237	0.00423U	-0.00459U	0.014U ^d
	Plutonium-238	0.0058U	0.0104U	-0.00515U ^d
	Plutonium-239/240	0U	0.0104U	0.0103U ^d
	Technetium-99	-1.53U	-1.28U	5.93UJ ^d
	Uranium	0.126U	0.128UJ	0.158UJ ^d
RW-10E	Uranium-233/234	0.0451U	0.069UJ	0.0733UJ ^d
	Uranium-235/236	0.0112U	0.0114U	0.0171U ^d
	Uranium-238	0.0406U	0.0414UJ	0.0504UJ ^d
	Americium-241	0.0225U	0.00496U	
	Neptunium-237	0.00442U	0.00927U	
	Plutonium-238	0U	0.0052U	
	Plutonium-239/240	0U	0.0208U	
	Technetium-99	-3.74U	1U	
	Uranium	0.0301U	0.143UJ	
	Uranium-233/234	0.0231U	0.0144U	
	Uranium-235/236	0.00574U	0U	
	Uranium-238	0.00923U	0.0481UJ	

Table 2.14. Local surface water monitoring program results – 2015 (continued)

Location	Parameter ^a	Second quarter ^{b,c}	Fourth quarter ^{b,c}
Background creeks	Americium-241	0.00453U	0.0193U
RW-10W	Neptunium-237	0U	0.00433U
	Plutonium-238	0.0171U	-0.0106U
	Plutonium-239/240	0.0114U	0.0265U
	Technetium-99	-1.19U	2.1U
	Uranium	0.0466U	0.127U
	Uranium-233/234	0.0277U	0.0387U
	Uranium-235/236	0.0115U	-0.00602U
	Uranium-238	0.0139U	0.0436UJ

^aResults are reported in µg/L (uranium) and pCi/L (all other parameters).

^bAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^cBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out. Some results are provided in scientific notation. The number and sign (+ or -) to the right of the “E” indicate the number of places to the right or left of the decimal point. For example, 3.4E-04 is 0.00034 (the decimal point moves four places to the left); 2.1E+02 is 210 (the decimal point moves two places to the right).

^dThis result is for the duplicate sample collected from this location. A duplicate sample is a sample collected from the same location at the same time and using the same sampling device (if possible) as the regular sample.

Table 2.15. Sediment monitoring program results – 2015

Parameter	Unit	Location/results ^{a,b}			
		<i>Scioto River and outfalls that discharge to the Scioto River</i>			
		<i>RM-6 Upstream @ Piketon</i>	<i>RM-1 Downstream @ Lucasville</i>	<i>RM-9 Outfall 012</i>	<i>RM-10 Outfall 010/Outfall 013</i>
Aluminum	mg/kg	2610J	3190J	5600J	3730J
Americium-241	pCi/g	0.00125UJ	0.00189U	-0.000806UJ	0.00243UJ
Antimony	mg/kg	0.0651DNU	0.064DNU	0.0645DNU	0.0643DNU
Arsenic	mg/kg	5.48*	6.21*	0.609*	7.3*
Barium	mg/kg	35.8*	43.5*	48.6*	54.2*
Beryllium	mg/kg	0.26D	0.308D	0.711D	0.598D
Cadmium	mg/kg	0.222D	0.296D	0.268D	0.179D
Calcium	mg/kg	39400DN	37600DN	1250DN	1890DN
Chromium	mg/kg	5.68N	6.18N	9.96N	15.5N
Copper	mg/kg	8.85	9.58	25.1	10
Iron	mg/kg	12000D	12800D	27500D	27300D
Lead	mg/kg	8.47	8.65	7.99	14.4
Magnesium	mg/kg	15000	13900	2300	1170
Manganese	mg/kg	355*D	396*D	236*D	1020*D
Mercury	mg/kg	0.0331	0.0237	0.0178U	0.0196
Neptunium-237	pCi/g	-0.000452U	0.00113U	0.00343UJ	0.000409U
Nickel	mg/kg	11.4	13.7	45.8	13.4
PCB, total	µg/kg	18.5U	18.2U	18.9U	48.2J
Plutonium-238	pCi/g	0.000622UJ	0.00261UJ	-0.000605U	0UJ
Plutonium-239/240	pCi/g	-0.000622UJ	0.00261UJ	0.00363U	0.00144UJ
Selenium	mg/kg	0.535*DN	0.552*DN	1.13*DN	0.567*DN
Silicon	mg/kg	377*N	429*N	204*N	233*N
Silver	mg/kg	0.325U	0.34U	0.321U	0.311U
Technetium-99	pCi/g	-0.121U	-0.0731U	-0.0291U	0.247
Thallium	mg/kg	0.139D	0.142D	0.12D	0.0783D
Uranium	µg/g	1.86	2.21	2.71	4.53
Uranium-233/234	pCi/g	0.58	0.682	0.952	2.2
Uranium-235/236	pCi/g	0.0251	0.0353	0.0464	0.106
Uranium-238	pCi/g	0.621	0.736	0.905	1.51
Zinc	mg/kg	51.9	56.6	67.1	111

Table 2.15. Sediment monitoring program results – 2015 (continued)

Parameter	Unit	Location/results ^{a,b}			
		<i>Little Beaver Creek</i>			
		<i>RM-12 Upstream</i>	<i>RM-12 Upstream (duplicate sample)</i>	<i>RM-11 X-230J7 Discharge</i>	<i>RM-8 Downstream @ Outfall 009 Discharge</i>
Aluminum	mg/kg	5120J	4980J	3300J	5430J
Americium-241	pCi/g	0.00856UJ	0.00146UJ	0.00501UJ	0.00227U
Antimony	mg/kg	0.0713DNU	0.0671DNU	0.287DNU	0.0709DNU
Arsenic	mg/kg	6.6*	7.27*	20.6*	12.3*
Barium	mg/kg	62.7*	64.8*	46.5*	113*
Beryllium	mg/kg	0.568D	0.635D	0.524D	1D
Cadmium	mg/kg	0.0837D	0.0991D	0.688D	0.556D
Calcium	mg/kg	1620DN	1200DN	114000DN	2910DN
Chromium	mg/kg	9.03N	9.33N	11.1N	17.2N
Copper	mg/kg	8.74	9.74	25.6	11.5
Iron	mg/kg	20200D	24100D	13600D	30400D
Lead	mg/kg	14	16.4	16.2	23.1
Magnesium	mg/kg	1160	992	51000D	1660
Manganese	mg/kg	846*D	617*D	782*D	1760*D
Mercury	mg/kg	0.0229	0.0265	0.979D	0.0545
Neptunium-237	pCi/g	0U	-0.000581U	0.00161U	0.00483UJ
Nickel	mg/kg	11	11.9	19.6	29.6
PCB, total	µg/kg	19.1U	18.7U	116	84.7
Plutonium-238	pCi/g	0U	0.00129U	0.00164UJ	0.00261U
Plutonium-239/240	pCi/g	0.00596UJ	0.00515UJ	0.0189J	0.00574UJ
Selenium	mg/kg	0.599*DN	0.643*DN	1.07*DN	0.968*DN
Silicon	mg/kg	486*N	463*N	516*N	265*N
Silver	mg/kg	0.353U	0.352U	0.388U	0.341U
Technetium-99	pCi/g	-0.102U	-0.0713U	3.9	1.54
Thallium	mg/kg	0.0778D	0.0761D	0.32D	0.173D
Uranium	µg/g	2.53	2.5	4.66	3.66
Uranium-233/234	pCi/g	0.862	0.833	6.23	2.09
Uranium-235/236	pCi/g	0.0493	0.0425	0.258	0.0946
Uranium-238	pCi/g	0.844	0.834	1.52	1.22
Zinc	mg/kg	43.7	48	253	96.7

Table 2.15. Sediment monitoring program results – 2015 (continued)

Parameter	Unit	Location/results ^{a,b}		
		<i>LittleBig Beaver Creek RM-7 Downstream @ Confluence</i>	<i>Big Beaver Creek RM-5 Upstream</i>	<i>RM-13 Downstream</i>
Aluminum	mg/kg	3610J	5040J	3450J
Americium-241	pCi/g	0.00522UJ	0.00427UJ	0UJ
Antimony	mg/kg	0.114DNU	0.0611DNU	0.059DNU
Arsenic	mg/kg	9.12*	6.1*	5.66*
Barium	mg/kg	56.4*	63*	55.6*
Beryllium	mg/kg	0.661D	0.475D	0.413D
Cadmium	mg/kg	0.605D	0.343D	0.371D
Calcium	mg/kg	5400DN	2680DN	49700DN
Chromium	mg/kg	15.8N	9.66N	7.52N
Copper	mg/kg	11.7	12.4	17.4
Iron	mg/kg	24800D	16200D	18200D
Lead	mg/kg	14.6	12.8	10.2
Magnesium	mg/kg	2550	1960	14000
Manganese	mg/kg	686*D	728*D	868*D
Mercury	mg/kg	0.0553	0.026	0.0236
Neptunium-237	pCi/g	0.0295	-0.000529U	0.00919J
Nickel	mg/kg	27	18.7	34
PCB, total	µg/kg	159	18.7U	20.2
Plutonium-238	pCi/g	0.000586U	0.0013UJ	0.00179UJ
Plutonium-239/240	pCi/g	0.0146	0.0026UJ	0.00179UJ
Selenium	mg/kg	0.769*DN	0.678*DN	0.558*DN
Silicon	mg/kg	367*N	436*N	351*N
Silver	mg/kg	0.323U	0.325U	0.301U
Technetium-99	pCi/g	16.3	0.196UJ	3.22
Thallium	mg/kg	0.159D	0.13D	0.162D
Uranium	µg/g	4.17J	2.72	2.61
Uranium-233/234	pCi/g	4.05	0.992	1.24
Uranium-235/236	pCi/g	0.2	0.0557	0.0689
Uranium-238	pCi/g	1.37U	0.904	0.866
Zinc	mg/kg	96.9	66	69.9

Table 2.15. Sediment monitoring program results – 2015 (continued)

Parameter	Unit	Location/results ^{a,b}			
		<i>Big Run Creek</i>			
		<i>RM-33 Upstream</i>	<i>RM-3 Downstream</i>	<i>RM-2 Downstream @ Wakefield</i>	<i>RM-2 Downstream @ Wakefield (duplicate sample)</i>
Aluminum	mg/kg	5000J	5200J	5290J	5550J
Americium-241	pCi/g	0.00165UJ	0.00232U	0.00507UJ	0.00663UJ
Antimony	mg/kg	0.133DNU	0.15DNU	0.0672DNU	0.0668DNU
Arsenic	mg/kg	13.1*	17.4*	8.29*	7.16*
Barium	mg/kg	63.6*	101*	62*	63.1*
Beryllium	mg/kg	0.8D	1.33D	0.657D	0.67D
Cadmium	mg/kg	0.697D	0.322D	0.372D	0.375D
Calcium	mg/kg	3580DN	2370DN	1120DN	1130DN
Chromium	mg/kg	12.3N	18.9N	10.4N	11.1N
Copper	mg/kg	12.9	14.2	10.9	11
Iron	mg/kg	27400D	44300D	21500D	21800D
Lead	mg/kg	18	29.9	16.3	16.2
Magnesium	mg/kg	1880	1010	1190	1210
Manganese	mg/kg	806*D	2460*D	816*D	898*D
Mercury	mg/kg	0.0306	0.0364	0.0277	0.0344
Neptunium-237	pCi/g	0.000454U	-0.000409U	0.00141UJ	0.00112U
Nickel	mg/kg	23.8	23.8	19.2	19.9
PCB, total	µg/kg	18.9U	46.8	18.7U	33.2
Plutonium-238	pCi/g	0.00261UJ	-0.000561U	0.00122U	-0.000627UJ
Plutonium-239/240	pCi/g	0.00522UJ	0.00224U	0.00548UJ	0.00439UJ
Selenium	mg/kg	0.81*DN	1.09*DN	0.726*DN	0.779*DN
Silicon	mg/kg	459*N	415*N	450*N	470*N
Silver	mg/kg	0.357U	0.345U	0.341U	0.342U
Technetium-99	pCi/g	-0.0852U	1.15	-0.0575U	-0.0314U
Thallium	mg/kg	0.194D	0.267D	0.154D	0.153D
Uranium	µg/g	3.71	5.73	4.2J	2.94J
Uranium-233/234	pCi/g	1.28	3.12	1.73J	1.18J
Uranium-235/236	pCi/g	0.0692	0.17	0.0762	0.0669
Uranium-238	pCi/g	1.24	1.9	1.4J	0.976J
Zinc	mg/kg	103	117	63.3	62.8

Table 2.15. Sediment monitoring program results – 2015 (continued)

Parameter	Unit	Location/results ^{a,b}			
		<i>Background creeks</i>			
		<i>RM-10N North background</i>	<i>RM-10S South background</i>	<i>RM-10E East background</i>	<i>RM-10W West background</i>
Aluminum	mg/kg	2710J	3180J	449J	5230J
Americium-241	pCi/g	0.00209U	0.00374U	0.00265UJ	0.00676UJ
Antimony	mg/kg	0.0589DNU	0.0604DNU	0.0565DNU	0.351DNU
Arsenic	mg/kg	5.27*	6.05*	0.603*	14*
Barium	mg/kg	30.6*	58.4*	7.18*	60.5*
Beryllium	mg/kg	0.268D	0.496D	0.0783D	1.24D
Cadmium	mg/kg	0.239D	0.059D	0.0283DU	2.16D
Calcium	mg/kg	8040DN	1560DN	298DN	2010DN
Chromium	mg/kg	5.35N	14N	1.75N	19N
Copper	mg/kg	6.73	5.12	0.451	22.8
Iron	mg/kg	11200D	22200D	4060D	45200D
Lead	mg/kg	6.44	16.1	1.83	23.8
Magnesium	mg/kg	4260	558	48.7	1470
Manganese	mg/kg	413*D	943*D	32.5*D	1060*D
Mercury	mg/kg	0.0148	0.0185	0.0149U	0.0301
Neptunium-237	pCi/g	-0.00043U	0.000422U	0.000899U	0.00115U
Nickel	mg/kg	14.5	6.41	0.843	51.9
PCB, total	µg/kg	18.2U	18.7U	18.2U	18.6U
Plutonium-238	pCi/g	0.000434U	0.000412U	0.000342U	-0.0011U
Plutonium-239/240	pCi/g	0.000868U	0.0033UJ	0.00273UJ	0.00219U
Selenium	mg/kg	0.468*DN	0.433*DN	0.113*DNU	0.773*DN
Silicon	mg/kg	299*N	348*N	147*N	232*N
Silver	mg/kg	0.301U	0.317U	0.293U	0.349U
Technetium-99	pCi/g	-0.0747U	-0.0667U	-0.115U	-0.104U
Thallium	mg/kg	0.0901D	0.0604DU	0.0565DU	0.453D
Uranium	µg/g	1.52	1.74	0.371J	6.49
Uranium-233/234	pCi/g	0.469	0.61	0.116	2.2
Uranium-235/236	pCi/g	0.0274	0.0384	0.00469UJ	0.115
Uranium-238	pCi/g	0.508	0.578	0.124	2.16
Zinc	mg/kg	41.7	35.3	5.43	196

^aAbbreviations and data qualifiers are as follows: * – duplicate analysis is not within control limits. D – the result is reported from a dilution. J – the reported result is estimated. N – sample spike recovery is not within control limits. U – undetected.

^bBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

Table 2.16. Soil and biota (vegetation) monitoring at ambient air monitoring stations – 2015

Parameter ^a	Location/results ^{b,c}			
	<i>A8 – On site at northwest boundary</i>		<i>T7 – On site near X-230L North Holding Pond</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.00111U	0.0045U	0.000274U	0.00376U
Neptunium-237	0.00033U	0.0019U	0U	-0.000746U
Plutonium-238	-0.000336U	-0.00064U	0.000908U	0U
Plutonium-239/240	0.00134U	0.00256U	0.000606U	0.00549UJ
Technetium-99	0.0165U	-0.0689U	0.00837U	-0.105U
Uranium	0.00809UJ	4.76	0.00251UJ	3.12
Uranium-233/234	0.00278UJ	1.59	0U	0.978
Uranium-235/236	0.00138U	0.0889	0U	0.0558
Uranium-238	0.0025UJ	1.59	0.000842U	1.04
	<i>A10 – On site on northwest segment of Perimeter Road</i>		<i>A29 – On site at OVEC</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.00251U	0.00431U	0.0016U	0.00409U
Neptunium-237	0.000645U	0.000869U	0.000632U	-0.000781U
Plutonium-238	0.000353U	0.00155U	0.000331U	-0.00127U
Plutonium-239/240	0.00177U	0.00155U	0.00232U	0.00824UJ
Technetium-99	0.0118U	0.00197U	0.00686U	-0.102U
Uranium	0.000679UJ	3.36	0.000703UJ	3.43
Uranium-233/234	0.00589J	1.06	0.000293U	1.07
Uranium-235/236	0.00147U	0.0591	-0.000364U	0.0659
Uranium-238	0U	1.12	0.000293U	1.14
	<i>A36 – On site at X-611 Water Treatment Plant</i>		<i>A6 – North of PORTS in Piketon</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.000893U	0.000902U	0U	0.00584UJ
Neptunium-237	0.000327U	0.000735U	-0.000653U	0.000515U
Plutonium-238	0.000658U	0.00244U	-0.000336U	0.000983U
Plutonium-239/240	0.000658U	0.00163UJ	0.00134U	0.0197
Technetium-99	0.00243U	-0.0332U	-0.0371U	-0.065U
Uranium	0.0148UJ	3	0.00178UJ	2.85
Uranium-233/234	0.0134J	1.01	0U	0.94
Uranium-235/236	0.000755U	0.0724	0U	0.0531
Uranium-238	0.00486UJ	0.998	0.000597U	0.949

Table 2.16. Soil and biota (vegetation) monitoring at ambient air monitoring stations – 2015 (continued)

Parameter ^a	Location/results ^{b,c}			
	<i>A24 – North of PORTS at Schuster Road</i>		<i>A41A - North of PORTS at Zahns Corner</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.000281U	0.00697UJ	0.00143U	0.00194U
Neptunium-237	0.000331U	0.000696U	-0.000956U	0U
Plutonium-238	-0.00159U	-0.00118U	-0.00122U	-0.00182U
Plutonium-239/240	0.00127U	0.00118U	0.000306U	0.0073UJ
Technetium-99	0.00525U	-0.0288U	0.0098U	-0.0618U
Uranium	0.00182UJ	3.49	0.00886UJ	2.78
Uranium-233/234	0.00122U	1.13	0.00263UJ	0.858
Uranium-235/236	0U	0.0647	0.000363U	0.0467
Uranium-238	0.00061U	1.16	0.00292UJ	0.928
	<i>A23 – Northeastern PORTS boundary</i>		<i>A12 – Eastern PORTS boundary</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.000834U	0.00665U	0.00147U	0.00153U
Neptunium-237	0U	0U	0U	0.000741U
Plutonium-238	-0.000308U	0.000764U	0U	0.00177U
Plutonium-239/240	0U	0.0122UJ	0.000681U	0.00354U
Technetium-99	0.0306U	-0.0603U	-0.0218U	-0.101U
Uranium	0.00595UJ	3.24	0.02J	3.04
Uranium-233/234	0.00143U	0.977	0.00877J	0.993
Uranium-235/236	0U	0.0512	0.000376U	0.0532
Uranium-238	0.002U	1.08	0.00665J	1.01
	<i>A15 – Southeast of PORTS on Loop Road</i>		<i>A3 – Southern PORTS boundary</i>	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0.000301U	0.00365U	0.00245U	0.00329U
Neptunium-237	-0.0003U	0.000702U	-0.000316U	0.00101U
Plutonium-238	0.000985U	-0.000706U	0.000344U	0.00185U
Plutonium-239/240	0.00131U	0.00707UJ	0.00138U	0.00649U
Technetium-99	0.00595U	-0.0512U	0.0127U	-0.0463U
Uranium	-0.000897UJ	3.08	0.00567UJ	2.37
Uranium-233/234	0.000302U	1.01	0.004UJ	0.845
Uranium-235/236	0U	0.0528	0.000383U	0.0391
Uranium-238	-0.000302U	1.03	0.00185U	0.789

Table 2.16. Soil and biota (vegetation) monitoring at ambient air monitoring stations – 2015 (continued)

Parameter ^a	Location/results ^{b,c}			
	A9 – South of PORTS		A28 – Southwest of PORTS on Camp Creek Road	
	Vegetation	Soil	Vegetation	Soil
Americium-241	0U	0.0101UJ	0.00248U	0.00228U
Neptunium-237	0U	0.000979U	0U	0.0022U
Plutonium-238	0U	0.0017U	-0.000598U	0U
Plutonium-239/240	0.00221U	0.0178	0.000599U	0.00173U
Technetium-99	0.0197U	-0.0476U	0.00129U	-0.0519U
Uranium	0.019J	2.4	0.0122UJ	2.85
Uranium-233/234	0.00657J	0.784	0.00559J	0.914
Uranium-235/236	0.00071U	0.0438	0.00183U	0.0442
Uranium-238	0.00628J	0.798	0.00383UJ	0.95
	<i>A37 – Background station near Otway</i>			
	Vegetation	Soil		
Americium-241	0.00122U	0.006U		
Neptunium-237	0.00168U	0.000705U		
Plutonium-238	0.000615U	0.00251U		
Plutonium-239/240	0.00185U	0.0088UJ		
Technetium-99	0.0219U	-0.0832U		
Uranium	0.00194UJ	3.15		
Uranium-233/234	0.000594U	1.07		
Uranium-235/236	0.00037U	0.0606		
Uranium-238	0.000594U	1.05		
	<i>Duplicate vegetation samples</i>		<i>Duplicate soil samples</i>	
	A3	A23	A9	A36
Americium-241	0.000281U	0.000587U	0.00954UJ	0.00783U
Neptunium-237	-0.000312U	0.000568U	0.000895U	0U
Plutonium-238	-0.000324U	0.000618U	0U	0.000848U
Plutonium-239/240	0.000649U	0.00154U	0.0168UJ	0.00934UJ
Technetium-99	0.0278U	0.0243U	-0.134U	-0.0145U
Uranium	0.00792UJ	0.00568UJ	2.22	3.17
Uranium-233/234	0.00174U	0.00382UJ	0.698	1.04
Uranium-235/236	0.00036U	0U	0.0389	0.0622
Uranium-238	0.00261U	0.00191U	0.742	1.06

^aAll parameters are measured in pCi/g with the exception of uranium which is measured in µg/g.

^bAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^cBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

Table 2.17. Biota (fish) monitoring program results – 2015

Parameter	Unit	Location/fish/results ^{a,b}	
		<i>Big Beaver Creek (RW-13)^c</i>	<i>Big Beaver Creek (RW-15) bass</i>
Americium-241	pCi/g	0.00082U	0.00446UJ
Neptunium-237	pCi/g	-0.00116U	0.000921U
Plutonium-238	pCi/g	0U	-0.000445U
Plutonium-239/240	pCi/g	0.000293U	0.000887U
PCB, total	µg/kg	20.8	21.8
Technetium-99	pCi/g	-0.0223U	0.0198U
Uranium	µg/g	0.0246UJ	0.000289U
Uranium-233/234	pCi/g	0.0251U	0U
Uranium-235/236	pCi/g	0.0173U	0.000624U
Uranium-238	pCi/g	0.00557U	0U
		<i>Little Beaver Creek (RW-8) bass</i>	<i>Little Beaver Creek (RW-8) bass (duplicate sample)</i>
Americium-241	pCi/g	0.000817U	0.00208U
Neptunium-237	pCi/g	0.00197U	-0.000269U
Plutonium-238	pCi/g	0.000366U	0.000594U
Plutonium-239/240	pCi/g	0.000366U	0.000297U
PCB, total	µg/kg	278	196
Technetium-99	pCi/g	-0.0939U	-0.0917U
Uranium	µg/g	-0.000813U	0.00352U
Uranium-233/234	pCi/g	0.00301UJ	0.0027UJ
Uranium-235/236	pCi/g	0U	0.00067U
Uranium-238	pCi/g	-0.000274U	0.00108U

^aAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^bBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

^cThe sample analyzed for radionuclides was large mouth bass/catfish and the sample analyzed for PCBs was sunfish.

Table 2.18. Biota (crops) monitoring program results – 2015

Parameter	Unit	Location/crop/results ^{a,b}		
		<i>Off-site #2 corn</i>	<i>Off-site #2 tomatoes</i>	<i>Off-site #3 okra</i>
Americium-241	pCi/g	0.00106U	0.00138U	0.00169U
Neptunium-237	pCi/g	0.000654U	0U	0U
Plutonium-238	pCi/g	-0.000289U	-0.000728U	-0.00105U
Plutonium-239/240	pCi/g	0.00116U	0.00146U	0.00174U
Technetium-99	pCi/g	-0.0505U	-0.0427U	0.00531U
Uranium	µg/g	0.000641U	0.00259U	0.000969U
Uranium-233/234	pCi/g	0.000534U	0.000817U	0.000819U
Uranium-235/236	pCi/g	-0.000332U	0.000339U	0.000339U
Uranium-238	pCi/g	0.000267U	0.000817U	0.000273U
		<i>Off-site #3 corn</i>	<i>Off-site #3 corn (duplicate sample)</i>	<i>Off-site #3 beans</i>
Americium-241	pCi/g	0.0015U	0.000835U	0.0011U
Neptunium-237	pCi/g	-0.000915U	-0.000304U	-0.000324U
Plutonium-238	pCi/g	0.00126U	-0.000333U	0.000348U
Plutonium-239/240	pCi/g	0.00063U	0.000333U	0.000696U
Technetium-99	pCi/g	-0.0607U	-0.0248U	-0.0109U
Uranium	µg/g	0.00182U	-0.000814U	0.000873U
Uranium-233/234	pCi/g	0.000558U	0.000821U	0U
Uranium-235/236	pCi/g	0.000347U	0U	0U
Uranium-238	pCi/g	0.000558U	-0.000274U	0.000293U
		<i>Off-site #3 tomatoes</i>	<i>Off-site #5 berries</i>	<i>Off-site #5 corn</i>
Americium-241	pCi/g	0.00203U	0.00166U	0.00181U
Neptunium-237	pCi/g	-0.000618U	0U	0.000927U
Plutonium-238	pCi/g	0.000648U	-0.00102U	0U
Plutonium-239/240	pCi/g	0.000324U	0.00102U	0.00146U
Technetium-99	pCi/g	-0.04U	0.0748U	-0.0602U
Uranium	µg/g	0.00165U	0.000149U	0.000921U
Uranium-233/234	pCi/g	0.000277U	0.000519U	0.00311U
Uranium-235/236	pCi/g	0U	0.000323U	0.000322U
Uranium-238	pCi/g	0.000555U	0U	0.000259U

Table 2.18. Biota (crops) monitoring program results – 2015 (continued)

Parameter	Unit	Location/results ^{a,b}		
		<i>Off-site #6 corn</i>	<i>Off-site #6 tomatoes</i>	<i>Off-site #6 tomatoes (duplicate sample)</i>
Americium-241	pCi/g	0.00234UJ	0.00112U	0.00182U
Neptunium-237	pCi/g	-0.000314U	0.000363U	0.000318U
Plutonium-238	pCi/g	-0.000309U	0U	-0.000917U
Plutonium-239/240	pCi/g	0U	0.00217U	0.00122U
Technetium-99	pCi/g	-0.00531U	-0.0216U	-0.0576U
Uranium	µg/g	0.00015U	0.00198U	0.0000000888U
Uranium-233/234	pCi/g	0.00026U	0.00112U	0.000553U
Uranium-235/236	pCi/g	0.000323U	0.000695U	0U
Uranium-238	pCi/g	0U	0.000559U	0U
		<i>Off-site #8 corn</i>	<i>Off-site #8 tomatoes</i>	
Americium-241	pCi/g	0.00131U	0.00137U	
Neptunium-237	pCi/g	0U	0.000955U	
Plutonium-238	pCi/g	-0.000614U	0U	
Plutonium-239/240	pCi/g	0.000307U	0U	
Technetium-99	pCi/g	-0.0438U	-0.0086U	
Uranium	µg/g	0.000326U	0.00188U	
Uranium-233/234	pCi/g	0.00085U	0U	
Uranium-235/236	pCi/g	0.000704U	0.000359U	
Uranium-238	pCi/g	0U	0.000577U	

^aAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^bBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

Table 2.19. Biota (deer) monitoring program results – 2015

Parameter	Unit	January 2015 ^{a,b}	March 2015 ^{a,b}	May 2015 ^{a,b}
<i>kidney</i>				
Americium-241	pCi/g	-0.000307U	0.00201U	0.000565U
Neptunium-237	pCi/g	0.000298U	0.000282U	0U
Plutonium-238	pCi/g	-0.000333U	0.000328U	0.000301U
Plutonium-239/240	pCi/g	0.000667U	0.000983U	0.00271UJ
Technetium-99	pCi/g	-0.0871U	0.00917U	-0.00913U
Uranium	µg/g	0.000000459U	0.00259U	0.000465UJ
Uranium-233/234	pCi/g	0.000286U	0.00218U	0.000807U
Uranium-235/236	pCi/g	0U	0.000338U	0.001U
Uranium-238	pCi/g	0U	0.000816U	0U
<i>Liver</i>				
Americium-241	pCi/g	0.000614U	0.000239U	0.00313UJ
Neptunium-237	pCi/g	0U	-0.000289U	-0.000318U
Plutonium-238	pCi/g	0U	-0.000318U	0U
Plutonium-239/240	pCi/g	0.000662U	0.000953U	0.000591U
Technetium-99	pCi/g	-0.072U	-0.0509U	0.0146U
Uranium	µg/g	-0.00019U	0.000584U	0.00657UJ
Uranium-233/234	pCi/g	0.000564U	0.00456U	0.00189U
Uranium-235/236	pCi/g	0.0014U	0.00126U	0.000335U
Uranium-238	pCi/g	-0.000282U	0U	0.00215UJ
<i>Muscle</i>				
Americium-241	pCi/g	0.00086U	0.000708U	0.00112U
Neptunium-237	pCi/g	0.00031U	0.000537U	-0.00184U
Plutonium-238	pCi/g	0.000709U	0.000312U	0.000581U
Plutonium-239/240	pCi/g	0.000355U	0.00187U	0.00029U
Technetium-99	pCi/g	-0.049U	-0.0177U	0.0165U
Uranium	µg/g	0.000156U	-0.000663U	0.000000133UJ
Uranium-233/234	pCi/g	0.000813U	0.00387UJ	0.000826U
Uranium-235/236	pCi/g	0.000337U	0.000344U	0U
Uranium-238	pCi/g	0U	-0.000277U	0U

**Table 2.19. Biota (deer) monitoring program results – 2015
 (continued)**

Parameter	Unit	May 2015 ^{a,b}	September 2015 ^{a,b}
<i>kidney</i>			
Americium-241	pCi/g	0.000822U	0.000895U
Neptunium-237	pCi/g	0U	0.000687U
Plutonium-238	pCi/g	-0.000285U	0.000339U
Plutonium-239/240	pCi/g	0.000569U	0.00102U
Technetium-99	pCi/g	0.0269U	-0.158U
Uranium	µg/g	0.000811UJ	0.00101U
Uranium-233/234	pCi/g	0.000282U	-0.000285U
Uranium-235/236	pCi/g	0.00175U	0.000354U
Uranium-238	pCi/g	0U	0.000285U
<i>Liver</i>			
Americium-241	pCi/g	0.0014U	0.00116U
Neptunium-237	pCi/g	-0.000304U	0.000643U
Plutonium-238	pCi/g	0.000292U	0.000304U
Plutonium-239/240	pCi/g	0.000585U	0.000912U
Technetium-99	pCi/g	0.0118U	-0.0813U
Uranium	µg/g	0.00273UJ	0.0013U
Uranium-233/234	pCi/g	0.00163U	0.000827U
Uranium-235/236	pCi/g	0.000675U	0.00103U
Uranium-238	pCi/g	0.000814U	0.000276U
<i>Muscle</i>			
Americium-241	pCi/g	0U	0.0031U
Neptunium-237	pCi/g	0U	0U
Plutonium-238	pCi/g	0U	0.000326U
Plutonium-239/240	pCi/g	0.000572U	0.00228U
Technetium-99	pCi/g	0.0433U	-0.0544U
Uranium	µg/g	0.000173UJ	0.000984U
Uranium-233/234	pCi/g	0.0021U	0.00138U
Uranium-235/236	pCi/g	0.000373U	0.000344U
Uranium-238	pCi/g	0U	0.000277U

^aAbbreviations and data qualifiers are as follows: U – undetected. J – the reported result is estimated.

^bBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

Table 2.20. Biota (off-site dairy) monitoring program results– 2015

Parameter	Units	Milk ^{a,b}	Eggs ^{a,b}
Americium-241	pCi/g	0.00106U	0.00199U
Neptunium-237	pCi/g	0U	0U
Plutonium-238	pCi/g	0U	0.000561U
Plutonium-239/240	pCi/g	0.00165U	0.000562U
Technetium-99	pCi/g	-0.000454U	-0.0498U
Uranium	µg/g	0.000699U	0.00149U
Uranium-233/234	pCi/g	0.00047U	0.00198U
Uranium-235/236	pCi/g	0U	0.00141U
Uranium-238	pCi/g	0.000235U	0.000283U

^aAbbreviations and data qualifiers are as follows: U – undetected.

^bBecause of the statistical nature of radiation detection, results for samples that have no radioactivity are often negative values because background radioactivity is subtracted out.

This page intentionally left blank.

3. DOSE

This section provides summary tables of air emissions and dose assessments completed by DOE for compliance with the National Emission Standards for Hazardous Air Pollutants for airborne radionuclide emissions. The following tables are provided in this section:

- Table 3.1. Emissions (Ci/year) from DOE air emission sources – 2015
- Table 3.2. Predicted radiation doses from airborne releases at PORTS – 2015
- Table 3.3. Dose calculations for ambient air monitoring stations – 2015.

Table 3.1. Emissions (Ci/year) from DOE air emission sources – 2015

Radionuclide	Group 1 ^a	Group 2 ^b	Group 3 ^c	DUF ₆ facility ^d
Americium-241	3.663E-07	-	6.188E-07	-
Neptunium-237	2.701E-07	-	9.455E-06	-
Plutonium-238	0	-	6.403E-08	-
Plutonium-239/240	2.095E-07	-	3.621E-06	-
Technetium-99	4.889E-03	1.791E-03	2.452E-02	-
Uranium-233/234	1.057E-03	5.335E-04	3.563E-04	1.38E-06
Uranium-235	4.990E-05	2.884E-05	1.480E-05	6.31E-08
Uranium-238	4.697E-04	5.466E-04	9.683E-05	3.38E-06
Thorium-228	3.740E-08	0	3.390E-10	-
Thorium-230	3.750E-05	4.057E-06	3.400E-10	-
Thorium-231	4.967E-05	2.884E-05	4.720E-06	1.99E-07
Thorium-232	2.290E-09	0	2.070E-11	-
Thorium-234	4.676E-04	5.466E-04	4.070E-05	1.82E-05
Protactinium-234m	4.676E-04	5.466E-04	4.070E-05	1.82E-05
Total	7.489E-03	4.026E-03	2.509E-02	4.142E-05

^aGroup 1 consists of the X-326 Top Purge/Emergency Jet Vents, X-326 Seal Exhaust Vents, X-710 Vents, XT-847 Glove Box, and X-622 Groundwater Treatment Facility.

^bGroup 2 consists of the X-344A Gulper Vent and X-344A Cold Trap Vent.

^cGroup 3 consists of the X-330 Vents, X-333 Vents, X-700 Vents, X-705 Vents, X-623 Groundwater Treatment Facility, X-624 Groundwater Treatment Facility, and X-627 Groundwater Treatment Facility.

^dDUF₆ – depleted uranium hexafluoride.

Note: Measurements are provided in scientific notation. The number and sign (+ or -) to the right of the “E” indicate the number of places to the right or left of the decimal point. For example, 3.4E-04 is 0.00034 (the decimal point moves four places to the left); 2.1E+02 is 210 (the decimal point moves two places to the right).

Table 3.2. Predicted radiation doses from airborne releases at PORTS – 2015

Effective dose to:	DOE releases	All PORTS releases (DOE and Centrus)
Maximally exposed individual (mrem/year)	0.037	0.037
Population ^a (person-rem/year)	0.224	0.224

^aPopulation within 50 miles (80 kilometers) of plant site.

Table 3.3. Dose calculations for ambient air monitoring stations – 2015

Station	Parameter ^a	Dose ^b (mrem/year)	Total dose for station ^c	Net dose for station ^d
A3	Americium-241	1.6E-09		
	Neptunium-237	8.4E-10		
	Plutonium-238	4.4E-10		
	Plutonium-239/240	1.2E-09		
	Technetium-99	4.7E-03		
	Uranium-233/234	7.7E-06		
	Uranium-235/236	4.6E-07	(0.0047)	
	Uranium-238	9.1E-06	4.7E-03	0
A6	Americium-241	2.0E-09		
	Neptunium-237	1.1E-09		
	Plutonium-238	1.4E-09		
	Plutonium-239/240	1.3E-09		
	Technetium-99	5.5E-03		
	Uranium-233/234	5.5E-07		
	Uranium-235/236	1.4E-07	(0.0055)	(0.00080)
	Uranium-238	6.1E-07	5.5E-03	8.0E-04
A8	Americium-241	1.6E-09		
	Neptunium-237	1.3E-09		
	Plutonium-238	7.1E-10		
	Plutonium-239/240	1.3E-09		
	Technetium-99	5.1E-03		
	Uranium-233/234	5.8E-06		
	Uranium-235/236	3.5E-07	(0.0051)	(0.00040)
	Uranium-238	2.7E-06	5.1E-03	4.0E-04
A9	Americium-241	1.1E-09		
	Neptunium-237	5.7E-10		
	Plutonium-238	9.3E-10		
	Plutonium-239/240	1.1E-09		
	Technetium-99	5.7E-03		
	Uranium-233/234	6.3E-06		
	Uranium-235/236	3.8E-07	(0.0057)	(0.0010)
	Uranium-238	7.6E-06	5.7E-03	1.0E-03

Table 3.3. Dose calculations for ambient air monitoring stations – 2015 (continued)

Station	Parameter ^a	Dose ^b (mrem/year)	Total dose for station ^c	Net dose for station ^d
A10	Americium-241	1.3E-05		
	Neptunium-237	1.5E-07		
	Plutonium-238	4.6E-09		
	Plutonium-239/240	1.5E-08		
	Technetium-99	4.9E-03		
	Uranium-233/234	3.0E-06		
	Uranium-235/236	2.0E-07	(0.0049)	(0.00020)
A12	Uranium-238	2.9E-06	4.9E-03	2.0E-04
	Americium-241	1.2E-05		
	Neptunium-237	3.7E-08		
	Plutonium-238	1.1E-09		
	Plutonium-239/240	7.0E-09		
	Technetium-99	3.6E-03		
	Uranium-233/234	3.6E-06		
A15	Uranium-235/236	2.8E-07	(0.0036)	
	Uranium-238	3.0E-06	3.6E-03	0
	Americium-241	1.1E-05		
	Neptunium-237	1.0E-07		
	Plutonium-238	1.9E-08		
	Plutonium-239/240	1.4E-08		
	Technetium-99	4.8E-03		
A23	Uranium-233/234	4.7E-06		
	Uranium-235/236	3.2E-07	(0.0048)	(0.00010)
	Uranium-238	5.7E-06	4.8E-03	1.0E-04
	Americium-241	1.4E-05		
	Neptunium-237	8.4E-08		
	Plutonium-238	2.3E-09		
	Plutonium-239/240	1.4E-08		
A24	Technetium-99	5.4E-03		
	Uranium-233/234	5.5E-06		
	Uranium-235/236	2.5E-07	(0.0054)	(0.00070)
	Uranium-238	2.1E-06	5.4E-03	7.0E-04
	Americium-241	1.2E-05		
	Neptunium-237	1.7E-07		
	Plutonium-238	3.6E-09		
A24	Plutonium-239/240	1.7E-08		
	Technetium-99	5.5E-03		
	Uranium-233/234	2.5E-06		
	Uranium-235/236	1.3E-07	(0.0055)	(0.00080)
	Uranium-238	1.7E-06	5.5E-03	8.0E-04

Table 3.3. Dose calculations for ambient air monitoring stations – 2015 (continued)

Station	Parameter ^a	Dose ^b (mrem/year)	Total dose for station ^c	Net dose for station ^d
A28	Americium-241	1.5E-05		
	Neptunium-237	2.6E-08		
	Plutonium-238	8.1E-10		
	Plutonium-239/240	7.5E-09		
	Technetium-99	5.8E-03		
	Uranium-233/234	4.3E-07		
	Uranium-235/236	2.6E-07	(0.0059)	(0.0012)
	Uranium-238	8.5E-07	5.9E-03	1.2E-03
A29	Americium-241	8.1E-06		
	Neptunium-237	1.0E-07		
	Plutonium-238	1.8E-09		
	Plutonium-239/240	9.7E-09		
	Technetium-99	5.3E-03		
	Uranium-233/234	7.8E-07		
	Uranium-235/236	1.4E-07	(0.0053)	(0.00060)
	Uranium-238	5.7E-07	5.3E-03	6.0E-04
A36	Americium-241	2.0E-09		
	Neptunium-237	1.4E-09		
	Plutonium-238	7.3E-10		
	Plutonium-239/240	1.3E-09		
	Technetium-99	2.6E-03		
	Uranium-233/234	4.9E-06		
	Uranium-235/236	3.0E-07	(0.0026)	
	Uranium-238	4.9E-06	2.6E-03	0
A37	Americium-241	2.2E-09		
	Neptunium-237	4.8E-10		
	Plutonium-238	1.7E-09		
	Plutonium-239/240	1.4E-09		
	Technetium-99	4.7E-03		
	Uranium-233/234	3.9E-07		
	Uranium-235/236	1.8E-07	(0.0047)	
	Uranium-238	6.0E-07	4.7E-03	-
A41A	Americium-241	1.9E-09		
	Neptunium-237	9.3E-10		
	Plutonium-238	9.3E-10		
	Plutonium-239/240	7.1E-10		
	Technetium-99	5.9E-03		
	Uranium-233/234	6.0E-07		
	Uranium-235/236	1.1E-07	(0.0059)	(0.0012)
	Uranium-238	3.9E-07	5.9E-03	1.2E-03

Table 3.3. Dose calculations for ambient air monitoring stations – 2015 (continued)

Station	Parameter ^a	Dose ^b (mrem/year)	Total dose for station ^c	Net dose for station ^d
T7	Americium-241	1.6E-09		
	Neptunium-237	8.7E-10		
	Plutonium-238	9.7E-10		
	Plutonium-239/240	1.3E-09		
	Technetium-99	3.6E-03		
	Uranium-233/234	2.8E-04		
	Uranium-235/236	8.2E-06	(0.0039)	
	Uranium-238	3.3E-06	3.9E-03	0

^aParameters listed in **bold** type were detected at least once in the samples collected in 2015 (see Table 2.10).

^bThe dose calculation is based on the maximum detection of each parameter at each station. For parameters that were not detected, half of the highest undetected result for the parameter was used to calculate the activity of each parameter in ambient air that is the basis for the dose. Measurements are provided in scientific notation. The number and sign (+ or -) to the right of the "E" indicate the number of places to the right or left of the decimal point. For example, 3.4E-04 is 0.00034 (the decimal point moves four places to the left); 2.1E+02 is 210 (the decimal point moves two places to the right).

^cThe total dose is provided in scientific notation and standard numeric format (in parentheses).

^dThe net dose is calculated by subtracting the total dose at Station A37 (background) from the total dose calculated for each station (the net dose is recorded as zero for stations with a gross dose less than the background station). The net dose is provided in scientific notation and standard numeric format (in parentheses).

This page intentionally left blank.

4. GROUNDWATER

This section summarizes analytical results for routine groundwater monitoring at PORTS in 2015 at the following locations:

- X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility
- Peter Kiewit (PK) Landfill
- Quadrant I Groundwater Investigative (5-Unit) Area
- X-749A Classified Materials Disposal Facility
- Quadrant II Groundwater Investigative (7-Unit) Area
- X-701B Former Holding Pond
- X-633 Former Recirculating Cooling Water Complex
- X-616 Former Chromium Sludge Surface Impoundments
- X-740 Former Waste Oil Handling Facility
- X-611A Former Lime Sludge Lagoons
- X-735 Landfills
- X-734 Landfills
- X-533 Former Switchyard Complex
- X-344C Former Hydrogen Fluoride Storage Building
- Surface water monitoring locations
- Exit pathway monitoring locations.

Results for radiological parameters and VOCs are reported in this section. Only those VOCs that were detected in at least one sampling event are listed in this section.

All results are included for radiological parameters, even if a specific constituent was not detected at a specific well or location during any sampling event in 2015. Sampling for radionuclides is not part of the monitoring programs for PK Landfill, X-633 Former Recirculating Cooling Water Complex, X-616 Former Chromium Sludge Surface Impoundments, X-740 Former Waste Oil Handling Facility, X-611A Former Lime Sludge Lagoons, X-533 Former Switchyard Complex, and X-344C Former Hydrogen Fluoride Storage Building.

Results for chromium at the X-616 Former Chromium Sludge Surface Impoundments are included in this section because chromium is a primary contaminant in this area. Results are provided for metals at the X-633 Former Recirculating Cooling Water Complex, X-611A Former Lime Sludge Lagoons, and X-533 Former Switchyard Complex because metals are the only analytical parameters for these areas.

Two VOCs, acetone and methylene chloride, were frequently detected in both environmental and blank samples (field and trip blanks) collected in 2015. Acetone and methylene chloride are common laboratory contaminants that are not typically detected in the PORTS groundwater plumes. Detections of acetone and methylene chloride are often qualified by the laboratory with a "B", which indicates that the analyte was also detected in the laboratory blank associated with the environmental sample and may be present due to laboratory contamination.

Other VOCs, including trichloroethene, 2-butanone, chloroform, and chloromethane were detected in trip and/or field blanks during 2015. These detections indicate that samples (both environmental samples and blank samples) may become contaminated with low concentrations of VOCs during other portions of the sampling process, although contamination can still occur in the laboratory. Other sources of contamination may include storage areas for sampling equipment (such as bottles and blank water), areas

in which samples are collected or prepared, sample containers, and storage areas after samples are collected (such as refrigerators or sample shipping containers).

The primary purpose of the groundwater data is to determine the nature and extent of contamination in groundwater and associated surface water at PORTS. Data collected in 2015 meet this purpose.

Complete groundwater monitoring results for sampling completed as required by the *Integrated Groundwater Monitoring Plan* (DOE 2014, DOE 2015) are provided in the *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant* (DOE 2016). The *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant* also provides the following information not included in this Data Report:

- Results for special studies conducted during 2015 at the X-633 Former Recirculating Cooling Water Complex and X-630 Former Recirculating Cooling Water Complex.
- Results for duplicate samples (samples collected from the same location, at the same time, and from the same sampling device as the regular sample), which are collected at a frequency of one per ten sampling locations per groundwater monitoring area. Duplicate samples are analyzed for the same parameters as the regular sample associated with the sampling location.

The following tables are included in this section:

- Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015
- Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015
- Table 4.3. VOCs detected at the PK Landfill – 2015
- Table 4.4. VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015
- Table 4.5. Results for radionuclides at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015
- Table 4.6. VOCs detected at the X-749A Classified Materials Disposal Facility – 2015
- Table 4.7. Results for radionuclides at the X-749A Classified Materials Disposal Facility – 2015
- Table 4.8. VOCs detected at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015
- Table 4.9. Results for radionuclides at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015
- Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015
- Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015
- Table 4.12. Results for chromium at the X-633 Former Recirculating Cooling Water Complex – 2015

- Table 4.13. VOCs detected at the X-616 Former Chromium Sludge Surface Impoundments – 2015
- Table 4.14. Results for chromium at the X-616 Former Chromium Sludge Surface Impoundments – 2015
- Table 4.15. VOCs detected at the X-740 Former Waste Oil Handling Facility – 2015
- Table 4.16. Results for beryllium and chromium at the X-611A Former Lime Sludge Lagoons – 2015
- Table 4.17. VOCs detected at the X-735 Landfills – 2015
- Table 4.18. Results for radionuclides at the X-735 Landfills – 2015
- Table 4.19. VOCs detected at the X-734 Landfills – 2015
- Table 4.20. Results for radionuclides at the X-734 Landfills – 2015
- Table 4.21. Results for cadmium and nickel at the X-533 Former Switchyard Complex – 2015
- Table 4.22. VOCs detected at the X-344C Former Hydrogen Fluoride Storage Building – 2015
- Table 4.23. VOCs detected at surface water monitoring locations – 2015
- Table 4.24. Results for radionuclides at surface water monitoring locations – 2015.

Tables for VOCs and radionuclides detected at exit pathway monitoring location F-29B are not provided because none were detected. Results for exit pathway monitoring locations sampled during 2015 (that are part of the monitoring programs for other areas) are provided in the tables for their respective monitoring areas as follows:

- Tables 4.1 and 4.2: VOCs and radionuclides detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility (wells X749-14B, X749-44G, X749-45G, X749-64B, X749-68G, X749-96G, X749-97G, and X749-98G).
- Tables 4.10 and 4.11: VOCs and radionuclides detected at X-701B Former Holding Pond area well X701-48G.
- Tables 4.23 and 4.24: VOCs and radionuclides detected at surface water monitoring locations BRC-SW02, LBC-SW04, UND-SW02, and WDD-SW03.

The following laboratory data qualifiers are used in the tables in this section:

Data qualifier	Meaning
B	Inorganics (metals): the result was less than the practical quantitation limit but greater than or equal to the instrument detection limit. Organics (VOCs): the analyte was detected in the laboratory blank sample.
E	Organics (VOCs): the result exceeds the calibration range.
J	The reported value is estimated.
U	Undetected

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
F-27G	1,1-Dichloroethane	µg/L			0.87 J		
	Acetone	µg/L			8.5 BJ		
	cis-1,2-Dichloroethene	µg/L			0.9 J		
	Trichloroethene	µg/L			0.18 J		
PK-08G	cis-1,2-Dichloroethene	µg/L			0.55 J		
	Trichloroethene	µg/L			14		
PK-09G	cis-1,2-Dichloroethene	µg/L			7.7		
	Trichloroethene	µg/L			470		
STSW-101G	1,1,1-Trichloroethane	µg/L		8		6.4	
	1,1,2-Trichloroethane	µg/L		0.74 J		0.67 J	
	1,1-Dichloroethane	µg/L		19		17	
	1,1-Dichloroethene	µg/L		47		38	
	1,2-Dichloroethane	µg/L		3.8		3	
	Chloroform	µg/L		1.7		1.3	
	cis-1,2-Dichloroethene	µg/L		16		12	
	Tetrachloroethene	µg/L		0.88 J		0.96 J	
STSW-102G	Trichloroethene	µg/L		51		42	
	1,1,1-Trichloroethane	µg/L		6.7		7.8	
	1,1,2-Trichloroethane	µg/L		0.34 J		0.36 J	
	1,1-Dichloroethane	µg/L		63		80	
	1,1-Dichloroethene	µg/L		39		43	
	1,2-Dichloroethane	µg/L		21		31	
	Benzene	µg/L		0.16 U		0.17 J	
	Chloroform	µg/L		2.9		3.5	
	cis-1,2-Dichloroethene	µg/L		20		26	
	trans-1,2-Dichloroethene	µg/L		0.18 J		0.21 J	
WP-01G	Trichloroethene	µg/L		150		180	
	Vinyl chloride	µg/L		0.12 J		0.17 J	
	Methylene chloride	µg/L		0.34 BJ		0.32 U	
	WP-03G	Acetone	µg/L	1.9 U	1.9 U	3.3 J	1.9 U
		Methylene chloride	µg/L	0.32 U	0.43 BJ	0.32 U	0.32 U
WP-04G	Methylene chloride	µg/L		0.35 BJ		0.32 U	
WP-05G	Methylene chloride	µg/L		0.32 BJ		0.32 U	
X120-03G	Chloroform	µg/L			0.4 J		
X120-05G	Acetone	µg/L			8.3 BJ		
	Trichloroethene	µg/L			2.2		
X120-06B	Acetone	µg/L			7.5 BJ		
X120-08G	1,1,1-Trichloroethane	µg/L			4.4		
	1,1,2-Trichloroethane	µg/L			0.61 J		
	1,1-Dichloroethane	µg/L			7.7		
	1,1-Dichloroethene	µg/L			28		
	1,2-Dichloroethane	µg/L			0.93 J		
	Acetone	µg/L			14		
	Chloroform	µg/L			0.94 J		
	cis-1,2-Dichloroethene	µg/L			0.65 J		
	Trichloroethene	µg/L			16		
	X120-09G	1,1,1-Trichloroethane	µg/L			4.6	
1,1,2-Trichloroethane		µg/L			0.6 J		
1,1-Dichloroethane		µg/L			8.5		
1,1-Dichloroethene		µg/L			23		

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X120-09G	1,2-Dichloroethane	µg/L			0.93 J	
	Chloroform	µg/L			0.87 J	
	cis-1,2-Dichloroethene	µg/L			0.98 J	
	Tetrachloroethene	µg/L			0.28 J	
	Trichloroethene	µg/L			16	
X120-10G	1,1,1-Trichloroethane	µg/L			4.6	
	1,1,2-Trichloroethane	µg/L			1	
	1,1-Dichloroethane	µg/L			12	
	1,1-Dichloroethene	µg/L			36	
	1,2-Dichloroethane	µg/L			1.2	
	Chloroform	µg/L			1.3	
	cis-1,2-Dichloroethene	µg/L			0.66 J	
X120-11G	Trichloroethene	µg/L			8.9	
	1,1-Dichloroethene	µg/L		0.46 J		0.84 J
	cis-1,2-Dichloroethene	µg/L		6.8		12
	trans-1,2-Dichloroethene	µg/L		0.29 J		0.3 J
X749-04G	Trichloroethene	µg/L		240		230
	Acetone	µg/L			10 J	
	Chloroform	µg/L			0.38 J	
	cis-1,2-Dichloroethene	µg/L			0.55 J	
	Tetrachloroethene	µg/L			6.2	
X749-05G	Trichloroethene	µg/L			520	
	1,1-Dichloroethane	µg/L			0.52 J	
	1,1-Dichloroethene	µg/L			0.24 J	
	Acetone	µg/L			6.9 J	
	Carbon tetrachloride	µg/L			0.41 J	
	Chloroform	µg/L			0.93 J	
	cis-1,2-Dichloroethene	µg/L			0.88 J	
X749-06G	Tetrachloroethene	µg/L			1.3	
	Trichloroethene	µg/L			77	
	1,1,1-Trichloroethane	µg/L		24		30
	1,1,2-Trichloroethane	µg/L		2.8		3.8 J
	1,1-Dichloroethane	µg/L		110		210
	1,1-Dichloroethene	µg/L		96		140
	1,2-Dichloroethane	µg/L		2.8		1.3 U
	Chloroform	µg/L		12		18
	cis-1,2-Dichloroethene	µg/L		31		52
	Tetrachloroethene	µg/L		11		16
X749-07G	Trichloroethene	µg/L		440		720
	Vinyl chloride	µg/L		0.6 J		1 U
	1,1,1-Trichloroethane	µg/L		12		16
	1,1,2-Trichloroethane	µg/L		0.32 J		0.27 U
	1,1-Dichloroethane	µg/L		15		23
	1,1-Dichloroethene	µg/L		20		21
	1,2-Dichloroethane	µg/L		7.1		10
	Chloroform	µg/L		1.4		1.8
	cis-1,2-Dichloroethene	µg/L		4.4		5.3
	Tetrachloroethene	µg/L		0.51 J		0.67 J
	Trichloroethene	µg/L		72		80
Vinyl chloride	µg/L		0.18 J		0.1 U	

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-08G	1,1,1-Trichloroethane	µg/L		7.3		3.8
	1,1-Dichloroethane	µg/L		1.8		0.89J
	1,1-Dichloroethene	µg/L		8.6		3.7
	Chloroform	µg/L		0.21J		0.16U
	cis-1,2-Dichloroethene	µg/L		2.1		0.92J
	Trichloroethene	µg/L		15		7.3
X749-09GA	1,1,1-Trichloroethane	µg/L		6.9		14
	1,1-Dichloroethane	µg/L		2.2		4.3
	1,1-Dichloroethene	µg/L		5.4		11
	Chloroform	µg/L		0.17J		0.33J
	cis-1,2-Dichloroethene	µg/L		1.6		2.9
	Trichloroethene	µg/L		6.1		9.1
X749-10GA	1,1-Dichloroethane	µg/L		4.6		3.3
	1,1-Dichloroethene	µg/L		10		6.8
	Chloroethane	µg/L		0.51J		0.41U
	cis-1,2-Dichloroethene	µg/L		3.1		2.3
	Trichloroethene	µg/L		0.34J		0.25J
	Vinyl chloride	µg/L		1.8		1.4
X749-13G	1,1,1-Trichloroethane	µg/L		4.1		4.6
	1,1-Dichloroethane	µg/L		1.4		1.5
	1,1-Dichloroethene	µg/L		8		8.4
	Chloroform	µg/L		0.32J		0.35J
	cis-1,2-Dichloroethene	µg/L		1.5		1.4
	Trichloroethene	µg/L		12		13
X749-20G	1,1,1-Trichloroethane	µg/L			0.69J	
	1,1-Dichloroethane	µg/L			1.9	
	1,1-Dichloroethene	µg/L			1.9	
	1,2-Dichloroethane	µg/L			0.39J	
	Acetone	µg/L			16B	
	cis-1,2-Dichloroethene	µg/L			1.6	
	Trichloroethene	µg/L			16	
X749-21G	1,1,1-Trichloroethane	µg/L		5.2		4.9
	1,1-Dichloroethane	µg/L		1.7		1.4
	1,1-Dichloroethene	µg/L		3.6		2.9
	cis-1,2-Dichloroethene	µg/L		0.79J		0.58J
	Trichloroethene	µg/L		6.7		5.8
X749-22G	1,1-Dichloroethane	µg/L		2.8		3
	1,1-Dichloroethene	µg/L		2.9		3.4
	cis-1,2-Dichloroethene	µg/L		0.66J		0.87J
	Vinyl chloride	µg/L		0.53J		0.52J
X749-26G	1,1,1-Trichloroethane	µg/L		4.8		5.7
	1,1-Dichloroethane	µg/L		13		16
	1,1-Dichloroethene	µg/L		20		19
	1,2-Dichloroethane	µg/L		6.3		8
	Chloroform	µg/L		1.2		1.3
	cis-1,2-Dichloroethene	µg/L		2.8		3.5
	Tetrachloroethene	µg/L		0.23J		0.21J
	Trichloroethene	µg/L		31		33
X749-27G	1,1,1-Trichloroethane	µg/L		37		18
	1,1,2-Trichloroethane	µg/L		1.5		0.97J

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-27G	1,1-Dichloroethane	µg/L		100		30
	1,1-Dichloroethene	µg/L		180		54
	1,2-Dichloroethane	µg/L		56		11
	Chloroethane	µg/L		2		0.41 U
	Chloroform	µg/L		13		4.3
	cis-1,2-Dichloroethene	µg/L		36		11
	Tetrachloroethene	µg/L		2.4		1.6
	trans-1,2-Dichloroethene	µg/L		0.21 J		0.15 U
	Trichloroethene	µg/L		240		98
	Vinyl chloride	µg/L		0.57 J		0.1 U
X749-28G	1,1,1-Trichloroethane	µg/L			5.4	
	1,1-Dichloroethane	µg/L			3.9	
	1,1-Dichloroethene	µg/L			13	
	1,2-Dichloroethane	µg/L			0.42 J	
	Acetone	µg/L			3.5 J	
	Chloroform	µg/L			0.78 J	
	cis-1,2-Dichloroethene	µg/L			0.57 J	
	Tetrachloroethene	µg/L			0.28 J	
X749-29G	Trichloroethene	µg/L			23	
	Acetone	µg/L			4.2 BJ	
X749-30G	Trichloroethene	µg/L			4.2	
	1,1-Dichloroethene	µg/L			1.5	
	Chloroform	µg/L			0.48 J	
X749-33G	cis-1,2-Dichloroethene	µg/L			0.71 J	
	Trichloroethene	µg/L			25	
	1,1,1-Trichloroethane	µg/L		20		18
	1,1,2-Trichloroethane	µg/L		0.93 J		1.2
X749-35G	1,1-Dichloroethane	µg/L		48		37
	1,1-Dichloroethene	µg/L		96		71
	1,2-Dichloroethane	µg/L		25		13
	Chloroethane	µg/L		0.45 J		0.56 J
	Chloroform	µg/L		5.8		4.6
	cis-1,2-Dichloroethene	µg/L		7.9		8.6
	Tetrachloroethene	µg/L		1.4		1.8
	Trichloroethene	µg/L		140		110
	Vinyl chloride	µg/L		0.31 J		0.1 U
	X749-36G	1,1,1-Trichloroethane	µg/L			49
1,1-Dichloroethane		µg/L			7	
1,1-Dichloroethene		µg/L			30	
Chloroform		µg/L			0.27 J	
cis-1,2-Dichloroethene		µg/L			5.3	
Tetrachloroethene		µg/L			0.23 J	
Trichloroethene		µg/L			72	
X749-37G	Vinyl chloride	µg/L			0.47 J	
	1,1,1-Trichloroethane	µg/L			0.39 J	
	1,1-Dichloroethane	µg/L			0.71 J	
	1,1-Dichloroethene	µg/L			2.2	
	Acetone	µg/L			5.5 J	
X749-37G	Trichloroethene	µg/L			2	
	1,1,1-Trichloroethane	µg/L		5.7		3.7

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-37G	1,1,2-Trichloroethane	µg/L		0.57J		0.37J
	1,1-Dichloroethane	µg/L		13		11
	1,1-Dichloroethene	µg/L		31		24
	1,2-Dichloroethane	µg/L		1.2		1
	Chloroform	µg/L		1.1		0.56J
	cis-1,2-Dichloroethene	µg/L		6.5		5
	Tetrachloroethene	µg/L		0.56J		0.48J
	Trichloroethene	µg/L		28		20
X749-38G	1,1,1-Trichloroethane	µg/L		9.2		15
	1,1,2-Trichloroethane	µg/L		0.88J		1.3
	1,1-Dichloroethane	µg/L		20		31
	1,1-Dichloroethene	µg/L		49		70
	1,2-Dichloroethane	µg/L		2.4		4
	Chloroform	µg/L		1.7		2.7
	cis-1,2-Dichloroethene	µg/L		15		21
	Tetrachloroethene	µg/L		0.9J		1.6
	Trichloroethene	µg/L		51		77
X749-40G	Chloroform	µg/L			0.47J	
X749-41G	Acetone	µg/L		1.9U		6.1J
	Chloroform	µg/L		0.25J		0.32U
	cis-1,2-Dichloroethene	µg/L		2.9		2.7
	Methylene chloride	µg/L		0.32U		0.71J
	trans-1,2-Dichloroethene	µg/L		0.84J		0.88J
	Trichloroethene	µg/L		320		460
		Trichloroethane	µg/L		0.41J	
X749-42G	1,1-Dichloroethane	µg/L		0.65J		1.2
	1,1-Dichloroethene	µg/L		2.4		4.1
	Chloroform	µg/L		0.16U		0.19J
	Trichloroethene	µg/L		2.8		6.1
X749-43G	1,1,1-Trichloroethane	µg/L			0.19J	
	1,1-Dichloroethane	µg/L			0.24J	
	1,1-Dichloroethene	µg/L			0.65J	
	Trichloroethene	µg/L			0.45J	
X749-44G	1,1-Dichloroethane	µg/L	0.37J	0.22U	0.22U	0.34J
	Acetone	µg/L	2.1UJ	4.8BJ	8.6J	1.9U
	Trichloroethene	µg/L	0.61J	0.2J	0.3J	0.53J
X749-45G	1,1-Dichloroethane	µg/L	0.22U	2.2	0.37J	0.22U
	1,1-Dichloroethene	µg/L	0.23U	1.5	0.23U	0.23U
	1,2-Dichloroethane	µg/L	0.13U	0.76J	0.13U	0.13U
	Acetone	µg/L	2.2UJ	1.9U	2.7J	1.9U
	cis-1,2-Dichloroethene	µg/L	0.15U	2.5	0.28J	0.15U
	Trichloroethene	µg/L	0.32J	4.2	0.9J	0.32J
X749-50B	1,1-Dichloroethane	µg/L			0.72J	
X749-54B	1,1-Dichloroethane	µg/L		1.9		0.22U
	Trichloroethene	µg/L		8.7		19
	Vinyl chloride	µg/L		0.4J		0.59J
X749-64B	Trichloroethene	µg/L			1.5	
X749-66G	Acetone	µg/L			8.1J	
X749-67G	1,1,1-Trichloroethane	µg/L	13	8.4	9.9	7.8
	1,1,2-Trichloroethane	µg/L	0.27U	0.75J	0.73J	0.57J

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-67G	1,1-Dichloroethane	µg/L	110	83 E	100	84
	1,1-Dichloroethene	µg/L	88	80 E	82	46
	1,2-Dichloroethane	µg/L	41	28	33	38
	Benzene	µg/L	0.16 U	0.42 J	0.32 U	0.16 U
	Chloroethane	µg/L	1.5 J	1.9 J	1.3 J	0.92 J
	Chloroform	µg/L	5	4.3	4.3	4.1
	cis-1,2-Dichloroethene	µg/L	59	56	56	42
	Methylene chloride	µg/L	0.35 UJ	0.32 U	0.64 U	0.38 J
	Tetrachloroethene	µg/L	0.36 J	0.4 J	0.4 U	0.2 U
	trans-1,2-Dichloroethene	µg/L	0.6 J	0.44 J	0.36 J	0.3 J
	Trichloroethene	µg/L	310	280	290	190
Vinyl chloride	µg/L	0.35 J	0.4 J	0.52 J	0.1 U	
X749-97G	1,1-Dichloroethane	µg/L	0.22 U	0.22 J	0.22 U	0.22 U
	cis-1,2-Dichloroethene	µg/L	0.15 U	0.17 J	0.15 U	0.15 U
	Trichloroethene	µg/L	0.96 J	0.41 J	0.16 U	0.16 U
X749-102G	1,1-Dichloroethane	µg/L	0.28 J	0.29 J	0.22 U	0.22 U
	1,1-Dichloroethene	µg/L	0.23 U	0.26 J	0.23 U	0.23 U
	Acetone	µg/L	1.9 U	7.5 BJ	1.9 U	1.9 U
	Trichloroethene	µg/L	0.34 J	0.35 J	0.16 J	0.16 U
X749-103G	Acetone	µg/L	1.9 U	1.9 U	2.5 J	1.9 U
X749-106G	1,1,1-Trichloroethane	µg/L		18		20
	1,1,2-Trichloroethane	µg/L		2		1.8
	1,1-Dichloroethane	µg/L		28		33
	1,1-Dichloroethene	µg/L		98		94
	1,2-Dichloroethane	µg/L		2.7		3.3
	Chloroform	µg/L		3.1		3.2
	cis-1,2-Dichloroethene	µg/L		4.8		4.4
	Tetrachloroethene	µg/L		1.2		1.1
	Trichloroethene	µg/L		65		64
	Vinyl chloride	µg/L		0.13 J		0.1 U
X749-107G	1,1,1-Trichloroethane	µg/L		19		22
	1,1,2-Trichloroethane	µg/L		2		2.2
	1,1-Dichloroethane	µg/L		30		37
	1,1-Dichloroethene	µg/L		110		98
	1,2-Dichloroethane	µg/L		2.9		3.8
	Chloroform	µg/L		3.4		3.7
	cis-1,2-Dichloroethene	µg/L		4.8		4.5
	Tetrachloroethene	µg/L		1		1
	Trichloroethene	µg/L		76		67
X749-108G	1,1,1-Trichloroethane	µg/L		34		40
	1,1,2-Trichloroethane	µg/L		2.9		2.5
	1,1-Dichloroethane	µg/L		38		45
	1,1-Dichloroethene	µg/L		120		110
	1,2-Dichloroethane	µg/L		3.6		4.3
	Acetone	µg/L		11		1.9 U
	Chloroform	µg/L		4.4		4.8
	cis-1,2-Dichloroethene	µg/L		5.7		5.1
	Tetrachloroethene	µg/L		1.5		1.5
	Trichloroethene	µg/L		99		98
Vinyl chloride	µg/L		0.2 J		0.1 U	

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-109G	1,1,1-Trichloroethane	µg/L		3.2		3.8
	1,1,2-Trichloroethane	µg/L		0.27 U		0.35 J
	1,1-Dichloroethane	µg/L		7.8		11
	1,1-Dichloroethene	µg/L		19		21
	1,2-Dichloroethane	µg/L		1.1		1.8
	Chloroform	µg/L		0.72 J		0.81 J
	cis-1,2-Dichloroethene	µg/L		3.5		4.3
	Tetrachloroethene	µg/L		0.21 J		0.22 J
	Trichloroethene	µg/L		20		22
X749-110G	1,1,1-Trichloroethane	µg/L		0.84 J		1.8
	1,1-Dichloroethane	µg/L		5		7.8
	1,1-Dichloroethene	µg/L		6.2		10
	1,2-Dichloroethane	µg/L		1.6		2.9
	Chloroethane	µg/L		0.41 U		0.66 J
	Chloroform	µg/L		0.6 J		0.57 J
	cis-1,2-Dichloroethene	µg/L		6.4		9.6
	trans-1,2-Dichloroethene	µg/L		0.15 U		0.3 J
	Trichloroethene	µg/L		23		33
X749-113G	Vinyl chloride	µg/L		0.1 U		0.15 J
	1,1,1-Trichloroethane	µg/L		15		19
	1,1,2-Trichloroethane	µg/L		0.34 J		0.4 J
	1,1-Dichloroethane	µg/L		17		23
	1,1-Dichloroethene	µg/L		30		38
	1,2-Dichloroethane	µg/L		9.2		14
	Chloroform	µg/L		2.2		2.6
	cis-1,2-Dichloroethene	µg/L		2.7		3.4
	Tetrachloroethene	µg/L		0.45 J		0.46 J
X749-114G	Trichloroethene	µg/L		54		58
	1,1,1-Trichloroethane	µg/L			0.22 J	
	1,1-Dichloroethane	µg/L			0.27 J	
	Benzene	µg/L			0.22 J	
X749-115G	cis-1,2-Dichloroethene	µg/L			1.3	
	Chloroform	µg/L			0.19 J	
	cis-1,2-Dichloroethene	µg/L			6.3	
X749-117G	Trichloroethene	µg/L			270	
	Chloroform	µg/L			1.5	
	cis-1,2-Dichloroethene	µg/L			0.19 J	
X749-118G	Tetrachloroethene	µg/L			0.36 J	
	Trichloroethene	µg/L			21	
	1,1-Dichloroethane	µg/L			0.85 J	
	Carbon tetrachloride	µg/L			0.43 J	
X749-119G	Chloroform	µg/L			0.52 J	
	cis-1,2-Dichloroethene	µg/L			0.78 J	
	Tetrachloroethene	µg/L			1.4	
	Trichloroethene	µg/L			73	
	Chloroform	µg/L			1.4	
X749-120G	cis-1,2-Dichloroethene	µg/L			0.55 J	
	Trichloroethene	µg/L			14	
	1,1,1-Trichloroethane	µg/L			860	
	1,1,2-Trichloroethane	µg/L			110	

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
X749-120G	1,1-Dichloroethane	µg/L			6800		
	1,1-Dichloroethene	µg/L			2700		
	1,2-Dichloroethane	µg/L			110		
	Acetone	µg/L			390 J		
	Chloroform	µg/L			410		
	cis-1,2-Dichloroethene	µg/L			2100		
	Methylene chloride	µg/L			220 B		
	Tetrachloroethene	µg/L			410		
	Trichloroethene	µg/L			14000		
	Vinyl chloride	µg/L			76		
X749-121G	1,1,1-Trichloroethane	µg/L			31		
	1,1,2-Trichloroethane	µg/L			0.69 J		
	1,1-Dichloroethane	µg/L			18		
	1,1-Dichloroethene	µg/L			120		
	1,2-Dichloroethane	µg/L			0.89 J		
	Acetone	µg/L			4.6 J		
	Chloroethane	µg/L			7.4		
	Chloroform	µg/L			0.96 J		
	cis-1,2-Dichloroethene	µg/L			12		
	Tetrachloroethene	µg/L			0.35 J		
X749-122G	Trichloroethene	µg/L			67		
	Vinyl chloride	µg/L			1.4		
	1,1,1-Trichloroethane	µg/L			360		
	1,1,2-Trichloroethane	µg/L			3.4 J		
	1,1-Dichloroethane	µg/L			98		
	1,1-Dichloroethene	µg/L			240		
	1,2-Dichloroethane	µg/L			6.4		
	Benzene	µg/L			3 J		
	Chloroform	µg/L			3.9 J		
	cis-1,2-Dichloroethene	µg/L			57		
X749-BG9G	trans-1,2-Dichloroethene	µg/L			1.8 J		
	Trichloroethene	µg/L			920		
	Vinyl chloride	µg/L			3.6 J		
	Acetone	µg/L		2.4 J		1.9 U	
	Trichloroethene	µg/L		0.33 J		0.26 J	
	X749-PZ02G	Trichloroethene	µg/L		0.42 J		0.36 J
		Trichloroethene	µg/L		0.42 J		0.36 J
	X749-PZ04G	1,1-Dichloroethane	µg/L	0.39 J	0.68 J	0.59 J	0.36 J
		1,1-Dichloroethene	µg/L	0.23 U	0.31 J	0.23 U	0.23 U
		cis-1,2-Dichloroethene	µg/L	0.15 U	0.26 J	0.18 J	0.15 U
X749-PZ05G	Trichloroethene	µg/L	1	1.8	1.4	0.93 J	
	Acetone	µg/L	1.9 U	1.9 U	1.9 J	1.9 U	
X749-PZ06G	1,1,1-Trichloroethane	µg/L		14		14	
	1,1,2-Trichloroethane	µg/L		1.3		1.3	
	1,1-Dichloroethane	µg/L		30		28	
	1,1-Dichloroethene	µg/L		82		85	
	1,2-Dichloroethane	µg/L		2.9		2.7	
	Chloroform	µg/L		2.8		2.6	
	cis-1,2-Dichloroethene	µg/L		4.3		4	
	Tetrachloroethene	µg/L		0.46 J		0.49 J	
Trichloroethene	µg/L		55		54		

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-PZ07G	1,1,1-Trichloroethane	µg/L			0.22 J	
	1,1-Dichloroethane	µg/L			0.22 J	
	1,1-Dichloroethene	µg/L			0.79 J	
	Trichloroethene	µg/L			1.4	
X749-PZ08G	1,1-Dichloroethane	µg/L		0.32 J		
	cis-1,2-Dichloroethene	µg/L		0.8 J		
	Trichloroethene	µg/L		1.3		
X749-PZ09G	1,1,1-Trichloroethane	µg/L		2		
	1,1-Dichloroethane	µg/L		3.1		
	1,1-Dichloroethene	µg/L		7		
	cis-1,2-Dichloroethene	µg/L		19		
	trans-1,2-Dichloroethene	µg/L		0.17 J		
	Trichloroethene	µg/L		35		
	Vinyl chloride	µg/L		0.59 J		
X749-PZ10G	1,1,1-Trichloroethane	µg/L		11		10
	1,1-Dichloroethane	µg/L		0.57 J		0.6 J
	1,1-Dichloroethene	µg/L		110		100
	Chloroform	µg/L		26		26
	cis-1,2-Dichloroethene	µg/L		0.45 J		0.55 J
	Methylene chloride	µg/L		0.64 U		0.75 J
	Trichloroethene	µg/L		440		370
X749-PZ11G	1,1,1-Trichloroethane	µg/L		17		
	1,1-Dichloroethane	µg/L		6.3		
	1,1-Dichloroethene	µg/L		7.1		
	Chloroform	µg/L		0.19 J		
	cis-1,2-Dichloroethene	µg/L		18		
	trans-1,2-Dichloroethene	µg/L		0.49 J		
	Trichloroethene	µg/L		69		
X749-PZ12G	Vinyl chloride	µg/L		1.2		
	1,1,1-Trichloroethane	µg/L		3.7		
	1,1-Dichloroethane	µg/L		29		
	1,1-Dichloroethene	µg/L		27		
	Benzene	µg/L		2		
	cis-1,2-Dichloroethene	µg/L		7.3		
	trans-1,2-Dichloroethene	µg/L		0.41 J		
X749-PZ13G	Trichloroethene	µg/L		4.6		
	Vinyl chloride	µg/L		2.1		
	1,1,1-Trichloroethane	µg/L		35		
	1,1,2-Trichloroethane	µg/L		0.3 J		
	1,1-Dichloroethane	µg/L		54		
	1,1-Dichloroethene	µg/L		98		
	1,2-Dichloroethane	µg/L		2.4		
	Benzene	µg/L		3.5		
	Chloroethane	µg/L		1.3 J		
	Chloroform	µg/L		0.85 J		
	cis-1,2-Dichloroethene	µg/L		22		
X749-WPW	trans-1,2-Dichloroethene	µg/L		0.58 J		
	Trichloroethene	µg/L		75		
	Vinyl chloride	µg/L		2.3		
	1,1,1-Trichloroethane	µg/L		120		82

Table 4.1. VOCs detected at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-WPW	1,1,2-Trichloroethane	µg/L		3.1J		2.7 U
	1,1-Dichloroethane	µg/L		66		76
	1,1-Dichloroethene	µg/L		300		200
	1,2-Dichloroethane	µg/L		6.3J		13
	Benzene	µg/L		3.7J		1.7J
	Chloroform	µg/L		2.6J		16
	cis-1,2-Dichloroethene	µg/L		550		160
	Tetrachloroethene	µg/L		3.9J		3.9J
	trans-1,2-Dichloroethene	µg/L		2.2J		1.5 U
	Trichloroethene	µg/L		2300		920
	Vinyl chloride	µg/L		15		9.5J

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
STSW-101G	Technetium-99	pCi/L		3.42 U		
	Uranium	µg/L		0.298 U		
	Uranium-233/234	pCi/L		0.0984 U		
	Uranium-235/236	pCi/L		0.0111 U		
	Uranium-238	pCi/L		0.0984 U		
STSW-102G	Technetium-99	pCi/L		34.1		
	Uranium	µg/L		1.27		
	Uranium-233/234	pCi/L		0.789		
	Uranium-235/236	pCi/L		0.0228 U		
	Uranium-238	pCi/L		0.422		
WP-01G	Technetium-99	pCi/L		-2.81 U		
	Uranium	µg/L		0.0749 U		
	Uranium-233/234	pCi/L		0.00935 U		
	Uranium-235/236	pCi/L		0.0116 U		
	Uranium-238	pCi/L		0.0234 U		
WP-02G	Technetium-99	pCi/L		-1.55 U		
	Uranium	µg/L		0.0736 U		
	Uranium-233/234	pCi/L		0.0214 U		
	Uranium-235/236	pCi/L		0.0213 U		
	Uranium-238	pCi/L		0.0214 U		
WP-03G	Technetium-99	pCi/L		-1.48 U		
	Uranium	µg/L		0.113 U		
	Uranium-233/234	pCi/L		0.0362 UJ		
	Uranium-235/236	pCi/L		0.0394 U		
	Uranium-238	pCi/L		0.0317 U		
WP-04G	Technetium-99	pCi/L		-4.16 U		
	Uranium	µg/L		0.0534 U		
	Uranium-233/234	pCi/L		0.0557 UJ		
	Uranium-235/236	pCi/L		0.00532 U		
	Uranium-238	pCi/L		0.0171 U		
WP-05G	Technetium-99	pCi/L		-2.17 U		
	Uranium	µg/L		0.258		
	Uranium-233/234	pCi/L		0.112		
	Uranium-235/236	pCi/L		0.0111 U		
	Uranium-238	pCi/L		0.0851		
WP-06G	Technetium-99	pCi/L		-2.69 U		
	Uranium	µg/L		0.857		
	Uranium-233/234	pCi/L		0.342		
	Uranium-235/236	pCi/L		0.034 U		
	Uranium-238	pCi/L		0.283		
WP-07G	Technetium-99	pCi/L		-3.26 U		
	Uranium	µg/L		0.214 UJ		
	Uranium-233/234	pCi/L		0.0526 UJ		
	Uranium-235/236	pCi/L		0.0109 U		
	Uranium-238	pCi/L		0.0701 UJ		
X120-08G	Technetium-99	pCi/L			-2.28 U	
	Uranium	µg/L			0.0962 U	
	Uranium-233/234	pCi/L			0.06 U	
	Uranium-235/236	pCi/L			0 U	
	Uranium-238	pCi/L			0.0323 U	

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
X749-06G	Technetium-99	pCi/L		8.77			
	Uranium	µg/L		0.196 U			
	Uranium-233/234	pCi/L		0.061 U			
	Uranium-235/236	pCi/L		0 U			
	Uranium-238	pCi/L		0.0657 U			
X749-07G	Americium-241	pCi/L		0.00881 U			
	Neptunium-237	pCi/L		0.0202 U			
	Plutonium-238	pCi/L		0.005 U			
	Plutonium-239/240	pCi/L		0.02 U			
	Technetium-99	pCi/L		15.3			
	Uranium	µg/L		0.201 U			
	Uranium-233/234	pCi/L		0.118			
	Uranium-235/236	pCi/L		0.0244 U			
	Uranium-238	pCi/L		0.0638 U			
	X749-08G	Americium-241	pCi/L		0.0133 U		
		Neptunium-237	pCi/L		0.0301 U		
Plutonium-238		pCi/L		0 U			
Plutonium-239/240		pCi/L		0.0123 U			
Technetium-99		pCi/L		9.59			
Uranium		µg/L		0.141 U			
Uranium-233/234		pCi/L		0.0724 U			
Uranium-235/236		pCi/L		0.00643 U			
X749-10GA	Uranium-238	pCi/L		0.0465 U			
	Americium-241	pCi/L		0 U			
	Neptunium-237	pCi/L		0.0125 U			
	Plutonium-238	pCi/L		0.0186 U			
	Plutonium-239/240	pCi/L		0.00931 U			
	Technetium-99	pCi/L		0.808 U			
	Uranium	µg/L		0.0267 U			
	Uranium-233/234	pCi/L		0.0376 U			
X749-13G	Uranium-235/236	pCi/L		0.00935 U			
	Uranium-238	pCi/L		0.00752 U			
	Technetium-99	pCi/L		3.54 U			
	Uranium	µg/L		0.927			
	Uranium-233/234	pCi/L		0.28			
X749-14B	Uranium-235/236	pCi/L		0.0327 U			
	Uranium-238	pCi/L		0.307			
	Americium-241	pCi/L		0.0445 U			
	Neptunium-237	pCi/L		0 U			
	Plutonium-238	pCi/L		0.00565 U			
	Plutonium-239/240	pCi/L		0.0339 U			
	Technetium-99	pCi/L		0.973 U			
	Uranium	µg/L		0.0282 U			
X749-20G	Uranium-233/234	pCi/L		0.0472 U			
	Uranium-235/236	pCi/L		-0.0065 U			
	Uranium-238	pCi/L		0.0105 U			
	Technetium-99	pCi/L			45.3		
	Uranium	µg/L			0.898		
	Uranium-233/234	pCi/L			0.342		
	Uranium-235/236	pCi/L			0.0243 U		

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-20G	Uranium-238	pCi/L			0.298	
X749-26G	Technetium-99	pCi/L		7.04 UJ		
	Uranium	µg/L		0.0341 U		
	Uranium-233/234	pCi/L		0.0192 U		
	Uranium-235/236	pCi/L		0.0119 U		
	Uranium-238	pCi/L		0.00959 U		
X749-27G	Technetium-99	pCi/L		62.5		
	Uranium	µg/L		0.291 UJ		
	Uranium-233/234	pCi/L		0.0754 UJ		
	Uranium-235/236	pCi/L		0.0235 U		
	Uranium-238	pCi/L		0.0943 UJ		
X749-28G	Technetium-99	pCi/L			-0.732 U	
	Uranium	µg/L			0.11 U	
	Uranium-233/234	pCi/L			0.0226 U	
	Uranium-235/236	pCi/L			0.00562 U	
	Uranium-238	pCi/L			0.0362 U	
X749-33G	Technetium-99	pCi/L		17.5		
	Uranium	µg/L		0.0368 U		
	Uranium-233/234	pCi/L		0.048 U		
	Uranium-235/236	pCi/L		0.0179 U		
	Uranium-238	pCi/L		0.00959 U		
X749-37G	Technetium-99	pCi/L		0.332 U		
	Uranium	µg/L		0.227 U		
	Uranium-233/234	pCi/L		0.165		
	Uranium-235/236	pCi/L		0.00623 U		
	Uranium-238	pCi/L		0.0752 U		
X749-44G	Americium-241	pCi/L		0.0133 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0.00635 U		
	Plutonium-239/240	pCi/L		0.0318 U		
	Technetium-99	pCi/L		1.59 U		
	Uranium	µg/L		0.294 U		
	Uranium-233/234	pCi/L		0.166		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0987 U		
X749-45G	Americium-241	pCi/L		-0.0046 U		
	Neptunium-237	pCi/L		0.0103 U		
	Plutonium-238	pCi/L		0.0107 U		
	Plutonium-239/240	pCi/L		0.0107 U		
	Technetium-99	pCi/L		2.55 U		
	Uranium	µg/L		0.0515 U		
	Uranium-233/234	pCi/L		0.0173 U		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0173 U		
X749-54B	Technetium-99	pCi/L		0.353 U		
	Uranium	µg/L		0.0189 U		
	Uranium-233/234	pCi/L		0.0212 U		
	Uranium-235/236	pCi/L		0.00661 U		
	Uranium-238	pCi/L		0.00531 U		
X749-64B	Americium-241	pCi/L			0.0228 U	

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-64B	Neptunium-237	pCi/L			0 U	
	Plutonium-238	pCi/L			-0.155 U	
	Plutonium-239/240	pCi/L			0.0103 U	
	Technetium-99	pCi/L			-0.0685 U	
	Uranium	µg/L			1.27	
	Uranium-233/234	pCi/L			1.89	
	Uranium-235/236	pCi/L			0.0183 U	
	Uranium-238	pCi/L			0.423	
X749-67G	Technetium-99	pCi/L		25.8		
	Uranium	µg/L		0.289		
	Uranium-233/234	pCi/L		0.119		
	Uranium-235/236	pCi/L		0.00571 U		
	Uranium-238	pCi/L		0.0963		
X749-68G	Americium-241	pCi/L			0 U	
	Neptunium-237	pCi/L			0.0642 U	
	Plutonium-238	pCi/L			0.0174 U	
	Plutonium-239/240	pCi/L			0.0695 U	
	Technetium-99	pCi/L			-3.61 U	
	Uranium	µg/L			0.0436 U	
	Uranium-233/234	pCi/L			0.0613 U	
	Uranium-235/236	pCi/L			0.0153 U	
X749-96G	Uranium-238	pCi/L			0.0123 U	
	Americium-241	pCi/L		0.0293 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0.0315 U		
	Plutonium-239/240	pCi/L		0.00525 U		
	Technetium-99	pCi/L		-1.65 U		
	Uranium	µg/L		0.0753 U		
	Uranium-233/234	pCi/L		0.0212 U		
X749-97G	Uranium-235/236	pCi/L		0.0264 U		
	Uranium-238	pCi/L		0.0212 U		
	Americium-241	pCi/L		0.0179 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0.00471 U		
	Plutonium-239/240	pCi/L		0.00942 U		
	Technetium-99	pCi/L		1.06 U		
	Uranium	µg/L		0.333 U		
X749-98G	Uranium-233/234	pCi/L		0.0767 U		
	Uranium-235/236	pCi/L		0.0136 U		
	Uranium-238	pCi/L		0.11		
	Americium-241	pCi/L		0.00493 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.0102 U		
	Technetium-99	pCi/L		-0.354 U		
X749-106G	Uranium	µg/L		0.133 U		
	Uranium-233/234	pCi/L		0.0602 U		
	Uranium-235/236	pCi/L		0.00681 U		
	Uranium-238	pCi/L		0.0438 U		
	Technetium-99	pCi/L		3.52 U		

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-106G	Uranium	µg/L		0.015 U		
	Uranium-233/234	pCi/L		0.0609 U		
	Uranium-235/236	pCi/L		0.0325 U		
	Uranium-238	pCi/L		0 U		
X749-108G	Technetium-99	pCi/L		5.69 U		
	Uranium	µg/L		0.0892 U		
	Uranium-233/234	pCi/L		0.0188 U		
	Uranium-235/236	pCi/L		0.0117 U		
X749-109G	Uranium-238	pCi/L		0.0282 U		
	Technetium-99	pCi/L		1.01 U		
	Uranium	µg/L		1.71		
	Uranium-233/234	pCi/L		0.448		
X749-110G	Uranium-235/236	pCi/L		0.0668 U		
	Uranium-238	pCi/L		0.564		
	Technetium-99	pCi/L		3.83 U		
	Uranium	µg/L		13.4		
X749-113G	Uranium-233/234	pCi/L		4.23		
	Uranium-235/236	pCi/L		0.213		
	Uranium-238	pCi/L		4.48		
	Technetium-99	pCi/L		8.01		
X749-120G	Uranium	µg/L		0.308 UJ		
	Uranium-233/234	pCi/L		0.0818 UJ		
	Uranium-235/236	pCi/L		0.0226 U		
	Uranium-238	pCi/L		0.1 UJ		
X749-121G	Technetium-99	pCi/L			64.6	
	Uranium	µg/L			0.279	
	Uranium-233/234	pCi/L			0.0884	
	Uranium-235/236	pCi/L			0.0055 U	
X749-PZ02G	Uranium-238	pCi/L			0.0928	
	Technetium-99	pCi/L			601	
	Uranium	µg/L			0.627	
	Uranium-233/234	pCi/L			0.213	
X749-PZ04G	Uranium-235/236	pCi/L			0.0113 U	
	Uranium-238	pCi/L			0.209	
	Technetium-99	pCi/L		-0.969 U		
	Uranium	µg/L		0.0288 U		
X749-PZ09G	Uranium-233/234	pCi/L		0.0339 U		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.00968 U		
	Technetium-99	pCi/L		-0.513 U		
X749-PZ10G	Uranium	µg/L		0.136 U		
	Uranium-233/234	pCi/L		0.0456 UJ		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0456 U		
X749-PZ09G	Technetium-99	pCi/L		224		
	Uranium	µg/L		4.96		
	Uranium-233/234	pCi/L		1.37		
	Uranium-235/236	pCi/L		0.107 U		
X749-PZ10G	Uranium-238	pCi/L		1.65		
	Technetium-99	pCi/L		21.9		

Table 4.2. Results for radionuclides at the X-749 Contaminated Materials Disposal Facility/X-120 Former Training Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749-PZ10G	Uranium	µg/L		0.135 U		
	Uranium-233/234	pCi/L		0.0771 U		
	Uranium-235/236	pCi/L		0.012 U		
	Uranium-238	pCi/L		0.0434 U		
X749-PZ11G	Technetium-99	pCi/L		-0.518 U		
	Uranium	µg/L		2.14		
	Uranium-233/234	pCi/L		0.81		
	Uranium-235/236	pCi/L		0.0697 U		
X749-PZ12G	Uranium-238	pCi/L		0.71		
	Technetium-99	pCi/L		0.966 U		
	Uranium	µg/L		1.55		
	Uranium-233/234	pCi/L		0.392		
X749-PZ13G	Uranium-235/236	pCi/L		0.068 U		
	Uranium-238	pCi/L		0.51		
	Technetium-99	pCi/L		2.2 U		
	Uranium	µg/L		0.783		
X749-WPW	Uranium-233/234	pCi/L		0.303		
	Uranium-235/236	pCi/L		0.0202 U		
	Uranium-238	pCi/L		0.26		
	Americium-241	pCi/L		0.0311 U		
	Neptunium-237	pCi/L		0.0129 U		
	Plutonium-238	pCi/L		-0.0055 U		
	Plutonium-239/240	pCi/L		0.00548 U		
	Technetium-99	pCi/L		62		
Uranium	µg/L		0.399			
Uranium-233/234	pCi/L		0.247			
Uranium-235/236	pCi/L		0.00591 U			
Uranium-238	pCi/L		0.133			

Table 4.3 VOCs detected at PK Landfill – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
MH GW-4	Acetone	µg/L			3.1 J		
	Chlorobenzene	µg/L			0.39 J		
	cis-1,2-Dichloroethene	µg/L			0.62 J		
	Vinyl chloride	µg/L			0.24 J		
MH GW-5	1,1-Dichloroethane	µg/L				0.33 J	
	cis-1,2-Dichloroethene	µg/L				1.8	
PK-15B	cis-1,2-Dichloroethene	µg/L		0.23 J		0.21 J	
PK-16G	cis-1,2-Dichloroethene	µg/L		0.15 U		0.49 J	
PK-17B	1,1-Dichloroethane	µg/L		1.7		3.5	
	1,1-Dichloroethane	µg/L		0.28 J		0.56 J	
	Benzene	µg/L		0.16 U		0.33 J	
	Chlorobenzene	µg/L		0.86 J		1.4	
	cis-1,2-Dichloroethene	µg/L		25		55	
	trans-1,2-Dichloroethene	µg/L		0.76 J		1.8	
	Trichloroethene	µg/L		0.47 J		1.3	
	Vinyl chloride	µg/L		5.3		22	
	PK-19B	1,1-Dichloroethane	µg/L		0.6 J		0.26 J
		Chloroethane	µg/L		1.2 J		1.3 J
Methylene chloride		µg/L		2.3		0.32 U	
Vinyl chloride		µg/L		0.16 J		0.1 U	
PK-21B	1,1-Dichloroethane	µg/L		130		130	
	1,1-Dichloroethane	µg/L		0.99 J		1	
	1,2-Dichloroethane	µg/L		0.58 J		0.13 U	
	Acetone	µg/L		1.9 U		6 J	
	Benzene	µg/L		0.54 J		0.64 J	
	cis-1,2-Dichloroethene	µg/L		8.6		10	
	Trichloroethene	µg/L		0.28 J		0.3 J	
	Vinyl chloride	µg/L		9.8		13	
	PK-PL6	1,1,1-Trichloroethane	µg/L	4	3.5	1.2	0.79 J
		1,1-Dichloroethane	µg/L	7.7	7.6	4.5	4.3
1,1-Dichloroethene		µg/L	2.3	2.1	0.65 J	0.76 J	
cis-1,2-Dichloroethene		µg/L	1.8	2.1	1.3	1.1	
Trichloroethene		µg/L	2	2.5	0.89 J	0.78 J	
Vinyl chloride		µg/L	0.33 J	0.47 J	0.33 J	0.35 J	
PK-PL6A	1,1,1-Trichloroethane	µg/L	5	5.1	4	2.3	
	1,1-Dichloroethane	µg/L	9.6	11	12	11	
	1,1-Dichloroethene	µg/L	2.7	3.2	3	2.5	
	Acetone	µg/L	1.9 U	1.9 U	3.3 J	1.9 U	
	cis-1,2-Dichloroethene	µg/L	2	2.7	2.5	2.5	
	Trichloroethene	µg/L	2.5	3.6	2.6	2.1	
	Vinyl chloride	µg/L	0.41 J	0.94 J	1	1.4	

Table 4.4. VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
X230K-14G	cis-1,2-Dichloroethene	µg/L			0.43 J		
	Trichloroethene	µg/L			4.4		
X230K-15G	Acetone	µg/L			1.9 J		
	Trichloroethene	µg/L			0.69 J		
X231A-01G	1,1-Dichloroethane	µg/L			1.2		
	cis-1,2-Dichloroethene	µg/L			0.45 J		
X231A-02G	Trichloroethene	µg/L			3.8		
	1,1,1-Trichloroethane	µg/L			3		
	1,1,2-Trichloroethane	µg/L			0.35 J		
	1,1-Dichloroethane	µg/L			4.2		
	1,1-Dichloroethene	µg/L			37		
	Acetone	µg/L			2.7 J		
	Chloroform	µg/L			1.5		
	cis-1,2-Dichloroethene	µg/L			11		
	Tetrachloroethene	µg/L			0.22 J		
	trans-1,2-Dichloroethene	µg/L			0.16 J		
	Trichloroethene	µg/L			190		
	X231A-04G	1,1-Dichloroethene	µg/L			0.67 J	
		Chloroform	µg/L			0.2 J	
		cis-1,2-Dichloroethene	µg/L			0.87 J	
X231B-02G	Trichloroethene	µg/L			10		
	1,1,1-Trichloroethane	µg/L	0.62 J		0.22 J		
	1,1,2-Trichloroethane	µg/L	0.29 J		0.27 U		
	1,1-Dichloroethane	µg/L	21		0.32 J		
	1,1-Dichloroethene	µg/L	48		18		
	Chloroform	µg/L	6.6		0.7 J		
	cis-1,2-Dichloroethene	µg/L	29		10		
	trans-1,2-Dichloroethene	µg/L	0.97 J		0.62 J		
	Trichloroethene	µg/L	180		190		
	Vinyl chloride	µg/L	3.3		0.1 U		
	X231B-03G	1,1,1-Trichloroethane	µg/L	4.1		2.4	
		1,1,2-Trichloroethane	µg/L	1.1		0.86 J	
		1,1-Dichloroethane	µg/L	3.6		2.7	
		1,1-Dichloroethene	µg/L	150		120	
Benzene		µg/L	0.25 J		0.22 J		
Chloroform		µg/L	0.47 J		0.4 J		
cis-1,2-Dichloroethene		µg/L	9.3		6.8		
Dichlorodifluoromethane		µg/L	0.32 J				
Tetrachloroethene		µg/L	0.23 J		0.22 J		
trans-1,2-Dichloroethene		µg/L	0.73 J		0.49 J		
Trichloroethene		µg/L	180		140		
X231B-06G		1,1,1-Trichloroethane	µg/L	8.1		25	
		1,1,2-Trichloroethane	µg/L	0.27 U		0.37 J	
		1,1-Dichloroethane	µg/L	6.5		16	
	1,1-Dichloroethene	µg/L	15		53		
	Chloroform	µg/L	2.3		0.7 J		
	cis-1,2-Dichloroethene	µg/L	4.4		3.5		
	Tetrachloroethene	µg/L	0.2 U		0.35 J		
	Trichloroethene	µg/L	58		160		
	Vinyl chloride	µg/L	0.1 U		0.39 J		

**Table 4.4. VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015
 (continued)**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X231B-07G	Chloroform	µg/L	0.85 J			
	cis-1,2-Dichloroethene	µg/L	2.9			
	Trichloroethene	µg/L	36			
X231B-11G	1,1,1-Trichloroethane	µg/L	2.2			
	1,1-Dichloroethane	µg/L	0.27 J			
	1,1-Dichloroethene	µg/L	11			
X231B-12G	Trichloroethene	µg/L	1.2			
	1,1,1-Trichloroethane	µg/L			1.5	
	1,1-Dichloroethene	µg/L			9.7	
X231B-14G	Trichloroethene	µg/L			2.8	
	Trichlorofluoromethane	µg/L			0.5 J	
	1,1,1-Trichloroethane	µg/L			0.81 J	
	1,1-Dichloroethane	µg/L			0.91 J	
X231B-15G	1,1-Dichloroethene	µg/L			14	
	2-Butanone	µg/L			2.1 J	
	Acetone	µg/L			2.7 J	
	Chloroform	µg/L			0.6 J	
	cis-1,2-Dichloroethene	µg/L			4.1	
	Trichloroethene	µg/L			69	
	1,1,1-Trichloroethane	µg/L			0.18 J	
X231B-16G	1,1-Dichloroethene	µg/L			1	
	Acetone	µg/L			3.5 J	
	Chloroform	µg/L			0.59 J	
	Trichloroethene	µg/L			0.49 J	
X231B-20G	1,1,1-Trichloroethane	µg/L			0.47 J	
	1,1-Dichloroethene	µg/L			2.1	
	Chloroform	µg/L			3.7	
	Trichloroethene	µg/L			0.24 J	
X231B-23G	1,1,1-Trichloroethane	µg/L			0.38 J	
	1,1-Dichloroethene	µg/L			18	
	Chloroform	µg/L			0.77 J	
	cis-1,2-Dichloroethene	µg/L			0.2 J	
	Trichloroethene	µg/L			27	
X231B-24B	Trichlorofluoromethane	µg/L			0.93 J	
	1,1,1-Trichloroethane	µg/L			0.25 J	
	1,1-Dichloroethene	µg/L			1.3	
	Chloroform	µg/L			0.18 J	
X231B-29G	Trichloroethene	µg/L			2	
	Trichloroethene	µg/L	1.4			
X231B-32B	cis-1,2-Dichloroethene	µg/L	0.17 J			
	Trichloroethene	µg/L	3.9			
X231B-36G	Acetone	µg/L			3.9 J	
	Trichloroethene	µg/L			0.19 J	
	Acetone	µg/L			2.4 J	
X231B-37G	Chloroform	µg/L			0.39 J	
	cis-1,2-Dichloroethene	µg/L			0.8 J	
	Trichloroethene	µg/L			210	
	1,1-Dichloroethane	µg/L			1.5	
X231B-37G	1,1-Dichloroethene	µg/L			1.3	
	Acetone	µg/L			3.2 J	

**Table 4.4. VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015
 (continued)**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X231B-37G	cis-1,2-Dichloroethene	µg/L			5.9	
	trans-1,2-Dichloroethene	µg/L			0.75 J	
	Trichloroethene	µg/L			13	
	Vinyl chloride	µg/L			0.35 J	
X231B-38G	1,1,1-Trichloroethane	µg/L	0.32 J			
	1,1-Dichloroethene	µg/L	0.67 J			
	1,2-Dichlorobenzene	µg/L	0.17 J			
	Trichloroethene	µg/L	0.3 J			
X326-09G	1,1-Dichloroethene	µg/L	400		400	
	Chloroform	µg/L	110 J		120	
	cis-1,2-Dichloroethene	µg/L	150 J		150	
	Trichloroethene	µg/L	25000		22000	
X326-10G	1,1-Dichloroethene	µg/L			4.6	
	Acetone	µg/L			2.9 BJ	
	cis-1,2-Dichloroethene	µg/L			0.98 J	
	Trichloroethene	µg/L			9.2	
X622-PZ01G	1,1-Dichloroethene	µg/L			0.59 J	
	Acetone	µg/L			3.4 J	
	Benzene	µg/L			0.18 J	
	cis-1,2-Dichloroethene	µg/L			21	
	trans-1,2-Dichloroethene	µg/L			1.3	
	Trichloroethene	µg/L			7.3	
	Vinyl chloride	µg/L			0.4 J	
X622-PZ02G	1,1,1-Trichloroethane	µg/L			1.4	
	1,1-Dichloroethane	µg/L			1.2	
	1,1-Dichloroethene	µg/L			20	
	Chloroform	µg/L			0.9 J	
	cis-1,2-Dichloroethene	µg/L			7.4	
	trans-1,2-Dichloroethene	µg/L			0.2 J	
	Trichloroethene	µg/L			170	
X622-PZ03G	Trichlorofluoromethane	µg/L			1.7 J	
	1,1,1-Trichloroethane	µg/L			1.4 J	
	1,1-Dichloroethane	µg/L			2.7	
	1,1-Dichloroethene	µg/L			8.7	
	Chloroform	µg/L			0.48 J	
	cis-1,2-Dichloroethene	µg/L			6.7	
	Trichloroethene	µg/L			350	
X626-07G	Trichlorofluoromethane	µg/L			4.5	
	1,1,1-Trichloroethane	µg/L	2.7		3.8	
	1,1,2-Trichloroethane	µg/L	1.6		3	
	1,1-Dichloroethane	µg/L	1.4		2.3	
	1,1-Dichloroethene	µg/L	300		460	
	1,2-Dichloroethane	µg/L	0.77 J		1.2 J	
	Benzene	µg/L	0.54 J		0.88 J	
	Chloroform	µg/L	0.5 J		0.62 J	
	cis-1,2-Dichloroethene	µg/L	1.1		1 J	
	Trichloroethene	µg/L	89		130	
X710-01G	Vinyl chloride	µg/L	0.11 J		0.2 U	
	cis-1,2-Dichloroethene	µg/L	0.38 J			
	Trichloroethene	µg/L	25			

**Table 4.4. VOCs detected at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015
 (continued)**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X760-02G	Trichloroethene	µg/L	0.49 J			
X760-03G	Acetone	µg/L			3.1 J	
	Chloroform	µg/L			0.38 J	
	cis-1,2-Dichloroethene	µg/L			3.2	
	Trichloroethene	µg/L			240	
	Vinyl chloride	µg/L			0.11 J	
X760-07G	cis-1,2-Dichloroethene	µg/L			15	
	Methylene chloride	µg/L			1.3 J	
	Trichloroethene	µg/L			550	
	Vinyl chloride	µg/L			0.71 J	
X770-17GA	Acetone	µg/L	1.9 U		4.7 J	
	Chloroform	µg/L	0.17 J		0.32 U	
	cis-1,2-Dichloroethene	µg/L	1.1		1.3 J	
	Trichloroethene	µg/L	290		380	

Table 4.5. Results for radionuclides at the Quadrant I Groundwater Investigative (5-Unit) Area – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X231A-01G	Technetium-99	pCi/L			28.3	
	Uranium	µg/L			13.3	
	Uranium-233/234	pCi/L			12.1	
	Uranium-235/236	pCi/L			0.764	
	Uranium-238	pCi/L			4.34	
X231A-02G	Technetium-99	pCi/L			1.64 U	
	Uranium	µg/L			0.222 U	
	Uranium-233/234	pCi/L			0.0746 U	
	Uranium-235/236	pCi/L			0 U	
	Uranium-238	pCi/L			0.0746 U	
X231A-04G	Technetium-99	pCi/L			1.78 U	
	Uranium	µg/L			0.271 U	
	Uranium-233/234	pCi/L			0.0523 U	
	Uranium-235/236	pCi/L			0.00591 U	
	Uranium-238	pCi/L			0.0903 U	
X231B-02G	Technetium-99	pCi/L			11.1	
	Uranium	µg/L			0.329	
	Uranium-233/234	pCi/L			0.136	
	Uranium-235/236	pCi/L			0.0113 U	
	Uranium-238	pCi/L			0.109	
X231B-03G	Americium-241	pCi/L			0.0332 U	
	Neptunium-237	pCi/L			0.00474 U	
	Plutonium-238	pCi/L			0 U	
	Plutonium-239/240	pCi/L			0.0195 U	
	Technetium-99	pCi/L			2.8 U	
	Uranium	µg/L			0.379	
	Uranium-233/234	pCi/L			0.112	
	Uranium-235/236	pCi/L			0.00582 U	
	Uranium-238	pCi/L			0.126	
X231B-06G	Americium-241	pCi/L			0.0484 U	
	Neptunium-237	pCi/L			-0.00851 U	
	Plutonium-238	pCi/L			0.0104 U	
	Plutonium-239/240	pCi/L			0.00521 U	
	Technetium-99	pCi/L			47.8	
	Uranium	µg/L			2.54	
	Uranium-233/234	pCi/L			3.38	
	Uranium-235/236	pCi/L			0.176	
	Uranium-238	pCi/L			0.825	
X326-09G	Technetium-99	pCi/L			0.574 U	
	Uranium	µg/L			0.164 UJ	
	Uranium-233/234	pCi/L			0.0737 UJ	
	Uranium-235/236	pCi/L			0.00611 U	
	Uranium-238	pCi/L			0.0541 UJ	
X626-07G	Technetium-99	pCi/L			-0.939 U	
	Uranium	µg/L			0.741	
	Uranium-233/234	pCi/L			0.278	
	Uranium-235/236	pCi/L			0.0235 U	
	Uranium-238	pCi/L			0.245	

Table 4.6 VOCs detected at the X-749A Classified Materials Disposal Facility – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749A-12G	cis-1,2-Dichloroethene	µg/L		4.8		
	Trichloroethene	µg/L		2.8		
X749A-18G	cis-1,2-Dichloroethene	µg/L		0.21 J		
	Trichloroethene	µg/L		4.5		
X749A-19G	Chloroform	µg/L		0.22 J		
	cis-1,2-Dichloroethene	µg/L		3.1		
	Trichloroethene	µg/L		34		

Table 4.7 Results for radionuclides at the X-749A Classified Materials Disposal Facility – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X749A-02G	Technetium-99	pCi/L		-0.389 U		
	Uranium	µg/L		0.152 UJ		
	Uranium-233/234	pCi/L		0.0674 UJ		
	Uranium-235/236	pCi/L		0.0112 U		
X749A-03G	Uranium-238	pCi/L		0.0494 UJ		
	Technetium-99	pCi/L		-2.58 U		
	Uranium	µg/L		0.225 UJ		
	Uranium-233/234	pCi/L		0.087		
X749A-04G	Uranium-235/236	pCi/L		0.0108 U		
	Uranium-238	pCi/L		0.0739 UJ		
	Technetium-99	pCi/L		-3.2 U		
	Uranium	µg/L		0.0693 U		
X749A-07G	Uranium-233/234	pCi/L		0.0135 U		
	Uranium-235/236	pCi/L		0.00558 U		
	Uranium-238	pCi/L		0.0224 U		
	Technetium-99	pCi/L		-1.46 U		
X749A-12G	Uranium	µg/L		9.07		
	Uranium-233/234	pCi/L		3.8		
	Uranium-235/236	pCi/L		0.156 U		
	Uranium-238	pCi/L		3.02		
X749A-14G	Technetium-99	pCi/L		-2.56 U		
	Uranium	µg/L		0.0666 U		
	Uranium-233/234	pCi/L		0.0437 U		
	Uranium-235/236	pCi/L		-0.0121 U		
X749A-16G	Uranium-238	pCi/L		0.0243 U		
	Technetium-99	pCi/L		-2.2 U		
	Uranium	µg/L		0.179 U		
	Uranium-233/234	pCi/L		0.0693 U		
X749A-17G	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0601 U		
	Technetium-99	pCi/L		4.36 U		
	Uranium	µg/L		0.0558 U		
X749A-18G	Uranium-233/234	pCi/L		0.0187 U		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0187 U		
	Technetium-99	pCi/L		-1.85 U		
X749A-19G	Uranium	µg/L		0.132 U		
	Uranium-233/234	pCi/L		0.0346 U		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0445 U		
X749A-18G	Technetium-99	pCi/L		-0.925 U		
	Uranium	µg/L		0.114 U		
	Uranium-233/234	pCi/L		0.0917		
	Uranium-235/236	pCi/L		0.0217 U		
X749A-19G	Uranium-238	pCi/L		0.035 U		
	Technetium-99	pCi/L		1.85 U		
	Uranium	µg/L		0.446		
	Uranium-233/234	pCi/L		0.129		
X749A-19G	Uranium-235/236	pCi/L		0.00618 U		
	Uranium-238	pCi/L		0.149		

Table 4.8. VOCs detected at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X700-02G	1,1,1-Trichloroethane	µg/L	5.5 J			
	1,1-Dichloroethane	µg/L	13 J			
	1,1-Dichloroethene	µg/L	120			
	cis-1,2-Dichloroethene	µg/L	1900			
	trans-1,2-Dichloroethene	µg/L	3.4 J			
	Trichloroethene	µg/L	4800			
	Vinyl chloride	µg/L	170			
X700-03G	cis-1,2-Dichloroethene	µg/L	0.52 J		0.18 J	
X700-04G	1,1-Dichloroethane	µg/L	4.2 J			
	1,1-Dichloroethene	µg/L	16			
	Chloroethane	µg/L	7.2 J			
	cis-1,2-Dichloroethene	µg/L	2500			
	trans-1,2-Dichloroethene	µg/L	31			
	Trichloroethene	µg/L	2000			
	Vinyl chloride	µg/L	4400			
X700-05G	1,1,2-Trichloroethane	µg/L	260			
	1,1-Dichloroethene	µg/L	300			
	Chloroform	µg/L	90 J			
	cis-1,2-Dichloroethene	µg/L	170000			
	trans-1,2-Dichloroethene	µg/L	140 J			
	Trichloroethene	µg/L	180000			
	Vinyl chloride	µg/L	5100			
X700-06G	1,1,1-Trichloroethane	µg/L	33 J			
	1,1,2-Trichloroethane	µg/L	1100			
	1,2-Dichloroethane	µg/L	79 J			
	Carbon tetrachloride	µg/L	58 J			
	Chloroform	µg/L	550			
	cis-1,2-Dichloroethene	µg/L	3200			
	trans-1,2-Dichloroethene	µg/L	33 J			
	Trichloroethene	µg/L	1000000			
Vinyl chloride	µg/L	250				
X701-26G	1,1-Dichloroethene	µg/L	1		0.74 J	
	Chloroform	µg/L	0.46 J		0.43 J	
	Tetrachloroethene	µg/L	2.8		2.3	
	Trichloroethene	µg/L	0.68 J		0.49 J	
X701-27G	1,1,1-Trichloroethane	µg/L	0.51 J		0.78 J	
	1,1-Dichloroethane	µg/L	0.46 J		0.55 J	
	1,1-Dichloroethene	µg/L	1.8		1.9	
	cis-1,2-Dichloroethene	µg/L	0.74 J		2.2	
	Trichloroethene	µg/L	5.8		12	
X701-45G	1,1-Dichloroethene	µg/L	0.35 J			
	cis-1,2-Dichloroethene	µg/L	0.44 J			
	Trichloroethene	µg/L	6.2			
X701-68G	1,1,1-Trichloroethane	µg/L	0.22 J			
	1,1-Dichloroethane	µg/L	0.27 J			
	1,1-Dichloroethene	µg/L	3.6			
	cis-1,2-Dichloroethene	µg/L	3.1			
	Trichloroethene	µg/L	23			
	Trichlorofluoromethane	µg/L	0.6 J			
X701-69G	1,1-Dichloroethene	µg/L	1 J			

**Table 4.8. VOCs detected at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015
 (continued)**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-69G	cis-1,2-Dichloroethene	µg/L	200			
	Tetrachloroethene	µg/L	0.46 J			
	trans-1,2-Dichloroethene	µg/L	5.5			
	Trichloroethene	µg/L	730			
	Vinyl chloride	µg/L	0.39 J			
X701-70G	1,1-Dichloroethene	µg/L	2.4 J			
	cis-1,2-Dichloroethene	µg/L	640			
	Trichloroethene	µg/L	2100			
X701-117GA	1,1-Dichloroethene	µg/L	3.9 J			
	cis-1,2-Dichloroethene	µg/L	190			
	trans-1,2-Dichloroethene	µg/L	0.67 J			
	Trichloroethene	µg/L	990			
X705-01GA	1,1-Dichloroethene	µg/L	0.45 J			
	Carbon tetrachloride	µg/L	0.49 J			
	Chloroform	µg/L	14			
	cis-1,2-Dichloroethene	µg/L	0.21 J			
	Tetrachloroethene	µg/L	0.43 J			
	Trichloroethene	µg/L	52			
X705-02G	1,1-Dichloroethene	µg/L	0.61 J			
	cis-1,2-Dichloroethene	µg/L	0.58 J			
	Trichloroethene	µg/L	43			
X705-03G	1,1-Dichloroethane	µg/L	1.1			
	1,1-Dichloroethene	µg/L	3.7			
	cis-1,2-Dichloroethene	µg/L	5.9			
	Tetrachloroethene	µg/L	0.38 J			
	trans-1,2-Dichloroethene	µg/L	0.32 J			
	Trichloroethene	µg/L	30			
X705-04G	Carbon tetrachloride	µg/L	2.9			
	Chloroform	µg/L	55			
	Tetrachloroethene	µg/L	0.68 J			
	Trichloroethene	µg/L	17			
X705-06G	1,1-Dichloroethene	µg/L	0.77 J			
	Chloroform	µg/L	0.64 J			
	cis-1,2-Dichloroethene	µg/L	1.5			
	Tetrachloroethene	µg/L	4.2			
	Trichloroethene	µg/L	22			
X705-07G	Bromodichloromethane	µg/L	0.24 J			
	Chloroform	µg/L	1.8			
	cis-1,2-Dichloroethene	µg/L	0.27 J			
	Trichloroethene	µg/L	6.4			
X705-08G	1,1-Dichloroethene	µg/L	18			
	Trichlorofluoromethane	µg/L	15			
X720-01G	1,1,1-Trichloroethane	µg/L	16 J			
	1,1-Dichloroethane	µg/L	29			
	1,1-Dichloroethene	µg/L	150			
	cis-1,2-Dichloroethene	µg/L	4000			
	trans-1,2-Dichloroethene	µg/L	10 J			
	Trichloroethene	µg/L	7600			
	Vinyl chloride	µg/L	680			
X720-08G	1,1-Dichloroethene	µg/L	100			

**Table 4.8. VOCs detected at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015
 (continued)**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X720-08G	cis-1,2-Dichloroethene	µg/L	26 J			
	Tetrachloroethene	µg/L	16 J			
	Trichloroethene	µg/L	7500			
X720-09G	1,1,1-Trichloroethane	µg/L	2500			
	1,1,2-Trichloroethane	µg/L	73 J			
	1,1-Dichloroethane	µg/L	160 J			
	1,1-Dichloroethene	µg/L	11000 J			
	1,2-Dichloroethane	µg/L	76 J			
	1,2-Dimethylbenzene	µg/L	140 J			
	Chloroform	µg/L	61 J			
	cis-1,2-Dichloroethene	µg/L	1800			
	Ethylbenzene	µg/L	99 J			
	m,p-Xylenes	µg/L	360 J			
	Tetrachloroethene	µg/L	470			
	Toluene	µg/L	700			
	Trichloroethene	µg/L	380000			
	Vinyl chloride	µg/L	67 J			

Table 4.9. Results for radionuclides at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X700-02G	Technetium-99	pCi/L	29			
	Uranium	µg/L	2.2			
	Uranium-233/234	pCi/L	0.756			
	Uranium-235/236	pCi/L	0.0425 U			
	Uranium-238	pCi/L	0.732			
X700-04G	Technetium-99	pCi/L	31.6			
	Uranium	µg/L	18.2			
	Uranium-233/234	pCi/L	7.48			
	Uranium-235/236	pCi/L	0.259			
	Uranium-238	pCi/L	6.07			
X700-05G	Technetium-99	pCi/L	2.17 U			
	Uranium	µg/L	2.55			
	Uranium-233/234	pCi/L	1.36			
	Uranium-235/236	pCi/L	0.029 U			
	Uranium-238	pCi/L	0.852			
X700-06G	Technetium-99	pCi/L	20.7			
	Uranium	µg/L	11.3			
	Uranium-233/234	pCi/L	5.37			
	Uranium-235/236	pCi/L	0.175			
	Uranium-238	pCi/L	3.77			
X701-26G	Technetium-99	pCi/L	33.8			
	Uranium	µg/L	5.18			
	Uranium-233/234	pCi/L	2.66			
	Uranium-235/236	pCi/L	0.0862 UJ			
	Uranium-238	pCi/L	1.73			
X701-68G	Technetium-99	pCi/L	19.1			
	Uranium	µg/L	3.5			
	Uranium-233/234	pCi/L	1.6			
	Uranium-235/236	pCi/L	0.0647 UJ			
	Uranium-238	pCi/L	1.17			
X701-69G	Technetium-99	pCi/L	1.45 U			
	Uranium	µg/L	6.06			
	Uranium-233/234	pCi/L	2.93			
	Uranium-235/236	pCi/L	0.131			
	Uranium-238	pCi/L	2.02			
X701-70G	Technetium-99	pCi/L	21.8			
	Uranium	µg/L	2.26			
	Uranium-233/234	pCi/L	1.11			
	Uranium-235/236	pCi/L	0.04 U			
	Uranium-238	pCi/L	0.753			
X705-01GA	Americium-241	pCi/L	0.0221 U			
	Neptunium-237	pCi/L	-0.0199 U			
	Plutonium-238	pCi/L	-0.0054 U			
	Plutonium-239/240	pCi/L	0.00544 U			
	Technetium-99	pCi/L	160			
	Uranium	µg/L	0.904			
	Uranium-233/234	pCi/L	0.328			
	Uranium-235/236	pCi/L	0.0107 U			
Uranium-238	pCi/L	0.302				
X705-02G	Technetium-99	pCi/L	2.8 U			

Table 4.9. Results for radionuclides at the Quadrant II Groundwater Investigative (7-Unit) Area – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X705-02G	Uranium	µg/L	4.99			
	Uranium-233/234	pCi/L	1.55			
	Uranium-235/236	pCi/L	0.0831 UJ			
	Uranium-238	pCi/L	1.66			
X705-07G	Technetium-99	pCi/L	100			
	Uranium	µg/L	1.29			
	Uranium-233/234	pCi/L	0.476			
	Uranium-235/236	pCi/L	0.0488 U			
X720-01G	Uranium-238	pCi/L	0.426			
	Technetium-99	pCi/L	-0.492 U			
	Uranium	µg/L	35.6			
	Uranium-233/234	pCi/L	11.9			
X720-08G	Uranium-235/236	pCi/L	0.65			
	Uranium-238	pCi/L	11.9			
	Technetium-99	pCi/L	191			
	Uranium	µg/L	3.26			
X720-09G	Uranium-233/234	pCi/L	2.83			
	Uranium-235/236	pCi/L	0.157			
	Uranium-238	pCi/L	1.07			
	Technetium-99	pCi/L	2.87 U			
X720-09G	Uranium	µg/L	10.7			
	Uranium-233/234	pCi/L	9.7			
	Uranium-235/236	pCi/L	0.515			
	Uranium-238	pCi/L	3.52			

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
LBC-PZ03G	cis-1,2-Dichloroethene	µg/L	140		110	
	trans-1,2-Dichloroethene	µg/L	1.1		1.1	
	Trichloroethene	µg/L	46		55	
	Vinyl chloride	µg/L	0.26 J		0.35 J	
LBC-PZ06G	Trichloroethene	µg/L	0.16 U		2	
LBC-PZ07G	Acetone	µg/L			15	
	cis-1,2-Dichloroethene	µg/L			0.2 J	
X230J7-01GA	Trichloroethene	µg/L			0.38 J	
	Chloroform	µg/L	0.32 U		0.18 J	
X230J7-02GA	cis-1,2-Dichloroethene	µg/L	0.95 J		0.63 J	
	Trichloroethene	µg/L	330		290	
	Chloroform	µg/L	0.32 U		0.21 J	
X230J7-03GA	cis-1,2-Dichloroethene	µg/L	3.4		3.8	
	Tetrachloroethene	µg/L	0.4 U		0.3 J	
	Trichloroethene	µg/L	420		390	
	Vinyl chloride	µg/L	0.2 U		0.21 J	
X230J7-04GA	cis-1,2-Dichloroethene	µg/L	320		160	
	trans-1,2-Dichloroethene	µg/L	5.4 J		3.6 J	
	Trichloroethene	µg/L	1700		2300	
	Vinyl chloride	µg/L	6.9 J		3.3 J	
X237-EPW	Acetone	µg/L			2.1 J	
	Trichloroethene	µg/L			2	
X237-WPW	1,1,2,2-Tetrachloroethane	µg/L			23 J	
	1,1,2-Trichloroethane	µg/L			33 J	
	1,1-Dichloroethene	µg/L			28 J	
	cis-1,2-Dichloroethene	µg/L			13000	
	trans-1,2-Dichloroethene	µg/L			67 J	
	Trichloroethene	µg/L			17000	
X701-01G	cis-1,2-Dichloroethene	µg/L			4600	
	Tetrachloroethene	µg/L			45 J	
	trans-1,2-Dichloroethene	µg/L			44 J	
	Trichloroethene	µg/L			44000	
X701-02G	Vinyl chloride	µg/L			360 J	
	1,1-Dichloroethene	µg/L	0.75 J		0.95 J	
	cis-1,2-Dichloroethene	µg/L	15		27	
	trans-1,2-Dichloroethene	µg/L	0.49 J		0.74 J	
	Trichloroethene	µg/L	84		160	
X701-06G	Vinyl chloride	µg/L	0.18 J		0.43 J	
	1,1-Dichloroethene	µg/L	0.38 J		0.27 J	
	Acetone	µg/L	1.9 U		3 BJ	
X701-15G	cis-1,2-Dichloroethene	µg/L	5.3		4.2	
	Trichloroethene	µg/L	17		16	
	1,1-Dichloroethane	µg/L	0.73 J		0.41 J	
	1,1-Dichloroethene	µg/L	7.4		2.8	
	Chloroform	µg/L	0.31 J		0.21 J	
	cis-1,2-Dichloroethene	µg/L	21		11	
	trans-1,2-Dichloroethene	µg/L	0.37 J		0.25 J	
X701-15G	Trichloroethene	µg/L	250		110	
	Vinyl chloride	µg/L	0.37 J		0.34 J	
X701-15G	1,1-Dichloroethene	µg/L	0.46 U		1.1 J	

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-15G	cis-1,2-Dichloroethene	µg/L	380		710	
	trans-1,2-Dichloroethene	µg/L	4.1		7.3	
	Trichloroethene	µg/L	9.1		12	
	Vinyl chloride	µg/L	0.1 U		4.2 J	
X701-16G	Trichloroethene	µg/L	0.16 U		0.32 J	
X701-20G	1,1,2,2-Tetrachloroethane	µg/L	62 J		84 U	
	1,1,2-Trichloroethane	µg/L	92 J		110 U	
	Acetone	µg/L	380 U		1500 BJ	
	cis-1,2-Dichloroethene	µg/L	1900		1500	
	Tetrachloroethene	µg/L	100 J		110 J	
	trans-1,2-Dichloroethene	µg/L	43 J		60 U	
X701-21G	Trichloroethene	µg/L	78000		80000	
	1,2-Dichlorobenzene	µg/L	0.31 J		0.27 J	
	Acetone	µg/L	1.9 U		3.3 J	
	Chloroform	µg/L	0.16 U		0.2 J	
	cis-1,2-Dichloroethene	µg/L	23		29	
	trans-1,2-Dichloroethene	µg/L	0.15 U		0.19 J	
	Trichloroethene	µg/L	14		22	
X701-23G	Vinyl chloride	µg/L	1.4		1.8	
	Acetone	µg/L			5.1 J	
X701-24G	Trichloroethene	µg/L			2.1	
	cis-1,2-Dichloroethene	µg/L	910		1100	
X701-25G	trans-1,2-Dichloroethene	µg/L	9.3 J		16 J	
	Trichloroethene	µg/L	6200		11000	
	Vinyl chloride	µg/L	26 J		31	
	Acetone	µg/L	1.9 U		3.6 BJ	
X701-30G	Trichloroethene	µg/L	0.68 J		0.67 J	
	cis-1,2-Dichloroethene	µg/L	0.2 J		0.17 J	
X701-31G	Trichloroethene	µg/L	4.9		4.3	
	Trichlorofluoromethane	µg/L	0.87 J		0.89 J	
	Acetone	µg/L			3.4 J	
X701-38G	Trichloroethene	µg/L			0.24 J	
	1,2-Dichlorobenzene	µg/L			0.25 J	
X701-42G	Chloroform	µg/L			0.16 J	
	1,2-Dichlorobenzene	µg/L			0.34 J	
	cis-1,2-Dichloroethene	µg/L			30	
	Trichloroethene	µg/L			5.2	
X701-58B	Vinyl chloride	µg/L			1.9	
X701-61B	Benzene	µg/L			0.25 J	
	1,2-Dimethylbenzene	µg/L			0.22 J	
X701-66G	m,p-Xylenes	µg/L			2.8	
	Trichloroethene	µg/L			1.4	
	1,1-Dichloroethene	µg/L	9.2 U		6 J	
	Chloroform	µg/L	19 J		10 J	
	cis-1,2-Dichloroethene	µg/L	310		220	
	Tetrachloroethene	µg/L	12 J		6.9 J	
X701-77G	Trichloroethene	µg/L	12000		5400	
	Vinyl chloride	µg/L	4 U		4.5	
	1,1-Dichloroethene	µg/L			4.9 J	
	cis-1,2-Dichloroethene	µg/L			72	

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-77G	Tetrachloroethene	µg/L			15 J	
	trans-1,2-Dichloroethene	µg/L			4 J	
	Trichloroethene	µg/L			5200	
	Vinyl chloride	µg/L			0.74 J	
X701-79G	Acetone	µg/L			2.3 J	
	cis-1,2-Dichloroethene	µg/L			4.6	
	Trichloroethene	µg/L			93	
X701-127G	1,1,2-Trichloroethane	µg/L	48 J		68 J	
	cis-1,2-Dichloroethene	µg/L	940		960	
	Tetrachloroethene	µg/L	37 J		40 U	
	Trichloroethene	µg/L	41000		36000	
X701-128G	Acetone	µg/L	190 U		340 BJ	
	cis-1,2-Dichloroethene	µg/L	330		240	
	Tetrachloroethene	µg/L	25 J		22 J	
	Trichloroethene	µg/L	26000		21000	
X701-130G	Acetone	µg/L			4400 BJ	
	cis-1,2-Dichloroethene	µg/L			1000	
	Methylene chloride	µg/L			680 BJ	
	Tetrachloroethene	µg/L			210 J	
	Trichloroethene	µg/L			160000	
	Vinyl chloride	µg/L			76 J	
X701-141G	1,1,2-Trichloroethane	µg/L			0.27 J	
	Acetone	µg/L			2.8 J	
	cis-1,2-Dichloroethene	µg/L			1.2	
	Trichloroethene	µg/L			210	
X701-142G	1,1,2-Trichloroethane	µg/L	19 J		12 J	
	1,1-Dichloroethene	µg/L	9.5 J		9.2 U	
	cis-1,2-Dichloroethene	µg/L	5000		2600	
	trans-1,2-Dichloroethene	µg/L	31 J		25 J	
	Trichloroethene	µg/L	11000		4900	
	Vinyl chloride	µg/L	45 J		14 J	
X701-143G	1,1-Dichloroethene	µg/L	0.72 J		0.51 J	
	cis-1,2-Dichloroethene	µg/L	460		360	
	trans-1,2-Dichloroethene	µg/L	6		4	
	Trichloroethene	µg/L	19		11	
	Vinyl chloride	µg/L	13		10	
X701-144G	1,1-Dichloroethene	µg/L	0.54 J			
	cis-1,2-Dichloroethene	µg/L	380			
	trans-1,2-Dichloroethene	µg/L	4.4			
	Trichloroethene	µg/L	0.86 J			
	Vinyl chloride	µg/L	80			
X701-BW1G	Acetone	µg/L			3.4 J	
X701-BW2G	Acetone	µg/L			1900 BJ	
	Chloroform	µg/L			200 J	
	cis-1,2-Dichloroethene	µg/L			420	
	Methylene chloride	µg/L			270 BJ	
	Trichloroethene	µg/L			37000	
X701-BW3G	1,1-Dichloroethane	µg/L			0.4 J	
	1,1-Dichloroethene	µg/L			0.89 J	
	cis-1,2-Dichloroethene	µg/L			70	

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
X701-BW3G	Tetrachloroethene	µg/L			0.2 J		
	trans-1,2-Dichloroethene	µg/L			0.33 J		
	Trichloroethene	µg/L			65		
	Vinyl chloride	µg/L			7.2		
X701-BW4G	Acetone	µg/L	1.9 U		1.9 J		
	cis-1,2-Dichloroethene	µg/L	6.1		6.9		
	trans-1,2-Dichloroethene	µg/L	0.39 J		0.54 J		
	Trichloroethene	µg/L	1.6		1.4		
X701-EW121G	Vinyl chloride	µg/L	0.28 J		0.32 J		
	1,1,1-Trichloroethane	µg/L	430		80 U		
	1,1,2,2-Tetrachloroethane	µg/L	450		130 J		
	1,1,2-Trichloroethane	µg/L	500		140 U		
	1,1-Dichloroethene	µg/L	250		120 U		
	Acetone	µg/L	380 U		1100 J		
	Carbon tetrachloride	µg/L	82 J		95 U		
	Chloroform	µg/L	100 J		80 U		
	Chloromethane	µg/L	180 J		150 U		
	cis-1,2-Dichloroethene	µg/L	1500 J		950		
	Tetrachloroethene	µg/L	2600		200 J		
	trans-1,2-Dichloroethene	µg/L	1700		92 J		
	Trichloroethene	µg/L	100000		87000		
	X701-EW122G	1,1,1-Trichloroethane	µg/L	16 U		18 J	
		1,1,2,2-Tetrachloroethane	µg/L	130		150	
		1,1,2-Trichloroethane	µg/L	27 U		36 J	
Acetone		µg/L	190 U		410 BJ		
cis-1,2-Dichloroethene		µg/L	270		320		
Tetrachloroethene		µg/L	140		200		
trans-1,2-Dichloroethene		µg/L	33 J		40 J		
X701-IRMPZ03G	Trichloroethene	µg/L	21000		35000		
	1,1,2-Trichloroethane	µg/L	2.2		1.3 J		
	1,1-Dichloroethene	µg/L	1.4 J		1.3 J		
	Chloroform	µg/L	0.36 J		0.64 U		
	cis-1,2-Dichloroethene	µg/L	500		620		
	Tetrachloroethene	µg/L	0.45 J		0.8 U		
	trans-1,2-Dichloroethene	µg/L	5.6		6.3		
	Trichloroethene	µg/L	910		780		
	Vinyl chloride	µg/L	0.44 J		1.2 J		
	X701-IRMPZ05G	1,1,2-Trichloroethane	µg/L			3.7 J	
Acetone		µg/L			34 J		
cis-1,2-Dichloroethene		µg/L			960		
trans-1,2-Dichloroethene		µg/L			9.6 J		
Trichloroethene		µg/L			2000		
X701-IRMPZ07G	Vinyl chloride	µg/L			5.3 J		
	1,1,2-Trichloroethane	µg/L	76 J				
	1,1-Dichloroethene	µg/L	37 J				
	cis-1,2-Dichloroethene	µg/L	6000				
	Tetrachloroethene	µg/L	59 J				
	trans-1,2-Dichloroethene	µg/L	38 J				
Trichloroethene	µg/L	73000					
Vinyl chloride	µg/L	390					

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-IRMPZ08G	1,1,2-Trichloroethane	µg/L	0.57 J		0.35 J	
	cis-1,2-Dichloroethene	µg/L	430		140	
	trans-1,2-Dichloroethene	µg/L	3.9		1.6	
	Trichloroethene	µg/L	180		130	
	Vinyl chloride	µg/L	0.26 J		0.26 J	
X701-TC01G	1,1,1-Trichloroethane	µg/L	140 J		46	
	1,1,2,2-Tetrachloroethane	µg/L	24 J		15 J	
	1,1-Dichloroethene	µg/L	27 J		9.9 J	
	Acetone	µg/L	190 JU		130 BJ	
	Chloromethane	µg/L	36 J		13 J	
	cis-1,2-Dichloroethene	µg/L	4400 J		2000	
	Tetrachloroethene	µg/L	110 J		32 J	
	trans-1,2-Dichloroethene	µg/L	160 J		61	
	Trichloroethene	µg/L	34000 J		9600	
	Vinyl chloride	µg/L	140 J		50	
	X701-TC03G	1,1,1-Trichloroethane	µg/L	140 J		92 J
1,1,2,2-Tetrachloroethane		µg/L	340 J		270	
Chloromethane		µg/L	150 J		62 J	
cis-1,2-Dichloroethene		µg/L	5700 J		5500	
Tetrachloroethene		µg/L	63 J		47 J	
trans-1,2-Dichloroethene		µg/L	930 J		600	
Trichloroethene		µg/L	45000 J		30000	
X701-TC05G	Vinyl chloride	µg/L	130 J		110 J	
	1,1,1-Trichloroethane	µg/L	140 J		88 J	
	1,1,2,2-Tetrachloroethane	µg/L	280 J		200	
	Chloromethane	µg/L	140 J		87 J	
	cis-1,2-Dichloroethene	µg/L	4200 J		3000	
	Tetrachloroethene	µg/L	67 J		40 U	
	trans-1,2-Dichloroethene	µg/L	690 J		410	
X701-TC10G	Trichloroethene	µg/L	36000 J		18000	
	Vinyl chloride	µg/L	80 J		38 J	
	1,1,1-Trichloroethane	µg/L	46 J		27 J	
	1,1,2,2-Tetrachloroethane	µg/L	47 J		27 J	
	cis-1,2-Dichloroethene	µg/L	2200 J		2000	
	Tetrachloroethene	µg/L	30 J		29 J	
X701-TC17G	trans-1,2-Dichloroethene	µg/L	300 J		170	
	Trichloroethene	µg/L	18000 J		13000	
	Vinyl chloride	µg/L	61 J		42	
	1,1,1-Trichloroethane	µg/L	16 JU		24 J	
	Chloromethane	µg/L	130 J		93 J	
	cis-1,2-Dichloroethene	µg/L	220 J		180	
X701-TC22G	Tetrachloroethene	µg/L	34 J		37 J	
	Trichloroethene	µg/L	13000 J		13000	
	Vinyl chloride	µg/L	10 JU		2 J	
	1,1,1-Trichloroethane	µg/L	48 J		34 J	
	1,1,2,2-Tetrachloroethane	µg/L	77 J		73 J	
	1,1,2-Trichloroethane	µg/L	40 J		37 J	
X701-TC22G	cis-1,2-Dichloroethene	µg/L	1500 J		1300	
	Tetrachloroethene	µg/L	91 J		74 J	
	trans-1,2-Dichloroethene	µg/L	240 J		200	

Table 4.10. VOCs detected at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter	
X701-TC22G	Trichloroethene	µg/L	33000J		23000		
	Vinyl chloride	µg/L	32J		20U		
X701-TC28G	1,1,1-Trichloroethane	µg/L	300J		170J		
	1,1,2,2-Tetrachloroethane	µg/L	210JU		200J		
	cis-1,2-Dichloroethene	µg/L	780J		540		
	Tetrachloroethene	µg/L	840J		690		
X701-TC48G	Trichloroethene	µg/L	260000J		230000		
	1,1,1-Trichloroethane	µg/L	3.1J		3.2U		
	1,1,2,2-Tetrachloroethane	µg/L	4.7J		13J		
	1,1,2-Trichloroethane	µg/L	2.7JU		14J		
	Benzene	µg/L	4.8J		3.2U		
	Bromomethane	µg/L	8.8J		6.5J		
	Chloroform	µg/L	5.6J		4.4J		
	Chloromethane	µg/L	130J		84		
	cis-1,2-Dichloroethene	µg/L	26J		34		
	Tetrachloroethene	µg/L	12J		34		
	trans-1,2-Dichloroethene	µg/L	4.1J		4.4J		
	Trichloroethene	µg/L	1400J		3500		
	X701-TC54G	1,1,1-Trichloroethane	µg/L	210J		160U	
		1,1,2,2-Tetrachloroethane	µg/L	1100J		910J	
cis-1,2-Dichloroethene		µg/L	380J		310J		
Tetrachloroethene		µg/L	500J		460J		
X701-TC61G	Trichloroethene	µg/L	230000J		160000		
	1,1,1-Trichloroethane	µg/L	110J		160U		
	1,1,2,2-Tetrachloroethane	µg/L	770		660J		
	Acetone	µg/L	760U		2500J		
	cis-1,2-Dichloroethene	µg/L	700		590J		
	Tetrachloroethene	µg/L	570		530J		
	trans-1,2-Dichloroethene	µg/L	110J		150U		
X701-TC67G	Trichloroethene	µg/L	100000		230000		
	1,1,1-Trichloroethane	µg/L	26J		16U		
	1,1,2,2-Tetrachloroethane	µg/L	38J		30J		
	cis-1,2-Dichloroethene	µg/L	270J		200		
	Tetrachloroethene	µg/L	89J		64J		
	trans-1,2-Dichloroethene	µg/L	18J		15U		
X744G-01G	Acetone	µg/L	1.9U		3.7J		
X744G-02G	Acetone	µg/L	1.9JU		2J		
	cis-1,2-Dichloroethene	µg/L	1.8J		1.9		
	Trichloroethene	µg/L	26J		32		
X744G-03G	Trichlorofluoromethane	µg/L	3.8J		3.2		
	cis-1,2-Dichloroethene	µg/L	0.48J		0.31J		
	Trichloroethene	µg/L	5.7J		3.9		

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
LBC-PZ03G	Technetium-99	pCi/L	4.44 U			
	Uranium	µg/L	0.274			
	Uranium-233/234	pCi/L	0.0534 UJ			
	Uranium-235/236	pCi/L	0 U			
	Uranium-238	pCi/L	0.0922			
LBC-PZ06G	Technetium-99	pCi/L	5.03 UJ			
	Uranium	µg/L	0.32			
	Uranium-233/234	pCi/L	0.0548 UJ			
	Uranium-235/236	pCi/L	0.0186 U			
	Uranium-238	pCi/L	0.105			
X230J7-01GA	Technetium-99	pCi/L	5.55 UJ			
	Uranium	µg/L	0.409			
	Uranium-233/234	pCi/L	0.155 UJ			
	Uranium-235/236	pCi/L	0.00566 U			
	Uranium-238	pCi/L	0.137			
X230J7-02GA	Technetium-99	pCi/L	91.1			
	Uranium	µg/L	0.142 UJ			
	Uranium-233/234	pCi/L	0.0871 UJ			
	Uranium-235/236	pCi/L	0.0114 U			
	Uranium-238	pCi/L	0.0459 UJ			
X230J7-03GA	Americium-241	pCi/L	0.0202 U			
	Neptunium-237	pCi/L	0.018 U			
	Plutonium-238	pCi/L	0.00543 U			
	Plutonium-239/240	pCi/L	0.0217 U			
	Technetium-99	pCi/L	51.1			
	Uranium	µg/L	0.529			
	Uranium-233/234	pCi/L	0.193			
	Uranium-235/236	pCi/L	0 U			
	Uranium-238	pCi/L	0.178			
X230J7-04GA	Technetium-99	pCi/L			1.21 U	
	Uranium	µg/L			0.068 U	
	Uranium-233/234	pCi/L			0.0429 U	
	Uranium-235/236	pCi/L			0.00889 U	
	Uranium-238	pCi/L			0.0215 U	
X701-01G	Technetium-99	pCi/L	4.39 U			
	Uranium	µg/L	4.18			
	Uranium-233/234	pCi/L	2.6			
	Uranium-235/236	pCi/L	0.0558 U			
	Uranium-238	pCi/L	1.4			
X701-02G	Technetium-99	pCi/L	8.46 UJ			
	Uranium	µg/L	0.895			
	Uranium-233/234	pCi/L	0.485			
	Uranium-235/236	pCi/L	0.0246 U			
	Uranium-238	pCi/L	0.297			
X701-06G	Technetium-99	pCi/L	44.4			
	Uranium	µg/L	2.32 J			
	Uranium-233/234	pCi/L	1.57			
	Uranium-235/236	pCi/L	0.0778 UJ			
	Uranium-238	pCi/L	0.768			
X701-15G	Technetium-99	pCi/L	4.4 U			

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-15G	Uranium	µg/L	0.119 U			
	Uranium-233/234	pCi/L	0.0648 UJ			
	Uranium-235/236	pCi/L	0.0134 U			
X701-16G	Uranium-238	pCi/L	0.0378 U			
	Technetium-99	pCi/L	4.85 UJ			
	Uranium	µg/L	0.262 UJ			
	Uranium-233/234	pCi/L	0.0794 UJ			
	Uranium-235/236	pCi/L	0.0247 U			
X701-18G	Uranium-238	pCi/L	0.0844 UJ			
	Technetium-99	pCi/L			-0.982 U	
	Uranium	µg/L			0.108 U	
	Uranium-233/234	pCi/L			0.0182 U	
	Uranium-235/236	pCi/L			0 U	
X701-19G	Uranium-238	pCi/L			0.0363 UJ	
	Technetium-99	pCi/L	-0.352 U			
	Uranium	µg/L	0.0297 U			
	Uranium-233/234	pCi/L	0.0319 U			
	Uranium-235/236	pCi/L	0.00566 U			
X701-20G	Uranium-238	pCi/L	0.00911 U			
	Americium-241	pCi/L	0.018 U		0.0225 U	
	Neptunium-237	pCi/L	0.00976 U		0.00479 U	
	Plutonium-238	pCi/L	0.0168 U		0 U	
	Plutonium-239/240	pCi/L	0.0224 U		0.0245 U	
	Technetium-99	pCi/L	167		151	
	Uranium	µg/L	0.105 U		0.305 UJ	
	Uranium-233/234	pCi/L	0.0954		0.0673 UJ	
	Uranium-235/236	pCi/L	0.0119 U		0.0258 U	
	Uranium-238	pCi/L	0.0334 U		0.0984 UJ	
X701-21G	Technetium-99	pCi/L	400			
	Uranium	µg/L	0.178 UJ			
	Uranium-233/234	pCi/L	0.0607 UJ			
	Uranium-235/236	pCi/L	-0.0063 U			
	Uranium-238	pCi/L	0.0607 U			
X701-23G	Technetium-99	pCi/L			8.63	
	Uranium	µg/L			0.00515 U	
	Uranium-233/234	pCi/L			0.0357 UJ	
	Uranium-235/236	pCi/L			0.0111 U	
	Uranium-238	pCi/L			0 U	
X701-24G	Americium-241	pCi/L	0.0201 U			
	Neptunium-237	pCi/L	0.00766 U			
	Plutonium-238	pCi/L	0.0108 U			
	Plutonium-239/240	pCi/L	0.0162 U			
	Technetium-99	pCi/L	8.12 UJ			
	Uranium	µg/L	0.279 UJ			
	Uranium-233/234	pCi/L	0.149			
	Uranium-235/236	pCi/L	0.0064 U			
X701-25G	Uranium-238	pCi/L	0.0927 UJ			
	Technetium-99	pCi/L	-0.399 U			
	Uranium	µg/L	0.0228 U			
	Uranium-233/234	pCi/L	0.0339 U			

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-25G	Uranium-235/236	pCi/L	0.0181 U			
	Uranium-238	pCi/L	0.00484 U			
X701-30G	Technetium-99	pCi/L	6.32 UJ			
	Uranium	µg/L	0.445			
	Uranium-233/234	pCi/L	0.0775 UJ			
	Uranium-235/236	pCi/L	0 U			
X701-31G	Uranium-238	pCi/L	0.149			
	Technetium-99	pCi/L			0.275 U	
	Uranium	µg/L			0.115 U	
	Uranium-233/234	pCi/L			0.0662 UJ	
	Uranium-235/236	pCi/L			0.00588 U	
X701-38G	Uranium-238	pCi/L			0.0378 UJ	
	Technetium-99	pCi/L			-2.64 U	
	Uranium	µg/L			0.0477 U	
	Uranium-233/234	pCi/L			0.0269 U	
	Uranium-235/236	pCi/L			0.0167 U	
X701-42G	Uranium-238	pCi/L			0.0134 U	
	Technetium-99	pCi/L			549	
	Uranium	µg/L			0.206 U	
	Uranium-233/234	pCi/L			0.0819 U	
	Uranium-235/236	pCi/L			0.00566 U	
X701-48G	Uranium-238	pCi/L			0.0682 U	
	Americium-241	pCi/L			0.0333 U	
	Neptunium-237	pCi/L			-0.00427 U	
	Plutonium-238	pCi/L			0.00566 U	
	Plutonium-239/240	pCi/L			0.017 U	
	Technetium-99	pCi/L			-2.47 U	
	Uranium	µg/L			0.105 U	
	Uranium-233/234	pCi/L			0.0139 U	
	Uranium-235/236	pCi/L			0.0173 U	
	Uranium-238	pCi/L			0.0325 U	
X701-58B	Technetium-99	pCi/L			-0.342 U	
	Uranium	µg/L			0.115 U	
	Uranium-233/234	pCi/L			0.147	
	Uranium-235/236	pCi/L			0.0115 U	
	Uranium-238	pCi/L			0.0369 U	
X701-61B	Technetium-99	pCi/L			-2.23 U	
	Uranium	µg/L			0.31	
	Uranium-233/234	pCi/L			0.133	
	Uranium-235/236	pCi/L			0.0127 U	
	Uranium-238	pCi/L			0.102	
X701-66G	Americium-241	pCi/L	0.0294 U		0.00428 U	
	Neptunium-237	pCi/L	0 U		-0.00439 U	
	Plutonium-238	pCi/L	-0.0107 U		-0.0288 U	
	Plutonium-239/240	pCi/L	0.0161 U		0.0288 U	
	Technetium-99	pCi/L	1800		916	
	Uranium	µg/L	0.271		0.271 U	
	Uranium-233/234	pCi/L	0.18		0.167	
	Uranium-235/236	pCi/L	0.0242 U		0.0183 U	
	Uranium-238	pCi/L	0.0875 UJ		0.0883 U	

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-77G	Technetium-99	pCi/L			54.5	
	Uranium	µg/L			0.0581 U	
	Uranium-233/234	pCi/L			0.0326 U	
	Uranium-235/236	pCi/L			0.00579 U	
	Uranium-238	pCi/L			0.0186 U	
X701-79G	Technetium-99	pCi/L			65.7	
	Uranium	µg/L			0.0517 U	
	Uranium-233/234	pCi/L			0.0388 U	
	Uranium-235/236	pCi/L			0.0181 U	
	Uranium-238	pCi/L			0.0145 U	
X701-127G	Americium-241	pCi/L	0 U		0.0582 UJ	
	Neptunium-237	pCi/L	0.0167 U		0 U	
	Plutonium-238	pCi/L	0.00528 U		-0.00525 U	
	Plutonium-239/240	pCi/L	0.0106 U		0.00526 U	
	Technetium-99	pCi/L	72.7		80.9	
	Uranium	µg/L	0.445		0.123 U	
	Uranium-233/234	pCi/L	0.161		0.0265 U	
	Uranium-235/236	pCi/L	0.0177 U		0.0264 U	
	Uranium-238	pCi/L	0.147		0.0371 U	
X701-128G	Americium-241	pCi/L	0.019 U			
	Neptunium-237	pCi/L	0 U			
	Plutonium-238	pCi/L	-0.0053 U			
	Plutonium-239/240	pCi/L	-0.0053 U			
	Technetium-99	pCi/L	16.5			
	Uranium	µg/L	0.217 UJ			
	Uranium-233/234	pCi/L	0.0575 UJ			
	Uranium-235/236	pCi/L	0.00596 U			
	Uranium-238	pCi/L	0.0718 UJ			
X701-130G	Technetium-99	pCi/L			1430	
	Uranium	µg/L			6.64	
	Uranium-233/234	pCi/L			11.3	
	Uranium-235/236	pCi/L			0.532	
	Uranium-238	pCi/L			2.15	
X701-BW1G	Technetium-99	pCi/L			-2 U	
	Uranium	µg/L			0.0541 U	
	Uranium-233/234	pCi/L			0.0318 U	
	Uranium-235/236	pCi/L			0 U	
	Uranium-238	pCi/L			0.0182 U	
X701-BW2G	Technetium-99	pCi/L			1130	
	Uranium	µg/L			0.0961 U	
	Uranium-233/234	pCi/L			0.0202 U	
	Uranium-235/236	pCi/L			0.0126 U	
	Uranium-238	pCi/L			0.0304 U	
X701-BW3G	Technetium-99	pCi/L			149	
	Uranium	µg/L			0.0663 U	
	Uranium-233/234	pCi/L			0.0487 U	
	Uranium-235/236	pCi/L			0.0182 U	
	Uranium-238	pCi/L			0.0195 U	
X701-BW4G	Technetium-99	pCi/L	67.6			
	Uranium	µg/L	0.0765 U			

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-BW4G	Uranium-233/234	pCi/L	0.0334 U			
	Uranium-235/236	pCi/L	0.0119 UJ			
X701-EW121G	Uranium-238	pCi/L	0.0239 U			
	Technetium-99	pCi/L	163		174	
	Uranium	µg/L	0.266 UJ		0.289 UJ	
	Uranium-233/234	pCi/L	0.132 UJ		0.139 UJ	
X701-EW122G	Uranium-235/236	pCi/L	0.0214 U		0.0157 U	
	Uranium-238	pCi/L	0.0861 UJ		0.0948 UJ	
	Technetium-99	pCi/L	273		301	
	Uranium	µg/L	0.471		0.369	
X701-TC01G	Uranium-233/234	pCi/L	0.176 UJ		0.178	
	Uranium-235/236	pCi/L	0.0193 U		0.00765 U	
	Uranium-238	pCi/L	0.155		0.123	
	Americium-241	pCi/L	0.0213 U		0.00484 U	
	Neptunium-237	pCi/L	0.017 U		0 U	
	Plutonium-238	pCi/L	0 U		0.0113 U	
	Plutonium-239/240	pCi/L	0.0209 U		0.0169 U	
	Technetium-99	pCi/L	437		23.9	
X701-TC03G	Uranium	µg/L	12.2		10.7	
	Uranium-233/234	pCi/L	9.35		8.1	
	Uranium-235/236	pCi/L	0.566		0.451	
	Uranium-238	pCi/L	4.02		3.52	
	Americium-241	pCi/L	0.00914 U		0.0177 U	
	Neptunium-237	pCi/L	0.0195 U		0.0087 U	
	Plutonium-238	pCi/L	-0.0053 U		-0.00498 U	
	Plutonium-239/240	pCi/L	0.0265 U		0.0349 U	
X701-TC05G	Technetium-99	pCi/L	1460		1170	
	Uranium	µg/L	5.79		4.05	
	Uranium-233/234	pCi/L	1.78		1.52	
	Uranium-235/236	pCi/L	0.0568 UJ		0.11 U	
	Uranium-238	pCi/L	1.94		1.34	
	Americium-241	pCi/L	0.023 U		0.0137 U	
	Neptunium-237	pCi/L	0.0278 U		-0.00449 U	
	Plutonium-238	pCi/L	-0.0054 U		0.00517 U	
X701-TC10G	Plutonium-239/240	pCi/L	0.0162 U		0.031 U	
	Technetium-99	pCi/L	1420		1230	
	Uranium	µg/L	4.07		4.17	
	Uranium-233/234	pCi/L	1.61		1.95	
	Uranium-235/236	pCi/L	0.126 UJ		0.0286 U	
	Uranium-238	pCi/L	1.35		1.4	
	Americium-241	pCi/L	0.0139 U		0.0178 U	
	Neptunium-237	pCi/L	0 U		0.0131 U	
X701-TC17G	Plutonium-238	pCi/L	0.0106 U		0.00486 U	
	Plutonium-239/240	pCi/L	0.0318 U		0.0194 U	
	Technetium-99	pCi/L	734		539	
	Uranium	µg/L	6.35 J		4.54 J	
	Uranium-233/234	pCi/L	2.81		1.8	
	Uranium-235/236	pCi/L	0.144		0.117 UJ	
	Uranium-238	pCi/L	2.11		1.51	
	Americium-241	pCi/L	0.00977 U		0.00434 U	

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-TC17G	Neptunium-237	pCi/L	0.00853 U		0.0184 U	
	Plutonium-238	pCi/L	0 U		-0.00937 U	
	Plutonium-239/240	pCi/L	0.00999 U		0.0234 U	
	Technetium-99	pCi/L	489		427	
	Uranium	µg/L	33.6		34.1	
	Uranium-233/234	pCi/L	12.5		12.6	
	Uranium-235/236	pCi/L	0.569		0.536	
	Uranium-238	pCi/L	11.2		11.4	
X701-TC22G	Americium-241	pCi/L	0.0314 U		0.0325 U	
	Neptunium-237	pCi/L	0.0101 U		0 U	
	Plutonium-238	pCi/L	-0.0105 U		-0.0197 U	
	Plutonium-239/240	pCi/L	0.0105 U		0.00985 U	
	Technetium-99	pCi/L	978		815	
	Uranium	µg/L	1.09		1.48 J	
	Uranium-233/234	pCi/L	0.4		0.498	
	Uranium-235/236	pCi/L	0.0439 U		0.0322 U	
X701-TC28G	Uranium-238	pCi/L	0.358		0.491	
	Americium-241	pCi/L	0.0184 U		0.0282 U	
	Neptunium-237	pCi/L	0 U		0.00918 U	
	Plutonium-238	pCi/L	-0.0105 U		0.00527 U	
	Plutonium-239/240	pCi/L	0.00523 U		0.0105 U	
	Technetium-99	pCi/L	716		566	
	Uranium	µg/L	18.7		16.7	
	Uranium-233/234	pCi/L	7.55		6.44	
X701-TC48G	Uranium-235/236	pCi/L	0.374		0.336	
	Uranium-238	pCi/L	6.21		5.55	
	Americium-241	pCi/L	0.0144 U		0.0135 U	
	Neptunium-237	pCi/L	-0.0090 U		0.00481 U	
	Plutonium-238	pCi/L	0.00529 U		-0.00918 U	
	Plutonium-239/240	pCi/L	0.0317 U		0.0184 U	
	Technetium-99	pCi/L	134		181	
	Uranium	µg/L	80.1		73.4	
X701-TC54G	Uranium-233/234	pCi/L	28.9		26.3	
	Uranium-235/236	pCi/L	1.39		1.5	
	Uranium-238	pCi/L	26.7		24.4	
	Americium-241	pCi/L	0.0218 U		0.0326 U	
	Neptunium-237	pCi/L	0 U		0 U	
	Plutonium-238	pCi/L	0.00535 U		-0.00532 U	
	Plutonium-239/240	pCi/L	-0.0054 U		0.0213 U	
	Technetium-99	pCi/L	721		664	
X701-TC61G	Uranium	µg/L	2.63		1.7	
	Uranium-233/234	pCi/L	0.807		0.626	
	Uranium-235/236	pCi/L	0.0433 U		0.0463 U	
	Uranium-238	pCi/L	0.876		0.564	
	Americium-241	pCi/L	0.0245 U		0.0231 U	
	Neptunium-237	pCi/L	-0.0092 U		-0.0048 U	
	Plutonium-238	pCi/L	-0.0107 U		-0.00524 U	
	Plutonium-239/240	pCi/L	0.0376 U		0.0105 U	
	Technetium-99	pCi/L	687		661	
	Uranium	µg/L	2.18		1.93	

Table 4.11. Results for radionuclides at the X-701B Former Holding Pond – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X701-TC61G	Uranium-233/234	pCi/L	0.693		0.707	
	Uranium-235/236	pCi/L	0.029 U		0.0503 U	
	Uranium-238	pCi/L	0.728		0.64	
X701-TC67G	Americium-241	pCi/L	0.0342 U		0.00895 U	
	Neptunium-237	pCi/L	0.0257 U		0.00426 U	
	Plutonium-238	pCi/L	0 U		0 U	
	Plutonium-239/240	pCi/L	0.0222 U		0.00986 U	
	Technetium-99	pCi/L	177		173	
	Uranium	µg/L	0.396		0.657	
	Uranium-233/234	pCi/L	0.138		0.188	
	Uranium-235/236	pCi/L	0 U		-0.0123 U	
	Uranium-238	pCi/L	0.133		0.223	

Table 4.12. Results for chromium at the X-633 Former Recirculating Cooling Water Complex – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X633-07G	Chromium	µg/L		450		630
X633-PZ04G	Chromium	µg/L		22		43

Table 4.13. VOCs detected at the X-616 Former Chromium Sludge Surface Impoundments – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X616-02G	1,1-Dichloroethene	µg/L	0.46 J			
	Trichloroethene	µg/L	0.45 J			
X616-09G	1,1,1-Trichloroethane	µg/L	4		3.7	
	1,1-Dichloroethene	µg/L	3.6		3.8	
	1,1-Dichloroethene	µg/L	35		35	
	1,2-Dichloroethene	µg/L	0.13 U		0.2 J	
	cis-1,2-Dichloroethene	µg/L	3.1		3.1	
	Trichloroethene	µg/L	24		24	
X616-13G	1,1,1-Trichloroethane	µg/L	4		4.5	
	1,1-Dichloroethene	µg/L	0.82 J		1	
	1,1-Dichloroethene	µg/L	23		29	
	cis-1,2-Dichloroethene	µg/L	0.35 J		0.57 J	
	Trichloroethene	µg/L	12		16	
	Trichlorofluoromethane	µg/L	5.6		6.8	
X616-14G	1,1,1-Trichloroethane	µg/L	1.6		1.7	
	1,1-Dichloroethene	µg/L	0.29 J		0.35 J	
	1,1-Dichloroethene	µg/L	7.2		8.7	
	Acetone	µg/L	1.9 U		1.9 J	
	Trichloroethene	µg/L	2.2		2.8	
	Trichlorofluoromethane	µg/L	0.58 J		0.69 J	
X616-16G	1,1-Dichloroethene	µg/L	0.24 J			
	1,1-Dichloroethene	µg/L	1.8			
	cis-1,2-Dichloroethene	µg/L	1.1			
	Trichloroethene	µg/L	2.8			
X616-20B	1,1,1-Trichloroethane	µg/L	0.3 J		0.43 J	
	1,1-Dichloroethene	µg/L	0.52 J		0.69 J	
	1,1-Dichloroethene	µg/L	3.8		5.3	
	Acetone	µg/L	1.9 U		2.3 J	
	cis-1,2-Dichloroethene	µg/L	0.4 J		0.67 J	
	Trichloroethene	µg/L	12		16	
X616-25G	1,1-Dichloroethene	µg/L	0.22 U		0.23 J	
	cis-1,2-Dichloroethene	µg/L	0.74 J		0.63 J	
	Trichloroethene	µg/L	1.8		1.2	
X616-28B	1,1,1-Trichloroethane	µg/L	0.96 J			
	1,1-Dichloroethene	µg/L	0.47 J			
	Trichloroethene	µg/L	0.38 J			

**Table 4.14. Results for chromium at the X-616 Former Chromium Sludge Surface Impoundments
 – 2015**

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X616-02G	Chromium	µg/L	0.5 U			
X616-05G	Chromium	µg/L	1200			
X616-09G	Chromium	µg/L	4.6			
X616-10G	Chromium	µg/L	0.5 U			
X616-13G	Chromium	µg/L	0.78 B			
X616-14G	Chromium	µg/L	0.62 B			
X616-16G	Chromium	µg/L	0.65 B			
X616-17G	Chromium	µg/L	27			
X616-19B	Chromium	µg/L	20			
X616-20B	Chromium	µg/L	1.2 B			
X616-21G	Chromium	µg/L	1.3 B			
X616-22G	Chromium	µg/L	0.5 U			
X616-24B	Chromium	µg/L	0.5 U			
X616-25G	Chromium	µg/L	1.6 B			
X616-26G	Chromium	µg/L	8.8			
X616-28B	Chromium	µg/L	0.55 B			

Table 4.15. VOCs detected at the X-740 Former Waste Oil Handling Facility – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X740-02G	1,1,1-Trichloroethane	µg/L		2.65		2.64
	1,1-Dichloroethane	µg/L		2.5		2.77
	1,1-Dichloroethene	µg/L		3.83		4.48
	Trichloroethene	µg/L		4.79		5.57
X740-03G	1,1-Dichloroethane	µg/L		1.6J		3.05
	1,1-Dichloroethene	µg/L		41		63.2
	1,2-Dichloroethane	µg/L		5.2		8.41
	Chloroethane	µg/L		5.7J		8.99
	cis-1,2-Dichloroethene	µg/L		350		386
	trans-1,2-Dichloroethene	µg/L		0.6U		1.06
	Trichloroethene	µg/L		6.4		5.8
X740-04G	Vinyl chloride	µg/L		8.4		12.8
	1,1,1-Trichloroethane	µg/L		0.51J		
	1,1-Dichloroethane	µg/L		0.23J		
	1,1-Dichloroethene	µg/L		0.59J		
X740-06G	Carbon disulfide	µg/L		0.6J		
X740-08G	1,1,1-Trichloroethane	µg/L		0.99J		
	1,1-Dichloroethane	µg/L		13		
	1,1-Dichloroethene	µg/L		1.6		
	cis-1,2-Dichloroethene	µg/L		16		
	trans-1,2-Dichloroethene	µg/L		4.7		
	Trichloroethene	µg/L		9.2		
	1,1,1-Trichloroethane	µg/L		10.9		2.81
X740-09B	1,1-Dichloroethane	µg/L		29.5		22.9
	1,1-Dichloroethene	µg/L		254		193
	1,2-Dichloroethane	µg/L		68.2		45.4
	Chloroform	µg/L		1.54		0.37J
	cis-1,2-Dichloroethene	µg/L		1360		683
	Methylene chloride	µg/L		2.16BJ		5U
	Tetrachloroethene	µg/L		12.4		12.2
	trans-1,2-Dichloroethene	µg/L		1.37		1.18
	Trichloroethene	µg/L		597		488
	Vinyl chloride	µg/L		2.25		1.83
X740-10G	1,1,1-Trichloroethane	µg/L		1.24		1.35
	1,1-Dichloroethane	µg/L		2.76		4.34
	1,1-Dichloroethene	µg/L		12.6		32.4
	1,2-Dichloroethane	µg/L		5.06		6.52
	cis-1,2-Dichloroethene	µg/L		56		101
	Tetrachloroethene	µg/L		2.25		2.68
	Trichloroethene	µg/L		103E		126
X740-11G	1,1,1-Trichloroethane	µg/L		0.79J		
	1,1-Dichloroethane	µg/L		0.48J		
	1,1-Dichloroethene	µg/L		6.7		
	1,2-Dichloroethane	µg/L		2.6		
	Chloroform	µg/L		0.23J		
X740-12B	Trichloroethene	µg/L		25		
X740-12B	Acetone	µg/L		2.2J		
X740-14B	1,1-Dichloroethene	µg/L		1.2		
	Trichloroethene	µg/L		6.3		

Table 4.15. VOCs detected at the X-740 Former Waste Oil Handling Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X740-18G	1,1-Dichloroethene	µg/L		1 U		1.51
	1,2-Dichloroethane	µg/L		0.37J		1 U
	2-Butanone	µg/L		267		187
	Acetone	µg/L		152		167
	Chloroethane	µg/L		1 U		0.91 J
	cis-1,2-Dichloroethene	µg/L		15.1		11.2
	Trichloroethene	µg/L		0.38J		1 U
	Vinyl chloride	µg/L		1 U		1.69
X740-19G	1,1-Dichloroethene	µg/L		0.52J		1.52
	1,2-Dichloroethane	µg/L		1 U		0.36J
	cis-1,2-Dichloroethene	µg/L		0.97J		4.92
	Tetrachloroethene	µg/L		0.84J		0.86J
	Trichloroethene	µg/L		8.58		10.5
X740-20G	1,1-Dichloroethene	µg/L		0.45J		0.51 J
	cis-1,2-Dichloroethene	µg/L		1.67		2.89
	Trichloroethene	µg/L		6.16		4.14
X740-21G	1,1-Dichloroethene	µg/L		1.02		0.81 J
	1,2-Dichloroethane	µg/L		0.35J		1 U
	cis-1,2-Dichloroethene	µg/L		0.46J		0.64 J
	Tetrachloroethene	µg/L		0.32J		1 U
	Trichloroethene	µg/L		12.7		9.36
X740-22G	1,1,1-Trichloroethane	µg/L		1.61		1.44
	1,1-Dichloroethane	µg/L		0.82J		0.97J
	1,1-Dichloroethene	µg/L		15		15.1
	1,2-Dichloroethane	µg/L		3.81		3.34
	cis-1,2-Dichloroethene	µg/L		3.36		4.45
	Methylene chloride	µg/L		1.81 BJ		5 U
	Tetrachloroethene	µg/L		1.9		2.01
	Trichloroethene	µg/L		99.2		92.7
X740-23M	Methylene chloride	µg/L		1.9 BJ		5 U
X740-PZ04M	Methylene chloride	µg/L		5 U		2.2 J
X740-PZ10G	1,1-Dichloroethene	µg/L		0.31 J		
	Methylene chloride	µg/L		0.68 BJ		
	Trichloroethene	µg/L		6.7		
X740-PZ12G	1,1,1-Trichloroethane	µg/L		1.51		1.34
	1,1-Dichloroethane	µg/L		1 U		0.61 J
	1,1-Dichloroethene	µg/L		6.85		6.16
	1,2-Dichloroethane	µg/L		3.37		2.98
	Chloroform	µg/L		0.32J		0.3 J
	Methylene chloride	µg/L		2.13 BJ		5 U
	Tetrachloroethene	µg/L		0.76J		0.72 J
	Trichloroethene	µg/L		61.6		62.7
X740-PZ14G	1,1,1-Trichloroethane	µg/L		2.2		
	1,1-Dichloroethane	µg/L		1.1		
	1,1-Dichloroethene	µg/L		19		
	1,2-Dichloroethane	µg/L		5.7		
	Chloroform	µg/L		0.54J		
	cis-1,2-Dichloroethene	µg/L		0.41 J		
	Tetrachloroethene	µg/L		1.6		
Trichloroethene	µg/L		130			

Table 4.15. VOCs detected at the X-740 Former Waste Oil Handling Facility – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X740-PZ17G	1,1,1-Trichloroethane	µg/L		1.1		
	1,1-Dichloroethane	µg/L		0.34J		
	1,1-Dichloroethene	µg/L		5		
	1,2-Dichloroethane	µg/L		2.1		
	Acetone	µg/L		3.2J		
	Chloroform	µg/L		0.23J		
	Trichloroethene	µg/L		28		

Table 4.16. Results for beryllium and chromium at the X-611A Former Lime Sludge Lagoons – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
F-07G	Beryllium	µg/L	1.9		0.85 B	
	Chromium	µg/L	12		4.8	
F-08B	Beryllium	µg/L	0.08 U		0.22 B	
	Chromium	µg/L	0.5 U		0.5 U	
X611-01B	Beryllium	µg/L	0.11 UJ		0.08 U	
	Chromium	µg/L	2.7		4.8	
X611-02BA	Beryllium	µg/L	0.08 U		0.08 U	
	Chromium	µg/L	0.5 U		0.5 U	
X611-03G	Beryllium	µg/L	0.08 U		0.08 U	
	Chromium	µg/L	0.5 U		0.5 U	
X611-04BA	Beryllium	µg/L	0.32 B		0.8 B	
	Chromium	µg/L	0.5 U		0.5 U	

Table 4.17. VOCs detected at the X-735 Landfills – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X735-02GA	1,1-Dichloroethane	µg/L		0.25 J		
X737-05B	Acetone	µg/L		2.5 J		
X737-06G	Acetone	µg/L		5.5 J		
X737-09G	Methylene chloride	µg/L		0.44 J		

Table 4.18. Results for radionuclides at the X-735 Landfills – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X735-01GA	Technetium-99	pCi/L		-1.47 U		
	Uranium	µg/L		0.0686 U		
	Uranium-233/234	pCi/L		0.0133 U		
	Uranium-235/236	pCi/L		0.00553 U		
	Uranium-238	pCi/L		0.0222 U		
X735-02GA	Technetium-99	pCi/L		-0.251 U		
	Uranium	µg/L		0.0233 U		
	Uranium-233/234	pCi/L		0.013 U		
	Uranium-235/236	pCi/L		-0.0054 U		
	Uranium-238	pCi/L		0.00867 U		
X735-03GA	Technetium-99	pCi/L		0.547 U		
	Uranium	µg/L		0.0106 U		
	Uranium-233/234	pCi/L		0.00887 U		
	Uranium-235/236	pCi/L		-0.0055 U		
	Uranium-238	pCi/L		0.00444 U		
X735-04GA	Technetium-99	pCi/L		4.21 U		
	Uranium	µg/L		0.0589 U		
	Uranium-233/234	pCi/L		0.0259 U		
	Uranium-235/236	pCi/L		0.0161 U		
	Uranium-238	pCi/L		0.0173 U		
X735-05GA	Technetium-99	pCi/L		0.388 U		
	Uranium	µg/L		0.19 UJ		
	Uranium-233/234	pCi/L		0.0956 UJ		
	Uranium-235/236	pCi/L		0.0416 U		
	Uranium-238	pCi/L		0.0574 UJ		
X735-06GAA	Technetium-99	pCi/L		1.54 U		
	Uranium	µg/L		0.0993 U		
	Uranium-233/234	pCi/L		0.0335 U		
	Uranium-235/236	pCi/L		0.0298 U		
	Uranium-238	pCi/L		0.0287 U		
X735-13GA	Technetium-99	pCi/L		1.45 U		
	Uranium	µg/L		0.177 U		
	Uranium-233/234	pCi/L		0.0898 UJ		
	Uranium-235/236	pCi/L		0.0745 U		
	Uranium-238	pCi/L		0.0479 UJ		
X735-16B	Technetium-99	pCi/L		0.459 U		
	Uranium	µg/L		0.029 U		
	Uranium-233/234	pCi/L		0 U		
	Uranium-235/236	pCi/L		0.00553 U		
	Uranium-238	pCi/L		0.0089 U		
X735-17B	Technetium-99	pCi/L		-2.33 U		
	Uranium	µg/L		0.229 U		
	Uranium-233/234	pCi/L		0.162		
	Uranium-235/236	pCi/L		0.0163 U		
	Uranium-238	pCi/L		0.0743 U		
X735-18B	Technetium-99	pCi/L		-1.57 U		
	Uranium	µg/L		0.0159 U		
	Uranium-233/234	pCi/L		0 U		
	Uranium-235/236	pCi/L		0.00555 U		
	Uranium-238	pCi/L		0.00446 U		

Table 4.18. Results for radionuclides at the X-735 Landfills – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X735-19G	Technetium-99	pCi/L		-0.478 U		
	Uranium	µg/L		0.0673 U		
	Uranium-233/234	pCi/L		0.0181 U		
	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.0226 U		
X735-20B	Technetium-99	pCi/L		0.915 U		
	Uranium	µg/L		0.0651 U		
	Uranium-233/234	pCi/L		0.0183 U		
	Uranium-235/236	pCi/L		0.0228 U		
	Uranium-238	pCi/L		0.0183 U		
X735-21G	Technetium-99	pCi/L		2.35 U		
	Uranium	µg/L		0.468		
	Uranium-233/234	pCi/L		0.224		
	Uranium-235/236	pCi/L		0.0186 U		
	Uranium-238	pCi/L		0.154		
X737-05B	Technetium-99	pCi/L		0.0801 U		
	Uranium	µg/L		-0.0088 U		
	Uranium-233/234	pCi/L		0.00481 U		
	Uranium-235/236	pCi/L		0.012 U		
	Uranium-238	pCi/L		-0.0048 U		
X737-06G	Technetium-99	pCi/L		1.99 U		
	Uranium	µg/L		0.127 UJ		
	Uranium-233/234	pCi/L		0.0514 UJ		
	Uranium-235/236	pCi/L		0.0348 U		
	Uranium-238	pCi/L		0.0374 UJ		
X737-07B	Technetium-99	pCi/L		0.501 U		
	Uranium	µg/L		0.0735 U		
	Uranium-233/234	pCi/L		0.0287 U		
	Uranium-235/236	pCi/L		0.0357 U		
	Uranium-238	pCi/L		0.0191 U		
X737-08B	Technetium-99	pCi/L		-0.0114 U		
	Uranium	µg/L		0.158 U		
	Uranium-233/234	pCi/L		0.13		
	Uranium-235/236	pCi/L		0.0116 U		
	Uranium-238	pCi/L		0.0512 U		
X737-09G	Technetium-99	pCi/L		-0.583 U		
	Uranium	µg/L		0.15 U		
	Uranium-233/234	pCi/L		0.0475 U		
	Uranium-235/236	pCi/L		0.0177 U		
	Uranium-238	pCi/L		0.0475 U		

Table 4.19. VOCs detected at the X-734 Landfills – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
RSY-02B	Acetone	µg/L		7.4 BJ		1.9 U
	Methylene chloride	µg/L		0.32 U		0.88 J
X734-02B	Acetone	µg/L		12		1.9 U
X734-03G	1,4-Dichlorobenzene	µg/L		0.23 J		0.16 U
	Chloromethane	µg/L		0.39 J		0.3 U
X734-05B	1,2-Dimethylbenzene	µg/L		0.24 J		0.25 J
	Benzene	µg/L		0.74 J		1.5
	Ethylbenzene	µg/L		0.44 J		0.38 J
	Toluene	µg/L		0.32 J		0.56 J
X734-14G	Acetone	µg/L		1.9 U		3.5 J
X734-16G	Acetone	µg/L		4 J		71 J
X734-22G	Methylene chloride	µg/L		0.5 UJ		1 J
	Trichloroethene	µg/L		0.16 U		0.25 J
X734-23G	Acetone	µg/L		2.9 J		1.9 U
	cis-1,2-Dichloroethene	µg/L		3		3.9
	trans-1,2-Dichloroethene	µg/L		0.16 J		0.21 J
	Vinyl chloride	µg/L		0.54 J		0.93 J

Table 4.20. Results for radionuclides at the X-734 Landfills – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
RSY-02B	Americium-241	pCi/L		0.0176 U		
	Neptunium-237	pCi/L		0.0046 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.011 U		
	Technetium-99	pCi/L		-0.891 U		
	Uranium	µg/L		0.0289 U		
	Uranium-233/234	pCi/L		0.0753 U		
	Uranium-235/236	pCi/L		-0.0067 U		
X734-01G	Uranium-238	pCi/L		0.0108 U		
	Americium-241	pCi/L		0.0142 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0.00537 U		
	Plutonium-239/240	pCi/L		0.0269 U		
	Technetium-99	pCi/L		-0.273 U		
	Uranium	µg/L		0.238 U		
	Uranium-233/234	pCi/L		0.053 U		
X734-02B	Uranium-235/236	pCi/L		0.018 U		
	Uranium-238	pCi/L		0.0771 U		
	Americium-241	pCi/L		0.00913 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.0231 U		
	Technetium-99	pCi/L		-1.87 U		
	Uranium	µg/L		0.034 U		
X734-03G	Uranium-233/234	pCi/L		0.0143 U		
	Uranium-235/236	pCi/L		0.0119 U		
	Uranium-238	pCi/L		0.00957 U		
	Americium-241	pCi/L		0.00923 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.0106 U		
	Technetium-99	pCi/L		-0.137 U		
X734-04G	Uranium	µg/L		3.11		
	Uranium-233/234	pCi/L		1.64		
	Uranium-235/236	pCi/L		0.084 U		
	Uranium-238	pCi/L		1.03		
	Americium-241	pCi/L		0.00908 U		
	Neptunium-237	pCi/L		0.0161 U		
	Plutonium-238	pCi/L		0.0101 U		
	Plutonium-239/240	pCi/L		0.0152 U		
X734-05B	Technetium-99	pCi/L		-1.89 U		
	Uranium	µg/L		2.4		
	Uranium-233/234	pCi/L		0.748		
	Uranium-235/236	pCi/L		0.0455 U		
	Uranium-238	pCi/L		0.8		
	Americium-241	pCi/L		0.0523 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		-0.0073 U		
X734-05B	Plutonium-239/240	pCi/L		0.0362 U		
	Technetium-99	pCi/L		-1.82 U		

Table 4.20. Results for radionuclides at the X-734 Landfills – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X734-05B	Uranium	µg/L		0.45		
	Uranium-233/234	pCi/L		0.233		
	Uranium-235/236	pCi/L		0.00691 U		
X734-06G	Uranium-238	pCi/L		0.15		
	Americium-241	pCi/L		0.0222 U		
	Neptunium-237	pCi/L		0.00458 U		
	Plutonium-238	pCi/L		0.0414 U		
	Plutonium-239/240	pCi/L		0.0178 U		
	Technetium-99	pCi/L		-0.934 U		
	Uranium	µg/L		0.0287 U		
	Uranium-233/234	pCi/L		0.0145 U		
X734-10G	Uranium-235/236	pCi/L		0 U		
	Uranium-238	pCi/L		0.00963 U		
	Americium-241	pCi/L		0.0139 U		
	Neptunium-237	pCi/L		0.0103 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.0289 U		
	Technetium-99	pCi/L		0.549 U		
	Uranium	µg/L		0.407		
X734-14G	Uranium-233/234	pCi/L		0.183		
	Uranium-235/236	pCi/L		0.0316 U		
	Uranium-238	pCi/L		0.132		
	Americium-241	pCi/L		0.0237 U		
	Neptunium-237	pCi/L		0.0368 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.021 U		
	Technetium-99	pCi/L		0.388 U		
X734-15G	Uranium	µg/L		0.962		
	Uranium-233/234	pCi/L		0.464		
	Uranium-235/236	pCi/L		0.0256 U		
	Uranium-238	pCi/L		0.319		
	Americium-241	pCi/L		-0.0096 U		
	Neptunium-237	pCi/L		0.00489 U		
	Plutonium-238	pCi/L		0.00505 U		
	Plutonium-239/240	pCi/L		0.0101 U		
X734-16G	Technetium-99	pCi/L		0.624 U		
	Uranium	µg/L		0.638		
	Uranium-233/234	pCi/L		0.303		
	Uranium-235/236	pCi/L		0.0202 U		
	Uranium-238	pCi/L		0.211		
	Americium-241	pCi/L		0.00449 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		0.00509 U		
X734-18G	Plutonium-239/240	pCi/L		0.0153 U		
	Technetium-99	pCi/L		-2 U		
	Uranium	µg/L		1.83		
	Uranium-233/234	pCi/L		0.761		
	Uranium-235/236	pCi/L		0.0489 U		
	Uranium-238	pCi/L		0.609		
	Americium-241	pCi/L		0.0252 U		

Table 4.20. Results for radionuclides at the X-734 Landfills – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X734-18G	Neptunium-237	pCi/L		0.00969 U		
	Plutonium-238	pCi/L		0.00526 U		
	Plutonium-239/240	pCi/L		0.0526 U		
	Technetium-99	pCi/L		-0.252 U		
	Uranium	µg/L		2.16		
	Uranium-233/234	pCi/L		1.16		
	Uranium-235/236	pCi/L		0.0276 U		
	Uranium-238	pCi/L		0.722		
X734-20G	Americium-241	pCi/L		0.0156 U		
	Neptunium-237	pCi/L		0.0092 U		
	Plutonium-238	pCi/L		0.00573 U		
	Plutonium-239/240	pCi/L		0.0115 U		
	Technetium-99	pCi/L		-1.48 U		
	Uranium	µg/L		0.00341 U		
	Uranium-233/234	pCi/L		0.0404 U		
	Uranium-235/236	pCi/L		-0.0251 U		
X734-22G	Uranium-238	pCi/L		0.00505 U		
	Americium-241	pCi/L		-0.0087 U		
	Neptunium-237	pCi/L		0.0102 U		
	Plutonium-238	pCi/L		0 U		
	Plutonium-239/240	pCi/L		0.0257 U		
	Technetium-99	pCi/L		0.205 U		
	Uranium	µg/L		1.13		
	Uranium-233/234	pCi/L		0.388		
X734-23G	Uranium-235/236	pCi/L		0.0294 U		
	Uranium-238	pCi/L		0.374		
	Americium-241	pCi/L		0.0177 U		
	Neptunium-237	pCi/L		0 U		
	Plutonium-238	pCi/L		-0.0169 U		
	Plutonium-239/240	pCi/L		0.00564 U		
	Technetium-99	pCi/L		-0.46 U		
	Uranium	µg/L		0.0358 U		
	Uranium-233/234	pCi/L		0.0202 U		
	Uranium-235/236	pCi/L		0.0126 U		
	Uranium-238	pCi/L		0.0101 U		

Table 4.21. Results for cadmium and nickel at the X-533 Former Switchyard Complex – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
F-03G	Cadmium	µg/L		46		40
	Nickel	µg/L		450		400
TCP-01G	Cadmium	µg/L		16		14
	Nickel	µg/L		190		170
X533-03G	Cadmium	µg/L		24		28
	Nickel	µg/L		340		380

Table 4.22. VOCs detected at the X-344C Former Hydrogen Fluoride Storage Building – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
X344C-01G	cis-1,2-Dichloroethene	µg/L	2			
	trans-1,2-Dichloroethene	µg/L	0.17 J			
	Trichloroethene	µg/L	0.31 J			

Table 4.23. VOCs detected at surface water monitoring locations – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
BRC-SW01	Acetone	µg/L	1.9 U	2J	14	2.6 J
	Bromodichloromethane	µg/L	1.4	2.8	0.65 J	0.54 J
	Bromoform	µg/L	0.37 J	0.19 U	0.63 J	0.47 J
	Chloroform	µg/L	2.3	6	1.2	0.66 J
	Dibromochloromethane	µg/L	1.1	1.5	1.1	0.9 J
BRC-SW02	Acetone	µg/L	1.9 U	4.6 J	1.9 U	1.9 U
BRC-SW05	Acetone	µg/L	1.9 U	7.1 J	1.9 U	1.9 U
EDD-SW01	Acetone	µg/L	1.9 U	1.9 U	2.4 J	1.9 U
	Bromodichloromethane	µg/L	1.2	1.6	1.8	0.22 J
	Bromoform	µg/L	0.55 J	0.19 U	1	0.19 U
	Chloroform	µg/L	1.5	3.1	1.5	0.34 J
	cis-1,2-Dichloroethene	µg/L	0.86 J	0.85 J	0.69 J	2.5
	Dibromochloromethane	µg/L	1.5	1.1	2.3	0.23 J
	Methylene chloride	µg/L	0.32 U	0.33 BJ	0.32 U	0.32 U
	Toluene	µg/L	0.17 U	0.17 U	0.21 J	0.17 U
	Trichloroethene	µg/L	1.2	1.1	0.44 J	3.8
	LBC-SW01	Acetone	µg/L	1.9 U	1.9 U	2.9 J
Bromodichloromethane		µg/L	0.57 J	0.49 J	1.5	0.17 U
Bromoform		µg/L	0.33 J	0.19 U	0.98 J	0.19 U
Chloroform		µg/L	0.69 J	0.87 J	1.2	0.16 U
cis-1,2-Dichloroethene		µg/L	0.47 J	0.33 J	1	1.8
Dibromochloromethane		µg/L	0.78 J	0.32 J	2.1	0.17 U
Trichloroethene		µg/L	0.51 J	0.43 J	0.43 J	3.1
LBC-SW02	Acetone	µg/L	1.9 U	1.9 U	2.9 J	1.9 U
	Bromodichloromethane	µg/L	0.3 J	0.33 J	0.6 J	0.17 U
	Bromoform	µg/L	0.2 J	0.19 U	0.44 J	0.19 U
	Chloroform	µg/L	0.36 J	0.61 J	0.49 J	0.16 U
	cis-1,2-Dichloroethene	µg/L	0.24 J	0.26 J	0.35 J	0.95 J
	Dibromochloromethane	µg/L	0.45 J	0.21 J	0.94 J	0.17 U
	Trichloroethene	µg/L	0.19 J	0.29 J	0.16 U	1.6
LBC-SW03	Acetone	µg/L	1.9 U	1.9 U	4.3 J	1.9 U
	Chloroform	µg/L	0.16 U	0.2 J	0.16 U	0.16 U
	cis-1,2-Dichloroethene	µg/L	0.15 U	0.15 U	0.15 U	0.39 J
	Dibromochloromethane	µg/L	0.17 J	0.17 U	0.17 U	0.17 U
	Trichloroethene	µg/L	0.16 U	0.16 U	0.16 U	0.47 J
LBC-SW04	Acetone	µg/L	1.9 U	1.9 U	3.7 J	1.9 U
	cis-1,2-Dichloroethene	µg/L	0.15 U	0.15 U	0.15 U	0.21 J
	Trichloroethene	µg/L	0.16 U	0.16 U	0.16 U	0.29 J
NHP-SW01	Acetone	µg/L	1.9 U	1.9 U	2.3 J	1.9 U
	Bromodichloromethane	µg/L	0.31 J	0.21 J	0.17 U	0.17 U
	Bromoform	µg/L	0.25 J	0.19 U	0.19 U	0.19 U
	Chloroform	µg/L	0.16 U	0.23 J	0.16 U	0.16 U
	Dibromochloromethane	µg/L	0.48 J	0.39 J	0.17 U	0.17 U
UND-SW01	1,1-Dichloroethene	µg/L	0.23 U	0.31 J	0.23 U	0.23 U
	Acetone	µg/L	1.9 U	1.9 U	7.3 J	1.9 U
	cis-1,2-Dichloroethene	µg/L	0.15 U	0.32 J	0.3 J	0.46 J
	Methylene chloride	µg/L	0.32 U	0.57 J	0.32 U	0.32 U
	Trichloroethene	µg/L	0.7 J	5.3	3.9	3.5
UND-SW02	Acetone	µg/L	2.6 UJ	1.9 U	3.7 J	1.9 U
WDD-SW01	Bromodichloromethane	µg/L	0.17 U	0.17 U	0.17 J	0.17 U

Table 4.23. VOCs detected at surface water monitoring locations – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
WDD-SW01	Bromoform	µg/L	0.19 U	0.19 U	0.69 J	0.19 U
	Chloroform	µg/L	0.28 J	0.22 J	0.16 U	0.16 U
	Dibromochloromethane	µg/L	0.17 U	0.17 U	0.46 J	0.17 U
WDD-SW02	Acetone	µg/L	1.9 U	1.9 U	1.9 U	3.5 J
	Bromodichloromethane	µg/L	0.17 U	0.17 U	0.42 J	2.5
	Bromoform	µg/L	0.19 U	0.19 U	0.52 J	1.2
	Chloroform	µg/L	0.16 U	0.16 U	0.25 J	2
	Dibromochloromethane	µg/L	0.17 U	0.17 U	0.8 J	3.7
WDD-SW03	Trichloroethene	µg/L	0.16 U	0.33 J	0.16 U	0.16 U
	Bromodichloromethane	µg/L	0.17 U	0.17 U	0.17 U	0.75 J
	Chloroform	µg/L	0.16 U	0.16 U	0.16 U	1
	Dibromochloromethane	µg/L	0.17 U	0.17 U	0.17 U	0.78 J

Table 4.24. Results for radionuclides at surface water monitoring locations – 2015

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
BRC-SW01	Americium-241	pCi/L		0.0225 U		0.025 U
	Neptunium-237	pCi/L		0.015 U		0 U
	Plutonium-238	pCi/L		0 U		0.00948 U
	Plutonium-239/240	pCi/L		0.00982 U		0.019 U
	Technetium-99	pCi/L	1.86 U	-2.87 U	2.35 U	-0.228 U
	Uranium	µg/L	3.08	0.478	0.135 U	0.758
	Uranium-233/234	pCi/L	5.91	0.532	0.158	0.437
	Uranium-235/236	pCi/L	0.267	0.0438 UJ	0.0231 U	0.0231 U
BRC-SW02	Uranium-238	pCi/L	0.993	0.154	0.0419 U	0.251
	Americium-241	pCi/L		0.0315 U		0.0197 U
	Neptunium-237	pCi/L		0.00506 U		-0.0049 U
	Plutonium-238	pCi/L		0.00501 U		-0.0104 U
	Plutonium-239/240	pCi/L		0.00501 U		0.00519 U
	Technetium-99	pCi/L	2.49 U	-2.78 U	4.13 U	3.16 U
	Uranium	µg/L	0.936	1.15 J	0.472	0.594
	Uranium-233/234	pCi/L	0.784	1.79	0.883	0.48
BRC-SW05	Uranium-235/236	pCi/L	0.0366 U	0.0794 UJ	0.0485 U	0.0264 U
	Uranium-238	pCi/L	0.309	0.374	0.151	0.196
	Americium-241	pCi/L		0.00437 U		0.00976 U
	Neptunium-237	pCi/L		0.0102 U		0 U
	Plutonium-238	pCi/L		0.00467 U		0 U
	Plutonium-239/240	pCi/L		0.0327 U		0.00507 U
	Technetium-99	pCi/L	0.99 U	-2.01 U	4.53 U	0.706 U
	Uranium	µg/L	1.3 J	1.61 J	0.558	0.64
EDD-SW01	Uranium-233/234	pCi/L	1.03	2.88	0.65	0.672
	Uranium-235/236	pCi/L	0.0884 UJ	0.0986 UJ	0.00663 U	0.0395 U
	Uranium-238	pCi/L	0.422	0.524	0.187	0.209
	Americium-241	pCi/L		0.00951 U		0 U
	Neptunium-237	pCi/L		-0.0172 U		0.0101 U
	Plutonium-238	pCi/L		0.00535 U		0.0108 U
	Plutonium-239/240	pCi/L		0.0161 U		0.0108 U
	Technetium-99	pCi/L	17.2	33.1	6.13 U	17.3
LBC-SW01	Uranium	µg/L	1.57	3.21	0.488	5.31
	Uranium-233/234	pCi/L	3.33	6.43	0.756	9.16
	Uranium-235/236	pCi/L	0.182	0.378	0.0459 U	0.428
	Uranium-238	pCi/L	0.498	1.02	0.157	1.72
	Americium-241	pCi/L		0.00963 U		0.0242 U
	Neptunium-237	pCi/L		0.00994 U		0.00897 U
	Plutonium-238	pCi/L		-0.0054 U		-0.00495 U
	Plutonium-239/240	pCi/L		0 U		0.0248 U
LBC-SW02	Technetium-99	pCi/L	7.96	8.96	7.34 U	11.3
	Uranium	µg/L	0.954	1.4	0.426	2.11 J
	Uranium-233/234	pCi/L	2.14	1.86	0.73	3.45
	Uranium-235/236	pCi/L	0.111 UJ	0.153	0.0239 U	0.149
	Uranium-238	pCi/L	0.303	0.448	0.139	0.685
	Americium-241	pCi/L		0.0368 U		0.0144 U
	Neptunium-237	pCi/L		0 U		0.00488 U
	Plutonium-238	pCi/L		-0.0052 U		0.00489 U
LBC-SW02	Plutonium-239/240	pCi/L		0.0312 U		0.00979 U
	Technetium-99	pCi/L	8.73	10.5	9.68	10

Table 4.24. Results for radionuclides at surface water monitoring locations – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
LBC-SW02	Uranium	µg/L	0.91	0.907	0.395	3.17 J
	Uranium-233/234	pCi/L	1.82	1.58	1.03	4.51
	Uranium-235/236	pCi/L	0.0732 UJ	0.0977 U	0.0474 U	0.206
	Uranium-238	pCi/L	0.294	0.29	0.125	1.03
LBC-SW03	Americium-241	pCi/L		0.0123 U		0.0427 U
	Neptunium-237	pCi/L		0 U		-0.00467 U
	Plutonium-238	pCi/L		-0.0050 U		0.0151 U
	Plutonium-239/240	pCi/L		0.0353 U		0.0352 U
	Technetium-99	pCi/L	7.06	7.92	4.65 U	10.1 J
	Uranium	µg/L	0.969	0.617	0.709	3.92
	Uranium-233/234	pCi/L	1.68	1.23	1.3	5.67
	Uranium-235/236	pCi/L	0.09 UJ	0.129	0.0516 U	0.301
LBC-SW04	Uranium-238	pCi/L	0.312	0.187	0.23	1.27
	Americium-241	pCi/L		0.0094 U		0.0245 U
	Neptunium-237	pCi/L		0 U		0.00921 U
	Plutonium-238	pCi/L		0.00545 U		0 U
	Plutonium-239/240	pCi/L		0.0273 U		0.0163 U
	Technetium-99	pCi/L	8.27	2.54 U	9.03	12.1
	Uranium	µg/L	1.95	1.12	0.841	4.29
	Uranium-233/234	pCi/L	2.11	1.14	1.36	6.98
NHP-SW01	Uranium-235/236	pCi/L	0.113 UJ	0.0375 U	0.0666 U	0.253
	Uranium-238	pCi/L	0.637	0.372	0.272	1.4
	Americium-241	pCi/L		0.0106 U		0.0096 U
	Neptunium-237	pCi/L		0.00468 U		0 U
	Plutonium-238	pCi/L		-0.0279 U		0.0105 U
	Plutonium-239/240	pCi/L		0.0279 U		0.00527 U
	Technetium-99	pCi/L	1.26 U	0.217 U	0.572 U	4.28 U
	Uranium	µg/L	6.66	5.16	3.41	3.72 J
UND-SW01	Uranium-233/234	pCi/L	2.7	2.38	1.26	2.18
	Uranium-235/236	pCi/L	0.17	0.088 U	0.0648 U	0.113
	Uranium-238	pCi/L	2.21	1.72	1.14	1.23
	Americium-241	pCi/L		0.026 U		0.0252 U
	Neptunium-237	pCi/L		-0.0045 U		-0.0128 U
	Plutonium-238	pCi/L		0.0104 U		-0.0151 U
	Plutonium-239/240	pCi/L		0 U		0.0101 U
	Technetium-99	pCi/L	-1.05 U	-2.56 U	1.19 U	-0.0925 U
UND-SW02	Uranium	µg/L	2.11 J	2.66 J	2.12	2.16 J
	Uranium-233/234	pCi/L	0.853	1.04	0.986	1.1
	Uranium-235/236	pCi/L	0.0474 UJ	0.0565 UJ	0.0321 U	0.0545 UJ
	Uranium-238	pCi/L	0.701	0.886	0.707	0.719
	Americium-241	pCi/L		0.0381 U		0.00906 U
	Neptunium-237	pCi/L		-0.0045 U		0.0136 U
	Plutonium-238	pCi/L		-0.0052 U		-0.00524 U
	Plutonium-239/240	pCi/L		0.031 U		0.021 U
WDD-SW01	Technetium-99	pCi/L	0.354 U	-4.15 U	-0.797 U	-1.71 U
	Uranium	µg/L	1.27 J	1.78	1.63	1.8
	Uranium-233/234	pCi/L	0.659	0.58	0.471	0.649
	Uranium-235/236	pCi/L	0.0124 U	0.0175 U	0.0747 U	0.0336 U
	Uranium-238	pCi/L	0.425	0.594	0.536	0.599
	Americium-241	pCi/L		0.0223 U		0.0138 U

Table 4.24. Results for radionuclides at surface water monitoring locations – 2015 (continued)

Sampling Location	Parameter	Unit	First quarter	Second quarter	Third quarter	Fourth quarter
WDD-SW01	Neptunium-237	pCi/L		-0.0052 U		0.0145 U
	Plutonium-238	pCi/L		0.0097 U		0.0161 U
	Plutonium-239/240	pCi/L		0.00485 U		0.0322 U
	Technetium-99	pCi/L	0.0794 U	10.6	-0.391 U	4.2 U
	Uranium	µg/L	3.81 J	4.56	0.841	2.13
	Uranium-233/234	pCi/L	2.45	5.04	0.431	1.04
	Uranium-235/236	pCi/L	0.129	0.28	0 U	0.0471 U
	Uranium-238	pCi/L	1.26	1.49	0.283	0.709
WDD-SW02	Americium-241	pCi/L		0.00481 U		0.0274 U
	Neptunium-237	pCi/L		0 U		0.00485 U
	Plutonium-238	pCi/L		0.00962 U		0 U
	Plutonium-239/240	pCi/L		0.0241 U		0.0248 U
	Technetium-99	pCi/L	-1.3 U	-1.2 U	-1.79 U	3.59 U
	Uranium	µg/L	2.46 J	3.16	0.533	0.215 UJ
	Uranium-233/234	pCi/L	1.13	1.88	0.431	0.158 UJ
	Uranium-235/236	pCi/L	0.07 UJ	0.0762 U	0.0173 U	0 U
WDD-SW03	Uranium-238	pCi/L	0.816	1.05	0.176	0.0724 UJ
	Americium-241	pCi/L		0.0131 U		0.0226 U
	Neptunium-237	pCi/L		0 U		-0.00891 U
	Plutonium-238	pCi/L		0.0102 U		0.0202 U
	Plutonium-239/240	pCi/L		0.0203 U		0.0101 U
	Technetium-99	pCi/L	-0.927 U	19.3	0.0688 U	-1.68 U
	Uranium	µg/L	2.49 J	2.94	1.23	1.15
	Uranium-233/234	pCi/L	1.51	4.89	0.533	0.471
Uranium-235/236	pCi/L	0.075 UJ	0.248	0.0411 U	0.029 U	
Uranium-238	pCi/L	0.824	0.948	0.406	0.382	

5. REFERENCES

- DOE 2014. *Integrated Groundwater Monitoring Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0032&D7, U.S. Department of Energy, Piketon, OH, May.
- DOE 2015. *Integrated Groundwater Monitoring Plan for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0032&D8, U.S. Department of Energy, Piketon, OH, July.
- DOE 2016. *2015 Groundwater Monitoring Report for the Portsmouth Gaseous Diffusion Plant, Piketon, Ohio*, DOE/PPPO/03-0672&D1, U.S. Department of Energy, Piketon, OH, March.
- DOE 2017. *U.S. Department of Energy Portsmouth Gaseous Diffusion Plant Annual Site Environmental Report –2015, Piketon, Ohio*, DOE/PPPO/03-0765&D1, U.S. Department of Energy, Piketon, OH, March.

This page intentionally left blank.

RECORD COPY DISTRIBUTION

File—FBP RMDC—RC